

Package ‘REddyProc’

March 30, 2019

Type Package

Version 1.2

Title Post Processing of (Half-)Hourly Eddy-Covariance Measurements

Description Standard and extensible Eddy-Covariance data post-processing

(Wutzler et al. (2018) <doi:10.5194/bg-15-5015-2018>)

includes

uStar-filtering, gap-filling, and flux-partitioning.

The Eddy-Covariance (EC) micrometeorological technique quantifies continuous exchange fluxes of gases, energy, and momentum between an ecosystem and the atmosphere.

It is important for understanding ecosystem dynamics and upscaling exchange fluxes.

(Aubinet et al. (2012) <doi:10.1007/978-94-007-2351-1>).

This package inputs pre-processed (half-)hourly data and supports further processing.

First, a quality-check and filtering is performed based on the relationship between measured flux and friction

velocity (uStar) to discard biased data

(Papale et al. (2006) <doi:10.5194/bg-3-571-2006>).

Second, gaps in the data are filled based on information from environmental conditions

(Reichstein et al. (2005) <doi:10.1111/j.1365-2486.2005.001002.x>).

Third, the net flux of carbon dioxide is partitioned

into its gross fluxes in and out of the ecosystem by night-time

based and day-time based approaches

(Lasslop et al. (2010) <doi:10.1111/j.1365-2486.2009.02041.x>).

URL <https://www.bgc-jena.mpg.de/bgi/index.php/Services/REddyProcWeb>,

<https://github.com/bgctw/REddyProc>

License GPL (>= 2)

Encoding UTF-8

LazyData true

RoxygenNote 6.1.1

VignetteBuilder knitr

LinkingTo Rcpp

Depends R (>= 3.0.0), methods

Imports dplyr, purrr, rlang, mlegp, tibble, magrittr, solartime

Suggests testthat, minpack.lm, segmented, knitr, rmarkdown, lognorm, ggplot2, tidyr, bigleaf (>= 0.7)

Collate 'CheckVal.R' 'DataFunctions.R' 'aEddy.R' 'EddyGapfilling.R' 'EddyPartitioning.R' 'EddyPlotting.R' 'EddyUStarFilterChangePointDetection.R' 'EddyUStarFilterDPR.R' 'Example.R' 'FileHandling.R' 'FileHandlingFormats.R' 'GeoFunctions.R' 'LRC_base.R' 'LRC_logisticSigmoid.R' 'LRC_nonrectangular.R' 'LRC_rectangular.R' 'PartitioningLasslop10.R' 'PartitioningLasslop10Nighttime.R' 'RcppExports.R' 'imports.R' 'logitnorm.R' 'variableNames.R' 'zzzDebugCode.R'

NeedsCompilation yes

Author Department for Biogeochemical Integration at MPI-BGC, Jena, Germany
[cph],
Thomas Wutzler [aut, cre],
Markus Reichstein [aut],
Antje Maria Moffat [aut, trl],
Olaf Menzer [ctb],
Mirco Migliavacca [aut],
Kerstin Sickel [ctb, trl],
Ladislav Šigut [ctb]

Maintainer Thomas Wutzler <twutz@bgc-jena.mpg.de>

Repository CRAN

Date/Publication 2019-03-30 16:30:16 UTC

R topics documented:

REddyProc-package	5
BerkeleyJulianDateToPOSIXct	6
DEGebExample	7
Example_DETha98	8
fCalcAVPfromVMFandPress	9
fCalcETfromLE	9
fCalcExtRadiation	10
fCalcPotRadiation	11
fCalcRHfromAVPandTair	12
fCalcSVPfromTair	13
fCalcVPDfromRHandTair	13
fCheckHHTimeSeries	14
fConvertCtoK	15
fConvertGlobalToVisible	16
fConvertKtoC	16
fConvertTimeToPosix	17
fConvertVisibleWm2toPhotons	19
filterLongRuns	19
filterLongRunsInVector	20

fLloydTaylor	21
fLoadEuroFlux16	22
fLoadTXTIntoDataframe	23
fWriteDataframeToFile	24
getAmerifluxToBGC05VariableNameMapping	25
getBGC05ToAmerifluxVariableNameMapping	26
getExamplePath	27
getFilledExampleDETha98Data	28
getREddyProcExampleDir	28
getTZone	29
globalDummyVars	30
LightResponseCurveFitter	30
LightResponseCurveFitter-class	31
LightResponseCurveFitter_computeCost	32
LightResponseCurveFitter_computeLRCGradient	33
LightResponseCurveFitter_fitLRC	34
LightResponseCurveFitter_getOptimizedParameterPositions	35
LightResponseCurveFitter_getParameterInitials	36
LightResponseCurveFitter_getParameterNames	37
LightResponseCurveFitter_getPriorLocation	37
LightResponseCurveFitter_getPriorScale	38
LightResponseCurveFitter_isParameterInBounds	39
LightResponseCurveFitter_optimLRC	40
LightResponseCurveFitter_optimLRCBounds	41
LightResponseCurveFitter_optimLRConAdjustedPrior	42
LightResponseCurveFitter_predictGPP	43
LightResponseCurveFitter_predictLRC	44
LogisticSigmoidLRCFitter	45
LogisticSigmoidLRCFitter-class	45
LogisticSigmoidLRCFitter_predictGPP	46
NonrectangularLRCFitter	47
NonrectangularLRCFitter-class	47
NonrectangularLRCFitter_getParameterNames	48
NonrectangularLRCFitter_predictGPP	49
partGLControl	50
partGLControlLasslopCompatible	52
partGLExtractStandardData	54
partitionNEEGL	56
POSIXctToBerkeleyJulianDate	59
RectangularLRCFitter	59
RectangularLRCFitter-class	60
RectangularLRCFitterCVersion	61
RectangularLRCFitterCVersion-class	61
RectangularLRCFitter_predictGPP	62
renameVariablesInDataframe	63
RHLightResponseCostC	63
sEddyProc	64
sEddyProc-class	65

sEddyProc_initialize	67
sEddyProc_sApplyUStarScen	69
sEddyProc_sCalcPotRadiation	69
sEddyProc_sEstimateUstarScenarios	70
sEddyProc_sEstUstarThold	71
sEddyProc_sEstUstarThreshold	72
sEddyProc_sEstUstarThresholdDistribution	73
sEddyProc_sExportData	74
sEddyProc_sExportResults	74
sEddyProc_sFillInit	75
sEddyProc_sFillLUT	76
sEddyProc_sFillMDC	77
sEddyProc_sGetData	78
sEddyProc_sGetEstimatedUstarThresholdDistribution	78
sEddyProc_sGetUstarScenarios	79
sEddyProc_sGLFluxPartition	80
sEddyProc_sGLFluxPartitionUStarScens	81
sEddyProc_sMDSGapFill	81
sEddyProc_sMDSGapFillAfterUstar	83
sEddyProc_sMDSGapFillAfterUstarDistr	85
sEddyProc_sMDSGapFillUStarScens	86
sEddyProc_sMRFluxPartition	87
sEddyProc_sMRFluxPartitionUStarScens	89
sEddyProc_sPlotDailySums	90
sEddyProc_sPlotDailySumsY	91
sEddyProc_sPlotDiurnalCycle	92
sEddyProc_sPlotFingerprint	93
sEddyProc_sPlotFingerprintY	94
sEddyProc_sPlotHHFluxes	95
sEddyProc_sPlotHHFluxesY	96
sEddyProc_sPlotNEEVersusUStarForSeason	97
sEddyProc_sSetLocationInfo	98
sEddyProc_sSetUstarScenarios	99
sEddyProc_sSetUstarSeasons	99
sEddyProc_sTKFluxPartition	100
sEddyProc_sTKFluxPartitionUStarScens	101
sEddyProc_useAnnualUStarThresholds	101
sEddyProc_useSeaonsalUStarThresholds	102
usControlUstarEst	103
usControlUstarSubsetting	104
usCreateSeasonFactorMonth	105
usCreateSeasonFactorMonthWithinYear	106
usCreateSeasonFactorYday	107
usCreateSeasonFactorYdayYear	108
usEstUstarThreshold	109
usEstUstarThresholdSingleFw1Binned	112
usEstUstarThresholdSingleFw2Binned	113
usGetAnnualSeasonUStarMap	113

usGetSeasonalSeasonUStarMap	114
usGetYearOfSeason	115

Index	116
--------------	------------

REddyProc-package	<i>Post Processing of (Half-)Hourly Eddy-Covariance Measurements</i>
-------------------	--

Description

Standard and extensible Eddy-Covariance data post-processing including uStar-filtering, gap-filling, and flux-partitioning (Wutzler et al. (2018) <doi:10.5194/bg-15-5015-2018>).

The Eddy-Covariance (EC) micrometeorological technique quantifies continuous exchange fluxes of gases, energy, and momentum between an ecosystem and the atmosphere. It is important for understanding ecosystem dynamics and upscaling exchange fluxes. (Aubinet et al. (2012) <doi:10.1007/978-94-007-2351-1>).

This package inputs pre-processed (half-)hourly data and supports further processing. First, a quality-check and filtering is performed based on the relationship between measured flux and friction velocity (uStar) to discard biased data (Papale et al. (2006) <doi:10.5194/bg-3-571-2006>).

Second, gaps in the data are filled based on information from environmental conditions (Reichstein et al. (2005) <doi:10.1111/j.1365-2486.2005.001002.x>).

Third, the net flux of carbon dioxide is partitioned into its gross fluxes in and out of the ecosystem by night-time based and day-time based approaches (Lasslop et al. (2010) <doi:10.1111/j.1365-2486.2009.02041.x>).

A general description and an online tool based on this package can be found here: <https://www.bgc-jena.mpg.de/bgi/index.php/Services/REddyProcWeb>.

Details

A **detailed example** of the processing can be found in the [useCase vignette](#).

A first overview of the REddyProc functions:

These functions help with the preparation of your data for the analysis:

- Loading text files into dataframes: [fLoadTXTIntoDataframe](#)
- Preparing a proper time stamp: [fConvertTimeToPosix](#)
- Calculating latent variables, e.g. VPD: [fCalcVPDfromRHandTair](#)

Then the data can be processed with the [sEddyProc-class](#) R5 reference class:

- Initializing the R5 reference class: [sEddyProc_initialize](#)
- Estimating the turbulence criterion, Ustar threshold, for omitting data from periods of low turbulence: Functions [sEddyProc_sEstUstarThreshold](#) and [sEddyProc_sEstUstarThresholdDistribution](#)
- Gap filling: [sEddyProc_sMDSGapFill](#) and [sEddyProc_sMDSGapFillAfterUstar](#).
- Flux partitioning based on Night-Time: [sEddyProc_sMRFluxPartition](#)

- Flux partitioning based on Day-Time: [sEddyProc_sGLFluxPartition](#)

Processing across different scenarios of u^* threshold estimate is supported by

- Estimating the turbulence criterion, Ustar threshold, for omitting data from periods of low turbulence: [sEddyProc_sEstimateUstarScenarios](#) and associated
 - query the thresholds to be used [sEddyProc_sGetUstarScenarios](#)
 - set the thresholds to be used [sEddyProc_sSetUstarScenarios](#)
 - query the estimated thresholds all different aggregation levels [sEddyProc_sGetEstimatedUstarThresholdDistr](#)
- Gap-Filling: [sEddyProc_sMDSGapFillUstarScens](#)
- Flux partitioning based on Night-Time (Reichstein 2005): [sEddyProc_sMRFluxPartitionUstarScens](#)
- Flux partitioning based on Day-Time (Lasslop 2010): [sEddyProc_sGLFluxPartitionUstarScens](#)
- Flux partitioning based on modified Day-Time (Keenan 2019): [sEddyProc_sTKFluxPartitionUstarScens](#)

Before or after processing, the data can be plotted:

- Fingerprint: [sEddyProc_sPlotFingerprint](#)
- Half-hourly fluxes and their daily means: [sEddyProc_sPlotHHFluxes](#)
- Daily sums (and their uncertainties): [sEddyProc_sPlotDailySums](#)
- Diurnal cycle: [sEddyProc_sPlotDiurnalCycle](#)

A **complete list** of REdyProc functions be viewed by clicking on the **Index** link at the bottom of this help page.

Also have a look at the [package vignettes](#).

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany

References

Reichstein M, Falge E, Baldocchi D et al. (2005) On the separation of net ecosystem exchange into assimilation and ecosystem respiration: review and improved algorithm. *Global Change Biology*, 11, 1424-1439.

BerkeleyJulianDateToPOSIXct

BerkeleyJulianDateToPOSIXct

Description

convert JulianDate format used in Berkeley release to POSIXct

Usage

```
BerkeleyJulianDateToPOSIXct(julianDate, tz = "GMT",
  ...)
```

Arguments

julianDate numeric vector representing times (see details for format)
 tz time zone used to represent the dates
 ... further arguments to [strptime](#), such as tz

Details

In the Berkeley-Release of the fluxnet data, the time is stored as an number with base10-digits representing YYYYMMddhhmm

Author(s)

TW, Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

See Also

[POSIXctToBerkeleyJulianDate fConvertTimeToPosix](#)

DEGebExample

Eddy covariance data from Gebesee crop site, Germany

Description

The data frame 'DEGebExample' contains half-hourly eddy covariance measurements from Gebesee of the years 2004 to 2006.

Usage

```
data(DEGebExample)
```

Format

For each column, the attributes 'varnames' for the variable names and 'units' for the variable units are provided.

Time stamp DateTime: POSIXct-time of the end of the half-hour period, Use as.POSIXlt(DateTime)\$year to get hour, day of year, ...

Flux measurements NEE

Meteo measurements Rg, Tair, rH, VPD, Ustar

For processing of the example data see `vignette("DEGebExample")`.

Details

DISCLAIMER: This example dataset should only be used for test purposes of the REddyProc R package. For other uses, the data is openly available through the European Fluxes Database (<http://www.europe-fluxdata.eu/home/site-details?id=3>) and upon registration the current version can be downloaded there.

Source

The data was downloaded from <http://www.europe-fluxdata.eu> at date 2016-01-25.

Example_DETha98	<i>Eddy covariance data from Tharandt, Germany</i>
-----------------	--

Description

The data frame 'EddyData.F' contains half-hourly eddy covariance measurements from Tharandt of the year 1998.

Usage

```
data(Example_DETha98)
```

Format

For each column, the attributes 'varnames' for the variable names and 'units' for the variable units are provided.

Time stamp Year - Year provided with century 1998.

DoY - Day of year provided as 1 to 365 (or 1 to 366 in leap years).

Hour - Hour provided as decimal 0.0 to 23.5.

Flux measurements NEE, LE, H

Meteo measurements Rg, Tair, Tsoil, rH, VPD, Ustar

For processing of the example data see [useCase vignette](#).

Source

The data originates from the CARBODATA CD.

fCalcAVPfromVMFandPress
fCalcAVPfromVMFandPress

Description

Calculate AVP from VMF and Press

Usage

fCalcAVPfromVMFandPress(VMF = VMF.V.n, Press = Press.V.n,
 VMF.V.n, Press.V.n)

Arguments

VMF	Vapor mole fraction (VMF, mol / mol)
Press	Atmospheric pressure (Press, hPa)
VMF.V.n	deprecated
Press.V.n	deprecated

Value

Data vector of actual vapor pressure (AVP, hPa (mbar))

Author(s)

AMM Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

fCalcETfromLE *fCalcETfromLE*

Description

Calculate ET from LE and Tair

Usage

fCalcETfromLE(LE = LE.V.n, Tair = Tair.V.n,
 LE.V.n, Tair.V.n)

Arguments

LE	Data vector of latent heat (LE, W m ⁻²)
Tair	Data vector of air temperature (Tair, degC)
LE.V.n	deprecated
Tair.V.n	deprecated

Value

Data vector of evapotranspiration (ET, mmol H₂O m⁻² s⁻¹)

Author(s)

AMM Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

fCalcExtRadiation *fCalcExtRadiation*

Description

Calculate the extraterrestrial solar radiation with the eccentricity correction

Usage

```
fCalcExtRadiation(DoY = DoY.V.n, DoY.V.n)
```

Arguments

DoY	
DoY.V.n	Data vector with day of year (DoY)

Value

Data vector of extraterrestrial radiation (ExtRad, W_m⁻²)

Author(s)

AMM Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

fCalcPotRadiation *fCalcPotRadiation*

Description

Calculate the potential radiation

Usage

```
fCalcPotRadiation(DoY = DoY.V.n, Hour = Hour.V.n,
  LatDeg = Lat_deg.n, LongDeg = Long_deg.n,
  TimeZone = TimeZone_h.n, useSolartime = TRUE,
  DoY.V.n, Hour.V.n, Lat_deg.n, Long_deg.n,
  TimeZone_h.n, useSolartime.b = TRUE)
```

Arguments

DoY	Data vector with day of year (DoY), same length as Hour or length 1
Hour	Data vector with time as decimal hour of local time zone
LatDeg	Latitude in (decimal) degrees
LongDeg	Longitude in (decimal) degrees
TimeZone	Time zone (in hours)
useSolartime	
DoY.V.n	deprecated
Hour.V.n	deprecated
Lat_deg.n	deprecated
Long_deg.n	deprecated
TimeZone_h.n	deprecated
useSolartime.b	deprecated

Value

Data vector of potential radiation (PotRad, W_m-2)

Author(s)

AMM Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

Examples

```

hour <- seq(8, 16, by = 0.1)
potRadSolar <- fCalcPotRadiation(160, hour, 39.94, -5.77, TimeZone = +1)
potRadLocal <- fCalcPotRadiation(160, hour, 39.94, -5.77, TimeZone = +1
, useSolartime = FALSE)
plot(potRadSolar ~ hour, type = 'l')
abline(v = 13, lty = "dotted")
lines(potRadLocal ~ hour, col = "blue")
abline(v = 12, col = "blue", lty = "dotted")
legend("bottomright", legend = c("solar time", "local winter time")
, col = c("black", "blue"), inset = 0.05, lty = 1)

```

fCalcRHfromAVPandTair *fCalcRHfromAVPandTair*

Description

Calculate relative humidity from actual vapour pressure and air temperature

Usage

```

fCalcRHfromAVPandTair(AVP = AVP.V.n, Tair = Tair.V.n,
AVP.V.n, Tair.V.n)

```

Arguments

AVP	Data vector of actual vapour pressure (AVP, hPa (mbar))
Tair	Data vector of air temperature (Tair, degC)
AVP.V.n	Data vector of actual vapour pressure (AVP, hPa (mbar))
Tair.V.n	Data vector of air temperature (Tair, degC)

Value

Data vector of relative humidity (rH, %)

Author(s)

AMM Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

fCalcSVPfromTair *fCalcSVPfromTair*

Description

Calculate SVP (of water) from Tair

Usage

fCalcSVPfromTair(Tair = Tair.V.n, Tair.V.n)

Arguments

Tair	Data vector of air temperature (Tair, degC)
Tair.V.n	deprecated

Value

Data vector of saturation vapor pressure (SVP, hPa (mbar))

Author(s)

AMM Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

fCalcVPDfromRHAndTair *fCalcVPDfromRHAndTair*

Description

Calculate VPD from rH and Tair

Usage

fCalcVPDfromRHAndTair(rH = RH.V.n, Tair = Tair.V.n,
RH.V.n, Tair.V.n)

Arguments

rH	Data vector of relative humidity (rH, %)
Tair	Data vector of air temperature (Tair, degC)
RH.V.n	deprecated
Tair.V.n	deprecated

Value

Data vector of vapour pressure deficit (VPD, hPa (mbar))

Author(s)

AMM Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

fCheckHHTimeSeries *fCheckHHTimeSeries*

Description

Check half-hourly time series data

Usage

```
fCheckHHTimeSeries(Time = Time.V.p, DTS = DTS.n,
  CallFunction = if (!missing(CallFunction.s)) CallFunction.s else "",
  Time.V.p, DTS.n, CallFunction.s)
```

Arguments

Time	Time vector in POSIX format
DTS	Number of daily time steps (24 or 48)
CallFunction	
Time.V.p	deprecated
DTS.n	deprecated
CallFunction.s	deprecated

Details

The number of steps per day can be 24 (hourly) or 48 (half-hourly).

The time stamp needs to be provided in POSIX time format, equidistant half-hours, and stamped on the half hour.

The sEddyProc procedures require at least three months of data.

Full days of data are preferred: the total amount of data rows should be a multiple of the daily time step, and

in accordance with FLUXNET standards, the dataset is spanning from the end of the first (half-)hour (0:30 or 1:00, respectively) and to midnight (0:00).

Value

Function stops on errors.

Author(s)

AMM Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

fConvertCtoK

fConvertCtoK

Description

Convert degree Celsius to degree Kelvin

Usage

```
fConvertCtoK(Celsius = Celsius.V.n, Celsius.V.n)
```

Arguments

Celsius	Data vector in Celsius (degC)
Celsius.V.n	deprecated way of specifying Celsius

Value

Data vector in temperature Kelvin (Temp_K, degK)

Author(s)

AMM Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

fConvertGlobalToVisible
fConvertGlobalToVisible

Description

Partition global (solar) radiation into only visible (the rest is UV and infrared)

Usage

```
fConvertGlobalToVisible(Global = Global.V.n,  
Global.V.n)
```

Arguments

Global	Data vector of global radiation (W m-2)
Global.V.n	deprecated

Value

Data vector of visible part of solar radiation (VisRad, W m-2)

Author(s)

AMM Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

fConvertKtoC *fConvertKtoC*

Description

Convert degree Kelvin to degree Celsius

Usage

```
fConvertKtoC(Kelvin = Kelvin.V.n, Kelvin.V.n)
```

Arguments

Kelvin	Data vector in Kelvin (degK)
Kelvin.V.n	deprecated, use Kelvin instead

Value

Data vector in temperature Celsius (Temp_C, degC)

Author(s)

AMM Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

fConvertTimeToPosix *fConvertTimeToPosix*

Description

Convert different time formats to POSIX

Usage

```
fConvertTimeToPosix(Data.F, TFormat = TFormat.s,
  Year = if (!missing(Year.s)) Year.s else "none",
  Month = if (!missing(Month.s)) Month.s else "none",
  Day = if (!missing(Day.s)) Day.s else "none",
  Hour = if (!missing(Hour.s)) Hour.s else "none",
  Min = if (!missing(Min.s)) Min.s else "none",
  TName = if (!missing(TName.s)) TName.s else "DateTime",
  TFormat.s, Year.s, Month.s, Day.s, Hour.s,
  Min.s, TName.s, tz = "GMT")
```

Arguments

Data.F	Data frame with time columns to be converted
TFormat	Abbreviation for implemented time formats, see details
Year	Column name of year
Month	Column name of month
Day	Column name of day
Hour	Column name of hour
Min	Column name of min
TName	Column name of new column
TFormat.s	deprecated
Year.s	deprecated
Month.s	deprecated

Day.s	deprecated
Hour.s	deprecated
Min.s	deprecated
TName.s	deprecated
tz	timezone used to store the data. Advised to keep GMT to avoid daytime shifting issues

Details

The different time formats are converted to POSIX (GMT) and a 'TimeDate' column is prefixed to the data frame

Implemented time formats:

YDH year, day of year, hour in decimal (e.g. 1998, 1, 10.5). The day (of year) format is (1-365 or 1-366 in leap years). The hour format is decimal time (0.0-23.5).

YMDH year, month, day of month, hour in decimal (e.g. 1998, 1, 1, 10.5) The month format is (1-12) The day (of month) format is (1-31).

YMDHM year, month, day of month, integer hour, minute (e.g. 1998, 1, 1, 10, 30) The hour format is (0-23) The minute format is (0-59)

Value

Data frame with prefixed POSIX time column.

Author(s)

AMM Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

See Also

[BerkeleyJulianDateToPOSIXct](#)

Examples

```
# See unit test in test_fConvertTimeToPosix for example
```

fConvertVisibleWm2toPhotons
fConvertVisibleWm2toPhotons

Description

Convert units of visible radiation from irradiance to photons flux

Usage

```
fConvertVisibleWm2toPhotons(Wm2 = Wm2.V.n,  
                             Wm2.V.n)
```

Arguments

Wm2	Data vector in units of irradiance (W m ⁻²)
Wm2.V.n	deprecated

Value

Data vector in units of photons flux (PPFD, umol photons m⁻² s⁻¹)

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

filterLongRuns *filterLongRuns*

Description

replace runs, i.e sequences of numerically equal values, by NA

Usage

```
filterLongRuns(data, colNames, ...)
```

Arguments

<code>data</code>	data.frame with columns to filter
<code>colNames</code>	string vector of names indicating which columns to filter
<code>...</code>	further arguments to <code>filterLongRunsInVector</code> such as <code>minNRunLength</code> .

Details

Longer runs, i.e. sequences of numerically identical values, in a series of measurements hint to problems during a noisy measurement, e.g. by sensor malfunction due to freezing. This function, replaces such values in such runs to indicate missing values.

Value

data.frame ans with long runs in specified columns replaced by NA

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

`filterLongRunsInVector`

filterLongRunsInVector

Description

replace runs of numerically equal values by NA

Usage

```
filterLongRunsInVector(x, minNRunLength = 8,
  replacement = NA, na.rm = TRUE)
```

Arguments

<code>x</code>	vector in which to replace long runs
<code>minNRunLength</code>	minimum length of a run to replace. Defaults to 4 hours in half-hourly spaced data.
<code>replacement</code>	value replacing the original values in long run
<code>na.rm</code>	set to FALSE if NA values interrupt runs

Value

vector x with long runs replaced by NA

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

 fLloydTaylor

Temperature dependence of soil respiration

Description

Temperature dependence of soil respiration after Equation 11 in Lloyd & Taylor (1994)

Usage

```
fLloydTaylor(RRef = R_ref.n, E0 = E_0.n,
             TSoil = Tsoil.n, TRef = if (missing(T_ref.n)) 273.15 +
               10 else T_ref.n, T0 = if (missing(T_0.n)) 227.13 else T_0.n,
             R_ref.n, E_0.n, Tsoil.n, T_ref.n, T_0.n)
```

Arguments

RRef	Respiration rate at reference temperature
E0	Temperature sensitivity ("activation energy") in Kelvin (degK)
TSoil	Soil temperature in Kelvin (degK)
TRef	
T0	
R_ref.n	deprecated way to specify RRef
E_0.n	deprecated way to specify E0
Tsoil.n	deprecated way to specify Tsoil
T_ref.n	deprecated way to specify TRef
T_0.n	deprecated way to specify T0

Value

Data vector of soil respiration rate (R, umol CO2 m⁻² s⁻¹)

Author(s)

AMM reference« Lloyd J, Taylor JA (1994) On the temperature dependence of soil respiration. *Functional Ecology*, 8, 315-323. Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

Examples

```
T <- c(-10:30)
resp <- fLloydTaylor(10, 330, T + 273.15)
plot(resp ~ T)
```

fLoadEuroFlux16

fLoadEuroFlux16

Description

reads a sequence of annual files in the format of europe-fluxdata 2016

Usage

```
fLoadEuroFlux16(siteName, dirName = "", additionalColumnNames = character(0))
```

Arguments

siteName scalar string: the name of the site, i.e. start of the filename before `__`

dirName scalar string: the directory where the files reside

additionalColumnNames
character vector: column names to read in addition to `c("Month", "Day", "Hour", "NEE_st", "qf_NEE_st", "ustar", "Ta", 'Rg')`

Details

The filenames should correspond to the pattern `<sitename>_<YYYY>_*.txt` And hold columns `c("Month", "Day", "Hour", "NEE_st", "qf_NEE_st", "ustar", "Ta", 'Rg')`. By default only those columns are read and reported only `c("DateTime", "NEE", "Ustar", "Tair", "Rg", "qf_NEE_st"` (Note the renaming). NEE is set to NA for all values with `"qf_NEE_st" != 0`. Values of `-9999.0` are replaced by NA

Author(s)

TW Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

fLoadTXTIntoDataframe *Load text file with one header and one unit row into data frame*

Description

If gaps with the flag -9999.0 exist, these are set to NA.

Usage

```
fLoadTXTIntoDataframe(FileName = FileName.s,
  Dir = if (!missing(Dir.s)) Dir.s else "",
  FileName.s, Dir.s = "")
```

Arguments

FileName	File name as a character string
Dir	Directory as a character string
FileName.s	deprecated
Dir.s	deprecated way of specifying Dir

Details

Function fLoadFluxNCIntoDataframe, which loads data from NetCDF-Files, has been moved to add-on package REddyProcNCDF. In addition, [fLoadEuroFlux16](#) loads data from several annual files in format corresponding to europe-fluxdata 2016.

For using only part of the records, use fFilterAttr to keep units attributes.

Value

Data frame with data from text file.

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

Examples

```
examplePath <- getExamplePath('Example_DETha98.txt', TRUE)
EddyData.F <- fLoadTXTIntoDataframe(examplePath)
```

fWriteDataframeToFile *fWriteDataframeToFile*

Description

Write data frame to ASCII tab-separated text file

Usage

```
fWriteDataframeToFile(Data.F, FileName = FileName.s,
  Dir = if (!missing(Dir.s)) Dir.s else "",
  Digits = if (!missing(Digits.n)) Digits.n else 5,
  FileName.s, Dir.s, Digits.n)
```

Arguments

Data.F	Data frame
FileName	File base name as a string
Dir	Directory as a string
Digits	
FileName.s	deprecated
Dir.s	deprecated
Digits.n	deprecated

Details

Missing values are flagged as -9999.0

Value

Output of data frame written to file of specified type.

Author(s)

AMM, KS Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

Examples

```
(Dir <- tempdir()) # directory where output is written to
fWriteDataframeToFile(Example_DETha98, 'OutputTest.txt', Dir = Dir)
```

```
getAmerifluxToBGC05VariableNameMapping
  getAmerifluxToBGC05VariableNameMapping
```

Description

map Ameriflux variable names to REddyProc defaults to names

Usage

```
getAmerifluxToBGC05VariableNameMapping(map = character(),
  mapDefault = c(YEAR = "Year", DOY = "DoY",
    NEE = "NEE", LE = "LE", H = "H",
    SW_IN = "Rg", TA = "Tair", TS = "Tsoil",
    RH = "rH", VPD = "VPD", USTAR = "Ustar",
    NEE_PI = "NEE_orig", H_PI = "H_orig",
    LE_PI = "LE_orig", NEE_F = "NEE_f",
    H_F = "H_f", LE_F = "LE_f", NEE_QC = "NEE_fqc",
    H_QC = "H_fqc", LE_QC = "LE_fqc"))
```

Arguments

map	named character vector: additional mapping, that extends or overwrites defaults in mapDefault
mapDefault	named character vector: default mapping

Details

Get a mapping of variable names of Ameriflux (Berkley 2016 Fluxnet release) to of REddyProc defaults to names

Author(s)

TW, Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

See Also

[renameVariablesInDataframe](#)

```
getBGC05ToAmerifluxVariableNameMapping
  getBGC05ToAmerifluxVariableNameMapping
```

Description

map REddyProc names the Berkeley 2016 release of the Fluxnet data

Usage

```
getBGC05ToAmerifluxVariableNameMapping(map = character(),
  mapDefault = c(Year = "YEAR", DoY = "DOY",
    Rg = "SW_IN", Tair = "TA", Tsoil = "TS",
    rH = "RH", VPD = "VPD", Ustar = "USTAR",
    NEE_orig = "NEE_PI", H_orig = "H_PI",
    LE_orig = "LE_PI", NEE_f = "NEE_F",
    H_f = "H_F", LE_f = "LE_F", NEE_fqc = "NEE_QC",
    H_fqc = "H_QC", LE_fqc = "LE_QC"))
```

Arguments

map	named character vector: additional mapping, that extends or overwrites defaults in mapDefault
mapDefault	named character vector: default mapping

Details

Get a mapping of variable names of REddyProc defaults to names of the Berkeley 2016 release of the Fluxnet data

Author(s)

TW, Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

See Also

[renameVariablesInDataframe](#)

Examples

```
# adding mapping of foo, and overwriting mapping of DoY
getBGC05ToAmerifluxVariableNameMapping(c(foo = "F00", DoY = "doy"))
```

getExamplePath	<i>getExamplePath</i>
----------------	-----------------------

Description

checks if example filename is existing and if not tries to download it.

Usage

```
getExamplePath(filename = "Example_DETha98.txt",  
               isTryDownload = FALSE, exampleDir = getREddyProcExampleDir(),  
               remoteDir = "")
```

Arguments

filename	the name of the example file
isTryDownload	scalar logical whether to try downloading the file to package or tmp directory. Because of CRAN checks, need to explicitly set to TRUE
exampleDir	directory where examples are looked up and downloaded to
remoteDir	the URL do download from

Details

Example input text data files are not distributed with the package, because it exceeds allowed package size. Rather, the example files will be downloaded when required from github by this function.

The remoteDir (github) must be reachable, and the writing directory must be writeable.

Value

the full path name to the example data or if not available an zero-length character. Allows to check for `if (length(getExamplePath())) ...`

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

```
getFilledExampleDETha98Data
      getFilledExampleDETha98Data
```

Description

Get or create the gapfilled version of the Example_DETha98 example data

Usage

```
getFilledExampleDETha98Data(exampleDir = getREddyProcExampleDir())
```

Arguments

exampleDir the directory where the cached filled example data is stored

Value

example data.frame Example_DETha98 processed by gapfilling.

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

```
getREddyProcExampleDir
      getREddyProcExampleDir
```

Description

get the example directory inside temporary directory

Usage

```
getREddyProcExampleDir(isPreferParentDir = identical(Sys.getenv("NOT_CRAN"),
  "true"), subDir = "REddyProcExamples")
```

Arguments

isPreferParentDir	logical scalar, whether to prefer temp parent directory instead of the R-session temp-Directory. See details.
subDir	the name of the subdirectory inside the tmp directory, where examples are stored

Details

If `isPreferParentDir = FALSE` (the default), the examples will be downloaded again for each new R-session in a session specific directory as given by `tempdir`. This corresponds to CRAN policy. IF TRUE, the parent of `tempdir` will be used, so that downloads of examples are preserved across R-sessions. This is the default if environment variable "NOT_CRAN" is defined, when running from `testthat::check`.

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

See Also

[getExamplePath](#)

getTZone	<i>getTZone</i>
----------	-----------------

Description

extracts the timezone attribute from POSIXct with default on missing

Usage

```
getTZone(x, default = "GMT")
```

Arguments

x	POSIXct vector
default	time zone returned, if x has not timezone associated or attribute is the zero string

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

Examples

```
getTZone(as.POSIXct("2010-07-01 16:00:00", tz = "etc/GMT-1") )
getTZone(as.POSIXct("2010-07-01 16:00:00") )
# printed with local time zone, but actually has no tz attribute
getTZone(Sys.time())
```

globalDummyVars	<i>globalDummyVars</i>
-----------------	------------------------

Description

Dummy global variables with the same name as fields in R5 classes have been defined.
Reason: Class methods have been defined as plain functions, so that they can be better documented.
However, the assignment operator <<- has no meaning in it and therefore R CMD check complains.
As a workaround they have been defined as global variable. Do not use them.

Author(s)

(Department for Biogeochemical Integration at MPI-BGC, Jena, Germany)

LightResponseCurveFitter	<i>LightResponseCurveFitter</i>
--------------------------	---------------------------------

Description

Constructs an instance of class [LightResponseCurveFitter-class](#)

Usage

```
LightResponseCurveFitter(...)
```

Arguments

...

Author(s)

(Department for Biogeochemical Integration at MPI-BGC, Jena, Germany)

LightResponseCurveFitter-class
Class "LightResponseCurveFitter"

Description

Base class for fitting parameters to light response curves (LRC)

Concrete classes for the following LRC functions are available:

- common rectangular hyperbolic light-response: [RectangularLRCFitter-class](#)
- nonrectangular hyperbolic light-response: [NonrectangularLRCFitter-class](#)
- logistic sigmoid light-response: [LogisticSigmoidLRCFitter-class](#)

They mostly differ in their prediction of GPP by method [LightResponseCurveFitter_predictGPP](#).

Extends

All reference classes extend and inherit methods from "[envRefClass](#)".

Methods

[LightResponseCurveFitter_computeLRCGradient](#)(theta, Rg, VPD, Temp, VPD0, fixVPD, TRef):

[LightResponseCurveFitter_predictGPP](#)(Rg, ...):

[LightResponseCurveFitter_predictLRC](#)(theta, Rg, VPD, Temp, VPD0, fixVPD, TRef):

[LightResponseCurveFitter_computeCost](#)(thetaOpt, theta, iOpt, flux, sdFlux, parameterPrior, sdParameterPrior):

[LightResponseCurveFitter_optimLRC](#)(theta, iOpt, sdParameterPrior, ..., ctrl, isUsingHessian):

[LightResponseCurveFitter_isParameterInBounds](#)(theta, sdTheta, RRefNight, ctrl):

[LightResponseCurveFitter_optimLRCOnAdjustedPrior](#)(theta, iOpt, dsDay, parameterPrior, ctrl, ...):

[LightResponseCurveFitter_getOptimizedParameterPositions](#)(isUsingFixedVPD, isUsingFixedAlpha):

[LightResponseCurveFitter_optimLRCBounds](#)(theta0, parameterPrior, ..., lastGoodParameters, ctrl):

[LightResponseCurveFitter_getParameterInitials](#)(thetaPrior):

[LightResponseCurveFitter_getPriorScale](#)(thetaPrior, medianRelFluxUncertainty, nRec, ctrl):

[LightResponseCurveFitter_getPriorLocation](#)(NEEDay, RRefNight, E0):

[LightResponseCurveFitter_fitLRC](#)(dsDay, E0, sdE0, RRefNight, controlGLPart, lastGoodParameters):

[LightResponseCurveFitter_getParameterNames](#)():

Author(s)

TW

 LightResponseCurveFitter_computeCost

LightResponseCurveFitter computeCost

Description

Computing residual sum of squares for predictions vs. data of NEE

Usage

```
LightResponseCurveFitter_computeCost(thetaOpt,
  theta, iOpt, flux, sdFlux, parameterPrior,
  sdParameterPrior, ...)
```

Arguments

thetaOpt	parameter vector with components of theta0 that are optimized
theta	parameter vector with positions as in argument of LightResponseCurveFitter_getParameterNames
iOpt	position in theta that are optimized
flux	numeric: NEE (-NEE) or GPP time series [$\mu\text{molCO}_2 / \text{m}^2 / \text{s}$], should not contain NA
sdFlux	numeric: standard deviation of Flux [$\mu\text{molCO}_2 / \text{m}^2 / \text{s}$], should not contain NA
parameterPrior	numeric vector along theta: prior estimate of parameter (range of values)
sdParameterPrior	standard deviation of parameterPrior
...	other arguments to LightResponseCurveFitter_predictLRC , such as VPD0, fixVPD

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

LightResponseCurveFitter_computeLRCGradient
LightResponseCurveFitter computeLRCGradient

Description

Gradient of [LightResponseCurveFitter_predictLRC](#)

Usage

```
LightResponseCurveFitter_computeLRCGradient(theta,
      Rg, VPD, Temp, VPD0 = 10, fixVPD = (k ==
      0), TRef = 15)
```

Arguments

theta	theta [numeric] -> parameter vector (theta[1] = k (k), theta[2] = beta (beta), theta[3] = alpha, theta[4] = RRef (rb), theta[4] = E0)
Rg	ppfd [numeric] -> photosynthetic flux density [$\mu\text{mol} / \text{m}^2 / \text{s}$] or Global Radiation
VPD	VPD [numeric] -> Vapor Pressure Deficit [hPa]
Temp	Temp [degC] -> Temperature [degC]
VPD0	VPDQ0 [hPa] -> Parameters VPD0 fixed to 10 hPa according to Lasslop et al 2010
fixVPD	boolean scalar or vector of nrow(theta): fixVPD if TRUE the VPD effect is not considered and VPD is not part of the computation
TRef	numeric scalar of Temperature (degree Celsius) for reference respiration RRef

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

 LightResponseCurveFitter_fitLRC

LightResponseCurveFitter_fitLRC

Description

Optimize rectangular hyperbolic light response curve in one window

Usage

```
LightResponseCurveFitter_fitLRC(dsDay, E0,
  sdE0, RRefNight, controlGLPart = partGLControl(),
  lastGoodParameters = rep(NA_real_, 7L))
```

Arguments

dsDay	data.frame with columns NEE, Rg, Temp_C, VPD, and no NAs in NEE
E0	temperature sensitivity of respiration
sdE0	standard deviation of E_0.n
RRefNight	basal respiration estimated from night time data
controlGLPart	further default parameters (see partGLControl)
lastGoodParameters	numeric vector returned by last reasonable fit

Details

Optimization is performed for three initial parameter sets that differ by β_0 ($\times 1.3$, $\times 0.8$). From those three, the optimization result is selected that yielded the lowest misfit. Starting values are: $k = 0$, $\beta = \text{interpercentileRange}(0.03, 0.97)$ of respiration, $\alpha = 0.1$, R_{ref} from nightTime estimate. E_0 is fixed to the night-time estimate, but varies for estimating parameter uncertainty.

If `controlGLPart.l$BootUncertainty == 0L` then the covariance matrix of the parameters is estimated by the Hessian of the LRC curve at optimum. Then, the additional uncertainty and covariance with uncertainty E_0 is neglected.

If `controlGLPart.l$BootUncertainty > 0L` then the covariance matrix of the parameters is estimated by a bootstrap of the data. In each draw, E_0 is drawn from $N \sim (E_0, \text{sd}E_0)$.

If there are no estimates for more than 20% of the bootstrapped samples The an NA-result with convergence code 1001L is returned.

Value

a list, If none of the optimizations from different starting conditions converged, the parameters are NA.

thetaOpt	numeric vector of optimized parameters including the fixed ones and E_0
----------	---

iOpt	index of parameters that have been optimized, here including E0, which has been optimized prior to this function.
thetaInitialGuess	the initial guess from data
covParms	numeric matrix of the covariance matrix of parameters, including E0
convergence	integer code specifying convergence problems: \0: good convergence \, 1-1000: see optim \, 1001: too few bootstraps converged \, 1002: fitted parameters were outside reasonable bounds \, 1003: too few valid records in window \, 1004: near zero covariance in bootstrap indicating bad fit \, 1005: covariance from curvature of fit yielded negative variances indicating bad fit \, 1006: prediction of highest PAR in window was far from saturation indicating insufficient data to constrain LRC \, 1010: no temperature-respiration relationship found \, 1011: too few valid records in window (from different location: partGLFitLRCOneWindow) \

Author(s)

TW, MM Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

See Also

partGLFitLRCWindows
[LightResponseCurveFitter_optimLRCBounds](#)

LightResponseCurveFitter_getOptimizedParameterPositions

LightResponseCurveFitter_getOptimizedParameterPositions

Description

get the positions of the parameters to optimize for given Fixed

Usage

```
LightResponseCurveFitter_getOptimizedParameterPositions(isUsingFixedVPD,
isUsingFixedAlpha)
```

Arguments

isUsingFixedVPD
boolean scalar: if TRUE, VPD effect set to zero and is not optimized

isUsingFixedAlpha
boolean scalar: if TRUE, initial slope is fixed and is not optimized

Details

If subclasses extend the parameter vector, they need to override this method.

Value

integer vector of positions in parameter vector

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

LightResponseCurveFitter_getParameterInitials

LightResponseCurveFitter_getParameterInitials

Description

return the prior distribution of parameters

Usage

```
LightResponseCurveFitter_getParameterInitials(thetaPrior)
```

Arguments

thetaPrior numeric vector prior estimate of parameters

Value

a numeric matrix (3, nPar) of initial values for fitting parameters

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

LightResponseCurveFitter_getParameterNames
LightResponseCurveFitter_getParameterNames

Description

return the parameter names used by this Light Response Curve Function

Usage

```
LightResponseCurveFitter_getParameterNames()
```

Value

string vector of parameter names. Positions are important.

k	VPD effect
beta	saturation of GPP at high radiation
alpha	initial slope
RRef	basal respiration (units of provided NEE, usually $\mu\text{mol CO}_2 \text{ m}^{-2} \text{ s}^{-2}$)
E0	temperature sensitivity estimated from night-time data (K)

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

LightResponseCurveFitter_getPriorLocation
LightResponseCurveFitter_getPriorLocation

Description

return the prior distribution of parameters

Usage

```
LightResponseCurveFitter_getPriorLocation(NEEDay,  
RRefNight, E0)
```

Arguments

NEEDay	numeric vector of daytime NEE
RRefNight	numeric scalar of basal respiration estimated from night-time data
E0	numeric scalar of night-time estimate of temperature sensitivity

Value

a numeric vector with prior estimates of the parameters

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

LightResponseCurveFitter_getPriorScale

LightResponseCurveFitter_getPriorScale

Description

return the prior distribution of parameters

Usage

```
LightResponseCurveFitter_getPriorScale(thetaPrior,
    medianRelFluxUncertainty, nRec, ctrl)
```

Arguments

thetaPrior	numeric vector of location of priors
medianRelFluxUncertainty	numeric scalar: median across the relative uncertainty of the flux values, i.e. sdNEE / NEE
nRec	integer scalar: number of finite observations
ctrl	list of further controls, with entry <code>isLasslopPriorsApplied</code>

Details

The beta parameter is quite well defined. Hence use a prior with a standard deviation. The specific results are sometimes a bit sensitive to the uncertainty of the beta prior. This uncertainty is set corresponding to 20 times the median relative flux uncertainty. The prior is weighted n times the observations in the cost. Hence, overall it is using a weight of 1 / 20 of the weight of all observations. However, its not well defined if PAR does not reach saturation. Need to check before applying this prior

Value

a numeric vector with prior estimates of the parameters

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

LightResponseCurveFitter_isParameterInBounds

LightResponseCurveFitter isParameterInBounds

Description

Check if estimated parameter vector is within reasonable bounds

Usage

```
LightResponseCurveFitter_isParameterInBounds(theta,
      sdTheta, RRefNight, ctrl)
```

Arguments

theta	estimate of parameter
sdTheta	estimate of uncertainty of the parameter
RRefNight	numeric scalar: night-time based estimate of basal respiration
ctrl	list of further controls

Details

check the Beta bounds that depend on uncertainty: outside if ($\beta > 100$ and $sd\beta \geq \beta$)

Value

FALSE if parameters are outside reasonable bounds, TRUE otherwise

Author(s)

TW, MM Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

LightResponseCurveFitter_optimLRC

LightResponseCurveFitter optimLRC

Description

call the optimization function

Usage

```
LightResponseCurveFitter_optimLRC(theta,  
  iOpt, sdParameterPrior, ..., ctrl, isUsingHessian)
```

Arguments

theta	numeric vector: starting parameters
iOpt	integer vector: positions of parameters to optimize
sdParameterPrior	numeric vector: prior uncertainty
...	further arguments to the cost function
ctrl	list of further controls
isUsingHessian	scalar boolean: set to TRUE to compute Hessian at optimum

Value

list of result of `optim` amended with list

theta	numeric vector: optimized parameter vector including the fixed components
iOpt	integer vector: position of parameters that have been optimized

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

LightResponseCurveFitter_optimLRBounds
LightResponseCurveFitter_optimLRBounds

Description

Optimize parameters with refitting with some fixed parameters if outside bounds

Usage

```
LightResponseCurveFitter_optimLRBounds(theta0,
    parameterPrior, ..., lastGoodParameters,
    ctrl)
```

Arguments

theta0	initial parameter estimate
parameterPrior	prior estimate of model parameters
...	further parameters to .optimLRC, such as dsDay
lastGoodParameters	parameters vector of last successful fit
ctrl	list of further controls, such as isNeglectVPDEffect = TRUE

Details

If parameters alpha or k are outside bounds (Table A1 in Lasslop 2010), refit with some parameters fixed to values from fit of previous window.

No parameters are reported if $\alpha < 0$ or $R_{Ref} < 0$ or $\beta_0 < 0$ or $\beta_0 > 250$

Not parameters are reported if the data did not contain records that are near light saturation. This is checked by comparing the prediction at highest PAR with the beta parameter

Value

list result of optimization as of [LightResponseCurveFitter_optimLRCOnAdjustedPrior](#) with entries

theta	numeric parameter vector that includes the fixed components
iOpt	integer vector of indices of the vector that have been optimized
convergence	scalar integer indicating bad conditions on fitting (see LightResponseCurveFitter_fitLRC)

Author(s)

TW, MM Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

See Also

[LightResponseCurveFitter_fitLRC](#)

LightResponseCurveFitter_optimLRConAdjustedPrior

LightResponseCurveFitter optimLRConAdjustedPrior

Description

Lower bound flux uncertainty and adjust prior uncertainty before calling optimLRC

Usage

```
LightResponseCurveFitter_optimLRConAdjustedPrior(theta,
  iOpt, dsDay, parameterPrior, ctrl, ...)
```

Arguments

theta	numeric vector of starting values
iOpt	integer vector: positions of subset of parameters that are optimized
dsDay	dataframe of NEE, sdNEE and predictors Rg, VPD and Temp
parameterPrior	numeric vector of prior parameter estimates (corresponding to theta) # TODO rename to thetaPrior
ctrl	list of further controls
...	further arguments to LightResponseCurveFitter_optimLRC (passed to LightResponseCurveFitter_

Details

Only those records are used for optimization where both NEE and sdNEE are finite. In larger settings, already filtered at

Optimization of LRC parameters takes into account the uncertainty of the flux values. In order to avoid very strong leverage, values with a very low uncertainty (< a lower quantile) are assigned the lower quantile is assigned. This procedure downweights records with a high uncertainty, but does not apply a large leverage for records with a very low uncertainty. Avoid this correction by setting `ctrl$isBoundLowerNEEUncertainty = FALSE`

The uncertainty of the prior, that maybe derived from fluxes) is allowed to adapt to the uncertainty of the fluxes. This is done in `link{LightResponseCurveFitter_getPriorScale}`

Value

result of [LightResponseCurveFitter_optimLRC](#) with items theta, iOpt and convergence

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

LightResponseCurveFitter_predictGPP

LightResponseCurveFitter predictGPP

Description

Light Response function for GPP

Usage

LightResponseCurveFitter_predictGPP(Rg, ...)

Arguments

Rg	ppfd [numeric] -> photosynthetic flux density [$\mu\text{mol} / \text{m}^2 / \text{s}$] or Global Radiation
...	further parameters to the LRC

Details

This method must be implemented by a specific subclass. Currently there are several alternatives:

- Rectangular: [RectangularLRCFitter_predictGPP](#)
- Nonrectangular: [NonrectangularLRCFitter_predictGPP](#)
- Rectangular: [LogisticSigmoidLRCFitter_predictGPP](#)

Value

numeric vector of length(Rg) of GPP

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

See Also

[partitionNEEGL](#)

LightResponseCurveFitter_predictLRC

LightResponseCurveFitter predictLRC

Description

Light Response Function

Usage

```
LightResponseCurveFitter_predictLRC(theta,
  Rg, VPD, Temp, VPD0 = 10, fixVPD = (k ==
  0), TRef = 15)
```

Arguments

theta	numeric vector of parameters
Rg	ppfd [numeric] -> photosynthetic flux density [umol / m2 / s] or Global Radiation
VPD	VPD [numeric] -> Vapor Pressure Deficit [hPa]
Temp	Temp [degC] -> Temperature [degC]
VPD0	VPD0 [hPa] -> Parameters VPD0 fixed to 10 hPa according to Lasslop et al 2010
fixVPD	boolean scalar or vector of nrow theta: fixVPD if TRUE the VPD effect is not considered and VPD is not part of the computation
TRef	numeric scalar of Temperature (degree Celsius) for reference respiration RRef

Details

Predict ecosystem fluxes (Reco, GPP, NEP = GPP-Reco) for given parameters and environmental conditions.

The VPD effect is included according to Lasslop et al., 2010.

If theta is a matrix, a different row of parameters is used for different entries of other inputs

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

LogisticSigmoidLRCFitter

LogisticSigmoidLRCFitter

Description

Constructs an instance of class [LogisticSigmoidLRCFitter-class](#)

Usage

```
LogisticSigmoidLRCFitter(...)
```

Arguments

...

Author(s)

(Department for Biogeochemical Integration at MPI-BGC, Jena, Germany)

LogisticSigmoidLRCFitter-class

Class "LogisticSigmoidLRCFitter"

Description

Logistic sigmoid light-response curve fitting.

Extends

Class "[LightResponseCurveFitter](#)", directly.

All reference classes extend and inherit methods from "[envRefClass](#)".

Methods

```
computeGPPGradient(Rg, Amax, alpha): ~~
```

```
predictGPP(Rg, Amax, alpha): ~~
```

The following methods are inherited (from the corresponding class): predictGPP ("LightResponseCurveFitter"), getParameterNames ("LightResponseCurveFitter"), fitLRC ("LightResponseCurveFitter"), getPriorLocation ("LightResponseCurveFitter"), getPriorScale ("LightResponseCurveFitter"), getParameterInitials ("LightResponseCurveFitter"), optimLRCBounds ("LightResponseCurveFitter"), getOptimizedParameterPositions ("LightResponseCurveFitter"), optimLRConAdjustedPrior ("LightResponseCurveFitter"), isParameterInBounds ("LightResponseCurveFitter"), optimLRC ("LightResponseCurveFitter"), computeCost ("LightResponseCurveFitter"), predictLRC ("LightResponseCurveFitter"), computeLRCGradient ("LightResponseCurveFitter")

```
LogisticSigmoidLRCFitter_predictGPP
```

```
LogisticSigmoidLRCFitter predictGPP
```

Description

Logistic Sigmoid Light Response function for GPP

Usage

```
LogisticSigmoidLRCFitter_predictGPP(Rg, Amax,
  alpha)
```

Arguments

Rg	ppfd [numeric] -> photosynthetic flux density [mumol / m2 / s] or Global Radiation
Amax	vector of length(Rg): saturation (beta parameter) adjusted for effect of VPD for each line of Rg
alpha	numeric scalar or vector of length(Rg): alpha parameter: slope at Rg = 0

Details

```
GPP <- Amax * tanh(alpha * Rg / Amax)
```

Value

numeric vector of length(Rg) of GPP

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

See Also

[LightResponseCurveFitter_predictGPP](#)

NonrectangularLRCFitter

NonrectangularLRCFitter

Description

Constructs an instance of class [NonrectangularLRCFitter-class](#)

Usage

```
NonrectangularLRCFitter(...)
```

Arguments

...

Author(s)

(Department for Biogeochemical Integration at MPI-BGC, Jena, Germany)

NonrectangularLRCFitter-class

Class "NonrectangularLRCFitter"

Description

Nonrectangular hyperbolic light-response curve fitting.

Extends

Class "[LightResponseCurveFitter](#)", directly.

All reference classes extend and inherit methods from "[envRefClass](#)".

Methods

```

computeGPPGradient(Rg, Amax, alpha, logitconv): ~~
getParameterNames(): ~~
getPriorLocation(NEEday, RRefNight, E0): ~~
getPriorScale(thetaPrior, medianRelFluxUncertainty, nRec, ctrl): ~~
getOptimizedParameterPositions(isUsingFixedVPD, isUsingFixedAlpha): ~~
predictLRC(theta, Rg, VPD, Temp, VPD0, fixVPD, TRef): ~~
predictGPP(Rg, Amax, alpha, conv): ~~
computeLRCGradient(theta, Rg, VPD, Temp, VPD0, fixVPD, TRef): ~~

```

The following methods are inherited (from the corresponding class): computeLRCGradient ("LightResponseCurveFitter"), predictGPP ("LightResponseCurveFitter"), predictLRC ("LightResponseCurveFitter"), getOptimizedParameterPositions ("LightResponseCurveFitter"), getPriorScale ("LightResponseCurveFitter"), getPriorLocation ("LightResponseCurveFitter"), getParameterNames ("LightResponseCurveFitter"), fitLRC ("LightResponseCurveFitter"), getParameterInitials ("LightResponseCurveFitter"), optimLRCBounds ("LightResponseCurveFitter"), optimLRConAdjustedPrior ("LightResponseCurveFitter"), isParameterInBounds ("LightResponseCurveFitter"), optimLRC ("LightResponseCurveFitter"), computeCost ("LightResponseCurveFitter")

NonrectangularLRCFitter_getParameterNames

NonrectangularLRCFitter getParameterNames

Description

return the parameter names used by this Light Response Curve Function

Usage

```
NonrectangularLRCFitter_getParameterNames()
```

Value

string vector of parameter names. Positions are important. Adds sixth parameter, logitconv to the parameters of [LightResponseCurveFitter_getParameterNames](#)

logitconv logit-transformed convexity parameter. The value at original scale is obtained by $conv = 1 / (1 + \exp(-\logitconv))$

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

See Also[NonrectangularLRCFitter_predictGPP](#)

`NonrectangularLRCFitter_predictGPP`*NonrectangularLRCFitter predictGPP*

Description

Nonrectangular hyperbolic Light Response function for GPP

Usage

```
NonrectangularLRCFitter_predictGPP(Rg, Amax,  
  alpha, conv)
```

Arguments

Rg	ppfd [numeric] -> photosynthetic flux density [mumol / m2 / s] or Global Radiation
Amax	numeric scalar or vector of length(Rg): beta parameter adjusted for VPD effect
alpha	numeric scalar or vector of length(Rg): alpha parameter: initial slope
conv	numeric scalar or vector of length(Rg): convexity parameter (see details)

Details

This function generalizes the [RectangularLRCFitter_predictGPP](#) by adding the convexity parameter `conv`. For `conv -> 0` (`logitconv -> -Inf`): approaches the rectangular hyperbolic. For `conv -> 1` (`logitconv -> + Inf`): approaches a step function. Expected values of `conv` are about 0.7-0.9 (Moffat 2012).

Value

numeric vector of length(Rg) of GPP

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

See Also[LightResponseCurveFitter_predictGPP](#)

partGLControl	<i>partGLControl</i>
---------------	----------------------

Description

Default list of parameters for Lasslop 2010 daytime flux partitioning For highest compatibility to the pvWave code of G.Lasslop (used by first BGC-online tool) see function [partGLControlLasslopCompatible](#).

Usage

```
partGLControl(LRCFitConvergenceTolerance = 0.001,
  nLRCFitConvergenceTolerance = 0.001,
  nBootUncertainty = 30L, minNRecInDayWindow = 10L,
  isAssociateParmsToMeanOfValid = TRUE,
  isLasslopPriorsApplied = TRUE, isUsingLasslopQualityConstraints = FALSE,
  isSdPredComputed = TRUE, isFilterMeteoQualityFlag = FALSE,
  isBoundLowerNEEUncertainty = TRUE, fixedTRefAtNightTime = NA,
  isExtendTRefWindow = TRUE, smoothTempSensEstimateAcrossTime = TRUE,
  isNeglectPotRadForNight = FALSE, NRHRfunction = FALSE,
  isNeglectVPDEffect = FALSE, isRefitMissingVPDWithNeglectVPDEffect = TRUE,
  fixedTempSens = data.frame(E0 = NA_real_,
    sdE0 = NA_real_, RRef = NA_real_),
  replaceMissingSdNEEParms = c(perc = 0.2,
    minSd = 0.7), neglectNEEUncertaintyOnMissing = FALSE,
  minPropSaturation = NA, useNighttimeBasalRespiration = FALSE)
```

Arguments

LRCFitConvergenceTolerance
convergence criterion for rectangular light response curve fit. If relative improvement of reducing residual sum of squares between predictions and observations is less than this criterion, assume convergence. Decrease to get more precise parameter estimates, Increase for speedup.

nLRCFitConvergenceTolerance
convergence criterion for nonrectangular light response curve fit. Here its a factor of machine tolerance.

nBootUncertainty
number of bootstrap samples for estimating uncertainty. Set to zero to derive uncertainty from curvature of a single fit

minNRecInDayWindow
Minimum number of data points for regression

isAssociateParmsToMeanOfValid
set to FALSE to associate parameters to the first record of the window for interpolation instead of mean across valid records inside a window

isLasslopPriorsApplied
set to TRUE to apply strong fixed priors on LRC fitting. Returned parameter estimates claimed valid for some case where not enough data was available

- `isUsingLasslopQualityConstraints`
set to TRUE to avoid quality constraints additional to Lasslop 2010
- `isSdPredComputed`
set to FALSE to avoid computing standard errors of Reco and GPP for small performance increase
- `isFilterMeteoQualityFlag`
set to TRUE to use only records where quality flag of meteo drivers (radiation, temperature, VPD) is zero, i.e. non-gapfilled for parameter estimation. For prediction, the gap-filled value is used always, to produce predictions also for gaps.
- `isBoundLowerNEEuncertainty`
set to FALSE to avoid adjustment of very low uncertainties before day-Time fitting that avoids the high leverage those records with unreasonable low uncertainty.
- `fixedTRefAtNightTime`
if a finite value (degree Centigrade) is given, it is used instead of median data temperature as reference temperature in estimation of temperature sensitivity from night data
- `isExtendTRefWindow`
set to FALSE to avoid successively extending the night-time window in order to estimate a temperature sensitivity where previous estimates failed
- `smoothTempSensEstimateAcrossTime`
set to FALSE to use independent estimates of temperature sensitivity on each windows instead of a vector of E0 that is smoothed over time
- `isNeglectPotRadForNight`
set to TRUE to not use potential radiation in determining night-time data.
- `NRHRfunction` deprecated: Flag if TRUE use the NRHRF for partitioning; Now use `lrcFitter = NonrectangularLRCF`
- `isNeglectVPDEffect`
set to TRUE to avoid using VPD in the computations. This may help when VPD is rarely measured.
- `isRefitMissingVPDWithNeglectVPDEffect`
set to FALSE to avoid repeating estimation with `isNeglectVPDEffect = TRUE` trying to predict when VPD is missing
- `fixedTempSens`
- `replaceMissingSdNEEParms`
parameters for replacing missing standard deviation of NEE. see `replaceMissingSdByPercentage`. Default sets missing uncertainty to 20% of NEE but at least 0.7 flux-units (usually $\mu\text{mol CO}_2 / \text{m}^2 / \text{s}$). Specify `c(NA, NA)` to avoid replacing missings in standard deviation of NEE and to omit those records from LRC fit.
- `neglectNEEuncertaintyOnMissing`
If set to TRUE: if there are records with missing uncertainty of NEE inside one window, set all uncertainties to 1. This overrules option `replaceMissingSdNEEParms`.
- `minPropSaturation`
quality criterion for sufficient data in window. If GPP prediction of highest PAR of window is less than `minPropSaturation * (GPP at light-saturation, i.e. beta)` this indicates that PAR is not sufficiently high to constrain the shape of the LRC

`useNighttimeBasalRespiration`

set to TRUE to estimate nighttime respiration based on basal respiration estimated on nighttime data instead of basal respiration estimated from daytime data. This implements the modified daytime method from Keenan 2019 (doi:10.1038/s41559-019-0809-2)

Value

list with entries of given arguments.

Author(s)

TW Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

See Also

[partitionNEEGL](#)

Examples

```
partGLControl(nBootUncertainty = 40L)
```

`partGLControlLasslopCompatible`

partGLControlLasslopCompatible

Description

Daytime flux partitioning parms compatible with with the pvWave

Usage

```
partGLControlLasslopCompatible(nBootUncertainty = 0L,
  minNRecInDayWindow = 10L, isAssociateParmsToMeanOfValid = FALSE,
  isLasslopPriorsApplied = TRUE, isUsingLasslopQualityConstraints = TRUE,
  isBoundLowerNEEUncertainty = FALSE, fixedTRefAtNightTime = 15,
  isExtendTRefWindow = FALSE, smoothTempSensEstimateAcrossTime = FALSE,
  isRefitMissingVPDWithNeglectVPDEffect = FALSE,
  minPropSaturation = NA, isNeglectVPDEffect = FALSE,
  replaceMissingSdNEEParms = c(NA, NA),
  neglectNEEUncertaintyOnMissing = TRUE,
  ...)
```

Arguments

nBootUncertainty
0: Derive uncertainty from curvature of a single fit, neglecting the uncertainty of previously estimated temperature sensitivity, E0

minNRecInDayWindow
Minimum number of 10 valid records for regression in a single window

isAssociateParmsToMeanOfValid
associate parameters to the first record of the window for interpolation instead of mean across valid records inside a window

isLasslopPriorsApplied
Apply fixed Lasslop priors in LRC fitting.

isUsingLasslopQualityConstraints
avoid quality constraints additional to the ones in Lasslop 2010

isBoundLowerNEEuncertainty
FALSE: avoid adjustment of very low uncertainties before day-Time fitting that avoids the high leverage those records with unreasonable low uncertainty.

fixedTRefAtNightTime
use fixed (degree Centigrade) temperature sensitivity instead of median data temperature as reference temperature in estimation of temperature sensitivity from night data

isExtendTRefWindow
avoid successively extending the night-time window in order to estimate a temperature sensitivity where previous estimates failed

smoothTempSensEstimateAcrossTime
FALSE: use independent estimates of temperature sensitivity on each windows instead of a vector of E0 that is smoothed over time

isRefitMissingVPDWithNeglectVPDEffect
FALSE: avoid repeating estimation with isNeglectVPDEffect = TRUE

minPropSaturation
NA: avoid quality constraint of sufficient saturation in data This option is overruled, i.e. not considered, if option isUsingLasslopQualityConstraints = TRUE.

isNeglectVPDEffect
FALSE: do not neglect VPD effect

replaceMissingSdNEEParms
do not replace missing NEE, but see option

neglectNEEuncertaintyOnMissing
if there are records with missing uncertainty of NEE inside one window, set all sdNEE to 1. This overrules option replaceMissingSdNEEParms.

... further arguments to [partGLControl](#)

Author(s)

TW Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de>

[aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

See Also

[partGLControl](#)

Examples

```
partGLControlLasslopCompatible()
```

```
partGLExtractStandardData
```

```
partGLExtractStandardData
```

Description

Relevant columns from original input with defined names

Usage

```
partGLExtractStandardData(ds, NEEVar = paste0("NEE",
  suffixDash, "_f"), QFNEEVar = if (!missing(QFNEEVar.s)) QFNEEVar.s else paste0("NEE",
  suffixDash, "_fqc"), QFNEEValue = if (!missing(QFNEEValue.n)) QFNEEValue.n else 0,
  NEESdVar = if (!missing(NEESdVar.s)) NEESdVar.s else paste0("NEE",
  suffixDash, "_fsd"), TempVar = paste0("Tair_f"),
  QFTempVar = if (!missing(QFTempVar.s)) QFTempVar.s else paste0("Tair_fqc"),
  QFTempValue = if (!missing(QFTempValue.n)) QFTempValue.n else 0,
  VPDVar = if (!missing(VPDVar.s)) VPDVar.s else paste0("VPD_f"),
  QFVPDVar = if (!missing(QFVPDVar.s)) QFVPDVar.s else paste0("VPD_fqc"),
  QFVPDValue = if (!missing(QFVPDValue.n)) QFVPDValue.n else 0,
  RadVar = if (!missing(RadVar.s)) RadVar.s else "Rg_f",
  QFRadVar = if (!missing(QFRadVar.s)) QFRadVar.s else paste0("Rg_fqc"),
  QFRadValue = if (!missing(QFRadValue.n)) QFRadValue.n else 0,
  PotRadVar = if (!missing(PotRadVar.s)) PotRadVar.s else "PotRad_NEW",
  suffix = if (!missing(Suffix.s)) Suffix.s else "",
  NEEVar.s, QFNEEVar.s, QFNEEValue.n, NEESdVar.s,
  TempVar.s, QFTempVar.s, QFTempValue.n,
  VPDVar.s, QFVPDVar.s, QFVPDValue.n, RadVar.s,
  QFRadVar.s, QFRadValue.n, PotRadVar.s,
  Suffix.s, controlGLPart = partGLControl())
```

Arguments

ds	dataset with all the specified input columns and full days in equidistant times
NEEVar	Variable of NEE
QFNEEVar	Quality flag of variable

QFNEEValue	Value of quality flag for <code>_good_</code> (original) data
NEESdVar	Variable of standard deviation of net ecosystem fluxes
TempVar	Filled air or soil temperature variable (degC)
QFTempVar	Quality flag of filled temperature variable
QFTempValue	Value of temperature quality flag for <code>_good_</code> (original) data
VPDVar	Filled Vapor Pressure Deficit, VPD (hPa)
QFVPDVar	Quality flag of filled VPD variable
QFVPDValue	Value of VPD quality flag for <code>_good_</code> (original) data
RadVar	Filled radiation variable
QFRadVar	Quality flag of filled radiation variable
QFRadValue	Value of radiation quality flag for <code>_good_</code> (original) data
PotRadVar	Variable name of potential rad. (W / m2)
suffix	string inserted into column names before identifier for NEE column defaults (see sEddyProc_sMDSGapFillAfterUstar).
NEEVar.s	deprecated
QFNEEVar.s	deprecated
QFNEEValue.n	deprecated
NEESdVar.s	deprecated
TempVar.s	deprecated
QFTempVar.s	deprecated
QFTempValue.n	deprecated
VPDVar.s	deprecated
QFVPDVar.s	deprecated
QFVPDValue.n	deprecated
RadVar.s	deprecated
QFRadVar.s	deprecated
QFRadValue.n	deprecated
PotRadVar.s	deprecated
Suffix.s	deprecated
controlGLPart	further default parameters, see partGLControl

Details

The LRC fit usually weights NEE records by its uncertainty. In order to also use records with missing NEESdVar, uncertainty of the missing values is by default set to a conservatively high value, parameterized by `controlGLPart$replaceMissingSdNEEParms`). Controlled by argument `replaceMissingSdNEEParms` in [partGLControl](#), but overruled by argument `neglectNEEUncertaintyOnMissing`.

Value

a data.frame with columns

sDateTime	first column of ds, usually the time stamp not used, but usually first column is a dateTime is kept for aiding debug
NEE	NEE filtered for quality flay
sdNEE	standard deviation of NEE with missing values replaced
Temp	Temperature, quality filtered if isTRUE(controlGLPart\$sisFilterMeteoQualityFlag)
VPD	Water pressure deficit, quality filtered if isTRUE(controlGLPart\$sisFilterMeteoQualityFlag)
Rg	Incoming radiation
isDay	Flag that is true for daytime records
isNight	Flag that is true for nighttime records

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

partitionNEEGL

partitionNEEGL

Description

Partitioning NEE fluxes into GP and Reco after daytime method.

Usage

```
partitionNEEGL(ds, NEEVar = if (!missing(NEEVar.s)) NEEVar.s else paste0("NEE",
  suffixDash, "_f"), TempVar = if (!missing(TempVar.s)) TempVar.s else "Tair_f",
  VPDVar = if (!missing(VPDVar.s)) VPDVar.s else "VPD_f",
  RadVar = if (!missing(RadVar.s)) RadVar.s else "Rg_f",
  suffix = if (!missing(Suffix.s)) Suffix.s else "",
  NEEVar.s, TempVar.s, VPDVar.s, RadVar.s,
  Suffix.s, ..., controlGLPart = partGLControl(),
  isVerbose = TRUE, nRecInDay = 48L, lrcFitter = RectangularLRCFitter())
```


Arguments

ds	dataset with all the specified input columns and full days in equidistant times
NEEVar	Variable of NEE
TempVar	Filled air or soil temperature variable (degC)
VPDVar	Filled Vapor Pressure Deficit - VPD - (hPa)
RadVar	Filled radiation variable
suffix	string inserted into column names before identifier for NEE column defaults (see sEddyProc_sMDSGapFillAfterUstar).
NEEVar.s	deprecated
TempVar.s	deprecated
VPDVar.s	deprecated
RadVar.s	deprecated
Suffix.s	deprecated identifier for NEE column defaults (see sEddyProc_sMDSGapFillAfterUstar).
...	further arguments to partGLExtractStandardData , such as PotRadVar
controlGLPart	further default parameters, see partGLControl
isVerbose	set to FALSE to suppress output messages
nRecInDay	number of records within one day (for half-hourly data its 48)
lrcFitter	R5 class instance responsible for fitting the light response curve. Current possibilities are <code>RectangularLRCFitter()</code> , <code>NonrectangularLRCFitter()</code> , and <code>LogisticSigmoidLRCFitter()</code> .

Details

Daytime-based partitioning of measured net ecosystem fluxes into gross primary production (GPP) and ecosystem respiration (Reco)

The fit to the light-response-curve is done by default using the Rectangular hyperbolic function, as in Lasslop et al. (2010) Alternative fittings can be used by providing the corresponding subclass of [LightResponseCurveFitter-class](#) to `lrcFitter` argument. (see [LightResponseCurveFitter_predictGPP](#))

While the extrapolation uses filled data, the parameter optimization uses only measured data, i.e. with specified quality flag. With the common case where VPD is missing for fitting the LRC, by default (with `controlGLPart$isRefitMissingVPDWithNeglectVPDEffect = TRUE`) is to redo the estimation of LRC parameters with neglecting the VPD-effect. Next, in the predictions (rows) with missing VPD are then replaced with predictions based on LRC-fits that neglected the VPD effect.

Value

Reco_DT_<suffix>	predicted ecosystem respiration: $\mu\text{mol CO}_2/\text{m}^2/\text{s}$
GPP_DT_<suffix>	predicted gross primary production $\mu\text{mol CO}_2/\text{m}^2/\text{s}$

<LRC>	Further light response curve (LRC) parameters and their standard deviation depend on the used LRC (e.g. for the non-rectangular LRCC see NonrectangularLRCFitter_getParameters). They are estimated for windows and are reported with the first record of the window
FP_VARnight	NEE filtered for nighttime records (others NA)
FP_VARday	NEE filtered for daytime records (others NA)
NEW_FP_Temp	temperature after filtering for quality flag degree Celsius
NEW_FP_VPD	vapour pressure deficit after filtering for quality flag, hPa
FP_RRef_Night	basal respiration estimated from nighttime (W / m2)
FP_qc	quality flag: 0: good parameter fit, 1: some parameters out of range, required refit, 2: next parameter estimate is more than two weeks away
FP_dRecPar	records until or after closest record that has a parameter estimate associated
FP_errorcode	information why LRC-fit was not successful or was rejected, see result of LightResponseCurveFitter_fit
FP_GPP2000	predicted GPP at VPD = 0 and PAR = 2000: a surrogate for maximum photosynthetic capacity
FP_OPT_VPD	list object of fitting results including iOpt and covParms
FP_OPT_NoVPD	same as FP_OPT_VPD holding optimization results with fit neglecting the VPD effect

Author(s)

TW Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

References

Lasslop G, Reichstein M, Papale D, et al. (2010) Separation of net ecosystem exchange into assimilation and respiration using a light response curve approach: critical issues and global evaluation. *Global Change Biology*, Volume 16, Issue 1, Pages 187-208

See Also

[partGLFitNightTimeTRespSens](#)

[partGLFitLRCWindows](#)

[partGLInterpolateFluxes](#)

POSIXctToBerkeleyJulianDate
POSIXctToBerkeleyJulianDate

Description

convert POSIXct to JulianDate format used in Berkeley release

Usage

```
POSIXctToBerkeleyJulianDate(sDateTime)
```

Arguments

sDateTime POSIXct vector

Details

In the Berkeley-Release of the fluxnet data, the time is stored as an number with base10-digits representing YYYYMMddhhmm

Author(s)

TW, Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

See Also

[BerkeleyJulianDateToPOSIXct](#),

RectangularLRCFitter *RectangularLRCFitter*

Description

Constructs an instance of class [RectangularLRCFitter-class](#)

Usage

```
RectangularLRCFitter(...)
```

Arguments

...

Author(s)

(Department for Biogeochemical Integration at MPI-BGC, Jena, Germany)

 RectangularLRCFitter-class

Class "RectangularLRCFitter"

Description

Common rectangular hyperbolic light-response curve fitting.

ExtendsClass "[LightResponseCurveFitter](#)", directly.All reference classes extend and inherit methods from "[envRefClass](#)".**Methods**

computeGPPGradient(Rg, Amax, alpha): ~~

predictGPP(Rg, Amax, alpha): ~~

The following methods are inherited (from the corresponding class): predictGPP ("LightResponseCurveFitter"), getParameterNames ("LightResponseCurveFitter"), fitLRC ("LightResponseCurveFitter"), getPriorLocation ("LightResponseCurveFitter"), getPriorScale ("LightResponseCurveFitter"), getParameterInitials ("LightResponseCurveFitter"), optimLRCBounds ("LightResponseCurveFitter"), getOptimizedParameterPositions ("LightResponseCurveFitter"), optimLRConAdjustedPrior ("LightResponseCurveFitter"), isParameterInBounds ("LightResponseCurveFitter"), optimLRC ("LightResponseCurveFitter"), computeCost ("LightResponseCurveFitter"), predictLRC ("LightResponseCurveFitter"), computeLRCGradient ("LightResponseCurveFitter")

Author(s)

TW

RectangularLRCFitterCVersion
RectangularLRCFitterCVersion

Description

Constructs an instance of class [RectangularLRCFitterCVersion-class](#)

Usage

RectangularLRCFitterCVersion(...)

Arguments

...

Author(s)

(Department for Biogeochemical Integration at MPI-BGC, Jena, Germany)

RectangularLRCFitterCVersion-class
Class "RectangularLRCFitterCVersion"

Description

Common rectangular hyperbolic light-response curve fitting, implemented with faster C-based cost function.

Extends

Class "[RectangularLRCFitter](#)", directly. Class "[LightResponseCurveFitter](#)", by class "[RectangularLRCFitter](#)", distance 2.

All reference classes extend and inherit methods from "[envRefClass](#)".

Methods

computeCost(thetaOpt, theta, iOpt, flux, sdFlux, parameterPrior, sdParameterPrior, ..., VPD0, fixVPD0, ...)

The following methods are inherited (from the corresponding class): computeCost ("LightResponseCurveFitter"), computeLRCGradient ("LightResponseCurveFitter"), predictGPP ("RectangularLRCFitter"), predictLRC ("LightResponseCurveFitter"), optimLRC ("LightResponseCurveFitter"), isParameterInBounds ("LightResponseCurveFitter"), optimLRCOnAdjustedPrior ("LightResponseCurveFitter"), getOptimizedParameterPositions ("LightResponseCurveFitter"), optimLRCBounds

```
("LightResponseCurveFitter"), getParameterInitials ("LightResponseCurveFitter"), getPriorScale ("LightResponseCurveFitter"), getPriorLocation ("LightResponseCurveFitter"), fitLRC ("LightResponseCurveFitter"), getParameterNames ("LightResponseCurveFitter"), predictGPP ("LightResponseCurveFitter"), computeGPPGradient ("RectangularLRCFitter")
```

RectangularLRCFitter_predictGPP

RectangularLRCFitter predictGPP

Description

Rectangular hyperbolic Light Response function for GPP

Usage

```
RectangularLRCFitter_predictGPP(Rg, Amax,
                                alpha)
```

Arguments

Rg	ppfd [numeric] -> photosynthetic flux density [mumol / m2 / s] or Global Radiation
Amax	vector of length(Rg): saturation (beta parameter) adjusted for effect of VPD for each line of Rg
alpha	numeric scalar or vector of length(Rg): alpha parameter: slope at Rg = 0

Value

numeric vector of length(Rg) of GPP

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

See Also

[LightResponseCurveFitter_predictGPP](#)

```
renameVariablesInDataframe
      renameVariablesInDataframe
```

Description

Rename the column names of a data.frame according to a given mapping

Usage

```
renameVariablesInDataframe(data.F, mapping = getBGC05ToAmerifluxVariableNameMapping())
```

Arguments

data.F	data.frame whose columns should be renamed
mapping	named character vector: specifying a renaming (name -> value) of the variables, see e.g. getAmerifluxToBGC05VariableNameMapping

Author(s)

TW, Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

```
RHLightResponseCostC  RHLightResponseCostC
```

Description

Computing residual sum of squares for predictions vs. data of NEE implemented in C

Usage

```
RHLightResponseCostC(theta, flux, sdFlux,
  parameterPrior, sdParameterPrior, Rg,
  VPD, Temp, VPD0, fixVPD)
```

Arguments

theta
flux
sdFlux
parameterPrior
sdParameterPrior

Rg
VPD
Temp
VPD0
fixVPD

Author(s)

(Department for Biogeochemical Integration at MPI-BGC, Jena, Germany)

sEddyProc

sEddyProc

Description

create an instance of class [sEddyProc-class](#)

Usage

sEddyProc(...)

Arguments

...

Author(s)

(Department for Biogeochemical Integration at MPI-BGC, Jena, Germany)

sEddyProc-class	Class "sEddyProc"
-----------------	-------------------

Description

R5 reference class for processing of site-level half-hourly eddy data

Extends

All reference classes extend and inherit methods from "[envRefClass](#)".

Fields

private, not to be accessed directly:

sID: Object of class character with Site ID

sDATA: Object of class data.frame with (fixed) site data

sINFO: Object of class list with site information

sLOCATION: Object of class list with site location information

sTEMP: Object of class data.frame of (temporary) result data

sUSTAR: Object of class list with results from uStar Threshold estimation

Methods

Setup, import and export

[sEddyProc_initialize](#)(ID.s, Data.F, ColNames.V.s, ColPOSIXTime.s, DTS.n, ColNamesNonNumeric.V.s, Lat

[sEddyProc_sSetLocationInfo](#)(Lat_deg.n, Long_deg.n, TimeZone_h.n)

[sEddyProc_sExportResults](#)(isListColumnsExported)

[sEddyProc_sExportData](#)()

[sEddyProc_sGetData](#)()

uStar threshold estimation

[sEddyProc_sEstUstarThresholdDistribution](#)(ctrlUstarEst.l, ctrlUstarSub.l, UstarColName, NEEColName, ')

[sEddyProc_sEstUstarThold](#)(UstarColName, NEEColName, TempColName, RgColName, ...)

[sEddyProc_sPlotNEEVersusUStarForSeason](#)(season.s, Format.s, Dir.s, UstarColName, NEEColName, TempCol

Gapfilling

[sEddyProc_sCalcPotRadiation](#)(useSolartime.b)

`sEddyProc_sMDSGapFill`(Var.s, QFVar.s, QFValue.n, V1.s, T1.n, V2.s, T2.n, V3.s, T3.n, FillAll.b, Ver

`sEddyProc_sMDSGapFillAfterUStarDistr`(..., UstarThres.df, UstarSuffix.V.s)

`sEddyProc_sMDSGapFillAfterUstar`(FluxVar.s, UstarVar.s, UstarThres.df, UstarSuffix.s, FlagEntryAfter

`sEddyProc_sFillMDC`(WinDays.i, Verbose.b)

`sEddyProc_sFillLLUT`(WinDays.i, V1.s, T1.n, V2.s, T2.n, V3.s, T3.n, V4.s, T4.n, V5.s, T5.n, Verbose.b

`sEddyProc_sFillInit`(Var.s, QFVar.s, QFValue.n, FillAll.b)

Flux partitioning

`sEddyProc_sMRFluxPartition`(FluxVar.s, QFFluxVar.s, QFFluxValue.n, TempVar.s, QFTempVar.s, QFTempVal

`sEddyProc_sGLFluxPartition`(..., debug.l, isWarnReplaceColumns)

Plotting

`sEddyProc_sPlotDailySums`(Var.s, VarUnc.s, Format.s, Dir.s, unit.s, ...)

`sEddyProc_sPlotDailySumsY`(Var.s, VarUnc.s, Year.i, timeFactor.n, massFactor.n, unit.s)

`sEddyProc_sPlotHHFluxes`(Var.s, QFVar.s, QFValue.n, Format.s, Dir.s)

`sEddyProc_sPlotHHFluxesY`(Var.s, QFVar.s, QFValue.n, Year.i)

`sEddyProc_sPlotDiurnalCycle`(Var.s, QFVar.s, QFValue.n, Format.s, Dir.s)

`sEddyProc_sPlotFingerprint`(Var.s, QFVar.s, QFValue.n, Format.s, Dir.s, ...)

`sEddyProc_sPlotFingerprintY`(Var.s, QFVar.s, QFValue.n, Year.i, Legend.b, Col.V, valueLimits)

Note

for examples see [useCase vignette](#)

Author(s)

AM, TW

sEddyProc_initialize *sEddyProc initialize*

Description

Initializing sEddyProc class during sEddyProc\$new.

Usage

```
sEddyProc_initialize(ID = ID.s, Data = Data.F,
  ColNames = ColNames.V.s, ColPOSIXTime = "DateTime",
  DTS = if (!missing(DTS.n)) DTS.n else 48,
  ColNamesNonNumeric = character(0), LatDeg = NA_real_,
  LongDeg = if (!missing(Long_deg.n)) Long_deg.n else NA_real_,
  TimeZoneHour = if (!missing(TimeZone_h.n)) TimeZone_h.n else NA_integer_,
  ID.s, Data.F, ColNames.V.s, ColPOSIXTime.s,
  DTS.n, ColNamesNonNumeric.V.s, Lat_deg.n,
  Long_deg.n, TimeZone_h.n, ...)
```

Arguments

ID	String with site ID
Data	Data frame with at least three month of (half-)hourly site-level eddy data
ColNames	Vector with selected column names, the fewer columns the faster the processing
ColPOSIXTime	Column name with POSIX time stamp
DTS	Daily time steps
ColNamesNonNumeric	Names of columns that should not be checked for numeric type, e.g. season column
LatDeg	Latitude in (decimal) degrees (-90 to + 90)
LongDeg	Longitude in (decimal) degrees (-180 to + 180)
TimeZoneHour	Time zone: hours shift to UTC, e.g. 1 for Berlin
ID.s	deprecated
Data.F	deprecated
ColNames.V.s	deprecated
ColPOSIXTime.s	deprecated
DTS.n	deprecated
ColNamesNonNumeric.V.s	deprecated
Lat_deg.n	deprecated
Long_deg.n	deprecated
TimeZone_h.n	deprecated
...	('...' required for initialization of class fields)

Details

The time stamp must be provided in POSIX format, see also [fConvertTimeToPosix](#). For required properties of the time series, see [fCheckHHTimeSeries](#).

Internally the half-hour time stamp is shifted to the middle of the measurement period (minus 15 minutes or 30 minutes).

All other columns may only contain numeric data. Please use NA as a gap flag for missing data or low quality data not to be used in the processing. The columns are also checked for plausibility with warnings if outside range.

There are several fields initialized within the class.

sID is a string for the site ID.

sDATA is a data frame with site data.

sTEMP is a temporal data frame with the processing results.

sINFO is a list containing the time series information:

DIMS Number of data rows

DTS Number of daily time steps (24 or 48)

Y.START Starting year

Y.END Ending year

Y.NUMS Number of years

Y.NAME Name for years

sUSTAR_SCEN a data.frame with first column the season, and other columns different uStar threshold estimates, as returned by [usGetAnnualSeasonUStarMap](#)

sLOCATION is a list of information on site location and timezone (see [sEddyProc_sSetLocationInfo](#)).

sTEMP is a data frame used only temporally.

Value

Initialized fields of sEddyProc.

Author(s)

AMM Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

```
sEddyProc_sApplyUStarScen
      sEddyProc sApplyUStarScen
```

Description

apply a function with changing the suffix argument

Usage

```
sEddyProc_sApplyUStarScen(FUN, ...)
```

Arguments

FUN	function to be applied
...	rurther arguements to FUN

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

```
sEddyProc_sCalcPotRadiation
      sEddyProc sCalcPotRadiation
```

Description

compute potential radiation from position and time

Usage

```
sEddyProc_sCalcPotRadiation(useSolartime = TRUE,
      useSolartime.b)
```

Arguments

useSolartime	
useSolartime.b	by default corrects hour (given in local winter time)

Value

column PotRad_NEW in sTEMP

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

sEddyProc_sEstimateUstarScenarios

sEddyProc sEstimateUstarScenarios

Description

Estimate the distribution of u^* threshold by bootstrapping over data

Usage

```
sEddyProc_sEstimateUstarScenarios(ctrlUstarEst = usControlUstarEst(),
  ctrlUstarSub = usControlUstarSubsetting(),
  UstarColName = "Ustar", NEEColName = "NEE",
  TempColName = "Tair", RgColName = "Rg",
  ..., seasonFactor = usCreateSeasonFactorMonth(sDATA$sDateTime),
  nSample = 200L, probs = c(0.05, 0.5,
    0.95), isVerbose = TRUE)
```

Arguments

ctrlUstarEst	control parameters for estimating u^* on a single binned series, see usControlUstarEst
ctrlUstarSub	control parameters for subsetting time series (number of temperature and u^* classes ...), see usControlUstarSubsetting
UstarColName	column name for u^*
NEEColName	column name for NEE
TempColName	column name for air temperature
RgColName	column name for solar radiation for omitting night time data
...	further arguments to sEddyProc_sEstUstarThreshold
seasonFactor	
nSample	the number of repetitions in the bootstrap
probs	the quantiles of the bootstrap sample to return. Default is the 5%, median and 95% of the bootstrap
isVerbose	set to FALSE to omit printing progress

Details

The choice of the criterion for sufficiently turbulent conditions ($u^* >$ chosen threshold) introduces large uncertainties in calculations based on gap-filled Eddy data. Hence, it is good practice to compare derived quantities based on gap-filled data using a range of u^* threshold estimates.

This method explores the probability density of the threshold by repeating its estimation on a bootstrapped sample. By default it returns the 90% confidence interval (argument `probs`). For larger intervals the sample number need to be increased (argument `probs`).

Quality Assurance If more than `ctrlUstarEst$minValidBootProp` (default 40%) did not report a threshold, no quantiles (i.e. NA) are reported.

Value

updated class. Request results by [sEddyProc_sGetEstimatedUstarThresholdDistribution](#)

Author(s)

TW Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

See Also

[sEddyProc_sEstUstarThold](#), [sEddyProc_sGetEstimatedUstarThresholdDistribution](#), [sEddyProc_sSetUstarScens](#), [sEddyProc_sMDSGapFillUstarScens](#)

sEddyProc_sEstUstarThold

sEddyProc\$sEstUstarThreshold - Estimating ustar threshold

Description

Calling [usEstUstarThreshold](#) for class data and storing results

Usage

```
sEddyProc_sEstUstarThold(UstarColName = "Ustar",
  NEEColName = "NEE", TempColName = "Tair",
  RgColName = "Rg", ..., seasonFactor = usCreateSeasonFactorMonth(sDATA$sDateTime))
```

Arguments

UstarColName column name for UStar
 NEEColName column name for NEE
 TempColName column name for air temperature
 RgColName column name for solar radiation for omitting night time data
 ... further arguments to [usEstUstarThreshold](#)
 seasonFactor

Value

result component uStarTh of [usEstUstarThreshold](#). In addition the result is stored in class variable sUSTAR_DETAILS.

Author(s)

TW Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

sEddyProc_sEstUstarThreshold

sEddyProc\$sEstUstarThreshold - Estimating ustar threshold

Description

Calling [usEstUstarThreshold](#) for class data and storing results

Usage

```
sEddyProc_sEstUstarThreshold(UstarColName = "Ustar",
  NEEColName = "NEE", TempColName = "Tair",
  RgColName = "Rg", ..., isWarnDeprecated = TRUE)
```

Arguments

UstarColName column name for UStar
 NEEColName column name for NEE
 TempColName column name for air temperature
 RgColName column name for solar radiation for omitting night time data
 ... further arguments to [usEstUstarThreshold](#)
 isWarnDeprecated
 set to FALSE to avoid deprecated warning.

Value

result of [usEstUstarThreshold](#). In addition the result is stored in class variable sUSTAR_DETAILS and the bins as additional columns to sTemp

Author(s)

TW Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

sEddyProc_sEstUstarThresholdDistribution
sEddyProc sEstUstarThresholdDistribution

Description

Estimate the distribution of u^* threshold by bootstrapping over data

Usage

```
sEddyProc_sEstUstarThresholdDistribution(...)
```

Arguments

... further parameters to [sEddyProc_sEstimateUstarScenarios](#)

Details

This method returns the results directly, without modifying the class. It is there for portability reasons. Recommended is the usage of method [sEddyProc_sEstimateUstarScenarios](#) to update the class and then getting the results from the class by [sEddyProc_sGetEstimatedUstarThresholdDistribution](#)

Value

result of [sEddyProc_sGetEstimatedUstarThresholdDistribution](#)

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

sEddyProc_sExportData *sEddyProc sExportData*

Description

Export class internal sDATA data frame

Usage

sEddyProc_sExportData()

Value

Return data frame sDATA with time stamp shifted back to original.

Author(s)

AMM Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

sEddyProc_sExportResults
sEddyProc sExportResults

Description

Export class internal sTEMP data frame with result columns

Usage

sEddyProc_sExportResults(isListColumnsExported = FALSE)

Arguments

isListColumnsExported
if TRUE export list columns in addition to numeric columns, such as the covariance matrices of the the day-time-partitioning LRC fits

Value

Return data frame sTEMP with results.

Author(s)

AMM Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

sEddyProc_sFillInit *sEddyProc\$sFillInit - Initialize gap filling*

Description

Initializes data frame sTEMP for newly generated gap filled data and qualifiers.

Usage

```
sEddyProc_sFillInit(Var.s, QFVar.s = "none",
  QFValue.n = NA_real_, FillAll.b = TRUE)
```

Arguments

Var.s	Variable to be filled
QFVar.s	Quality flag of variable to be filled
QFValue.n	Value of quality flag for <code>_good_</code> (original) data, other data is set to missing
FillAll.b	Fill all values to estimate uncertainties

Details

Description of newly generated variables with gap filled data and qualifiers:

VAR_orig - Original values used for gap filling

VAR_f - Original values and gaps filled with mean of selected datapoints (condition depending on gap filling method)

VAR_fqc - Quality flag assigned depending on gap filling method and window length (0 = original data, 1 = most reliable, 2 = medium, 3 = least reliable)

VAR_fall - All values considered as gaps (for uncertainty estimates)

VAR_fall_qc - Quality flag assigned depending on gap filling method and window length (1 = most reliable, 2 = medium, 3 = least reliable)

VAR_fnum - Number of datapoints used for gap-filling

VAR_fsd - Standard deviation of datapoints used for gap filling (uncertainty)

VAR_fmeth - Method used for gap filling (1 = similar meteo condition (sFillLUT with Rg, VPD, Tair), 2 = similar meteo (sFillLUT with Rg only), 3 = mean diurnal course (sFillMDC))

VAR_fwin - Full window length used for gap filling

Long gaps (larger than 60 days) are not filled.

Author(s)

AMM Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

sEddyProc_sFillLUT *sEddyProc sFillLUT*

Description

Look-Up Table (LUT) algorithm of up to five conditions within prescribed window size

Usage

```
sEddyProc_sFillLUT(WinDays.i, V1.s = "none",
  T1.n = NA_real_, V2.s = "none", T2.n = NA_real_,
  V3.s = "none", T3.n = NA_real_, V4.s = "none",
  T4.n = NA_real_, V5.s = "none", T5.n = NA_real_,
  Verbose.b = TRUE)
```

Arguments

WinDays.i	Window size for filling in days
V1.s	Condition variable 1
T1.n	Tolerance interval 1
V2.s	Condition variable 2
T2.n	Tolerance interval 2
V3.s	Condition variable 3
T3.n	Tolerance interval 3
V4.s	Condition variable 4
T4.n	Tolerance interval 4
V5.s	Condition variable 5
T5.n	Tolerance interval 5
Verbose.b	Print status information to screen

Details

Quality flags

- 1: at least one variable and nDay <= 14
- 2: three variables and nDay in [14,56) or one variable and nDay in [14,28)
- 3: three variables and nDay > 56 or one variable and nDay > 28

Value

LUT filling results in sTEMP data frame.

Author(s)

AMM Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

sEddyProc_sFillMDC *sEddyProc sFillMDC*

Description

Mean Diurnal Course (MDC) algorithm based on average values within +/- one hour of adjacent days

Usage

```
sEddyProc_sFillMDC(WinDays.i, Verbose.b = TRUE)
```

Arguments

WinDays.i	Window size for filling in days
Verbose.b	Print status information to screen

Details

Quality flag

- 1: nDay <= 1
- 2: nDay [2,5)
- 3: nDay > 5

Value

MDC filling results in sTEMP data frame.

Author(s)

AMM Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

sEddyProc_sGetData *sEddyProc sGetData*

Description

Get class internal sDATA data frame

Usage

```
sEddyProc_sGetData()
```

Value

Return data frame sDATA.

Author(s)

AMM Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

sEddyProc_sGetEstimatedUstarThresholdDistribution
sEddyProc sGetEstimatedUstarThresholdDistribution

Description

return the results of [sEddyProc_sEstimateUstarScenarios](#)

Usage

```
sEddyProc_sGetEstimatedUstarThresholdDistribution()
```

Value

A data.frame with columns aggregationMode, year, and UStar estimate based on the non-resampled data. The other columns correspond to the quantiles of Ustar estimate for given probabilities (argument probs) based on the distribution of estimates using resampled the data.

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

See Also

[sEddyProc_sSetUstarScenarios](#)

sEddyProc_sGetUstarScenarios

sEddyProc sGetUstarScenarios

Description

get the current uStar processing scenarios

Usage

```
sEddyProc_sGetUstarScenarios()
```

Details

the associated suffixes can be retrieved by `colnames(myClass$sGetUstarScenarios())[-1]`

Value

a data.frame with first column listing each season and other column a scenario of uStar thresholds.

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

See Also

[sEddyProc_sSetUstarScenarios](#)

sEddyProc_sGLFluxPartition
sEddyProc sGLFluxPartition

Description

Daytime-based Flux partitioning after Lasslop et al. (2010)

Usage

```
sEddyProc_sGLFluxPartition(..., debug = list(useLocaltime = FALSE),
  debug.1, isWarnReplaceColumns = TRUE)
```

Arguments

...	arguments to <code>partitionNEEGL</code> in addition to the dataset such as <code>suffix</code>
debug	List with debugging control.
	useLocaltime if TRUE use local time zone instead of geo-solar time to compute potential radiation
debug.1	deprecated, renamed to debug
isWarnReplaceColumns	set to FALSE to avoid the warning on replacing output columns

Details

Daytime-based partitioning of measured net ecosystem fluxes into gross primary production (GPP) and ecosystem respiration (Reco)

Value

Flux partitioning results are in sTEMP data frame of the class.

Author(s)

MM, TW Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

References

Lasslop G, Reichstein M, Papale D, et al. (2010) Separation of net ecosystem exchange into assimilation and respiration using a light response curve approach: critical issues and global evaluation. *Global Change Biology*, Volume 16, Issue 1, Pages 187-208

sEddyProc_sGLFluxPartitionUStarScens
sEddyProc sGLFluxPartitionUStarScens

Description

Flux partitioning after Lasslop et al. (2010)

Usage

```
sEddyProc_sGLFluxPartitionUStarScens(...)
```

Arguments

... arguments to [sEddyProc_sGLFluxPartition](#)

Details

Daytime-based partitioning of measured net ecosystem fluxes into gross primary production (GPP) and ecosystem respiration (Reco) for all u^* threshold scenarios.

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

sEddyProc_sMDSGapFill *sEddyProc sMDSGapFill*

Description

MDS gap filling algorithm adapted after the PV-Wave code and paper by Markus Reichstein.

Usage

```
sEddyProc_sMDSGapFill(Var = Var.s, QFVar = if (!missing(QFVar.s)) QFVar.s else "none",
  QFValue = if (!missing(QFValue.n)) QFValue.n else NA_real_,
  V1 = if (!missing(V1.s)) V1.s else "Rg",
  T1 = if (!missing(T1.n)) T1.n else 50,
  V2 = if (!missing(V2.s)) V2.s else "VPD",
  T2 = if (!missing(T2.n)) T2.n else 5,
  V3 = if (!missing(V3.s)) V3.s else "Tair",
```

```

T3 = if (!missing(T3.n)) T3.n else 2.5,
FillAll = if (!missing(FillAll.b)) FillAll.b else TRUE,
isVerbose = if (!missing(Verbose.b)) Verbose.b else TRUE,
suffix = if (!missing(Suffix.s)) Suffix.s else "",
minNWarnRunLength = if (Var == "NEE") 4 *
    .self$sINFO$DTS/24 else NA_integer_,
Var.s, QFVar.s, QFValue.n, V1.s, T1.n,
V2.s, T2.n, V3.s, T3.n, FillAll.b, Verbose.b,
Suffix.s)

```

Arguments

Var	Variable to be filled
QFVar	
QFValue	
V1	Condition variable 1 (default: Global radiation 'Rg' in W m-2)
T1	Tolerance interval 1 (default: 50 W m-2)
V2	Condition variable 2 (default: Vapour pressure deficit 'VPD' in hPa)
T2	Tolerance interval 2 (default: 5 hPa)
V3	Condition variable 3 (default: Air temperature 'Tair' in degC)
T3	Tolerance interval 3 (default: 2.5 degC)
FillAll	Fill all values to estimate uncertainties
isVerbose	Print status information to screen
suffix	String suffix needed for different processing setups on the same dataset (for explanations see below)
minNWarnRunLength	scalar integer: warn if nubmer of subsequent numerically equal values exceeds this number. Set to Inf or NA for no warnings. defaults for "NEE" to records across 4 hours and no warning for others.
Var.s	deprecated
QFVar.s	deprecated
QFValue.n	deprecated
V1.s	deprecated
T1.n	deprecated
V2.s	deprecated
T2.n	deprecated
V3.s	deprecated
T3.n	deprecated
FillAll.b	deprecated
Verbose.b	deprecated
Suffix.s	deprecated

Details

Initialize temporal data frame sTEMP for newly generated gap filled data and qualifiers, see [sEddyProc_sFillInit](#) for explanations on suffixes.

Runs of numerically equal numbers hint to problems of the data and cause unreasonable estimates of uncertainty. This routine warns the user.

MDS gap filling algorithm calls the subroutines Look Up Table [sEddyProc_sFillLUT](#) and Mean Diurnal Course [sEddyProc_sFillMDC](#) with different window sizes as described in the reference.

To run dataset only with MDC algorithm [sEddyProc_sFillMDC](#), set condition variable V1 to 'none'.

Different processing setups on the same dataset Attention: When processing the same site data set with different setups for the gap filling or flux partitioning (e.g. due to different ustar filters), a string suffix is needed! This suffix is added to the result column names to distinguish the results of the different setups.

Value

Gap filling results in sTEMP data frame (with renamed columns).

Author(s)

AMM, TW Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

References

Reichstein, M. et al. (2005) On the separation of net ecosystem exchange into assimilation and ecosystem respiration: review and improved algorithm. *Global Change Biology*, 11, 1424-1439.

sEddyProc_sMDSGapFillAfterUstar

sEddyProc sMDSGapFillAfterUstar

Description

sEddyProc\$sMDSGapFillAfterUstar - MDS gap filling algorithm after u* filtering

Usage

```
sEddyProc_sMDSGapFillAfterUstar(fluxVar,
  uStarVar = "Ustar", uStarTh = .self$sGetUstarScenarios()[
    c("season", uStarSuffix), drop = FALSE],
  uStarSuffix = "uStar", isFlagEntryAfterLowTurbulence = FALSE,
  isFilterDayTime = FALSE, swThr = 10,
  RgColName = "Rg", ...)
```

Arguments

fluxVar	Flux variable to gap fill after ustar filtering
uStarVar	Column name of friction velocity u^* (ms ⁻¹), default 'Ustar'
uStarTh	data.frame with first column, season names, and second column estimates of uStar Threshold. Alternatively, a single value to be used as threshold for all records. If only one value is given, it is used for all records.
uStarSuffix	Different suffixes required are for different u^* scenarios
isFlagEntryAfterLowTurbulence	Set to TRUE for flagging the first entry after low turbulence as bad condition (by value of 2).
isFilterDayTime	Set to TRUE to also filter day-time values, default only filters night-time data
swThr	threshold of solar radiation below which data is marked as night time respiration.
RgColName	Column name of incoming short wave radiation
...	Other arguments passed to sEddyProc_sMDSGapFill

Details

Calling [sEddyProc_sMDSGapFill](#) after filtering for (provided) friction velocity u^*

The u^* threshold(s) are provided with argument `uStarTh` for filtering the conditions of low turbulence. After filtering, the data is gap filled using the MDS algorithm [sEddyProc_sMDSGapFill](#).

With `isFlagEntryAfterLowTurbulence` set to TRUE, to be more conservative, in addition to the data acquired when `uStar` is below the threshold, the first half hour measured with good turbulence conditions after a period with low turbulence is also removed (Papaple et al. 2006).

Value

Vector with quality flag from filtering (here 0: good data , 1: low turbulence, 2: first half hour after low turbulence , 3: no threshold available, 4: missing `uStar` value) Gap filling results are in `sTEMP` data frame (with renamed columns) that can be retrieved by [sEddyProc_sExportResults](#).

Author(s)

AMM, TW Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

See Also

- [sEddyProc_sEstimateUstarScenarios](#) and `link{sEddyProc_sEstUstarThold}` for estimating the u^* threshold from the data.
- [sEddyProc_sMDSGapFillUstarScens](#) for automated gapfilling for several scenarios of u^* threshold estimates.

```
sEddyProc_sMDSGapFillAfterUStarDistr
      sEddyProc sMDSGapFillAfterUStarDistr
```

Description

GapFilling for several filters of estimated friction velocity Ustar thresholds.

Usage

```
sEddyProc_sMDSGapFillAfterUStarDistr(...,
  uStarTh, uStarSuffixes = colnames(uStarTh)[-1])
```

Arguments

...	other arguments to sEddyProc_sMDSGapFillAfterUstar and sEddyProc_sMDSGapFill such as <code>fluxVar</code>
<code>uStarTh</code>	data.frame with first column, season names, and remaining columns different estimates of uStar Threshold. If the data.frame has only one row, then each uStar threshold estimate is applied to the entire dataset. Entries in first column must match levels in argument <code>seasonFactor</code>
<code>uStarSuffixes</code>	String vector to distinguish result columns for different ustar values. Its length must correspond to column numbers in <code>UstarThres.m.n</code> .

Details

This method is superseded by [sEddyProc_sMDSGapFillUstarScens](#) and only there for backward portability.

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

sEddyProc_sMDSGapFillUStarScens

sEddyProc sMDSGapFillUStarScens

Description

GapFilling for several filters of estimated friction velocity Ustar thresholds.

Usage

sEddyProc_sMDSGapFillUStarScens(...)

Arguments

... other arguments to [sEddyProc_sMDSGapFillAfterUstar](#) and [sEddyProc_sMDSGapFill](#) such as fluxVar

Details

sEddyProc\$sMDSGapFillUStarDistr: calling [sEddyProc_sMDSGapFillAfterUstar](#) for several filters of friction velocity Ustar.

The scenarios need to be set before by [sEddyProc_sSetUstarScenarios](#) or accepting the defaults annual estimates of `link{sEddyProc_sEstimateUstarScenarios}`.

Then the difference between output columns NEE_U05_f and NEE_U95_f corresponds to the uncertainty introduced by the uncertain estimate of the u^* threshold.

Value

Matrix (columns correspond to u^* Scenarios) with quality flag from filtering ustar (0 - good data, 1 - filtered data)

Gap filling results in sTEMP data frame (with renamed columns), that can be retrieved by [sEddyProc_sExportResults](#). Each of the outputs is calculated for several u^* r-estimates and distinguished by a suffix after the variable. E.g. with an an entry "U05" in uStarSuffixes in [sEddyProc_sSetUstarScenarios](#) the corresponding filled NEE can be found in output column "NEE_U05_f".

Author(s)

TW Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

See Also

[../doc/useCase.html](#)

```
sEddyProc_sMRFluxPartition
      sEddyProc sMRFluxPartition
```

Description

Nighttime-based partitioning of net ecosystem fluxes into gross fluxes GPP and REco

Usage

```
sEddyProc_sMRFluxPartition(FluxVar = if (missing(FluxVar.s)) "NEE_f" else FluxVar.s,
  QFFluxVar = if (missing(QFFluxVar.s)) "NEE_fqc" else QFFluxVar.s,
  QFFluxValue = if (missing(QFFluxValue.n)) 0L else QFFluxValue.n,
  TempVar = if (missing(TempVar.s)) "Tair_f" else TempVar.s,
  QFTempVar = if (missing(QFTempVar.s)) "Tair_fqc" else QFTempVar.s,
  QFTempValue = if (missing(QFTempValue.n)) 0 else QFTempValue.n,
  RadVar = if (missing(RadVar.s)) "Rg" else RadVar.s,
  TRef = if (missing(T_ref.n)) 273.15 +
    15 else T_ref.n, suffix = if (missing(Suffix.s)) "" else Suffix.s,
  FluxVar.s, QFFluxVar.s, QFFluxValue.n,
  TempVar.s, QFTempVar.s, QFTempValue.n,
  RadVar.s, T_ref.n, Suffix.s, debug.l,
  debug = if (!missing(debug.l)) debug.l else list(useLocaltime = FALSE),
  parsE0Regression = list())
```

Arguments

FluxVar	Variable name of column with original and filled net ecosystem fluxes (NEE)
QFFluxVar	Quality flag of NEE variable
QFFluxValue	Value of quality flag for <code>_good_</code> (original) data
TempVar	Filled air- or soil temperature variable (degC)
QFTempVar	Quality flag of filled temperature variable
QFTempValue	Value of temperature quality flag for <code>_good_</code> (original) data
RadVar	Unfilled (original) radiation variable
TRef	Reference temperature in Kelvin (degK) used in <code>fLloydTaylor</code> for regressing Flux and Temperature
suffix	String suffix needed for different processing setups on the same dataset (for explanations see below)
FluxVar.s	deprecated
QFFluxVar.s	deprecated
QFFluxValue.n	deprecated
TempVar.s	deprecated
QFTempVar.s	deprecated

QFTempValue.n	deprecated
RadVar.s	deprecated
T_ref.n	deprecated
Suffix.s	deprecated
debug.l	deprecated
debug	List with debugging control (passed also to sEddyProc_sRegrE0fromShortTerm for providing fixedE0 = myE0).
	useLocaltime see details on solar vs local time
parsE0Regression	list with further parameters passed down to sEddyProc_sRegrE0fromShortTerm and fRegrE0fromShortTerm, such as TempRange

Details

Description of newly generated variables with partitioning results: • PotRad - Potential radiation

- FP_NEEnight - Good (original) NEE nighttime fluxes used for flux partitioning
- FP_Temp - Good (original) temperature measurements used for flux partitioning
- E_0 - Estimated temperature sensitivity
- R_ref - Estimated reference respiration
- Reco - Estimated ecosystem respiration
- GPP_f - Estimated gross primary production

Background This partitioning is based on the regression of nighttime respiration with temperature using the Lloyd-Taylor-Function [fLloydTaylor](#). First the temperature sensitivity E_0 is estimated from short term data, see sEddyProc_sRegrE0fromShortTerm. Next the reference temperature R_ref is estimated for successive periods throughout the whole dataset (see sEddyProc_sRegrRref). These estimates are then used to calculate the respiration during daytime and nighttime and with this GPP. Attention: Gap filling of the net ecosystem fluxes (NEE) and temperature measurements (Tair or Tsoil) is required prior to the partitioning!

Selection of daytime data based on solar time The respiration-temperature regression is very sensitive to the selection of night- and daytime data. Nighttime is selected by a combined threshold of current solar radiation and potential radiation. The current implementation calculates potential radiation based on exact solar time, based on latitude and longitude. (see [fCalcPotRadiation](#)) Therefore it might differ from implementations that use local winter clock time instead.

Different processing setups on the same dataset Attention: When processing the same site data set with different setups for the gap filling or flux partitioning (e.g. due to different uStar filters), a string suffix is needed! This suffix is added to the result column names to distinguish the results of the different setups. If a suffix is provided and if the defaults for FluxVar and QFFluxVar are used, the suffix will be added to their variable names (e.g. 'NEE_f' will be renamed to 'NEE_uStar_f' and 'NEE_fqc' to 'NEE_uStar_fqc' for the suffix = 'uStar'). Currently, this works only with defaults of FluxVar = 'NEE_f' and QFFluxVar = 'NEE_fqc'.

Value

Flux partitioning results (see variables in details) in sTEMP data frame (with renamed columns). On success, return value is NULL. On failure an integer scalar error code is returned: -111 if regression of E_0 failed due to insufficient relationship in the data.

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

References

Reichstein M, Falge E, Baldocchi D et al. (2005) On the separation of net ecosystem exchange into assimilation and ecosystem respiration: review and improved algorithm. *Global Change Biology*, 11, 1424-1439.

sEddyProc_sMRFluxPartitionUStarScens

sEddyProc sMRFluxPartitionUStarScens

Description

Flux partitioning after Reichstein et al. (2005)

Usage

```
sEddyProc_sMRFluxPartitionUStarScens(...)
```

Arguments

... arguments to [sEddyProc_sMRFluxPartition](#)

Details

Nighttime-based partitioning of measured net ecosystem fluxes into gross primary production (GPP) and ecosystem respiration (Reco) for all u^* threshold scenarios.

Value

NULL, it adds output columns in the class

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

sEddyProc_sPlotDailySums

sEddyProc\$sPlotDailySums - Image with daily sums of each year

Description

Generates image in specified format ('pdf' or 'png') with daily sums, see also [sEddyProc_sPlotDailySumsY](#).

Usage

```
sEddyProc_sPlotDailySums(Var = Var.s, VarUnc = "none",
  Format = if (!missing(Format.s)) Format.s else "pdf",
  Dir = if (!missing(Dir.s)) Dir.s else "plots",
  unit = if (!missing(unit.s)) unit.s else "gC/m2/day",
  ..., Var.s, VarUnc.s, Format.s, Dir.s,
  unit.s)
```

Arguments

Var	(Filled) variable to plot
VarUnc	Uncertainty estimates for variable
Format	Graphics file format ('pdf' or 'png')
Dir	Directory for plotting
unit	unit of the daily sums
...	further arguments to sEddyProc_sPlotDailySumsY , such as timeFactor and massFactor.
Var.s	deprecated
VarUnc.s	deprecated
Format.s	deprecated
Dir.s	deprecated
unit.s	deprecated

Author(s)

KS, AMM Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

sEddyProc_sPlotDailySumsY

sEddyProc\$sPlotDailySumsY - Plot daily sum of specified year

Description

The daily sums for a single year are plotted to the current device, scaled to all data. The daily sums are only calculated for days with complete data. This function first computes the average flux for each day. If the original unit is not "per day", then it need to be converted to "per day" by argument timeFactor. Furthermore, a change of the mass unit is provided by argument massFactor. The default parameters assume original units of mumol CO₂ / m² / second and convert to gC / m² / day. The conversion factors allow plotting variables with different units

Usage

```
sEddyProc_sPlotDailySumsY(Var = Var.s, VarUnc = "none",
  Year = Year.i, timeFactor = if (!missing(timeFactor.n)) timeFactor.n else 3600 *
    24, massFactor = if (!missing(massFactor.n)) massFactor.n else (44.0096/1e+06) *
    (12.011/44.0096), unit = if (!missing(unit.s)) unit.s else "gC/m2/day",
  data = cbind(sDATA, sTEMP), dts = sINFO$DTS,
  Var.s, VarUnc.s, Year.i, timeFactor.n,
  massFactor.n, unit.s)
```

Arguments

Var	(Filled) variable to plot
VarUnc	Uncertainty estimates for variable
Year	Year to plot
timeFactor	time conversion factor with default per second to per day
massFactor	mass conversion factor with default from mumol CO ₂ to g C
unit	unit of the daily sums
data	data.frame with variables to plot
dts	numeric integer
Var.s	
VarUnc.s	

```

Year.i
timeFactor.n
massFactor.n
unit.s

```

Author(s)

AMM, KS Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

```

sEddyProc_sPlotDiurnalCycle
      sEddyProc sPlotDiurnalCycle

```

Description

Generates image in specified format ('pdf' or 'png') with diurnal cycles.

Usage

```

sEddyProc_sPlotDiurnalCycle(Var = Var.s,
  QFVar = if (!missing(QFVar.s)) QFVar.s else "none",
  QFValue = if (!missing(QFValue.n)) QFValue.n else NA_real_,
  Format = if (!missing(Format.s)) Format.s else "pdf",
  Dir = if (!missing(Dir.s)) Dir.s else "plots",
  data = cbind(sDATA, sTEMP), dts = sINFO$DTS,
  Var.s, QFVar.s, QFValue.n, Format.s,
  Dir.s)

```

Arguments

Var	Variable to plot
QFVar	Quality flag of variable to be filled
QFValue	Value of quality flag for data to plot
Format	Graphics file format (e.g. 'pdf', 'png')
Dir	Directory for plotting
data	data.frame with variables to plot
dts	numeric integer
Var.s	deprecated
QFVar.s	deprecated

QFValue.n	deprecated
Format.s	deprecated
Dir.s	deprecated

Author(s)

KS, AMM Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

sEddyProc_sPlotFingerprint

sEddyProc sPlotFingerprint

Description

Generates fingerprint in file

Usage

```
sEddyProc_sPlotFingerprint(Var = Var.s, QFVar = "none",
  QFValue = if (!missing(QFValue.n)) QFValue.n else NA_real_,
  Format = if (!missing(Format.s)) Format.s else "pdf",
  Dir = if (!missing(Dir.s)) Dir.s else "plots",
  ..., Var.s, QFVar.s = "none", QFValue.n = NA_real_,
  Format.s = "pdf", Dir.s = "plots")
```

Arguments

Var	Variable to plot
QFVar	Quality flag of variable to be filled
QFValue	Value of quality flag for data to plot
Format	
Dir	Directory for plotting
...	further arguments to sEddyProc_sPlotFingerprintY
Var.s	Variable to plot
QFVar.s	Quality flag of variable to be filled
QFValue.n	Value of quality flag for data to plot
Format.s	Graphics file format (e.g. 'pdf', 'png')
Dir.s	Directory for plotting

Author(s)

KS, AMM Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

sEddyProc_sPlotFingerprintY

sEddyProc sPlotFingerprintY

Description

Plot fingerprint for a single year scaled to all data.

Usage

```
sEddyProc_sPlotFingerprintY(Var = Var.s,
  QFVar = "none", QFValue = if (!missing(QFValue.n)) QFValue.n else NA_real_,
  Year = Year.i, onlyLegend = if (!missing(Legend.b)) Legend.b else F,
  colors = if (!missing(Col.V)) Col.V else colorRampPalette(c("#00007F",
    "blue", "#007FFF", "cyan", "#7FFF7F",
    "yellow", "#FF7F00", "red", "#7F0000"))(50),
  valueLimits = range(Plot.V.n, na.rm = TRUE),
  data = cbind(sDATA, sTEMP), dts = sINFO$dts,
  Var.s, QFVar.s, QFValue.n, Year.i, Legend.b,
  Col.V)
```

Arguments

Var	Variable to plot
QFVar	
QFValue	
Year	Year to plot
onlyLegend	Plot only legend
colors	Color palette for fingerprint plot (can be also defined by user), i.e. color scale argument to image
valueLimits	values outside this range will be set to the range borders to avoid distorting colour scale e.g. valueLimits = quantile(EddyProc.C\$sDATA\$NEE, prob = c(0.05, 0.95), na.rm = TRUE)
data	data.frame with variables to plot
dts	numeric integer of hours in day
Var.s	deprecated

QFVar.s	deprecated
QFValue.n	deprecated
Year.i	deprecated
Legend.b	deprecated
Col.V	deprecated

Author(s)

AMM, KS, TW Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

sEddyProc_sPlotHHFluxes

sEddyProc sPlotHHFluxes

Description

Produce image-plot with half-hourly fluxes for each year

Usage

```
sEddyProc_sPlotHHFluxes(Var = Var.s, QFVar = if (!missing(QFVar.s)) QFVar.s else "none",
  QFValue = if (!missing(QFValue.n)) QFValue.n else NA_real_,
  Format = if (!missing(Format.s)) Format.s else "pdf",
  Dir = if (!missing(Dir.s)) Dir.s else "plots",
  Var.s, QFVar.s, QFValue.n, Format.s,
  Dir.s)
```

Arguments

Var	Variable to plot
QFVar	Quality flag of variable to be filled
QFValue	Value of quality flag for data to plot
Format	Graphics file format (e.g. 'pdf', 'png')
Dir	Directory for plotting
Var.s	deprecated
QFVar.s	deprecated
QFValue.n	deprecated
Format.s	deprecated
Dir.s	deprecated

Details

Generates image in specified format ('pdf' or 'png') with half-hourly fluxes and their daily means, see also [sEddyProc_sPlotHHFluxesY](#).

Author(s)

KS, AMM Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

sEddyProc_sPlotHHFluxesY

sEddyProc sPlotHHFluxesY

Description

Plot half-hourly fluxes for a single year scaled to all data.

Usage

```
sEddyProc_sPlotHHFluxesY(Var = Var.s, QFVar = if (!missing(QFVar.s)) QFVar.s else "none",
  QFValue = if (!missing(QFValue.n)) QFValue.n else NA_real_,
  Year = Year.i, data = cbind(sDATA, sTEMP),
  dts = sINFO$DTS, Var.s, QFVar.s, QFValue.n,
  Year.i)
```

Arguments

Var	Variable to plot
QFVar	
QFValue	
Year	Year to plot
data	data.frame with variables to plot
dts	numeric integer
Var.s	deprecated
QFVar.s	deprecated
QFValue.n	deprecated
Year.i	deprecated

Author(s)

AMM, KS Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

sEddyProc_sPlotNEEVersusUStarForSeason

sEddyProc sPlotNEEVersusUStarForSeason

Description

Generates image in specified format ('pdf' or 'png')

Usage

```
sEddyProc_sPlotNEEVersusUStarForSeason(season = levels(data$season)[1],
  format = "pdf", dir = "plots", UstarColName = "Ustar",
  NEEColName = "NEE", TempColName = "Tair",
  WInch = 16 * 0.394, HInchSingle = 6 *
    0.394, ..., data = cbind(sDATA, sTEMP,
    sUSTAR_DETAILS$bins[, c("uStarBin",
    "tempBin")]))
```

Arguments

season	string of season, i.e. time period to plot
format	string of Graphics file format ('pdf' or 'png')
dir	string of Directory for plotting
UstarColName	column name for UStar
NEEColName	column name for NEE
TempColName	column name for air temperature
WInch	width of the plot in inches, defaults to 16cm
HInchSingle	height of a subplot in inches, defaults to 6cm
...	other arguments to <code>.plotNEEVersusUStarTempClass</code> , such as <code>xlab</code> and <code>ylab</code> axis label strings
data	

Author(s)

TW Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

sEddyProc_sSetLocationInfo

sEddyProc sSetLocationInfo

Description

set Location and time Zone information to sLOCATION

Usage

```
sEddyProc_sSetLocationInfo(LatDeg = if (!missing(Lat_deg.n)) Lat_deg.n else NA_real_,
  LongDeg = if (!missing(Long_deg.n)) Long_deg.n else NA_real_,
  TimeZoneHour = if (!missing(TimeZone_h.n)) TimeZone_h.n else NA_integer_,
  Lat_deg.n, Long_deg.n, TimeZone_h.n)
```

Arguments

LatDeg	Latitude in (decimal) degrees (-90 to + 90)
LongDeg	Longitude in (decimal) degrees (-180 to + 180)
TimeZoneHour	Time zone: hours shift to UTC, e.g. 1 for Berlin
Lat_deg.n	deprecated
Long_deg.n	deprecated
TimeZone_h.n	deprecated

Author(s)

TW Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

```
sEddyProc_sSetUstarScenarios
      sEddyProc sSetUstarScenarios
```

Description

set uStar processing scenarios

Usage

```
sEddyProc_sSetUstarScenarios(uStarTh, uStarSuffixes = colnames(uStarTh)[-1])
```

Arguments

uStarTh	data.frame as returned by usGetAnnualSeasonUstarMap or usGetSeasonalSeasonUstarMap : First column, season names, and remaining columns different estimates of uStar Threshold. If uStarTh has only one row, then each uStar threshold estimate is applied to the entire dataset. Entries in first column must match levels in argument seasonFactor of sEddyProc_sEstUstarThresholdDistribution
uStarSuffixes	the suffixes appended to result column names by default the column names of uStarTh unless its first season column

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

See Also

[sEddyProc_sGetUstarScenarios](#)

```
sEddyProc_sSetUstarSeasons
      sEddyProc sSetUstarSeasons
```

Description

Defining seasons for the uStar threshold estimation

Usage

```
sEddyProc_sSetUstarSeasons(seasonFactor = usCreateSeasonFactorMonth(sDATA$sDateTime))
```

Arguments

seasonFactor factor for subsetting times with different uStar threshold (see details)

Value

class with updated seasonFactor

Author(s)

TW Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

sEddyProc_sTKFluxPartition

sEddyProc sTKFluxPartition

Description

Modified daytime-based Flux partitioning after Keenan et al. (2019)

Usage

```
sEddyProc_sTKFluxPartition(..., controlGLPart = partGLControl())
```

Arguments

... arguments to [sEddyProc_sGLFluxPartition](#) in addition to the dataset
controlGLPart further default parameters, such as suffix

Value

Flux partitioning results are in sTEMP data frame of the class.

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

sEddyProc_sTKFluxPartitionUStarScens
sEddyProc sTKFluxPartitionUStarScens

Description

Flux partitioning after Lasslop 2015

Usage

sEddyProc_sTKFluxPartitionUStarScens(...)

Arguments

... arguments to [sEddyProc_sTKFluxPartition](#)

Details

Daytime-based partitioning of measured net ecosystem fluxes into gross primary production (GPP) and ecosystem respiration (Reco) for all u^* threshold scenarios.

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

sEddyProc_useAnnualUStarThresholds
sEddyProc useAnnualUStarThresholds

Description

use seasonal estimates of uStar thresholds

Usage

sEddyProc_useAnnualUStarThresholds()

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

See Also

[sEddyProc_sSetUstarScenarios](#), [sEddyProc_useSeaonsalUStarThresholds](#)

sEddyProc_useSeaonsalUStarThresholds

sEddyProc useSeaonsalUStarThresholds

Description

use seasonal estimates of uStar trhesholds

Usage

sEddyProc_useSeaonsalUStarThresholds()

Author(s)

Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

See Also

[sEddyProc_sSetUstarScenarios](#), [sEddyProc_useSeaonsalUStarThresholds](#)

 usControlUstarEst *usControlUstarEst*

Description

Default list of parameters for determining UStar of a single binned series

Usage

```
usControlUstarEst(ustPlateauFwd = 10, ustPlateauBack = 6,
  plateauCrit = 0.95, corrCheck = 0.5,
  firstUStarMeanCheck = 0.2, isOmitNoThresholdBins = TRUE,
  isUsingCPTSeveralT = FALSE, isUsingCPT = FALSE,
  minValidUStarTempClassesProp = 0.2, minValidBootProp = 0.4,
  minNuStarPlateau = 3L)
```

Arguments

ustPlateauFwd number of subsequent uStar bin values to compare to in fwd mode

ustPlateauBack number of subsequent uStar bin values to compare to in back mode

plateauCrit significant differences between a uStar value and the mean of a "plateau"

corrCheck threshold value for correlation between Tair and u * data

firstUStarMeanCheck
if first uStar bin average of a class is already larger than this value, the temperature class is skipped.

isOmitNoThresholdBins
if TRUE, bins where no threshold was found are ignored. Set to FALSE to report highest uStar bin for these cases

isUsingCPTSeveralT
set to TRUE to use changePointDetection without binning uStar but with additionally changed aggregation scheme for several temperature classifications

isUsingCPT set to TRUE to use changePointDetection without binning uStar before in usual aggregation method (good for comparing methods, but not recommended, overruled by isUsingCPTSeveralT = TRUE)

minValidUStarTempClassesProp
seasons, in which only less than this proportion of temperature classes a threshold was detected, are excluded from aggregation

minValidBootProp
minimum proportion of bootstrap samples for which a threshold was detected. Below this proportion NA quantiles are reported.

minNuStarPlateau
minimum number of records in plateau, threshold must be larger than mean of this many bins

Author(s)

TW Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

See Also

[usEstUstarThresholdSingleFw2Binned](#), [usControlUstarSubsetting](#)

Examples

```
usControlUstarEst()
```

```
usControlUstarSubsetting
      usControlUstarSubsetting
```

Description

Default list of parameters for subsetting the data for uStarThreshold estimation

Usage

```
usControlUstarSubsetting(taClasses = 7, UstarClasses = 20,
  swThr = 10, minRecordsWithinTemp = 100,
  minRecordsWithinSeason = 160, minRecordsWithinYear = 3000,
  isUsingOneBigSeasonOnFewRecords = TRUE)
```

Arguments

taClasses	set number of air temperature classes
UstarClasses	set number of Ustar classes
swThr	nighttime data threshold for solar radiation [Wm ⁻²]
minRecordsWithinTemp	integer scalar: the minimum number of Records within one Temperature-class
minRecordsWithinSeason	integer scalar: the minimum number of Records within one season
minRecordsWithinYear	integer scalar: the minimum number of Records within one year
isUsingOneBigSeasonOnFewRecords	boolean scalar: set to FALSE to avoid aggregating all seasons on too few records

Author(s)

TW Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

See Also

[usEstUstarThresholdSingleFw2Binned](#) , [usControlUstarSubsetting](#)

Examples

```
usControlUstarSubsetting()
```

```
usCreateSeasonFactorMonth
      usCreateSeasonFactorMonth
```

Description

Compute year-spanning Seasonfactor by starting month

Usage

```
usCreateSeasonFactorMonth(dates, month = as.POSIXlt(dates)$mon +
  1L, year = as.POSIXlt(dates)$year + 1900L,
  startMonth = c(3, 6, 9, 12))
```

Arguments

dates	POSIXct vector of length of the data set to be filled, specifying the center-time of each record
month	integer (1-12) vector of length of the data set to be filled, specifying the month for each record
year	integer vector of length of the data set to be filled, specifying the year
startMonth	integer vector specifying the starting month for each season, counting from one. Default is (Dez, Jan, Feb)(Mar, April, May)(June, July, August), (Sept, Oct, Nov)

Details

Compute factors to denote the season for uStar-Filtering by specifying starting months, with continuous seasons spanning year boundaries. If Jan is not a starting month, then the first months of each year will be part of the last period in the year. E.g. with the default the fourth period of the first year consists of Jan, Feb, Dec.

REddyProc internally works with a timestamp 15 minutes after the start of each half hour. When providing the dates argument, user may shift the start time by `dates = myDataset$DateTime + 15 * 60`

Value

Integer vector `length(dates)`, with each unique value representing one season

Author(s)

TW Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

See Also

[usCreateSeasonFactorMonthWithinYear](#), [usCreateSeasonFactorYday](#), [usCreateSeasonFactorYdayYear](#)

`usCreateSeasonFactorMonthWithinYear`

usCreateSeasonFactorMonthWithinYear

Description

Compute year-bounded Seasonfactor by starting month

Usage

```
usCreateSeasonFactorMonthWithinYear(dates,
  month = as.POSIXlt(dates)$mon + 1, year = as.POSIXlt(dates)$year +
  1900, startMonth = c(3, 6, 9, 12))
```

Arguments

<code>dates</code>	POSIXct vector of length of the data set to be filled, specifying the center-time of each record
<code>month</code>	integer (1-12) vector of length of the data set to be filled, specifying the month for each record
<code>year</code>	integer vector of length of the data set to be filled, specifying the year

`startMonth` integer vector specifying the starting month for each season, counting from one. Default is (Dez, Jan, Feb)(Mar, April, May)(June, July, August), (Sept, Oct, Nov)

Details

Calculate factors to denote the season for uStar-Filtering by specifying starting months, with seasons not spanning year boundaries. If Jan is not a starting month, then the first months of each year will be part of the last period in the year. E.g. with the default the fourth period of the first year consists of Jan, Feb, Dec.

Value

Integer vector length(`dates`), with each unique value representing one season

Author(s)

TW Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

See Also

[usCreateSeasonFactorMonth](#)

usCreateSeasonFactorYday

usCreateSeasonFactorYday

Description

Compute year-spanning Seasonfactor by starting year-day

Usage

```
usCreateSeasonFactorYday(dates, yday = as.POSIXlt(dates)$yday +
  1L, year = as.POSIXlt(dates)$year + 1900L,
  startYday = c(335, 60, 152, 244))
```

Arguments

dates	POSIXct vector of length of the data set to be filled, specifying the center-time of each record
yday	integer (1-366) vector of length of the data set to be filled, specifying the day of the year (1..366) for each record
year	integer vector of length of the data set to be filled, specifying the year
startYday	integer vector (1-366) specifying the starting yearDay for each season in increasing order

Details

With default parameterization, dates are assumed to denote begin or center of the eddy time period.

If working with dates that denote the end of the period, use `yday = as.POSIXlt(fGetBeginOfEddyPeriod(dates))$yday`

Value

Integer vector of length `nrow(ds)`, each unique class representing one season

Author(s)

TW Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

See Also

[usCreateSeasonFactorMonth](#)

usCreateSeasonFactorYdayYear

usCreateSeasonFactorYdayYear

Description

Compute year-spanning Seasonfactor by starting year and yearday

Usage

```
usCreateSeasonFactorYdayYear(dates, yday = as.POSIXlt(dates)$yday +
  1L, year = as.POSIXlt(dates)$year + 1900L,
  starts)
```

Arguments

dates	POSIXct vector of length of the data set to be filled, specifying the center-time of each record
yday	integer (1-366) vector of length of the data set to be filled, specifying the day of the year (1..366) for each record
year	integer vector of length of the data set to be filled, specifying the year
starts	data.frame with first column specifying the starting yday (integer 1-366) and second column the year (integer e.g. 1998) for each season in increasing order

Details

With default parameterization, dates are assumed to denote begin or center of the eddy time period.

If working with dates that denote the end of the period, use `yday = as.POSIXlt(fGetBeginOfEddyPeriod(dates))$yday`

Value

Integer vector of length `nrow(ds)`, each unique class representing one season

Author(s)

TW Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

See Also

[usCreateSeasonFactorMonth](#)

usEstUstarThreshold *usEstUstarThreshold - Estimating ustar threshold*

Description

Estimate the Ustar threshold by aggregating the estimates for seasonal and temperature subsets.

Usage

```
usEstUstarThreshold(ds, seasonFactor = usCreateSeasonFactorMonth(ds$dateTime),
  yearOfSeasonFactor = usGetYearOfSeason(seasonFactor,
    ds$dateTime), ctrlUstarEst = usControlUstarEst(),
  ctrlUstarSub = usControlUstarSubsetting(),
  fEstimateUstarBinned = usEstUstarThresholdSingleFw2Binned,
  isCleaned = FALSE)
```

Arguments

ds	data.frame with columns "sDateTime", "Ustar", "NEE", "Tair", and "Rg"
seasonFactor	factor for subsetting times (see details)
yearOfSeasonFactor	named integer vector: for each seasonFactor level, get the year (aggregation period) that this season belongs to
ctrlUstarEst	control parameters for estimating uStar on a single binned series, see usControlUstarEst
ctrlUstarSub	control parameters for subsetting time series (number of temperature and Ustar classes ...), see usControlUstarSubsetting
fEstimateUstarBinned	function to estimate UStar on a single binned series, see usEstUstarThresholdSingleFw2Binned
isCleaned	set to TRUE, if the data was cleaned already, to avoid expensive call to usGetValidUstarIndices .

Details

The threshold for sufficiently turbulent conditions u^* (Ustar) is estimated for different subsets of the time series. From the estimates for each season (each value in seasonFactor) the maximum of all seasons of one year is reported as estimate for this year. Within each season the time series is split by temperature classes. Among these Ustar estimates, the median is reported as season value.

In order to split the seasons, the uses must provide a vector with argument seasonFactor. All positions with the same factor, belong to the same season. It is conveniently generated by one of the following functions:

- [usCreateSeasonFactorMonth](#) (default DJF-MAM-JJA-SON with December from previous to January of the year)
- [usCreateSeasonFactorMonthWithinYear](#) (default DJF-MAM-JJA-SON with December from the same year)
- [usCreateSeasonFactorYday](#) for a refined specification of season starts.
- [usCreateSeasonFactorYdayYear](#) for specifying different seasons season between years.

The estimation of Ustar on a single binned series can be selected argument fEstimateUstarBinned.

- [usEstUstarThresholdSingleFw1Binned](#)
- [usEstUstarThresholdSingleFw2Binned](#) (default)

This function is called by

- [sEddyProc_sEstUstarThold](#) which stores the result in the class variables (sUSTAR and sDATA).
- [sEddyProc_sEstUstarThresholdDistribution](#) which additionally estimates median and confidence intervals for each year by bootstrapping the original data within seasons.

For inspecting the NEE~uStar relationship plotting is provided by [sEddyProc_sPlotNEEversusUstarForSeason](#)

change point detection (CPT) method With specifying `ctrlUstarEst = usControlUstarEst(isUsingCPTSeveralT = change point detection is applied instead of the moving point test (e.g. with Fw2Binned).`

The sometimes sensitive binning of uStar values within a temperature class is avoided. Further, possible spurious thresholds are avoid by testing that the model with a threshold fits the data better than a model without a threshold using a likelihood ratio test. In addition, with CPT seasons are excluded where a threshold was detected in only less than `ctrlUstarEst$minValidUstarTempClassesProp` (default 20%) of the temperature classes.

Note, that this method often gives higher estimates of the $u * \text{threshold}$.

One-big-season fallback If there are too few records within one year, or when no season yielded a finite $u * \text{Threshold}$ estimate, then the yearly $u * \text{Th}$ is estimated by pooling the data from seasons within one `seasonYear`. The user can suppress using pooled data on few records by providing option `ctrlUstarSub$isUsingOneBigSeasonOnFewRecords = FALSE` (see [usControlUstarSubsetting](#))

Value

A list with entries `data.frame` with columns "aggregationMode", "seasonYear", "season", "uStar" with rows for "single": the entire aggregate (median across years), "seasonYear": each year (maximum across seasons or estimate on pooled data), "season": each season (median across temperature classes)

<code>seasonYear</code>	<code>data.frame</code> listing results for year with columns "seasonYear", "uStarMaxSeason" the maximum across seasonal estimates within the year, "uStarPooled" the estimate based on data pooled across the year (only calculated on few valid records or on <code>uStarMaxSeason</code> was nonfinite), "nRec" number of valid records (only if the pooled estimate was calculated), "uStarAggr" chosen estimate, corresponding to <code>uStarPooled</code> if this was calculated, or <code>uStarMaxSeason</code> or <code>uStarTh</code> across years if the former was non-finite
<code>season</code>	<code>data.frame</code> listing results for each season, "nRec" the number of valid records, "uStarSeasonEst" the estimate for based on data within the season (median across temperature classes), "uStarAggr" chose estimate, corresponding to <code>uStarSeasonEst</code> , or the yearly <code>seasonYear\$uStarAggr</code> , if the former was non-finite
<code>tempInSeason</code>	numeric matrix (<code>nTemp</code> x <code>nAggSeason</code>): estimates for each temperature subset for each season
<code>bins</code>	columns <code>season</code> , <code>tempBin</code> and <code>uStarBin</code> for each record of input <code>ds</code> reporting classes of similar environmental conditions that the record belongs to.

Author(s)

TW, OM Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

References

Ustar filtering following the idea in Papale, D. et al. (2006) Towards a standardized processing of net ecosystem exchange measured with eddy covariance technique: algorithms and uncertainty estimation. *Biogeosciences* 3(4): 571-583.

usEstUstarThresholdSingleFw1Binned
usEstUstarThresholdSingleFw1Binned

Description

estimate the Ustar threshold for single subset, using FW1 algorithm

Usage

```
usEstUstarThresholdSingleFw1Binned(Ust_bins.f,  
  ctrlUstarEst = usControlUstarEst())
```

Arguments

Ust_bins.f data.frame with columns NEE_avg and Ust_avg, of Ustar bins
ctrlUstarEst parameter list, see [usControlUstarEst](#) for defaults and description

Details

Relying on binned NEE and Ustar

Author(s)

TW, OM Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

References

inspired by Papale 2006

```
usEstUstarThresholdSingleFw2Binned
      usEstUstarThresholdSingleFw2Binned
```

Description

estimate the Ustar threshold for single subset, using FW2 algorithm

Usage

```
usEstUstarThresholdSingleFw2Binned(Ust_bins.f,
      ctrlUstarEst = usControlUstarEst())
```

Arguments

Ust_bins.f data.frame with columns NEE_avg and Ust_avg, of Ustar bins
 ctrlUstarEst parameter list, see [usControlUstarEst](#) for defaults and description

Details

Demand that threshold is higher than ctrlUstarEst\$minNuStarPlateau records. If fewer records

Author(s)

TW, OM Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

```
usGetAnnualSeasonUStarMap
      usGetAnnualSeasonUStarMap
```

Description

extract mapping season -> uStar columns from Distribution result

Usage

```
usGetAnnualSeasonUStarMap(uStarTh)
```

Arguments

uStarTh result of [sEddyProc_sEstUstarThresholdDistribution](#) or [sEddyProc_sEstUstarThreshold\\$uStarT](#)

Value

a data frame with first column the season, and other columns different uStar threshold estimates

Author(s)

TW Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

usGetSeasonalSeasonUStarMap

usGetSeasonalSeasonUStarMap

Description

extract mapping season -> uStar columns from Distribution result

Usage

usGetSeasonalSeasonUStarMap(uStarTh)

Arguments

uStarTh result of [sEddyProc_sEstUstarThresholdDistribution](#) or [sEddyProc_sEstUstarThreshold\\$uStarT](#)

Details

from result of [sEddyProc_sEstUstarThresholdDistribution](#)

Value

a data frame with first column the season, and other columns different uStar threshold estimates

Author(s)

TW Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

usGetYearOfSeason	<i>usGetYearOfSeason</i>
-------------------	--------------------------

Description

determine the year of the record of middle of seasons

Usage

```
usGetYearOfSeason(seasonFactor, sDateTime.v)
```

Arguments

seasonFactor	factor vector of length data: for each record which season it belongs to
sDateTime.v	POSIX.t vector of length data: for each record: center of half-hour period (corresponding to sDATA\$sDateTime)

Value

named integer vector, with names corresponding to seasons

Author(s)

TW Department for Biogeochemical Integration at MPI-BGC, Jena, Germany <REddyProc-help@bgc-jena.mpg.de> [cph], Thomas Wutzler <twutz@bgc-jena.mpg.de> [aut, cre], Markus Reichstein <mreichstein@bgc-jena.mpg.de> [aut], Antje Maria Moffat <antje.moffat@bgc.mpg.de> [aut, trl], Olaf Menzer <omenzer@bgc-jena.mpg.de> [ctb], Mirco Migliavacca <mmiglia@bgc-jena.mpg.de> [aut], Kerstin Sickel <ksickel@bgc-jena.mpg.de> [ctb, trl], Ladislav Šigut <sigut.l@czechglobe.cz> [ctb]

Index

*Topic **classes**

LightResponseCurveFitter-class, [31](#)
LogisticSigmoidLRCFitter-class, [45](#)
NonrectangularLRCFitter-class, [47](#)
RectangularLRCFitter-class, [60](#)
RectangularLRCFitterCVersion-class,
[61](#)
sEddyProc-class, [65](#)

*Topic **dataset**

DEGebExample, [7](#)
Example_DETha98, [8](#)

*Topic **package**

REddyProc-package, [5](#)
_REddyProc_RHLightResponseCostC
(RHLightResponseCostC), [63](#)

BerkeleyJulianDateToPOSIXct, [6](#), [18](#), [59](#)

check, [29](#)

DEGebExample, [7](#)

envRefClass, [31](#), [45](#), [47](#), [60](#), [61](#), [65](#)

Example_DETha98, [8](#)

fCalcAVPfromVMFandPress, [9](#)

fCalcETfromLE, [9](#)

fCalcExtRadiation, [10](#)

fCalcPotRadiation, [11](#), [88](#)

fCalcRHfromAVPandTair, [12](#)

fCalcSVPfromTair, [13](#)

fCalcVPDfromRHandTair, [5](#), [13](#)

fCheckHHTimeSeries, [14](#), [68](#)

fConvertCtoK, [15](#)

fConvertGlobalToVisible, [16](#)

fConvertKtoC, [16](#)

fConvertTimeToPosix, [5](#), [7](#), [17](#), [68](#)

fConvertVisibleWm2toPhotons, [19](#)

filterLongRuns, [19](#)

filterLongRunsInVector, [20](#), [20](#)

fLloydTaylor, [21](#), [88](#)

fLoadEuroFlux16, [22](#), [23](#)

fLoadTXTIntoDataframe, [5](#), [23](#)

fWriteDataframeToFile, [24](#)

getAmerifluxToBGC05VariableNameMapping,
[25](#), [63](#)

getBGC05ToAmerifluxVariableNameMapping,
[26](#)

getExamplePath, [27](#), [29](#)

getFilledExampleDETha98Data, [28](#)

getREddyProcExampleDir, [28](#)

getTZone, [29](#)

globalDummyVars, [30](#)

image, [94](#)

LightResponseCurveFitter, [30](#), [45](#), [47](#), [60](#),
[61](#)

LightResponseCurveFitter-class, [31](#)

LightResponseCurveFitter_computeCost,
[31](#), [32](#), [42](#)

LightResponseCurveFitter_computeLRCGradient,
[31](#), [33](#)

LightResponseCurveFitter_fitLRC, [31](#), [34](#),
[41](#), [42](#), [58](#)

LightResponseCurveFitter_getOptimizedParameterPositions,
[31](#), [35](#)

LightResponseCurveFitter_getParameterInitials,
[31](#), [36](#)

LightResponseCurveFitter_getParameterNames,
[31](#), [32](#), [37](#), [48](#)

LightResponseCurveFitter_getPriorLocation,
[31](#), [37](#)

LightResponseCurveFitter_getPriorScale,
[31](#), [38](#)

LightResponseCurveFitter_isParameterInBounds,
[31](#), [39](#)

LightResponseCurveFitter_optimLRC, [31](#),
[40](#), [42](#), [43](#)

- LightResponseCurveFitter_optimLRCBounds, [31, 35, 41](#)
- LightResponseCurveFitter_optimLRConAdjustedPredictions, [31, 41, 42](#)
- LightResponseCurveFitter_predictGPP, [31, 43, 47, 49, 57, 62](#)
- LightResponseCurveFitter_predictLRC, [31–33, 44](#)
- LogisticSigmoidLRCFitter, [45](#)
- LogisticSigmoidLRCFitter-class, [45](#)
- LogisticSigmoidLRCFitter_predictGPP, [43, 46](#)

- NonrectangularLRCFitter, [47](#)
- NonrectangularLRCFitter-class, [47](#)
- NonrectangularLRCFitter_getParameterNames, [48, 58](#)
- NonrectangularLRCFitter_predictGPP, [43, 49, 49](#)

- optim, [35, 40](#)

- partGLControl, [34, 50, 53–55, 57](#)
- partGLControlLasslopCompatible, [50, 52](#)
- partGLExtractStandardData, [54, 57](#)
- partitionNEEGL, [44, 52, 56, 80](#)
- POSIXctToBerkeleyJulianDate, [7, 59](#)

- RectangularLRCFitter, [59, 61](#)
- RectangularLRCFitter-class, [60](#)
- RectangularLRCFitter_predictGPP, [43, 49, 62](#)
- RectangularLRCFitterCVersion, [61](#)
- RectangularLRCFitterCVersion-class, [61](#)
- REddyProc (REddyProc-package), [5](#)
- REddyProc-package, [5](#)
- renameVariablesInDataframe, [25, 26, 63](#)
- RHLightResponseCostC, [63](#)

- sDATA (globalDummyVars), [30](#)
- sEddyProc, [64](#)
- sEddyProc-class, [65](#)
- sEddyProc_initialize, [5, 65, 67](#)
- sEddyProc_sApplyUStarScen, [69](#)
- sEddyProc_sCalcPotRadiation, [65, 69](#)
- sEddyProc_sEstimateUstarScenarios, [6, 70, 73, 78, 84](#)
- sEddyProc_sEstUstarThold, [65, 71, 71, 110](#)
- sEddyProc_sEstUstarThreshold, [5, 70, 72, 113, 114](#)
- sEddyProc_sEstUstarThresholdDistribution, [5, 65, 73, 99, 110, 113, 114](#)
- sEddyProc_sExportData, [65, 74](#)
- sEddyProc_sExportResults, [65, 74, 84, 86](#)
- sEddyProc_sFillInit, [66, 75, 83](#)
- sEddyProc_sFillLUT, [66, 76, 83](#)
- sEddyProc_sFillMDC, [66, 77, 83](#)
- sEddyProc_sGetData, [65, 78](#)
- sEddyProc_sGetEstimatedUstarThresholdDistribution, [6, 71, 73, 78](#)
- sEddyProc_sGetUstarScenarios, [6, 79, 99](#)
- sEddyProc_sGLFluxPartition, [6, 66, 80, 81, 100](#)
- sEddyProc_sGLFluxPartitionUStarScens, [6, 81](#)
- sEddyProc_sMDSGapFill, [5, 66, 81, 84–86](#)
- sEddyProc_sMDSGapFillAfterUstar, [5, 55, 57, 66, 83, 85, 86](#)
- sEddyProc_sMDSGapFillAfterUstarDistr, [66, 85](#)
- sEddyProc_sMDSGapFillUStarScens, [6, 71, 84, 85, 86](#)
- sEddyProc_sMRFluxPartition, [5, 66, 87, 89](#)
- sEddyProc_sMRFluxPartitionUStarScens, [6, 89](#)
- sEddyProc_sPlotDailySums, [6, 66, 90](#)
- sEddyProc_sPlotDailySumsY, [66, 90, 91](#)
- sEddyProc_sPlotDiurnalCycle, [6, 66, 92](#)
- sEddyProc_sPlotFingerprint, [6, 66, 93](#)
- sEddyProc_sPlotFingerprintY, [66, 93, 94](#)
- sEddyProc_sPlotHHFluxes, [6, 66, 95](#)
- sEddyProc_sPlotHHFluxesY, [66, 96, 96](#)
- sEddyProc_sPlotNEEversusUStarForSeason, [65, 97, 110](#)
- sEddyProc_sSetLocationInfo, [65, 68, 98](#)
- sEddyProc_sSetUstarScenarios, [6, 71, 79, 86, 99, 102](#)
- sEddyProc_sSetUstarSeasons, [99](#)
- sEddyProc_sTKFluxPartition, [100, 101](#)
- sEddyProc_sTKFluxPartitionUStarScens, [6, 101](#)
- sEddyProc_useAnnualUstarThresholds, [101](#)
- sEddyProc_useSeasonalUstarThresholds, [102, 102](#)
- sID (globalDummyVars), [30](#)
- sINFO (globalDummyVars), [30](#)
- sLOCATION (globalDummyVars), [30](#)

sPlotFingerprint
 (sEddyProc_sPlotFingerprint),
 93

sTEMP (globalDummyVars), 30

strptime, 7

sUSTAR (globalDummyVars), 30

tempdir, 29

usControlUstarEst, 70, 103, 110, 112, 113

usControlUstarSubsetting, 70, 104, 104,
 105, 110, 111

usCreateSeasonFactorMonth, 105, 107–110

usCreateSeasonFactorMonthWithinYear,
 106, 106, 110

usCreateSeasonFactorYday, 106, 107, 110

usCreateSeasonFactorYdayYear, 106, 108,
 110

usEstUstarThreshold, 71–73, 109

usEstUstarThresholdSingleFw1Binned,
 110, 112

usEstUstarThresholdSingleFw2Binned,
 104, 105, 110, 113

usGetAnnualSeasonUstarMap, 68, 99, 113

usGetSeasonalSeasonUstarMap, 99, 114

usGetYearOfSeason, 115