

Package ‘SWMPPrExtension’

November 6, 2019

Type Package

Title Functions for Analyzing and Plotting Estuary Monitoring Data

Version 1.1.2

Maintainer Dave Eslinger <dave.eslinger@noaa.gov>

Description Tools for performing routine analysis and plotting tasks with environmental data from the System Wide Monitoring Program of the National Estuarine Research Reserve System <<http://cdmo.baruch.sc.edu/>>. This package builds on the functionality of the SWMPPr package <<https://cran.r-project.org/web/packages/SWMPPr/index.html>>, which is used to retrieve and organize the data. The combined set of tools address common challenges associated with continuous time series data for environmental decision making, and are intended for use in annual reporting activities.

References:

Beck, Marcus W. (2016) <ISSN 2073-4859><<https://journal.r-project.org/archive/2016-1/beck.pdf>>

Rudis, Bob (2014) <<https://rud.is/b/2014/11/16/moving-the-earth-well-alaska-hawaii-with-r/>>.

United States Environmental Protec-

tion Agency (2015) <https://cfpub.epa.gov/si/si_public_record_Report.cfm?dirEntryId=327030>.

United States Environmental Protec-

tion Agency (2012) <<http://citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.646.1973&rep=rep1&type=pdf>>.

BugReports <https://github.com/NOAA-OCM/SWMPPrExtension/issues>

License CC0

Encoding UTF-8

LazyData true

Depends R (>= 3.2.0), SWMPPr

Imports broom, dplyr, EnvStats, flextable, ggplot2, ggthemes, grDevices, leaflet, lubridate, magrittr, maptools, methods, officer, tidyr, scales, RColorBrewer, rgdal, rgeos, rlang, sp

RoxygenNote 6.1.1

NeedsCompilation no

Author Julie Padilla [aut, ctb],
 Marcus Beck [ctb],
 Kimberly Cressman [ctb],
 Dave Eslinger [cre, ctb],
 Bob Rudis [ctb]

Repository CRAN

Date/Publication 2019-11-06 14:10:02 UTC

R topics documented:

annual_range	3
assign_season	4
cbm_spatial	6
create_sk_flextable_list	7
create_sk_national_ft_reserves	8
create_sk_national_ft_results	9
elknmnut	10
elksmwq	10
elk_spatial	11
ft_col_names	11
generate_results_table	12
generate_station_table	13
geographic_unique_stations	13
get_reserve	14
get_shp_name	15
get_sites	15
get_site_code	16
get_site_coordinates	17
historical_daily_range	17
historical_range	19
import_local_nut	21
lm_p_labs	22
load_shp_file	23
national_sk_map	23
raw_boxplot	25
remove_inf_and_nan	26
reserve_locs	27
res_custom_map	27
res_custom_sk_map	29
res_local_map	30
res_national_map	32
res_sk_map	33
sampling_stations	35
seasonal_barplot	36
seasonal_boxplot	37
seasonal_dot	40
set_date_breaks	42

set_date_break_labs	43
sk_seasonal	43
sk_tidy	45
std_param_check	45
summarise_handoff_files	46
threshold_criteria_plot	47
threshold_identification	50
threshold_percentile_plot	52
threshold_summary	54
title_labeler	56
us_aea	57
y_count_labeler	57
y_labeler	58

Index	60
--------------	-----------

annual_range	<i>Annual Range Timeseries</i>
--------------	--------------------------------

Description

Assess variability within each season for a single year

Usage

```
annual_range(swmpr_in, ...)
```

```
## S3 method for class 'swmpr'
annual_range(swmpr_in, param = NULL, target_yr = NULL,
  criteria = NULL, free_y = FALSE, log_trans = FALSE,
  converted = FALSE, criteria_lab = "WQ Threshold",
  plot_title = FALSE, plot = TRUE, ...)
```

Arguments

swmpr_in	input swmpr object
...	additional arguments passed to other methods. See assign_season
param	chr string of variable to plot
target_yr	numeric, the target year that should be compared against the historic range. If target year is not specified then the dot will not be plotted.
criteria	numeric, a numeric criteria that will be plotted as a horizontal line
free_y	logical, should the y-axis be free? Defaults to FALSE. If FALSE, defaults to zero, unless negative values are present. If TRUE, y-axis limits are selected by ggplot
log_trans	logical, should y-axis be log? Defaults to FALSE
converted	logical, were the units converted from the original units used by CDMO? Defaults to FALSE. See <code>y_labeler</code> for details.

criteria_lab	chr, label for the threshold criteria defined in criteria. Defaults to "WQ Threshold"
plot_title	logical, should the station name be included as the plot title? Defaults to FALSE
plot	logical, should a plot be returned? Defaults to TRUE

Details

This function summarizes average daily values, average daily minimums/maximums, and absolute minimums/maximums across user-defined seasons for a target year (`target_yr`).

The user also has the option to add a threshold hold line using the `criteria` argument. Typically, this value is a water quality threshold, which is why `criteria_lab` defaults to 'WQ Threshold'. However, the user has the option to specify any other type of threshold they wish. when doing so, the value for `criteria_lab` should be changed accordingly.

Value

Returns a [ggplot](#) object

Author(s)

Julie Padilla

See Also

[ggplot](#), [assign_season](#), [y_labeler](#)

Examples

```
## get data, prep
data(elksmwq)
dat <- elksmwq

dat <- qaqc(elksmwq, qaqc_keep = c('0', '3', '5'))
do_plt <- annual_range(dat, param = 'do_mgl', target_yr = 2012)
do_plt <- annual_range(dat, param = 'do_mgl', target_yr = 2012, criteria = 2)
```

assign_season

Assign seasons to SWMP sampling data

Description

Assign seasons to SWMP sampling data on a monthly basis or user-defined seasonal basis

Usage

```
assign_season(data, season_grps = NULL, season_names = NULL,  
              season_start = NULL, abb = TRUE)
```

Arguments

<code>data</code>	a vector of POSIXct dates
<code>season_grps</code>	A list of seasons. Months (1-12) are assigned to different groups based on user preference. Defaults to 12 months, starting with January. Must assign a minimum of two seasons
<code>season_names</code>	A string vector of season names. The number of season names must match the length of the season list. A minimum of two seasons must be assigned (e.g., 'Wet', 'Dry'). Defaults to 12 months, starting with January. The number of season names must match the number of seasons
<code>season_start</code>	defaults to 12 months, starting with January
<code>abb</code>	logical, should abbreviations for month names be used? Defaults to TRUE

Details

A helper function used by multiple data analyses to assign seasons to sampling data and to order the seasons. To assist with plotting, the seasons are assigned as factors. Seasons are assigned by first grouping the months into a list of `season_grps` and then specifying one name for each grouping using `season_names`. If `season_grps` is specified then `season_names` must also be defined. If neither argument is specified then the season assignments will default to monthly values. Using the `season_start` argument, the user can designate which season should be the first factor level. This assignment affects plot order for most functions. If `season_start` is not specified, then it will default to the first season in the list (January for monthly seasons and the first season in `season_names` for user-defined seasons).

Value

Returns a vector of ordered season factors.

Author(s)

Julie Padilla

Examples

```
data(elksmwq)  
dat <- elksmwq  
  
seas <- assign_season(dat$datetimestamp, abb = FALSE)  
levels(seas)  
  
seas <- assign_season(dat$datetimestamp, abb = TRUE)
```

```
levels(seas)

seas <- assign_season(dat$datetimestamp, season_start = 'Mar')
levels(seas)

seas <- assign_season(dat$datetimestamp, abb = FALSE, season_start = 'March')
levels(seas)

seas <- assign_season(dat$datetimestamp,
  season_grps = list(c(1,2,3), c(4,5,6), c(7,8,9), c(10, 11, 12)),
  season_names = c('Winter', 'Spring', 'Summer', 'Fall'), season_start = 'Spring')
levels(seas)

seas <- assign_season(dat$datetimestamp, season_grps = list(c(10:12, 1:3), c(4:9)),
  season_names = c('Wet', 'Dry'))
levels(seas)
```

cbm_spatial

Spatial Data from Chesapeake Bay - Maryland

Description

Shapefile for Chesapeake Bay - Maryland reserve boundary

Usage

```
data(cbm_spatial)
```

Format

A [SpatialPolygons](#) object

Source

CDMO

References

NOAA National Estuarine Research Reserve System (NERRS). System-wide Monitoring Program. Data accessed from the NOAA NERRS Centralized Data Management Office website: <http://www.nerrsdata.org/>; accessed 08 October 2016

```
create_sk_flextable_list
```

Create a List of Flextable Objects

Description

Create a list of flextable objects to display Seasonal Kendall results in the NERRS reserve level template

Usage

```
create_sk_flextable_list(sk_result, stations, param,
  trend_col = c("#247BA0", "#A3DFFF", "#D9D9D9", "white"),
  font_col_default = "#444E65", font_sz_stn = 6, font_sz_result = 12,
  font_sz_head = 6, ht_head = 0.28, ht_body = 0.202,
  is_swmp = TRUE, stn_name = NULL, stn_abbrev = NULL,
  par_name = NULL)
```

Arguments

sk_result	a data.frame of reformatted results from sk_seasonal
stations	chr, vector of stations to be displayed
param	chr, vector of parameters to be displayed
trend_col	chr, a four element vector that specifies colors for increasing, decreasing, no change, and insufficient data trends
font_col_default	chr, default color to be used for trend table
font_sz_stn	int, specify the font size of displayed station names
font_sz_result	int, specify the font size of the displayed results
font_sz_head	int, specify the font size of the table header row
ht_head	num, specify the cell height of the table body rows. Units for this parameter are in inches.
ht_body	num, specify the cell height of the table header row. Units for this parameter are in inches.
is_swmp	logical, are the station names and parameter names consistent with SWMP station and parameter names? If either of these conditions is false then this parameter should be set to FALSE and then the user should define stn_name, stn_abbrev, and par_name. default is TRUE.
stn_name	chr, a list of full station names that the user would like to add to the trend table (e.g., "Cat Point")
stn_abbrev	chr, a list of station abbreviations that the user would like to add to the trend table (e.g., "CP" as an abbreviation for Cat Point).
par_name	chr, a list of parameter names to be used if the names do not match standard CDMO parameters.

Details

This function is intended for internal use with the NERRS reserve level reporting scripts. Using the results from the reserve level trend analysis, `create_sk_flextable_list` creates a list of two `flextable` objects to be displayed in the NERRS reserve level template. The first `flextable` in the list contains the two-letter station IDs for each station and the full location name of each station. The second table lists the seasonal kendall results and the names of the parameters of interest.

Value

Returns a list of `flextable` objects

Author(s)

Julie Padilla

`create_sk_national_ft_reserves`

Create a Flextable Object of Reserve Names

Description

Create a `flextable` of reserve names for use with the NERRS national level template.

Usage

```
create_sk_national_ft_reserves(sk_result, font_sz_stn = 8,
                              font_sz_head = 8, ht_head = 0.75, ht_body = 0.2)
```

Arguments

<code>sk_result</code>	a <code>data.frame</code> of reformatted results from <code>sk_seasonal</code>
<code>font_sz_stn</code>	int, specify the font size of displayed station names
<code>font_sz_head</code>	int, specify the font size of the table header row
<code>ht_head</code>	num, specify the cell height of the table body rows. Units for this parameter are in inches.
<code>ht_body</code>	num, specify the cell height of the table header row. Units for this parameter are in inches.

Details

This function is intended for internal use with the NERRS national level reporting scripts. Using results from the reserve level trend analyses, `create_sk_national_ft_reserves` creates a `flextable` object of reserve names for display in the NERRS national level template.

Value

Returns a `flextable` object

Author(s)

Julie Padilla

`create_sk_national_ft_results`*Create a Flextable Object of Seasonal Kendall Results*

Description

Create a flextable object to display Seasonal Kendall results for each reserve in the NERRS national level template

Usage

```
create_sk_national_ft_results(sk_result, param, font_sz_result = 12,  
                             font_sz_head = 8, ht_head = 0.375, ht_body = 0.2)
```

Arguments

<code>sk_result</code>	a <code>data.frame</code> of reformatted results generated by national Level template scripts from reserve level handoff files
<code>param</code>	chr, the name of the parameter that corresponds to the seasonal kendall results in <code>sk_result</code>
<code>font_sz_result</code>	int, specify the font size of the displayed results
<code>font_sz_head</code>	int, specify the font size of the table header row
<code>ht_head</code>	num, specify the cell height of the table body rows. Units for this parameter are in inches.
<code>ht_body</code>	num, specify the cell height of the table header row. Units for this parameter are in inches.

Details

This function is intended for internal use with the NERRS national level reporting scripts. Using results from the reserve level trend analyses, `create_sk_national_ft_results` creates a flextable object of seasonal kendall results to be displayed in the NERRS national level template.

Value

Returns a [flextable](#) object

Author(s)

Julie Padilla

elknmnut

Nutrient Data from Elkhorn Slough - North Marsh Station

Description

Monthly nutrient data from Elkhorn Slough North Marsh station

Usage

```
data(elknmnut)
```

Format

A `data.frame` object

Source

CDMO

References

NOAA National Estuarine Research Reserve System (NERRS). System-wide Monitoring Program. Data accessed from the NOAA NERRS Centralized Data Management Office website: <http://www.nerrsdata.org/>; accessed 08 October 2016

elksmwq

Water Quality Data from Elkhorn Slough - South Marsh Station

Description

Water Quality data from Elkhorn Slough South Marsh station

Usage

```
data(elksmwq)
```

Format

A `data.frame` object

Source

CDMO

References

NOAA National Estuarine Research Reserve System (NERRS). System-wide Monitoring Program. Data accessed from the NOAA NERRS Centralized Data Management Office website: <http://www.nerrsdata.org/>; accessed 08 October 2016

`elk_spatial`*Spatial Data from Elkhorn Slough*

Description

Shapefile for Elkhorn Slough reserve boundary

Usage

```
data(elk_spatial)
```

Format

A [SpatialPolygons](#) object

Source

CDMO

References

NOAA National Estuarine Research Reserve System (NERRS). System-wide Monitoring Program. Data accessed from the NOAA NERRS Centralized Data Management Office website: <http://www.nerrsdata.org/>; accessed 08 October 2016

`ft_col_names`*Convert Parameter Abbreviations*

Description

Convert SWMPr parameter abbreviations into formats appropriate for use with NERRS reserve level template [flextable](#)

Usage

```
ft_col_names(param)
```

Arguments

`param` chr, vector of parameter abbreviations

Details

A helper function used internally by [create_sk_flextable_list](#) to label [flextable](#) columns in the trend table for the reserve level report.

Value

Returns a `data.frame` of user-specified results to be displayed

Author(s)

Julie Padilla

generate_results_table

Filter Reformatted Seasonal Kendall Results

Description

Filters a `dataframe` of user-specified results for display in the NERRS reserve level report

Usage

```
generate_results_table(sk_result, stations, param)
```

Arguments

sk_result	a <code>data.frame</code> of reformatted seasonal kendall results from sk_seasonal .
stations	chr, vector of station names included in <code>sk_result</code> that will be displayed in the NERRS reserve level report
param	chr, vector of parameters included in <code>sk_result</code> that will be displayed in the NERRS reserve level report

Details

A helper function used internally by [create_sk_flextable_list](#) to create a `data.frame` of user specified parameters to be displayed in the reserve level report.

Value

Returns a `data.frame` of user-specified results to be displayed

Author(s)

Julie Padilla

`generate_station_table`*Filter Reformatted Seasonal Kendall Results*

Description

Filters a dataframe of user-specified results for display in the NERRS reserve level report

Usage

```
generate_station_table(sk_result, stations)
```

Arguments

<code>sk_result</code>	a <code>data.frame</code> of reformatted seasonal kendall results from sk_seasonal .
<code>stations</code>	<code>chr</code> , vector of stations listed in <code>sk_result</code> that should be displayed in the NERRS reserve level report

Details

Used internally by [create_sk_flexable_list](#) to create a `data.frame` of user specified parameters to be displayed

Value

Returns a `data.frame` of user-specified results to be displayed

Author(s)

Julie Padilla

`geographic_unique_stations`*Return a vector of geographically unique NERR Stations*

Description

Creates an alphabetically sorted, vector of geographically unique stations for mapping

Usage

```
geographic_unique_stations(nerr_site_id)
```

Arguments

<code>nerr_site_id</code>	<code>chr</code> vector of valid NERR stations
---------------------------	--

Details

This function is intended for internal use with the NERRS reserve level reporting scripts and is used along with [res_local_map](#). It takes a vector of NERR site ids and only returns geographically unique locations.

Value

returns a vector of NERR stations

Author(s)

Julie Padilla

Examples

```
stns <- c('apacpnut', 'apacpwq', 'apadbnut', 'apadbwq', 'apaebmet',  
'apaebnut', 'apaebwq', 'apaesnut', 'apaeswq')  
  
geographic_unique_stations(stns)
```

get_reserve

Identify NERRS reserve from metadata

Description

Identify the NERRS reserve from metadata in the data file

Usage

```
get_reserve(data.file)
```

Arguments

data.file location of data

Details

This function is intended for internal use with the NERRS reserve level reporting scripts. It determines the name of the full name of the NERRS reserve associated with the data in the user-specified data folder.

Value

Returns a character string of the full reserve name

Author(s)

Julie Padilla

get_shp_name	<i>Identify shapefile for NERRS reserve</i>
--------------	---

Description

Identify the shapefile name associated with the reserve in the data file

Usage

```
get_shp_name(gis.file.loc)
```

Arguments

gis.file.loc path to gis file location

Details

This function is intended for internal use with the NERRS reserve level reporting scripts. It identifies the name of the shapefile associated with the NERRS reserve.

Value

Returns a character string of the shapefile for the reserve boundary

Author(s)

Julie Padilla

get_sites	<i>Identify NERRS reserve stations from metadata</i>
-----------	--

Description

Identify the NERRS reserve sampling stations based on the metadata in the data file

Usage

```
get_sites(data.file, type = c("wq", "nut", "met"), active = TRUE,
          primary = TRUE)
```

Arguments

data.file	location of data
type	chr string of data station type ('wq', 'nut', or 'met')
active	logical. Should inactive stations be excluded? Defaults to TRUE
primary	logical. Should non-primary stations be excluded? Defaults to TRUE

Details

This function is intended for internal use with the NERRS reserve level reporting scripts. It returns the sampling stations associated with the data in the user-specified data folder.

Value

Returns a character vector of reserve stations

Author(s)

Julie Padilla

get_site_code

Return NERRS reserve site code based on data in the data file

Description

Identify the 3-letter NERRS reserve code from metadata in the data file

Usage

```
get_site_code(data.file)
```

Arguments

data.file data source location

Details

This function is intended for internal use with the NERRS reserve level reporting scripts. It returns the 3-letter reserve code associated with the data in the user-specified data folder.

Value

Returns 3-letter, reserve site code as chr

Author(s)

Julie Padilla

get_site_coordinates *Identify NERRS sampling locations from metadata*

Description

Identify the latitude/longitude for sampling stations based on the metadata in the data file

Usage

```
get_site_coordinates(data.file, active = TRUE)
```

Arguments

data.file	location of data
active	logical. Only return active stations?

Details

This function is intended for internal use with the NERRS reserve level reporting scripts. It returns the names, station codes, and coordinates associated with the data in the user-specified data folder.

Value

Returns a dataframe of station ids, station names, lat/long

Author(s)

Julie Padilla

historical_daily_range
Historical Daily Range Timeseries

Description

Compare daily averages for a target year to historical highs and lows

Usage

```
historical_daily_range(swmp_r_in, ...)

## S3 method for class 'swmp_r'
historical_daily_range(swmp_r_in, param = NULL,
  hist_rng = NULL, target_yr = NULL, criteria = NULL,
  free_y = FALSE, log_trans = FALSE, converted = FALSE,
  criteria_lab = "WQ Threshold", plot_title = FALSE, plot = TRUE,
  ...)
```

Arguments

<code>swmpr_in</code>	input swmpr object
<code>...</code>	not used
<code>param</code>	chr string of variable to plot
<code>hist_rng</code>	numeric vector, if historic range is not specified then the min/max values of the data set will be used.
<code>target_yr</code>	numeric, the target year that should be compared against the historic range. If target year is not specified then dot will not be plotted
<code>criteria</code>	numeric, a numeric criteria that will be plotted as a horizontal line
<code>free_y</code>	logical, should the y-axis be free? Defaults to FALSE. If FALSE, defaults to zero, unless negative values are present. If TRUE, y-axis limits are selected by ggplot
<code>log_trans</code>	logical, should y-axis be log? Defaults to FALSE
<code>converted</code>	logical, were the units converted from the original units used by CDMO? Defaults to FALSE. See <code>y_labeler</code> for details.
<code>criteria_lab</code>	chr, label for the threshold criteria defined in <code>criteria</code> . Defaults to "WQ Threshold"
<code>plot_title</code>	logical, should the station name be included as the plot title? Defaults to FALSE
<code>plot</code>	logical, should a plot be returned? Defaults to TRUE

Details

This function compares the average daily minimums/maximums and absolute daily minimums/maximums from a historical range to the average daily value from a target year. If `hist_rng` is not specified then the minimum and maximum years within the data set will be used. If `target_yr` is not specified then only the results for the `hist_rng` will be returned.

The user also has the option to add a threshold line using the `criteria` argument. Typically, this value is a water quality threshold, which is why `criteria_lab` defaults to 'WQ Threshold'. However, the user has the option to specify any other type of threshold they wish. when doing so, the value for `criteria_lab` should be changed accordingly.

Value

Returns a [ggplot](#) object

Author(s)

Julie Padilla, Kimberly Cressman

See Also

[ggplot](#), [y_labeler](#)

Examples

```

data(apacpwq)
dat <- apacpwq

dat <- qaqc(apacpwq, qaqc_keep = c('0', '3', '5'))
# with criteria
y <- historical_daily_range(dat, param = 'do_mgl', target_yr = 2013, criteria = 2)

# w/o criteria
x <- historical_daily_range(dat, param = 'do_mgl', target_yr = 2013)

# add a y label
x <- x + labs(x = NULL, y = "Dissolved Oxygen (mg/L)")

```

historical_range *Historical Monthly/Seasonal Range Timeseries*

Description

Compare seasonal averages/minimums/maximums for a target year to historical seasonal averages/minimums/maximums

Usage

```

historical_range(swmpr_in, ...)

## S3 method for class 'swmpr'
historical_range(swmpr_in, param = NULL,
  hist_rng = NULL, target_yr = NULL, criteria = NULL,
  free_y = FALSE, log_trans = FALSE, converted = FALSE,
  criteria_lab = "WQ Threshold", plot_title = FALSE, plot = TRUE,
  ...)

```

Arguments

swmpr_in	input swmpr object
...	additional arguments passed to other methods. See assign_season
param	chr string of variable to plot
hist_rng	numeric vector, if historic range is not specified then the min/max values of the data set will be used.
target_yr	numeric, the target year that should be compared against the historic range. If target year is not specified then dot will not be plotted

<code>criteria</code>	numeric, a numeric criteria that will be plotted as a horizontal line
<code>free_y</code>	logical, should the y-axis be free? Defaults to FALSE. If FALSE, defaults to zero, unless negative values are present. If TRUE, y-axis limits are selected by ggplot
<code>log_trans</code>	logical, should y-axis be log? Defaults to FALSE
<code>converted</code>	logical, were the units converted from the original units used by CDMO? Defaults to FALSE. See <code>y_labeler</code> for details.
<code>criteria_lab</code>	chr, label for the threshold criteria defined in <code>criteria</code> . Defaults to "WQ Threshold"
<code>plot_title</code>	logical, should the station name be included as the plot title? Defaults to FALSE
<code>plot</code>	logical, should a plot be returned? Defaults to TRUE

Details

This function summarizes average daily values and average daily minimums/maximums across user-defined seasons for a target year (`target_yr`) and for a historical range (`hist_rng`). If `hist_rng` is not specified then the minimum and maximum years within the data set will be used. If `target_yr` is not specified then only the results for the `hist_rng` will be returned.

The user also has the option to add a threshold hold line using the `criteria` argument. Typically, this value is a water quality threshold, which is why `criteria_lab` defaults to 'WQ Threshold'. However, the user has the option to specify any other type of threshold they wish. when doing so, the value for `criteria_lab` should be changed accordingly.

Value

Returns a [ggplot](#) object

Author(s)

Julie Padilla, Kimberly Cressman

See Also

[ggplot](#), [assign_season](#), [y_labeler](#)

Examples

```
data(elksmwq)

dat <- qaqc(elksmwq, qaqc_keep = c('0', '3', '5'))
# with criteria
y <- historical_range(dat, param = 'do_mgl', target_yr = 2013, criteria = 2)

# w/o criteria
x <- historical_range(dat, param = 'do_mgl', target_yr = 2013)
```

```
# add a y label
x <- x + labs(x = NULL, y = "Dissolved Oxygen (mg/L)")
```

import_local_nut	<i>Import local CDMO data</i>
------------------	-------------------------------

Description

Import local data that were obtained from the CDMO through the zip downloads feature

Usage

```
import_local_nut(path, station_code, collMethd = c(1, 2),
  trace = FALSE)
```

Arguments

path	chr string of full path to .csv files with raw data, can be a zipped or unzipped directory where the former must include the .zip extension
station_code	chr string of station to import, typically 7 or 8 characters including wq, nut, or met extensions, may include full name with year, excluding file extension
collMethd	chr string of nutrient data to subset. 1 indicates monthly, 2 indicates diel. Default is both diel and monthly data.
trace	logical indicating if progress is sent to console, default FALSE

Details

The function is designed to import local data that were downloaded from the CDMO outside of R. This approach works best for larger data requests, specifically those from the zip downloads feature in the advanced query section of the CDMO. The function may also work using data from the data export system, but this feature has not been extensively tested. The downloaded data will be in a compressed folder that includes multiple .csv files by year for a given data type (e.g., apacpwq2002.csv, apacpwq2003.csv, apacpnut2002.csv, etc.). The import_local function can be used to import files directly from the compressed folder or after the folder is decompressed. In the former case, the requested files are extracted to a temporary directory and then deleted after they are loaded into the current session. An example dataset is available online to illustrate the format of the data provided through the zip downloads feature. See the link below to access these data. All example datasets included with the package were derived from these raw data.

Occasionally, duplicate time stamps are present in the raw data. The function handles duplicate entries differently depending on the data type (water quality, weather, or nutrients). For water quality and nutrient data, duplicate time stamps are simply removed. Note that nutrient data often contain replicate samples with similar but not duplicated time stamps within a few minutes of each other. Replicates with unique time stamps are not removed but can be further processed using [rem_reps](#). Weather data prior to 2007 may contain duplicate time stamps at frequencies for 60 (hourly) and 144 (daily) averages, in addition to 15 minute frequencies. Duplicate values that correspond to the smallest value in the frequency column (15 minutes) are retained.

This function differs from `import_local` in that it allows for special handling of nutrient data. Using this function, the user can separate diel sampling data from low-tide sampling data using the `collMthd` argument.

Zip download request through CDMO: <http://cdmo.baruch.sc.edu/aqs/zips.cfm>

Example dataset: https://s3.amazonaws.com/swmpexdata/zip_ex.zip

Value

Returns a `swmpr` object with all parameters and QAQC columns for the station. The full date range in the raw data are also imported.

Author(s)

Marcus Beck, Julie Padilla (additional of `codecollMthd` argument) maintainer: Julie Padilla

See Also

[all_params](#), [all_params_dtrng](#), [rem_reps](#), [single_param](#)

lm_p_labs

P-Value labels for Plotting

Description

Generate a dataframe of p-value labels based on p-values from linear regression

Usage

```
lm_p_labs(dat_in)
```

Arguments

`dat_in` `data.frame` with year, season, min, mean, max columns

Details

A helper function that returns a `data.frame` of p-value labels for use with the `seasonal_dot`. P-values are taken from linear regression `lm`.

Value

Returns `data.frame` for use with `seasonal_dot`

Author(s)

Julie Padilla

See Also

[lm](#)

load_shp_file	<i>Load and format shapefile for reserve level map</i>
---------------	--

Description

Load and format shapefile for use with `res_local_map`

Usage

```
load_shp_file(path, dissolve_boundaries = TRUE)
```

Arguments

path	path to shapefile and name
dissolve_boundaries	logical, should reserve boundaries be dissolved? Defaults to TRUE

Details

This function is intended for internal use with the NERRS reserve level reporting scripts. It loads a NERRS boundary shp file and dissolves unnecessary reserve boundaries. The resulting sp object is then used with [res_sk_map](#) and [res_local_map](#)

Value

Returns a `sp` object

Author(s)

Julie Padilla

national_sk_map	<i>Reserve National Map with Seasonal Kendall Results</i>
-----------------	---

Description

Create a base map for NERRS reserves in ggplot with seasonal kendall results

Usage

```
national_sk_map(incl = c("contig", "AK", "HI", "PR"),
  highlight_states = NULL, sk_reserves = NULL, sk_results = NULL,
  sk_fill_colors = c("#247BA0", "#A3DFFF", "#444E65", "#595959"),
  agg_county = TRUE)
```

Arguments

<code>incl</code>	chr vector to include AK, HI , and PR (case sensitive)
<code>highlight_states</code>	chr vector of state FIPS codes
<code>sk_reserves</code>	chr vector of 3 letter reserve codes that have seasonal kendall results
<code>sk_results</code>	chr vector of seasonal kendall results. Results can be 'inc', 'dec', 'insig', or 'insuff' which stand for 'increasing trend', 'decreasing trend', 'statistically insignificant trend', or 'insufficient data to detect trend'
<code>sk_fill_colors</code>	chr vector of colors used to fill seasonal kendall result markers
<code>agg_county</code>	logical, should counties be aggregated to the state-level? Defaults to TRUE

Details

Create a base map of the US with options for including AK, HI, and PR. The user can choose which states and NERRS reserves to highlight. This function was developed, in part, from a blog post by Bob Rudis.

To ensure the proper plotting of results, the order of the results vector for `sk_results` should match the order of the reserves vector for `sk_reserves`.

Value

Returns a `ggplot` object

Author(s)

Bob Rudis, Julie Padilla Maintainer: Julie Padilla

References

Rudis, Bob. 2014. "Moving The Earth (well, Alaska & Hawaii) With R". *rud.is (blog)*. November 16, 2014. <https://rud.is/b/2014/11/16/moving-the-earth-well-alaska-hawaii-with-r/>

Examples

```
##National map highlighting west coast states and NERRS (including AK)
nerr_states_west <- c('02', '06', '41', '53')

nerrs_codes <- c('pdb', 'sos', 'sfb', 'elk', 'tjr', 'kac')
nerrs_sk_results <- c('inc', 'inc', 'dec', 'insig', 'insuff', 'dec')

national_sk_map(sk_reserve = nerrs_codes, sk_results = nerrs_sk_results)
```

raw_boxplot

Boxplots of raw data by user-defined season for a target year

Description

Boxplots of raw data by user-defined season for a target year

Usage

```
raw_boxplot(swmpr_in, ...)

## S3 method for class 'swmpr'
raw_boxplot(swmpr_in, param = NULL, target_yr = NULL,
  criteria = NULL, free_y = FALSE, log_trans = FALSE,
  converted = FALSE, plot_title = FALSE, ...)
```

Arguments

swmpr_in	input swmpr object
...	additional arguments passed to other methods. See assign_season and y_labeler .
param	chr string of variable to plot
target_yr	numeric, if target year is not specified then all data in the data frame will be used.
criteria	numeric, a numeric criteria that will be plotted as a horizontal line
free_y	logical, should the y-axis be free? Defaults to FALSE. If FALSE, defaults to zero, unless negative values are present. If TRUE, y-axis limits are selected by ggplot
log_trans	logical, should y-axis be log? Defaults to FALSE
converted	logical, were the units converted from the original units used by CDMO? Defaults to FALSE. See y_labeler for details.
plot_title	logical, should the station name be included as the plot title? Defaults to FALSE

Details

This function produces boxplots of raw, unaggregated data by user-specified season for year of interest

Value

A [ggplot](#) object

Author(s)

Julie Padilla

See Also

[ggplot](#), [assign_season](#), [y_labeler](#)

Examples

```
## get data, prep
data(elksmwq)
dat <- elksmwq

dat <- qaqc(elksmwq, qaqc_keep = c('0', '3', '5'))
raw_boxplot(dat, param = 'do_mgl')
```

remove_inf_and_nan *Replace Inf/-Inf/NaN values*

Description

Replace Inf, -Inf, and NaN in a matrix with NA

Usage

```
remove_inf_and_nan(x)
```

Arguments

x input matrix

Details

This function replaces Inf, -Inf, and NaN in a matrix with NA. It is used internally by several functions.

Value

Returns a matrix object

Author(s)

Julie Padilla

reserve_locs	<i>NERRS Sampling Location Data Frame</i>
--------------	---

Description

Create a data.frame of selected NERRS locations for plotting with `res_national_map`

Usage

```
reserve_locs(incl = c("contig", "AK", "HI", "PR"),
             subset_reserve = NULL)
```

Arguments

<code>incl</code>	Str vector to include AK, HI, and PR
<code>subset_reserve</code>	chr string of 3 letter reserve IDs to include as data points. To include He'eia use the reserve code 'HEA'.

Details

A helper function used to generate a data.frame of selected reserve locations for use with [res_national_map](#).

Value

Returns a data.frame for internal use with `res_national_map`

Author(s)

Julie Padilla

res_custom_map	<i>Local Reserve Map for Custom Stations</i>
----------------	--

Description

Create a stylized reserve-level map of custom station locations for use with the reserve level reporting template

Usage

```
res_custom_map(stations, x_loc, y_loc, bbox, shp, station_labs = TRUE,
               station_col = NULL, lab_loc = NULL, scale_pos = "bottomleft")
```

Arguments

stations	chr string of the reserve stations to include in the map
x_loc	num vector of x coordinates for stations
y_loc	num vector of y coordinates for stations
bbox	a bounding box associated with the reserve. Must be in the format of c(X1, Y1, X2, Y2)
shp	SpatialPolygons object
station_labs	logical, should stations be labeled? Defaults to TRUE
station_col	chr vector of colors used to color station points. Defaults to 'black'.
lab_loc	chr vector of 'R' and 'L', one letter for each station. if no lab_loc is specified then labels will default to the left.
scale_pos	scale_pos where should the scale be placed? Options are 'topleft', 'topright', 'bottomleft', or 'bottomright'. Defaults to 'bottomleft'

Details

Creates a stylized, reserve-level base map. The user can specify the reserve and stations to plot. The user can also specify a bounding box. For multi-component reserves, the user should specify a bounding box that highlights the component of interest.

This function does not automatically detect conflicts between station labels. The lab_loc argument allows the user to specify "R" or "L" for each station to prevent labels from conflicting with each other.

This function is intended to be used with mapview::mapshot to generate a png for the reserve-level report.

Value

Returns a leaflet object

Author(s)

Julie Padilla

Examples

```
### set plotting parameters
stns <- c('custom stn 1', 'custom stn 2')
x_coords <- c(-121.735281, -121.750369)
y_coords <- c(36.850377, 36.806667)
shp_fl <- elk_spatial
bounding_elk <- c(-121.810978, 36.868218, -121.708667, 36.764050)
lab_dir <- c('L', 'R')
pos <- 'bottomleft'

### plot
res_custom_map(stations = stns, x_loc = x_coords, y_loc = y_coords,
bbox = bounding_elk, lab_loc = lab_dir, scale_pos = pos, shp = shp_fl)
```

```
res_custom_map(stations = stns, x_loc = x_coords, y_loc = y_coords,
bbox = bounding_elk, lab_loc = lab_dir, scale_pos = pos,
shp = shp_fl, station_col = c('red', 'green'))
```

res_custom_sk_map *Local Reserve Map With Seasonal Kendall Results for Custom Stations*

Description

Create a stylized reserve-level map of seasonal kendall results from custom station locations for use with the reserve level reporting template

Usage

```
res_custom_sk_map(stations, x_loc, y_loc, sk_result = NULL, bbox, shp,
station_labs = TRUE, lab_loc = NULL, scale_pos = "bottomleft")
```

Arguments

stations	chr string of the reserve stations to include in the map
x_loc	num vector of x coordinates for stations
y_loc	num vector of y coordinates for stations
sk_result	vector of values denoting direction and significance of seasonal kendall results. Result should be c('inc', 'dec', 'insig') for sig. negative, no sig. results, and sig. positive result
bbox	a bounding box associated with the reserve. Must be in the format of c(X1, Y1, X2, Y2)
shp	SpatialPolygons object
station_labs	logical, should stations be labeled? Defaults to TRUE
lab_loc	chr vector of 'R' and 'L', one letter for each station. if no lab_loc is specified then labels will default to the left.
scale_pos	scale_pos where should the scale be placed? Options are 'topleft', 'topright', 'bottomleft', or 'bottomright'. Defaults to 'bottomleft'

Details

Creates a stylized, reserve-level base map for displaying seasonal kendall results from [sk_seasonal](#). The user can specify the reserve and stations to plot. The user can also specify a bounding box. For multi-component reserves, the user should specify a bounding box that highlights the component of interest.

To display seasonal trends, the user must specify c('inc', 'dec', 'insig') for each station listed in the stations argument.

Value

returns a leaflet object. This function is intended to be used with mapshot to generate a png for the reserve level report

Author(s)

Julie Padilla

Examples

```
### set plotting parameters
stns <- c('custom stn 1', 'custom stn 2')
x_coords <- c(-121.735281, -121.750369)
y_coords <- c(36.850377, 36.806667)
shp_fl <- elk_spatial
bounding_elk <- c(-121.810978, 36.868218, -121.708667, 36.764050)
lab_dir <- c('R', 'L')
trnds <- c('inc', 'dec')
pos <- 'bottomleft'

### plot
res_custom_sk_map(stations = stns, x_loc = x_coords,
sk_result = trnds, y_loc = y_coords,
bbox = bounding_elk, lab_loc = lab_dir,
scale_pos = pos, shp = shp_fl)
```

res_local_map

Local Reserve Map

Description

Create a stylized reserve-level map for use with the reserve level reporting template

Usage

```
res_local_map(nerr_site_id, stations, bbox, shp, station_labs = TRUE,
lab_loc = NULL, scale_pos = "bottomleft")
```

Arguments

nerr_site_id	chr string of the reserve to make, first three characters used by NERRS
stations	chr string of the reserve stations to include in the map
bbox	a bounding box associated with the reserve. Must be in the format of c(X1, Y1, X2, Y2)
shp	SpatialPolygons object
station_labs	logical, should stations be labeled? Defaults to TRUE

lab_loc chr vector of 'R' and 'L', one letter for each station. if no lab_loc is specified then labels will default to the left.

scale_pos scale_pos where should the scale be placed? Options are 'topleft', 'topright', 'bottomleft', or 'bottomright'. Defaults to 'bottomleft'

Details

Creates a stylized, reserve-level base map. The user can specify the reserve and stations to plot. The user can also specify a bounding box. For multi-component reserves, the user should specify a bounding box that highlights the component of interest.

This function does not automatically detect conflicts between station labels. The lab_loc argument allows the user to specify "R" or "L" for each station to prevent labels from conflicting with each other.

This function is intended to be used with mapview::mapshot to generate a png for the reserve-level report.

Value

returns a leaflet object

Author(s)

Julie Padilla

Examples

```
## a compact reserve
### set plotting parameters
stations <-
sampling_stations[(sampling_stations$NERR.Site.ID == 'elk'
& sampling_stations$Status == 'Active'), ]$Station.Code
to_match <- c('wq', 'met')
stns <- stations[grep(paste(to_match, collapse = '|'), stations)]
shp_fl <- elk_spatial
bounding_elk <- c(-121.810978, 36.868218, -121.708667, 36.764050)
lab_dir <- c('L', 'R', 'L', 'L', 'L')
labs <- c('ap', 'cw', 'nm', 'sm', 'vm')
pos <- 'bottomleft'

### plot
res_local_map('elk', stations = stns, bbox = bounding_elk,
lab_loc = lab_dir, scale_pos = pos, shp = shp_fl)

## a multicomponent reserve (show two different bounding boxes)
### set plotting parameters
stations <-
sampling_stations[(sampling_stations$NERR.Site.ID == 'cbm'
& sampling_stations$Status == 'Active'), ]$Station.Code
to_match <- c('wq', 'met')
```

```

stns <- stations[grep(paste(to_match, collapse = '|'), stations)]
shp_fl <- cbm_spatial
bounding_cbm_1 <- c(-77.393, 39.741, -75.553, 38.277)
bounding_cbm_2 <- c(-76.862006, 38.811571, -76.596508, 38.642454)
lab_dir <- c('L', 'R', 'L', 'L', 'L')
labs <- c('ap', 'cw', 'nm', 'sm', 'vm')
pos <- 'bottomleft'

### plot
res_local_map('cbm', stations = stns, bbox = bounding_cbm_1,
lab_loc = lab_dir, scale_pos = pos, shp = shp_fl)

res_local_map('cbm', stations = stns, bbox = bounding_cbm_2,
lab_loc = lab_dir, scale_pos = pos, shp = shp_fl)

```

res_national_map	<i>Reserve National Map</i>
------------------	-----------------------------

Description

Create a base map for NERRS reserves in ggplot

Usage

```

res_national_map(incl = c("contig", "AK", "HI", "PR"),
  highlight_states = NULL, highlight_reserves = NULL,
  agg_county = TRUE)

```

Arguments

incl	chr vector to include AK, HI , and PR (case sensitive)
highlight_states	chr vector of state FIPS codes
highlight_reserves	chr vector of 3 letter reserve codes
agg_county	logical, should counties be aggregated tot he state-level? Defaults to TRUE

Details

Create a base map of the US with options for including AK, HI, and PR. The user can choose which states and NERRS reserves to highlight. This function was developed, in part, from a blog post by Bob Rudis.

Value

Returns a [ggplot](#) object

Author(s)

Bob Rudis, Julie Padilla Maintainer: Julie Padilla

References

Rudis, Bob. 2014. "Moving The Earth (well, Alaska & Hawaii) With R". rud.is (blog). November 16, 2014. <https://rud.is/b/2014/11/16/moving-the-earth-well-alaska-hawaii-with-r/>

Examples

```
##National map highlighting states with NERRS
nerr_states <- c('01', '02', '06', '10', '12', '13', '15'
, '23', '24', '25', '27', '28', '33', '34', '36', '37', '39'
, '41', '44', '45', '48', '51', '53', '55', '72')

res_national_map(highlight_states = nerr_states)

#' ##Just the national map
res_national_map()

##National map highlighting west coast states and NERRS (including AK)
nerr_states_west <- c('02', '06', '41', '53')

nerrs_codes <- c('pdb', 'sos', 'sfb', 'elk', 'tjr', 'kac')

res_national_map(highlight_states = nerr_states_west, highlight_reserve = nerrs_codes)
```

res_sk_map

Local Reserve Map With Seasonal Kendall Results

Description

Create a stylized reserve-level map of seasonal kendall results for use with the reserve level reporting template

Usage

```
res_sk_map(nerr_site_id, stations, sk_result = NULL, bbox, shp,
  station_labs = TRUE, lab_loc = NULL, scale_pos = "bottomleft")
```

Arguments

nerr_site_id chr string of the reserve to make, first three characters used by NERRS
stations chr string of the reserve stations to include in the map

sk_result	vector of values denoting direction and significance of seasonal kendall results. Result should be c('inc', 'dec', 'insig', 'insuff') for significant positive, significant negative, no significant results, and insufficient data to calculate result.
bbox	a bounding box associated with the reserve. Must be in the format of c(X1, Y1, X2, Y2)
shp	SpatialPolygons object
station_labs	logical, should stations be labeled? Defaults to TRUE
lab_loc	chr vector of 'R' and 'L', one letter for each station. if no lab_loc is specified then labels will default to the left.
scale_pos	scale_pos where should the scale be placed? Options are 'topleft', 'topright', 'bottomleft', or 'bottomright'. Defaults to 'bottomleft'

Details

Creates a stylized, reserve-level base map for displaying seasonal kendall results from [sk_seasonal](#). The user can specify the reserve and stations to plot. The user can also specify a bounding box. For multi-component reserves, the user should specify a bounding box that highlights the component of interest.

To display seasonal trends, the user must specify c('inc', 'dec', 'insig') for each station listed in the stations argument.

Value

returns a leaflet object. This function is intended to be used with mapshot to generate a png for the reserve level report

Author(s)

Julie Padilla

Examples

```
## a compact reserve
### set plotting parameters
stations <-
sampling_stations[(sampling_stations$NERR.Site.ID == 'elk'
& sampling_stations$Status == 'Active'), ]$Station.Code
to_match <- c('wq')
stns <- stations[grep(paste(to_match, collapse = '|'), stations)]
shp_fl <- elk_spatial
bounding_elk <- c(-121.810978, 36.868218, -121.708667, 36.764050)
pos <- 'bottomleft'
sk_res <- c('inc', 'dec', 'dec', 'insig')

### plot
res_sk_map('elk', stations = stns, sk_result = sk_res,
bbox = bounding_elk, scale_pos = pos, shp = shp_fl)
```

```
## a multicomponent reserve (showing two different bounding boxes)
### set plotting parameters
stations <-
sampling_stations[(sampling_stations$NERR.Site.ID == 'cbm'
& sampling_stations$Status == 'Active'), ]$Station.Code
to_match <- c('wq')
stns <- stations[grep(paste(to_match, collapse = '|'), stations)]
shp_fl <- cbm_spatial
bounding_cbm_1 <- c(-77.393, 39.741, -75.553, 38.277)
bounding_cbm_2 <- c(-76.862006, 38.811571, -76.596508, 38.642454)
pos <- 'bottomleft'
sk_res <- c('inc', 'dec', 'dec', 'insig')

### plot
res_sk_map('cbm', stations = stns, sk_result = sk_res, bbox = bounding_cbm_1,
scale_pos = pos, shp = shp_fl)

res_sk_map('cbm', stations = stns, sk_result = sk_res, bbox = bounding_cbm_2,
scale_pos = pos, shp = shp_fl)
```

sampling_stations *Detailed of NERRS site data*

Description

Metadata on NERRS stations provided by the Central Data Management Office (CDMO) when data is downloaded

Usage

```
data(sampling_stations)
```

Format

A `data.frame` object

Source

CDMO

References

NOAA National Estuarine Research Reserve System (NERRS). System-wide Monitoring Program. Data accessed from the NOAA NERRS Centralized Data Management Office website: <http://www.nerrsdata.org/>; accessed 08 October 2016

seasonal_barplot	<i>Cumulative Bar Plot</i>
------------------	----------------------------

Description

Cumulative bar plot over a historic range

Usage

```
seasonal_barplot(swmpr_in, ...)

## S3 method for class 'swmpr'
seasonal_barplot(swmpr_in, param = NULL,
  hist_rng = NULL, log_trans = FALSE, converted = FALSE,
  hist_avg = TRUE, bar_position = "stack", season_facet = FALSE,
  plot_title = FALSE, plot = TRUE, ...)
```

Arguments

swmpr_in	input swmpr object
...	additional arguments passed to other methods. See assign_season
param	chr string of variable to plot
hist_rng	numeric vector, if historic range is not specified then the min/max values of the data set will be used.
log_trans	logical, should y-axis be log? Defaults to FALSE
converted	logical, were the units converted from the original units used by CDMO? Defaults to FALSE. See y_labeler for details.
hist_avg	logical, should a historical average be included? Defaults to TRUE.
bar_position	chr string, options available are stack or dodge. Defaults to stack
season_facet	logical, should plot be faceted by season? Defaults to FALSE.
plot_title	logical, should the station name be included as the plot title? Defaults to FALSE
plot	logical, should a plot be returned? Defaults to TRUE

Details

This function uses barplots to summarize parameters that are best viewed on a cumulative basis (e.g., precipitation). Data are aggregated on a seasonal and annual basis.

There are two ways to make interannual comparisons: on an aggregate basis and on a seasonal basis. If the argument `season_facet = FALSE` then parameter totals from each season will be added together to compose one, multi-color bar. If `season_facet = TRUE` then parameter totals from each season separated into multiple plots for easier intra-season comparison across years.

Value

A [ggplot](#) object

Author(s)

Julie Padilla

See Also[ggplot](#), [assign_season](#), [y_labeler](#)**Examples**

```
data(apaebmet)
dat <- qaqc(apaebmet, qaqc_keep = c('0', '3', '5'))

x <- seasonal_barplot(dat, param = 'totprcp'
  , season_grps = list(c(1,2,3), c(4,5,6), c(7,8,9), c(10, 11, 12))
  , season_names = c('Winter', 'Spring', 'Summer', 'Fall')
  , hist_avg = TRUE
  , converted = FALSE)

# return a table instead of a figure
y <- seasonal_barplot(dat, param = 'totprcp'
  , season_grps = list(c(1,2,3), c(4,5,6), c(7,8,9), c(10, 11, 12))
  , season_names = c('Winter', 'Spring', 'Summer', 'Fall')
  , converted = FALSE
  , plot = FALSE)

## divide plot into seasonal facets
x <- seasonal_barplot(dat, param = 'totprcp'
  , season_grps = list(c(1,2,3), c(4,5,6), c(7,8,9), c(10, 11, 12))
  , season_names = c('Winter', 'Spring', 'Summer', 'Fall')
  , season_facet = TRUE
  , hist_avg = TRUE
  , converted = FALSE)

## convert from mm to in
dat$totprcp <- dat$totprcp / 25.4

x <- seasonal_barplot(dat, param = 'totprcp'
  , season_grps = list(c(1,2,3), c(4,5,6), c(7,8,9), c(10, 11, 12))
  , season_names = c('Winter', 'Spring', 'Summer', 'Fall')
  , hist_avg = TRUE
  , converted
  = TRUE)
```

Description

Annual time series for year of interest on top of long-term percentiles

Usage

```
seasonal_boxplot(swmpr_in, ...)

## S3 method for class 'swmpr'
seasonal_boxplot(swmpr_in, param = NULL,
  hist_rng = NULL, target_yr = NULL, criteria = NULL,
  free_y = FALSE, log_trans = FALSE, converted = FALSE,
  criteria_lab = "WQ Threshold", stat_lab = "Average",
  plot_title = FALSE, plot = TRUE, FUN = function(x) mean(x, na.rm =
  TRUE), ...)
```

Arguments

swmpr_in	input swmpr object
...	additional arguments passed to other methods. See assign_season
param	chr string of variable to plot
hist_rng	numeric vector, if historic range is not specified then the min/max values of the data set will be used.
target_yr	numeric, the target year that should be compared against the historic range. If target year is not specified then dot will not be plotted
criteria	numeric, a numeric criteria that will be plotted as a horizontal line
free_y	logical, should the y-axis be free? Defaults to FALSE. If FALSE, defaults to zero, unless negative values are present. If TRUE, y-axis limits are selected by ggplot
log_trans	logical, should y-axis be log? Defaults to FALSE
converted	logical, were the units converted from the original units used by CDMO? Defaults to FALSE. See y_labeler for details.
criteria_lab	chr, label for the threshold criteria defined in criteria. Defaults to "WQ Threshold"
stat_lab	chr, label for the summary statistic defined in FUN. Defaults to "Average"
plot_title	logical, should the station name be included as the plot title? Defaults to FALSE
plot	logical, should a plot be returned? Defaults to TRUE
FUN	function used to aggregate daily SWMP data

Details

This function uses boxplots to summarize statistics calculated on a daily basis across user-defined seasons for all years within the historic range (`hist_rng`). If `hist_rng` is not specified then the minimum and maximum years within the data set will be used. The summary statistics used to generate the boxplots are ggplot2 defaults: the center of the box is a median, and the lower/upper limits of the box are the 25-th and 75-th percentiles. The whiskers extend to the furthest data point within 1.5 * inter-quartile range (IQR). The dots beyond the whiskers are data points that are

greater than $1.5 * IQR$. If the user selects a `target_yr`, then a median summary statistic value will be plotted as a point against the boxplots.

Using the `FUN` argument, the user can specify the daily summary statistic to use. Commonly used statistics are `min(x, na.rm = TRUE)`, `mean(x, na.rm = TRUE)`, and `max(x, na.rm = TRUE)`. After specifying `FUN`, the user should also specify `stat_lab`, which is used to construct appropriate legend labels.

The user also has the option to add a threshold hold line using the `criteria` argument. Typically, this value is a water quality threshold, which is why `criteria_lab` defaults to 'WQ Threshold'. However, the user has the option to specify any other type of threshold they wish. when doing so, the value for `criteria_lab` should be changed accordingly.

Value

Returns a [ggplot](#) object or a data.frame if `plot = FALSE`

Author(s)

Julie Padilla

See Also

[ggplot](#), [assign_season](#)

Examples

```
dat <- elksmwq

dat <- qaqc(dat, qaqc_keep = c('0', '3', '5'))

do_plt <- seasonal_boxplot(dat, param = 'do_mgl')

do_plt <- seasonal_boxplot(dat, param = 'do_mgl',
  target_yr = 2015,
  season = list(c(1,2,3), c(4,5,6), c(7,8,9), c(10, 11, 12)),
  season_names = c('Winter', 'Spring', 'Summer', 'Fall'),
  season_start = 'Spring')

do_plt_min <- seasonal_boxplot(dat, param = 'do_mgl',
  stat_lab = 'Minimum', FUN = function(x) min(x, na.rm = TRUE))

do_plt_max <- seasonal_boxplot(dat, param = 'do_mgl',
  stat_lab = 'Maximum', FUN = function(x) max(x, na.rm = TRUE))
```

seasonal_dot

*Seasonal Dot Plot***Description**

Plot average/min/max seasonal values faceted by season

Usage

```
seasonal_dot(swmpr_in, ...)
```

```
## S3 method for class 'swmpr'
seasonal_dot(swmpr_in, param = NULL, lm_trend = FALSE,
  lm_lab = FALSE, free_y = FALSE, log_trans = FALSE,
  converted = FALSE, plot_title = FALSE, plot = TRUE, ...)
```

Arguments

swmpr_in	input swmpr object
...	additional arguments passed to other methods. See assign_season
param	chr string of variable to plot
lm_trend	logical, add linear trend line?
lm_lab	logical, add significance label? Statistically significant results will appear in bold.
free_y	logical, should the y-axis be free? Defaults to FALSE. If FALSE, defaults to zero, unless negative values are present. If TRUE, y-axis limits are selected by ggplot
log_trans	logical, should y-axis be log? Defaults to FALSE
converted	logical, were the units converted from the original units used by CDMO? Defaults to FALSE. See y_labeler for details.
plot_title	logical, should the station name be included as the plot title? Defaults to FALSE
plot	logical, should a plot be returned? Defaults to TRUE

Details

This function summarizes minimum, mean, and maximum values calculated on a seasonal basis to allow for easier intra-season comparisons over time.

lm_trend = TRUE adds a linear regression to the plot, and lm_lab = TRUE will add p-values from the linear regression to the plot. If the p-values are significant ($p < 0.05$) then the text will appear in bold. lm_lab text is color coded to match with the corresponding dots.

Value

Returns a [ggplot](#) object

Author(s)

Julie Padilla

See Also[ggplot](#), [assign_season](#), [y_labeler](#)**Examples**

```

dat_wq <- elkswmq
#dat_wq <- subset(dat_wq, subset = c('2010-01-01 0:00', '2017-01-01 0:00'))
dat_wq <- qaqc(dat_wq, qaqc_keep = c(0, 3, 5))

x <-
  seasonal_dot(dat_wq, param = 'do_mgl'
              , lm_trend = TRUE
              , lm_lab = TRUE
              , plot_title = TRUE)

x <-
  seasonal_dot(dat_wq, param = 'do_mgl'
              , lm_trend = FALSE
              , lm_lab = FALSE
              , plot_title = TRUE)

x <-
  seasonal_dot(dat_wq, param = 'do_mgl'
              , lm_trend = TRUE
              , lm_lab = FALSE
              , plot_title = TRUE)

dat_nut <- elknmnut
dat_nut <- subset(dat_nut, subset = c('2007-01-01 0:00', '2017-01-01 0:00'))
dat_nut <- qaqc(dat_nut, qaqc_keep = c(0, 3, 5))

x <-
  seasonal_dot(dat_nut
              , param = 'chla_n'
              , season_grps = list(c(1,2,3), c(4,5,6), c(7,8,9), c(10, 11, 12))
              , season_names = c('Winter', 'Spring', 'Summer', 'Fall')
              , season_start = 'Spring'
              , lm_trend = FALSE
              , lm_lab = FALSE
              , plot_title = TRUE)

x <-
  seasonal_dot(dat_nut, param = 'chla_n'
              , lm_trend = TRUE
              , lm_lab = FALSE
              , plot_title = TRUE)

```

```
x <-  
  seasonal_dot(dat_nut, param = 'chla_n'  
              , lm_trend = TRUE  
              , lm_lab = TRUE  
              , plot_title = TRUE)
```

set_date_breaks *Set reasonable date breaks*

Description

Select reasonable breaks for [scale_x_datetime](#)

Usage

```
set_date_breaks(rng)
```

Arguments

rng date range years

Details

A helper function for easier date label setting

Value

Returns a chr string for date_breaks

Author(s)

Julie Padilla

See Also

[set_date_break_labs](#), [scale_x_datetime](#)

set_date_break_labs *Set reasonable date breaks labels*

Description

Select reasonable labels for breaks used in [scale_x_datetime](#)

Usage

```
set_date_break_labs(rng)
```

Arguments

rng date range years

Details

A helper function for easier date label setting

Value

Returns a chr string for date_labels

Author(s)

Julie Padilla

See Also

[set_date_breaks](#), [scale_x_datetime](#)

sk_seasonal *Seasonal Kendall Analysis for Seasonal Data*

Description

Non-parametric test for monotonic seasonal trends

Usage

```
sk_seasonal(swmp_r_in, ...)
```

```
## S3 method for class 'swmp_r'
```

```
sk_seasonal(swmp_r_in, param = NULL, alpha = 0.05,  
  data_min = 5, envStats_summary = FALSE, stat_lab = "Average",  
  FUN = function(x) mean(x, na.rm = TRUE), ...)
```

Arguments

swmpr_in	input swmpr object
...	additional arguments passed to other methods. See assign_season
param	chr string of variable to plot
alpha	num, alpha value to use to significance test. Defaults to 0.05.
data_min	num, the minimum number of observations required to perform the analysis. Defaults to 5
envStats_summary	logical, should the standard EnvStats::kendallSeasonalTrendTest be returned? Defaults to FALSE. See Details for more information.
stat_lab	chr, label for the summary statistic defined in FUN. Defaults to "Average".
FUN	function used to aggregate seasonal SWMP data.

Details

This function performs a seasonal kendall test on seasonally aggregated values using [kendallSeasonalTrendTest](#).

Data are aggregated on a user-specified seasonal basis using the FUN argument. For example, using default settings, sk_seasonal would perform a seasonal kendall test on average monthly values. However, if the user set FUN = min(x, na.rm = TRUE) then a seasonal kendall would be performed on monthly minimum values.

If EnvStats_summary = TRUE then the detailed output summary from [kendallSeasonalTrendTest](#) will be returned. If EnvStats_summary = FALSE then an abbreviated summary will be returned in a data.frame. The abbreviated summary contains the station name, the type of statistic used to summarize the data on a seasonal basis (specified by stat_lab), and the following results from [kendallSeasonalTrendTest](#): tau, slope, p-value for the chi-square test, and the p-value for the trend test.

Value

Returns a data.frame object or a summary from EnvStats::kendallSeasonalTrendTest

Author(s)

Julie Padilla

See Also

[assign_season](#), [y_labeler](#), [kendallSeasonalTrendTest](#)

Examples

```
dat_wq <- elksmwq
dat_wq <- qaqc(dat_wq, qaqc_keep = c(0, 3, 5))

x <- sk_seasonal(dat_wq, param = 'temp')
```

sk_tidy	<i>Tidy Seasonal Kendall Results</i>
---------	--------------------------------------

Description

Tidy results from [kendallSeasonalTrendTest](#)

Usage

```
sk_tidy(data, station, param, stat, alpha = 0.05)
```

Arguments

data	a htest object produced by kendallSeasonalTrendTest
station	chr string sampling station
param	chr string of variable to plot
stat	chr, label to be used for statistic used to group data
alpha	num, significance level. Defaults to 0.05

Details

A helper function used by [sk_seasonal](#) to return a table of tidied values.

Value

Returns a data.frame of results from [kendallSeasonalTrendTest](#)

Author(s)

Julie Padilla

std_param_check	<i>Standard Parameter Check</i>
-----------------	---------------------------------

Description

Determine if a parameter is one of the standard SWMP parameters

Usage

```
std_param_check(param)
```

Arguments

param	chr string of variable abbreviation
-------	-------------------------------------

Details

A helper function used internally by several plotting functions to determine if parameter has a standard y-axis label. To accommodate the needs of the reserve-level annual report, this function also recognizes dissolved organic phosphorus (DIP) and dissolved inorganic nitrogen (DIN) as standard parameters.

Value

Returns TRUE or FALSE

Author(s)

Julie Padilla

Examples

```
std_param_check('do_mgl')

std_param_check('nitrogen')
```

summarise_handoff_files

Summarise Hand-off Files from Reserve Level Reports

Description

Summarise the seasonal kendall results from reserve level report hand-off files

Usage

```
summarise_handoff_files(path, param, res_region = NULL)
```

Arguments

path	chr string of full path to .csv handoff files
param	chr string of variable to summarise
res_region	a data.frame of look-up values that match 3-letter NERR site ids with regions

Details

This function is intended for use with the NERRS national level reporting scripts. It returns a data.frame that summarises the result of the reserve level seasonal kendall trend analyses found in the hand-off files generated by the reserve level reporting scripts. The summary groups reserves into regional classifications based on user-specified regions given in res_region.

Value

Returns a data.frame

Author(s)

Julie Padilla

threshold_criteria_plot

Water Quality Threshold Plot For Parameters With Criteria

Description

Observed data compared against user-defined water quality thresholds

Usage

```
threshold_criteria_plot(swmpr_in, ...)
```

```
## S3 method for class 'swmpr'
threshold_criteria_plot(swmpr_in, param = NULL,
  rng = NULL, thresholds = NULL, threshold_labs = c("Good", "Fair",
  "Poor"), threshold_cols = c("#ABD9E9", "#FFFFCC", "#FEC596"),
  crit_threshold = NULL, log_trans = FALSE, monthly_smooth = FALSE,
  plot_title = FALSE, ...)
```

Arguments

swmpr_in	input swmpr object
...	additional arguments passed to other methods. See y_labeler .
param	chr string of the variable to plot
rng	num, years to include in the plot. This variable can either be one year (e.g., rng = 2012), or two years (e.g. rng = c(2012, 2016)), If range is not specified then the entire data set will be used.
thresholds	numeric vector, numeric criteria that will be plotted in the background
threshold_labs	chr vector of labels for categories created by thresholds.
threshold_cols	chr vector of color values for categories created by thresholds.
crit_threshold	num, value at which the critical threshold line should be plotted. Typically the same value used to establish the 'Poor' threshold.
log_trans	logical, should y-axis be log? Defaults to FALSE
monthly_smooth	logical, calculate a monthly average? Defaults to FALSE
plot_title	logical, should the station name be included as the plot title? Defaults to FALSE

Details

This function visualizes exceedances of numeric criteria which are specified using thresholds. Suggested numeric criteria for several parameters (dissolved oxygen, dissolved inorganic phosphorus, dissolved inorganic nitrogen, and chlorophyll-a) can be found in the USEPA National Coastal Condition Report (2012).

If the parameter of interest does not have numeric criteria, then `threshold_percentile_plot` is recommended.

Value

Returns a `ggplot` object

Author(s)

Julie Padilla

References

United States Environmental Protection Agency (USEPA). 2012. "National Coastal Condition Report IV." <http://citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.646.1973&rep=rep1&type=pdf>

See Also

[ggplot,y_labeler](#)

Examples

```
data(apacpwq)
dat_wq <- apacpwq

dat_wq <- qaqc(dat_wq, qaqc_keep = c(0, 3, 5))

## Due to the volume of instantaneous data, these plots are a bit slow
x <-
  threshold_criteria_plot(dat_wq, param = 'do_mgl'
                        , rng = 2012
                        , thresholds = c(2, 5)
                        , threshold_labs = c('Poor', 'Fair', 'Good')
                        , monthly_smooth = TRUE
                        , threshold_cols = c('#FEC596', '#FFFFCC', '#ABD9E9'))

y <-
  threshold_criteria_plot(dat_wq, param = 'do_mgl'
                        , thresholds = c(2, 5)
                        , threshold_labs = c('Poor', 'Fair', 'Good')
                        , threshold_cols = c('#FEC596', '#FFFFCC', '#ABD9E9'))

z <-
  threshold_criteria_plot(dat_wq, param = 'do_mgl'
                        , rng = 2012
```



```

, thresholds = c(2, 5)
, threshold_labs = c('Poor', 'Fair', 'Good')
, threshold_cols = c('#FEC596', '#FFFFCC', '#ABD9E9')
, monthly_smooth = TRUE)

## A few examples with only two thresholds
xx <-
  threshold_criteria_plot(dat_wq, param = 'do_mgl'
    , rng = 2012
    , thresholds = c(2, 2)

    # A dummy blank (') value must be added as a threshold label
    , threshold_labs = c('Poor', '', 'Good')
    , threshold_cols = c('#FEC596', '#FFFFCC', '#ABD9E9')
    , monthly_smooth = TRUE)

xy <-
  threshold_criteria_plot(dat_wq, param = 'do_mgl'
    , rng = 2012
    , thresholds = c(5, 5)

    # A dummy blank (') value must be added as a threshold label
    , threshold_labs = c('Poor', '', 'Good')
    , threshold_cols = c('#FEC596', '#FEC596', '#ABD9E9')
    , monthly_smooth = TRUE)

xz <-
  threshold_criteria_plot(dat_wq, param = 'do_mgl'
    , rng = 2012
    , thresholds = c(2, 5)
    , threshold_labs = c('Poor', 'Good', 'Poor')
    , threshold_cols = c('#FEC596', '#ABD9E9', '#FEC596')
    , monthly_smooth = TRUE)

data(apacpnut)
dat_nut <- apacpnut

dat_nut <- qaqc(dat_nut, qaqc_keep = c(0, 3, 5))
dat_nut <- rem_reps(dat_nut)

x <-
  threshold_criteria_plot(dat_nut, param = 'chla_n'
    , thresholds = c(2, 5)
    , threshold_labs = c('Good', 'Fair', 'Poor'))

y <-
  threshold_criteria_plot(dat_nut, param = 'chla_n'
    , rng = 2012
    , thresholds = c(2, 5)
    , threshold_labs = c('Good', 'Fair', 'Poor'))

```

```
## Nutrient plots are not capable of accidentally displaying any kind of smooth
z <-
  threshold_criteria_plot(dat_nut, param = 'chla_n'
                        , rng = 2012
                        , thresholds = c(2, 5)
                        , threshold_labs = c('Good', 'Fair', 'Poor')
                        , monthly_smooth = TRUE)
```

threshold_identification

Tabulate Threshold Exceedances

Description

Tabulate user-specified threshold exceedances

Usage

```
threshold_identification(swmpr_in, ...)
```

```
## S3 method for class 'swmpr'
threshold_identification(swmpr_in, param,
  parameter_threshold, threshold_type, time_threshold = NULL, ...)
```

Arguments

swmpr_in	input swmpr object
...	arguments passed to other methods
param	vector of parameters to evaluate
parameter_threshold	vector of numerical thresholds to evaluate parameters against
threshold_type	vector of logical operators ('<', '>', '<=', '>=', '==', '!=')
time_threshold	The amount of time an event must last to be counted (in hours)

Details

This function creates tabular summary of events when a user-specified threshold is exceeded.

Before using this function, the user must apply [setstep](#) to normalize the `datetime` time step.

For MET and WQ data, the user must specify `time_threshold`. This argument is the minimum duration that an event must last in order to be counted. For example, if `time_threshold = 2`, `param = "do_mgl"`, `parameter_threshold = 2`, and `threshold_type = "<"` then dissolved oxygen must be lower than 2 mg/L for more than two hours or the event will not be summarized in the final table. For NUT parameters, all exceedances are included in the tabular summary.

Recommended thresholds for chlorophyll-a, dissolved inorganic nitrogen, dissolved inorganic phosphorus, and dissolved oxygen can be found in the National Coastal Condition Assessment 2010 (USEPA 2016)

 threshold_percentile_plot

Threshold Percentile Plot

Description

Observed data compared against user-defined percentiles

Usage

```
threshold_percentile_plot(swmpr_in, ...)

## S3 method for class 'swmpr'
threshold_percentile_plot(swmpr_in, param = NULL,
  hist_rng = NULL, target_yr = NULL, percentiles = c(0.05, 0.95),
  free_y = FALSE, by_month = FALSE, log_trans = FALSE,
  converted = FALSE, plot_title = FALSE, ...)
```

Arguments

swmpr_in	input swmpr object
...	additional arguments passed to other methods (not used for this function).
param	chr, variable to plot
hist_rng	num, years to include in the plot. This variable can either be one year (e.g., hist_rng = 2012), or two years (e.g. hist_rng = c(2012, 2016)) , If range is not specified then the entire data set will be used.
target_yr	num, year of interest for plotting. If not specified, the entire data set will be plotted.
percentiles	num, percentiles to calculate (maximum: 2). Defaults to 5th and 95th percentiles.
free_y	logical, should the y-axis be free? Defaults to FALSE. If FALSE, defaults to zero, unless negative values are present. If TRUE, y-axis limits are selected by ggplot
by_month	logical. should percentiles be calculated on a monthly basis? Defaults to FALSE
log_trans	logical, should y-axis be log? Defaults to FALSE
converted	logical, were the units converted from the original units used by CDMO? Defaults to FALSE. See y_labeler for details.
plot_title	logical, should the station name be included as the plot title? Defaults to FALSE

Details

This function provides an alternative to [threshold_criteria_plot](#). For parameters that may not have numeric threshold criteria, a percentile threshold can be used instead. For a one-tailed analysis, the 90-th percentile is recommended. For a two-tailed analysis, the 5-th and 95-th percentiles are recommended.

Using `by_month`, the user can specify whether the percentiles should be calculated on a monthly basis or by using the entire data set.

Recommended thresholds for chlorophyll-a, dissolved inorganic nitrogen, dissolved inorganic phosphorus, and dissolved oxygen can be found in the National Coastal Condition Assessment 2010 (USEPA 2016)

Value

Returns a `ggplot` object

Author(s)

Julie Padilla

References

United States Environmental Protection Agency (USEPA). 2015. "National Coastal Condition Assessment 2010". EPA 841-R-15-006. https://cfpub.epa.gov/si/si_public_record_Report.cfm?dirEntryId=327030

See Also

`ggplot`

Examples

```
dat_wq <- qaqc(elksmwq, qaqc_keep = c(0, 3, 5))
dat_wq <- subset(dat_wq, subset = '2007-01-01 0:00', operator = '>=')

x <-
  threshold_percentile_plot(dat_wq, param = 'do_mgl'
    , hist_rng = c(2007, 2014), by_month = FALSE)

y <-
  threshold_percentile_plot(dat_wq, param = 'do_mgl', percentiles = c(0.95)
    , hist_rng = c(2007, 2014), target_yr = 2014, by_month = FALSE)

x2 <-
  threshold_percentile_plot(dat_wq, param = 'do_mgl'
    , hist_rng = c(2007, 2014), by_month = TRUE)

y2 <-
  threshold_percentile_plot(dat_wq, param = 'do_mgl'
    , hist_rng = c(2007, 2014), target_yr = 2014, by_month = TRUE)

dat_nut <- qaqc(elknmnut, qaqc_keep = c(0, 3, 5))
dat_nut <- subset(dat_nut, subset = '2007-01-01 0:00', operator = '>=')
dat_nut <- rem_reps(dat_nut)

x <-
```

```

threshold_percentile_plot(dat_nut, param = 'chla_n'
, hist_rng = c(2007, 2014), by_month = FALSE)

y <-
threshold_percentile_plot(dat_nut, param = 'chla_n'
, hist_rng = c(2007, 2014), target_yr = 2016, by_month = FALSE)

```

threshold_summary *Summary Plots for Threshold Identification*

Description

Summary plots for threshold identification analysis

Usage

```

threshold_summary(swmpr_in, ...)

## S3 method for class 'swmpr'
threshold_summary(swmpr_in, param = NULL,
  summary_type = c("month", "season", "year"),
  parameter_threshold = NULL, threshold_type = NULL,
  time_threshold = NULL, converted = FALSE, pal = "Set3",
  plot_title = FALSE, plot = TRUE, label_y_axis = TRUE, ...)

```

Arguments

swmpr_in	input swmpr object
...	additional arguments passed to other methods. See assign_season for more details.
param	chr string of variable to plot (one only)
summary_type	Choose from month, season, or year aggregation
parameter_threshold	vector of numerical thresholds to evaluate parameters against
threshold_type	vector of logical operators ('<', '>', '<=', '>=', '==', '!=')
time_threshold	The amount of time an event must last to be counted (in hours)
converted	logical, were the units converted from the original units used by CDMO? Defaults to FALSE. See y_labeler for details.
pal	Select a palette for boxplot fill colors. See scale_fill_brewer for more details.
plot_title	logical, should the station name be included as the plot title? Defaults to FALSE
plot	logical, should a plot be returned? Defaults to TRUE
label_y_axis	logical, include label for y-axis?

Details

This function provides a graphical or tabular summary of the results from `threshold_identification`. The user can summarize results on a monthly, seasonal, or annual basis by specifying `summary_type = c('month', 'season', 'year')`. If `summary_type = 'season'`, then the user should also define `season`, `season_names`, and `season_start`, as required by `lcodeassign_season`. The user can specify 'month' for nutrient parameters, but this is not recommended and will produce a warning.

Recommended thresholds for chlorophyll-a, dissolved inorganic nitrogen, dissolved inorganic phosphorus, and dissolved oxygen can be found in the National Coastal Condition Assessment 2010 (USEPA 2016)

Value

Returns a `ggplot` object (if `plot = TRUE`) or a dataframe (if `plot = FALSE`)

Author(s)

Julie Padilla

References

United States Environmental Protection Agency (USEPA). 2015. "National Coastal Condition Assessment 2010". EPA 841-R-15-006. https://cfpub.epa.gov/si/si_public_record_Report.cfm?dirEntryId=327030

See Also

[assign_season](#), [ggplot](#), [threshold_identification](#), [scale_fill_brewer](#)

Examples

```
## Water quality examples
dat_wq <- qaqc(apacpwq, qaqc_keep = c(0, 3, 5))
dat_wq <- setstep(dat_wq)

x <-
  threshold_summary(dat_wq, param = 'do_mgl', parameter_threshold = 2
    , threshold_type = '<', time_threshold = 2, summary_type = 'month'
    , plot_title = TRUE)

y <-
  threshold_summary(dat_wq, param = 'do_mgl', parameter_threshold = 2,
    threshold_type = '<', time_threshold = 2, summary_type = 'season',
    season = list(c(1,2,3), c(4,5,6), c(7,8,9), c(10, 11, 12)),
    season_names = c('Winter', 'Spring', 'Summer', 'Fall'),
    season_start = 'Winter',
    plot_title = TRUE)

## Nutrient examples
dat_nut <- qaqc(apacpnut, qaqc_keep = c(0, 3, 5))
```

```
x <-
  threshold_summary(dat_nut, param = 'chla_n',
    parameter_threshold = 10,
    threshold_type = '>', summary_type = 'month',
    plot_title = TRUE)

y <-
  threshold_summary(dat_nut, param = 'chla_n', parameter_threshold = 10,
    threshold_type = '>', summary_type = 'season',
    season = list(c(1,2,3), c(4,5,6), c(7,8,9), c(10, 11, 12)),
    season_names = c('Winter', 'Spring', 'Summer', 'Fall'),
    season_start = 'Winter', plot_title = TRUE)

z <-
  threshold_summary(dat_nut, param = 'chla_n', parameter_threshold = 10,
    threshold_type = '>', summary_type = 'year',
    plot_title = TRUE, plot = TRUE)
```

title_labeler

Generate Plot Title Based on NERR Site ID

Description

Generate a plot title based on SWMP station abbreviation

Usage

```
title_labeler(nerr_site_id)
```

Arguments

nerr_site_id chr string of NERR site id

Details

A helper function used internally by several plotting functions to generate plot titles.

Value

Returns character vector

Author(s)

Julie Padilla

Examples

```
t1 <- title_labeler('elkapwq')
```

us_aea *US County Map*

Description

US County boundaries from the US Census Bureau's MAF/TIGER geographic database. Re-projected using Albers Equal Area.

Usage

```
data(us_aea)
```

Format

A [SpatialPolygonsDataFrame](#) object

Source

[US Census Bureau](#)

References

United States Census Bureau. Data accessed from the US Census Bureau website: <http://www2.census.gov/geo/tiger/GENZ2> accessed 06 April 2018

y_count_labeler *Generate y-axis Label Based on SWMP Parameter Abbreviation*

Description

Generate a y-axis label based on SWMP parameter abbreviation and threshold criteria

Usage

```
y_count_labeler(param, parameter_threshold, threshold_type,
  time_threshold = NULL, converted = FALSE)
```

Arguments

param	chr string of variable abbreviation
parameter_threshold	vector of numerical thresholds to evaluate parameters against
threshold_type	vector of logical operators ('<', '>', '<=', '>=', '==', '!=')
time_threshold	The amount of time an event must last to be counted (in hours)
converted	logical, should the parameter label units be converted from metric to english? Defaults to FALSE. Currently available for temp, depth, cdepth, level, clevel, atemp, wspd, maxwspd, and totprcp

Details

A helper function used internally by several plotting functions to generate y-axis labels. This function does not convert sample results from metric to english. It only adjusts the units in the y-axis label.

Value

Returns character vector or an unevaluated expression

Author(s)

Julie Padilla

Examples

```
y_lab <- y_count_labeler(param = 'do_mgl', parameter_threshold = 2
, threshold_type = '<', time_threshold = 2, converted = FALSE)
```

y_labeler

Generate y-axis Label Based on SWMP Parameter Abbreviation

Description

Generate a y-axis label based on SWMP parameter abbreviation

Usage

```
y_labeler(param, converted = FALSE)
```

Arguments

param	chr string of variable abbreviation
converted	logical, should the parameter label units be converted from metric to english? Defaults to FALSE. Currently available for temp, depth, cdepth, level, clevel, atemp, wspd, maxwspd, and totprcp

Details

A helper function used internally by several plotting functions to generate y-axis labels. This function does not convert sample results from metric to english. It only adjusts the units in the y-axis label.

Value

Returns character vector or an unevaluated expression

y_labeler

59

Author(s)

Julie Padilla

Examples

```
y_lab <- y_labeler('do_mgl')
```

Index

*Topic **datasets**

- cbm_spatial, 6
 - elk_spatial, 11
 - elkmmnut, 10
 - elksmwq, 10
 - sampling_stations, 35
 - us_aea, 57
- all_params, 22
- all_params_dtrng, 22
- annual_range, 3
- assign_season, 3, 4, 4, 19, 20, 25, 26, 36–41, 44, 54, 55
- cbm_spatial, 6
- create_sk_flextable_list, 7, 12, 13
- create_sk_national_ft_reserves, 8
- create_sk_national_ft_results, 9
- data.frame, 10, 35
- elk_spatial, 11
- elkmmnut, 10
- elksmwq, 10
- flextable, 8, 9, 11, 12
- ft_col_names, 11
- generate_results_table, 12
- generate_station_table, 13
- geographic_unique_stations, 13
- get_reserve, 14
- get_shp_name, 15
- get_site_code, 16
- get_site_coordinates, 17
- get_sites, 15
- ggplot, 4, 18, 20, 24–26, 32, 36, 37, 39–41, 48, 53, 55
- historical_daily_range, 17
- historical_range, 19
- import_local, 22
- import_local_nut, 21
- kendallSeasonalTrendTest, 44, 45
- lm, 22
- lm_p_labs, 22
- load_shp_file, 23
- national_sk_map, 23
- raw_boxplot, 25
- rem_reps, 21, 22
- remove_inf_and_nan, 26
- res_custom_map, 27
- res_custom_sk_map, 29
- res_local_map, 14, 23, 30
- res_national_map, 27, 32
- res_sk_map, 23, 33
- reserve_locs, 27
- sampling_stations, 35
- scale_fill_brewer, 54, 55
- scale_x_datetime, 42, 43
- seasonal_barplot, 36
- seasonal_boxplot, 37
- seasonal_dot, 22, 40
- set_date_break_labs, 42, 43
- set_date_breaks, 42, 43
- setstep, 50
- single_param, 22
- sk_seasonal, 7, 8, 12, 13, 29, 34, 43, 45
- sk_tidy, 45
- sp, 23
- SpatialPolygons, 6, 11
- SpatialPolygonsDataFrame, 57
- std_param_check, 45
- summarise_handoff_files, 46
- threshold_criteria_plot, 47, 52
- threshold_identification, 50, 55

threshold_percentile_plot, [52](#)
threshold_summary, [54](#)
title_labeler, [56](#)

us_aea, [57](#)

y_count_labeler, [57](#)
y_labeler, [4](#), [18](#), [20](#), [25](#), [26](#), [37](#), [41](#), [44](#), [47](#),
[48](#), [58](#)