

Package ‘decido’

August 22, 2018

Version 0.2.0

Title Bindings for 'Mapbox' Ear Cutting Triangulation Library

Description Provides constrained triangulation of polygons. Ear cutting (or ear clipping) applies constrained triangulation by successively 'cutting' triangles from a polygon defined by path/s. Holes are supported by introducing a bridge segment between polygon paths. This package wraps the 'header-only' library 'earcut.hpp' <<https://github.com/mapbox/earcut.hpp.git>> which includes a reference to the method used by Held, M. (2001) <doi:10.1007/s00453-001-0028-4>.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

ByteCompile true

LinkingTo Rcpp

Depends R (>= 3.0.0)

Imports Rcpp

RoxygenNote 6.1.0

Suggests covr, testthat, knitr, oz, rmarkdown

SystemRequirements C++11

VignetteBuilder knitr

URL <https://hypertidy.github.io/decido>

BugReports <https://github.com/hypertidy/decido/issues>

NeedsCompilation yes

Author Michael Sumner [aut, cre],
Andrew Smith [ctb] (provided C++ guidance),
Mapbox [cph] (author of header library earcut.hpp),
Mark Padgham [ctb] (help with CRAN issues)

Maintainer Michael Sumner <mdsumner@gmail.com>

Repository CRAN

Date/Publication 2018-08-21 22:10:07 UTC

R topics documented:

earcut	2
plot_ears	3
Index	5

earcut	<i>Constrained polygon triangulation</i>
--------	--

Description

Produce a triangulation index into x,y coordinates of a polygon that may include holes. Holes are specified by input argument `holes` which marks the starting index of each hole, if any.

Usage

```
earcut(xy, holes = 0, ...)
```

Default S3 method:
earcut(xy, holes = 0L, ...)

Arguments

<code>xy</code>	xy-coordinates, either a list, matrix, or data frame
<code>holes</code>	index of starting position of each hole in x,y, leave set to 0 if no holes
<code>...</code>	unused

Details

Ear cutting (or ear clipping) applies constrained triangulation by successively 'cutting' triangles from a polygon defined by path/s. Holes are supported, the earcut library works with single-island-with-holes polygons, analogous to the POLYGON type in simple features.

To understand the specification of holes, see the examples with comment starting "1) Notice how the hole begins ..." in relation to the example code.

Value

integer vector of triangle index, in sets of three

See Also

plot_ears

Examples

```

## single ring polygon
x <- c(0, 0, 0.75, 1, 0.5, 0.8, 0.69)
y <- c(0, 1, 1, 0.8, 0.7, 0.6, 0)
(ind <- earcut(cbind(x, y)))
plot_ears(cbind(x, y), ind)

## polygon with a hole
x <- c(0, 0, 0.75, 1, 0.5, 0.8, 0.69,
      0.2, 0.5, 0.5, 0.3, 0.2)
y <- c(0, 1, 1, 0.8, 0.7, 0.6, 0,
      0.2, 0.2, 0.4, 0.6, 0.4)
ind <- earcut(cbind(x, y), holes = 8)
plot_ears(cbind(x, y), ind)

## 1) Notice how the hole begins at index 8,
## hence holes = 8 above, and holes = c(8, 13) below
plot_ears(cbind(x, y), ind, col = "grey", border = NA)
text(x, y, labels = seq_along(x), pos = 2)

## add another hole
x <- c(0, 0, 0.75, 1, 0.5, 0.8, 0.69,
      0.2, 0.5, 0.5, 0.3, 0.2,
      0.15, 0.23, 0.2)
y <- c(0, 1, 1, 0.8, 0.7, 0.6, 0,
      0.2, 0.2, 0.4, 0.6, 0.4,
      0.65, 0.65, 0.81)
ind <- earcut(cbind(x, y), holes = c(8, 13))
plot_ears(cbind(x, y), ind, col = "grey")
# simpler shape with more than one hole
# the two inside holes are open to each other
# (so we can use the same data for one hole or two)
x <- c(0, 0, 1, 1,
      0.4, 0.2, 0.2, 0.4,
      0.6, 0.8, 0.8, 0.6
)
y <- c(0, 1, 1, 0,
      0.2, 0.2, 0.4, 0.4,
      0.6, 0.6, 0.4, 0.4
)
ind <- decido::earcut(cbind(x, y), holes = c(5, 9))
plot_ears(cbind(x, y), ind, col = "grey")
plot_holes(cbind(x, y), holes = c(5, 9), col = "grey")
ind <- decido::earcut(cbind(x, y), holes = 5)
plot_ears(cbind(x, y), ind, col = "grey")
plot_holes(cbind(x, y), holes = 5, col = "grey")

```

Description

Plot the triangles produced by [earcut](#), or plot the polygon paths using the same interface as [earcut](#) uses. This allows for easy comparison and checking of what the results should be.

Usage

```
plot_ears(xy, idx, add = FALSE, ...)
```

```
plot_holes(xy, holes = 0, add = FALSE, ...)
```

Arguments

xy	xy-coordinates, either a list, matrix, or data frame
idx	index of triangles
add	add to current plot, or create a new
...	arguments to polypath
holes	index of starting position of holes (see earcut)

Details

For both functions the first input is a matrix of x,y coordinates.

For [plot_ears](#) the second input is the index output of [earcut](#). The index is treated in sets of 3 values, with individual calls to [polypath](#) to draw a polygon for each triangle.

For [plot_holes](#) the second input is the `holes` argument that would be used for [earcut](#). This is used to split the coordinates at these positions, inserting NA values as per the mechanism used by [graphics::polypath](#) to break coordinates into separate polygon rings. (There's no winding rule here `plot_rules` is hard-coded to always use the evenodd rule, so that winding order may be ignored).

See Also

[earcut](#)

Examples

```
## after ?polypath
x <- cbind(c(.1, .1, .9, .9, .2, .2, .8, .8),
          c(.1, .9, .9, .1, .2, .8, .8, .2))
plot_holes(x, holes = 5, col = "grey")
```

Index

earcut, [2](#), [4](#)

graphics::polypath, [4](#)

plot_ears, [3](#), [4](#)

plot_holes, [4](#)

plot_holes(plot_ears), [3](#)

polypath, [4](#)