

Package ‘detrendr’

July 8, 2019

Type Package

Title Detrend Images

Version 0.6.4

Maintainer Rory Nolan <rorynolan@gmail.com>

Description Detrend fluorescence microscopy image series for fluorescence fluctuation and correlation spectroscopy ('FCS' and 'FFS') analysis. This package contains functionality published in a 2016 paper <doi:10.1093/bioinformatics/btx434> but it has been extended since then with the Robin Hood algorithm and thus contains unpublished work.

License BSD_3_clause + file LICENSE

Encoding UTF-8

LazyData true

SystemRequirements GNU make

Depends R (>= 3.1)

LinkingTo Rcpp (>= 1.0.1), RcppParallel (>= 4.4.3)

Imports Rcpp (>= 1.0.1), RcppParallel (>= 4.4.3), parallel, checkmate (>= 1.9.3), magrittr (>= 1.5), dplyr, foreach, doParallel, iterators, purrr, ijtiff (>= 2.0.2), autothresholdr (>= 1.3.3), rlang (>= 0.3.3), stringr (>= 1.2.0), filesstrings (>= 3.1.5), plyr, glue (>= 1.3.0), sigmoid, matrixStats, stringi (>= 1.3.1), assertthat, withr (>= 2.1.0), fs (>= 1.3.1)

URL <https://rorynolan.github.io/detrendr>,
<https://www.github.com/rorynolan/detrendr>

BugReports <https://www.github.com/rorynolan/detrendr/issues>

RoxygenNote 6.1.1

Suggests testthat, knitr, rmarkdown, covr, abind, lattice, pacman, tidy, graphics, gridExtra, arrayhelpers, MASS, mgcv, spelling

VignetteBuilder knitr

Language en-US

NeedsCompilation yes

Author Rory Nolan [aut, cre] (<<https://orcid.org/0000-0002-5239-4043>>),
 Luis Alvarez [ctb, cph] (<<https://orcid.org/0000-0003-1316-1906>>),
 Sergi Padilla-Parra [ctb, ths, cph]
 (<<https://orcid.org/0000-0002-8010-9481>>)

Repository CRAN

Date/Publication 2019-07-08 16:40:03 UTC

R topics documented:

apply_on_pillars	2
best_degree	3
best_l	4
best_swaps	5
best_tau	6
brightness_pillars	7
detrend-directory	8
detrended_img	10
detrending	11
detrendr	13
mean_frames	14
pillar-stats	14
rfromboxes	15
rtoboxes	16
Index	17

apply_on_pillars	<i>Apply a function to each pillar of a 3-dimensional array.</i>
------------------	--

Description

Define a 'pillar' of a 3-dimensional array as pillar i, j of array `arr` being `arr[i, j,]`. This function applies a specified function to each pillar.

Usage

```
apply_on_pillars(arr3d, FUN)
```

Arguments

<code>arr3d</code>	A 3-dimensional array.
<code>FUN</code>	A function which takes a vector as input and, for a given input length, outputs a vector of constant length (can be 1).

Value

If FUN is returning length 1 vectors, a matrix whereby $\text{mat}[i, j] = \text{FUN}(\text{arr3d}[i, j, \])$.
 If FUN is returning vectors of length $l > 1$, a 3-dimensional array whereby $\text{arr}[i, j, \] = \text{FUN}(\text{arr3d}[i, j, \])$.

best_degree	<i>Find the best polynomial degree for polynomial detrending.</i>
-------------	---

Description

Use Nolan's algorithm to find the ideal polynomial degree for polynomial detrending.

Usage

```
best_degree(img, parallel = FALSE, purpose = c("FCS", "FFS"))
```

Arguments

img	A 4-dimensional array in the style of an ijtiff_img (indexed by $\text{img}[y, x, \text{channel}, \text{frame}]$) or a 3-dimensional array which is a single channel of an ijtiff_img (indexed by $\text{img}[y, x, \text{frame}]$).
parallel	Would you like to use multiple cores to speed up this function? If so, set the number of cores here, or to use all available cores, use <code>parallel = TRUE</code> .
purpose	What type of calculation do you intend to perform on the detrended image? If it is an FFS (fluorescence fluctuation spectroscopy) calculation (like number and brightness), choose 'FFS'. If it is an FCS (fluorescence correlation spectroscopy) calculation (like cross-correlated number and brightness or autocorrelation), choose 'FCS'. The difference is that if purpose is 'FFS', the time series is corrected for non-stationary mean and variance, whereas if purpose is 'FCS', the time series is corrected for non-stationary mean only. 'purpose' is not required for <i>Robin Hood</i> detrending.

Value

If no detrend is necessary, this function returns NA. If a detrend is required, this function returns a natural number which is the ideal polynomial degree for polynomial detrending. If there are multiple channels, the function returns a vector, one degree parameter for each channel.

References

Rory Nolan, Luis A. J. Alvarez, Jonathan Elegheert, Maro Iliopoulou, G. Maria Jakobsdottir, Marina Rodriguez-Muñoz, A. Radu Aricescu, Sergi Padilla-Parra; nandb—number and brightness in R with a novel automatic detrending algorithm, *Bioinformatics*, <https://doi.org/10.1093/bioinformatics/btx434>.

Examples

```
## Not run:
## These examples are not run on CRAN because they take too long.
## You can still try them for yourself.
img <- ijrtiff::read_tif(system.file("extdata", "bleached.tif",
  package = "detrandr"
))
best_degree(img, parallel = 2)

## End(Not run)
```

best_l

Find the best length parameter for boxcar detrending.

Description

Use Nolan's algorithm to find the ideal length parameter for boxcar detrending. Boxcar detrending is also referred to as 'running average'.

Usage

```
best_l(img, parallel = FALSE, purpose = c("FCS", "FFS"))
```

Arguments

img	A 4-dimensional array in the style of an ijrtiff_img (indexed by <code>img[y, x, channel, frame]</code>) or a 3-dimensional array which is a single channel of an ijrtiff_img (indexed by <code>img[y, x, frame]</code>).
parallel	Would you like to use multiple cores to speed up this function? If so, set the number of cores here, or to use all available cores, use <code>parallel = TRUE</code> .
purpose	What type of calculation do you intend to perform on the detrended image? If it is an FFS (fluorescence fluctuation spectroscopy) calculation (like number and brightness), choose 'FFS'. If it is an FCS (fluorescence correlation spectroscopy) calculation (like cross-correlated number and brightness or autocorrelation), choose 'FCS'. The difference is that if purpose is 'FFS', the time series is corrected for non-stationary mean and variance, whereas if purpose is 'FCS', the time series is corrected for non-stationary mean only. 'purpose' is not required for <i>Robin Hood</i> detrending.

Value

If no detrend is necessary, this function returns NA. If a detrend is required, this function returns a natural number which is the ideal length parameter for boxcar detrending. If there are multiple channels, the function returns a vector, one l parameter for each channel.

References

Rory Nolan, Luis A. J. Alvarez, Jonathan Elegheert, Maro Iliopoulou, G. Maria Jakobsdottir, Marina Rodriguez-Muñoz, A. Radu Aricescu, Sergi Padilla-Parra; nandb—number and brightness in R with a novel automatic detrending algorithm, *Bioinformatics*, <https://doi.org/10.1093/bioinformatics/btx434>.

Examples

```
## Not run:
## These examples are not run on CRAN because they take too long.
## You can still try them for yourself.
img <- ijtiff::read_tif(system.file("extdata", "bleached.tif",
  package = "detrendr"
))
best_l(img, parallel = 2, purpose = "FFS")

## End(Not run)
```

best_swaps

Find the best swaps parameter for Robin Hood detrending.

Description

Use Nolan's algorithm to find the ideal swaps parameter for *Robin Hood* detrending.

Usage

```
best_swaps(img, quick = FALSE)
```

Arguments

img	A 4-dimensional array in the style of an ijtiff_img (indexed by <code>img[y, x, channel, frame]</code>) or a 3-dimensional array which is a single channel of an ijtiff_img (indexed by <code>img[y, x, frame]</code>).
quick	If FALSE (the default), the swap finding routine is run several times to get a consensus for the best parameter. If TRUE, the swap finding routine is run only once.

Value

A natural number. The ideal swaps parameter for boxcar detrending. If there are multiple channels, the function returns a vector, one swaps parameter for each channel.

Examples

```
## Not run:
## These examples are not run on CRAN because they take too long.
## You can still try them for yourself.
img <- ijttiff::read_tif(system.file("extdata", "bleached.tif",
  package = "detrindr"
))
best_swaps(img)

## End(Not run)
```

best_tau

Find the best tau parameter for exponential smoothing detrending.

Description

Use Nolan's algorithm to find the ideal tau parameter for exponential smoothing detrending.

Usage

```
best_tau(img, cutoff = 0.05, parallel = FALSE, purpose = c("FCS",
  "FFS"))
```

Arguments

img	A 4-dimensional array in the style of an ijttiff_img (indexed by <code>img[y, x, channel, frame]</code>) or a 3-dimensional array which is a single channel of an ijttiff_img (indexed by <code>img[y, x, frame]</code>).
cutoff	In <i>exponential filtering</i> detrending, for the weighted average, every point gets a weight. This can slow down the computation massively. However, many of the weights will be approximately zero. With cutoff, we say that any point with weight less than or equal to cutoff times the maximum weight may be ignored; so with <code>cutoff = 0.05</code> , any weight less than 5% of the maximum weight may be ignored. The default value of this parameter is sensible and its value should not be set to anything else without good reason.
parallel	Would you like to use multiple cores to speed up this function? If so, set the number of cores here, or to use all available cores, use <code>parallel = TRUE</code> .
purpose	What type of calculation do you intend to perform on the detrended image? If it is an FFS (fluorescence fluctuation spectroscopy) calculation (like number and brightness), choose 'FFS'. If it is an FCS (fluorescence correlation spectroscopy) calculation (like cross-correlated number and brightness or autocorrelation), choose 'FCS'. The difference is that if purpose is 'FFS', the time series is corrected for non-stationary mean and variance, whereas if purpose is 'FCS', the time series is corrected for non-stationary mean only. 'purpose' is not required for <i>Robin Hood</i> detrending.

Value

If no detrend is necessary, this function returns NA. If a detrend is required, this function returns a natural number which is the ideal tau parameter for exponential smoothing detrending. If there are multiple channels, the function returns a vector, one tau parameter for each channel.

References

Rory Nolan, Luis A. J. Alvarez, Jonathan Elegheert, Maro Iliopoulou, G. Maria Jakobsdottir, Marina Rodriguez-Muñoz, A. Radu Aricescu, Sergi Padilla-Parra; nandb—number and brightness in R with a novel automatic detrending algorithm, *Bioinformatics*, <https://doi.org/10.1093/bioinformatics/btx434>.

Examples

```
## Not run:
## These examples are not run on CRAN because they take too long.
## You can still try them for yourself.
img <- ijttiff::read_tif(system.file("extdata", "bleached.tif",
  package = "detrendr"
))[, , 1, ]
best_tau(img, parallel = 2)

## End(Not run)
```

brightness_pillars *Get the brightness of pillars of a 3d array.*

Description

For an [ijttiff_img](#)-style array `img` (indexed as `img[y, x, channel, frame]`), 3-dimensional array `mat3d`, pillar `xy` of channel `ch` is defined as `img[y, x, ch,]`. This function computes the brightness, of each pillar.

Usage

```
brightness_pillars(img, parallel = FALSE)
```

Arguments

<code>img</code>	A 4-dimensional array in the style of an ijttiff_img (indexed by <code>img[y, x, channel, frame]</code>) or a 3-dimensional array which is a single channel of an ijttiff_img (indexed by <code>img[y, x, frame]</code>).
<code>parallel</code>	Would you like to use multiple cores to speed up this function? If so, set the number of cores here, or to use all available cores, use <code>parallel = TRUE</code> .

Value

An [ijttiff_img](#)-style array `arr` with one frame. `arr[y, x, ch, 1]` is equal to `var(img[y, x, ch,]) / mean(img[y, x, ch,])`

Examples

```
aaa <- array(1:16, dim = c(2, 2, 4))
brightness_pillars(aaa)
```

detrend-directory *Detrend all TIFF images in an entire folder.*

Description

Batch processing. Apply any of the available detrending routines to detrend all of the TIFF images in a folder, saving the detrended images as TIFF files in the same folder.

Usage

```
dir_detrend_robinhood(folder_path = ".", swaps = "auto",
  thresh = NULL, quick = FALSE, msg = TRUE)
```

```
dir_detrend_rh(folder_path = ".", swaps = "auto", thresh = NULL,
  quick = FALSE, msg = TRUE)
```

```
dir_detrend_boxcar(folder_path = ".", l, purpose = c("FCS", "FFS"),
  thresh = NULL, parallel = FALSE, msg = TRUE)
```

```
dir_detrend_exp(folder_path = ".", tau, purpose = c("FCS", "FFS"),
  thresh = NULL, parallel = FALSE, msg = TRUE)
```

```
dir_detrend_polynom(folder_path = ".", degree, purpose = c("FCS",
  "FFS"), thresh = NULL, parallel = FALSE, msg = TRUE)
```

Arguments

folder_path	The path (relative or absolute) to the folder you wish to process.
swaps	The number of swaps (giving of one count from rich to poor) to perform during the <i>Robin Hood</i> detrending. Set this to "auto" (the default) to use Nolan's algorithm to automatically find a suitable value for this parameter (recommended). For multi-channel images, it is possible to have a different swaps for each channel by specifying swaps as a vector or list.
thresh	The threshold or thresholding method (see autothreshldr::mean_stack_thresh()) to use on the image prior to detrending.
quick	If FALSE (the default), the swap finding routine is run several times to get a consensus for the best parameter. If TRUE, the swap finding routine is run only once.
msg	Receive messages to tell you how the processing of the directory is going? Default is yes.

l	The length parameter for <i>boxcar</i> detrending. The size of the sliding window will be $2 * l + 1$. This must be a positive integer. Set this to "auto" to use Nolan's algorithm to automatically find a suitable value for this parameter (recommended). For multi-channel images, it is possible to have a different l for each channel by specifying l as a vector or list.
purpose	What type of calculation do you intend to perform on the detrended image? If it is an FFS (fluorescence fluctuation spectroscopy) calculation (like number and brightness), choose 'FFS'. If it is an FCS (fluorescence correlation spectroscopy) calculation (like cross-correlated number and brightness or autocorrelation), choose 'FCS'. The difference is that if purpose is 'FFS', the time series is corrected for non-stationary mean and variance, whereas if purpose is 'FCS', the time series is corrected for non-stationary mean only. 'purpose' is not required for <i>Robin Hood</i> detrending.
parallel	Would you like to use multiple cores to speed up this function? If so, set the number of cores here, or to use all available cores, use parallel = TRUE.
tau	The <i>tau</i> parameter for <i>exponential filtering</i> detrending. This must be a positive number. Set this to "auto" to use Nolan's algorithm to automatically find a suitable value for this parameter (recommended). For multi-channel images, it is possible to have a different tau for each channel by specifying tau as a vector or list.
degree	The degree of the polynomial to use for the polynomial detrending. This must be a positive integer. Set this to "auto" to use Nolan's algorithm to automatically find a suitable value for this parameter (recommended). For multi-channel images, it is possible to have a different degree for each channel by specifying degree as a vector or list.

Details

These functions include a thresholding option, unlike their non-batch processing counterparts which they wrap (i.e. [img_detrend_boxcar](#), [img_detrend_exp](#) and [img_detrend_polynom](#)). This is because, when working interactively, it's easy to threshold and then detrend, but for batch processing, it's not so easy to efficiently do one after the other, so it's nice to have that taken care of should you want it.

Value

Silently, a character vector of the paths to the detrended images.

Examples

```
## Not run:
setwd(tempdir())
file.copy(
  c(
    system.file("extdata", "bleached.tif", package = "detrendr"),
    system.file("img", "2ch_ij.tif", package = "ijtiff")
  ),
  ".",
)
```

```

dir_detrend_robinhood(thresh = "huang")
dir_detrend_boxcar(l = "auto", thresh = "tri", purpose = "FFS")
dir_detrend_exp(tau = "auto", thresh = "tri", purpose = "FCS")
dir_detrend_polynom(degree = "auto", thresh = "huang", purpose = "FFS")

## End(Not run)

```

detrended_img	<i>Detrended image class.</i>
---------------	-------------------------------

Description

A [detrended_img](#) is a 4-dimensional array of positive integers in the style of an [ijtiff_img](#) (indexed by `img[y, x, channel, frame]`) which is the result of a detrending routine. It has 4 attributes:

`method` The detrending method used. This must be one of "boxcar", "exponential" or "polynomial".

`parameter` The value of the parameter used. This will be the `l`, `tau` or `degree` parameter for the respective methods.

`auto` A boolean that is TRUE if the parameter was found automatically or FALSE if it was manually selected.

`purpose` Either "FCS" or "FFS" to denote whether the detrending was done for the purpose of fluorescence correlation spectroscopy or fluorescence fluctuation spectroscopy calculations respectively. `purpose` is not required for *Robin Hood* detrending.

Usage

```
detrended_img(img, method, parameter, auto, purpose = NULL)
```

Arguments

<code>img</code>	The detrended image series. A 4-dimensional array of non-negative integers in the style of an ijtiff_img , or a 3-dimensional array of non-negative integers which represents a single channel of an ijtiff_img -style array (indexed by <code>img[y, x, frame]</code>).
<code>method</code>	The method used. One of "robinhood", "boxcar", "exponential" or "polynomial".
<code>parameter</code>	A number. The detrend parameter used. One per channel.
<code>auto</code>	Logical. Was automatic detrending used? One per channel.
<code>purpose</code>	Either "FCS" or "FFS". Was the image detrended for the purpose of doing FCS or FFS calculations? See detrending . <code>purpose</code> is not required for <i>Robin Hood</i> detrending.

Details

Sometimes when detrending, you can get slight negative values in the detrended image. These values should really just be zero, so this constructor function sets negative values of `img` to zero.

Value

An object of class `detrended_img`.

detrending	<i>Detrend images.</i>
------------	------------------------

Description

Correct images for bleaching (or any other effect that introduces an unwanted trend) by *detrending*.

Usage

```
img_detrend_robinhood(img, swaps = "auto", quick = FALSE)
```

```
img_detrend_rh(img, swaps = "auto", quick = FALSE)
```

```
img_detrend_boxcar(img, l, purpose = c("FCS", "FFS"), parallel = FALSE)
```

```
img_detrend_exp(img, tau, cutoff = 0.05, purpose = c("FCS", "FFS"),
  parallel = FALSE)
```

```
img_detrend_polynom(img, degree, purpose = c("FCS", "FFS"),
  parallel = FALSE)
```

Arguments

img	A 4-dimensional array in the style of an ijtiff_img (indexed by <code>img[y, x, channel, frame]</code>) or a 3-dimensional array which is a single channel of an ijtiff_img (indexed by <code>img[y, x, frame]</code>).
swaps	The number of swaps (giving of one count from rich to poor) to perform during the <i>Robin Hood</i> detrending. Set this to "auto" (the default) to use Nolan's algorithm to automatically find a suitable value for this parameter (recommended). For multi-channel images, it is possible to have a different swaps for each channel by specifying swaps as a vector or list.
quick	If FALSE (the default), the swap finding routine is run several times to get a consensus for the best parameter. If TRUE, the swap finding routine is run only once.
l	The length parameter for <i>boxcar</i> detrending. The size of the sliding window will be $2 * l + 1$. This must be a positive integer. Set this to "auto" to use Nolan's algorithm to automatically find a suitable value for this parameter (recommended). For multi-channel images, it is possible to have a different l for each channel by specifying l as a vector or list.
purpose	What type of calculation do you intend to perform on the detrended image? If it is an FFS (fluorescence fluctuation spectroscopy) calculation (like number

and brightness), choose 'FFS'. If it is an FCS (fluorescence correlation spectroscopy) calculation (like cross-correlated number and brightness or autocorrelation), choose 'FCS'. The difference is that if purpose is 'FFS', the time series is corrected for non-stationary mean and variance, whereas if purpose is 'FCS', the time series is corrected for non-stationary mean only. 'purpose' is not required for *Robin Hood* detrending.

parallel	Would you like to use multiple cores to speed up this function? If so, set the number of cores here, or to use all available cores, use <code>parallel = TRUE</code> .
tau	The <i>tau</i> parameter for <i>exponential filtering</i> detrending. This must be a positive number. Set this to "auto" to use Nolan's algorithm to automatically find a suitable value for this parameter (recommended). For multi-channel images, it is possible to have a different tau for each channel by specifying tau as a vector or list.
cutoff	In <i>exponential filtering</i> detrending, for the weighted average, every point gets a weight. This can slow down the computation massively. However, many of the weights will be approximately zero. With cutoff, we say that any point with weight less than or equal to cutoff times the maximum weight may be ignored; so with <code>cutoff = 0.05</code> , any weight less than 5% of the maximum weight may be ignored. The default value of this parameter is sensible and its value should not be set to anything else without good reason.
degree	The degree of the polynomial to use for the polynomial detrending. This must be a positive integer. Set this to "auto" to use Nolan's algorithm to automatically find a suitable value for this parameter (recommended). For multi-channel images, it is possible to have a different degree for each channel by specifying degree as a vector or list.

Details

There are 4 detrending methods available: *Robin Hood*, *boxcar*, *exponential filtering* and *polynomial*. *Robin Hood* is described in Nolan et al., 2018. The others are described in Nolan et al., 2017.

- *Robin Hood* is a method whereby counts are taken from frames with higher mean intensity and given directly to frames of lower intensity.
- *Boxcar* detrending with parameter l is a moving average detrending method using a sliding window of size $2l + 1$.
- *Exponential filtering* detrending is a moving weighted average method where for parameter *tau* the weights are calculated as $\exp(-t/\text{tau})$ where t is the distance from the point of interest.
- *Polynomial* detrending works by fitting a polynomial line to a series of points and then correcting the series to remove the trend detailed by this polynomial fit.

Value

The detrended image, an object of class `detrended_img`.

References

Rory Nolan, Luis A. J. Alvarez, Jonathan Elegheert, Maro Iliopoulou, G. Maria Jakobsdottir, Marina Rodriguez-Muñoz, A. Radu Aricescu, Sergi Padilla-Parra; nandb—number and brightness in R with a novel automatic detrending algorithm, *Bioinformatics*, <https://doi.org/10.1093/bioinformatics/btx434>.

Examples

```
## Not run:
## These examples are not run on CRAN because they take too long.
## You can still try them for yourself.

img <- ijttiff::read_tif(system.file("extdata", "bleached.tif",
  package = "detrendr"
))
corrected <- img_detrend_rh(img)
corrected <- img_detrend_boxcar(img, "auto", purpose = "fcs", parallel = 2)
corrected10 <- img_detrend_boxcar(img, 10, purpose = "fcs", parallel = 2)
corrected50 <- img_detrend_boxcar(img, 50, purpose = "fcs", parallel = 2)
corrected <- img_detrend_exp(img, "auto", purpose = "ffs", parallel = 2)
corrected10 <- img_detrend_exp(img, 10, purpose = "ffs", parallel = 2)
corrected50 <- img_detrend_exp(img, 50, purpose = "fcs", parallel = 2)
corrected <- img_detrend_polynom(img, "auto", purpose = "ffs", parallel = 2)
corrected2 <- img_detrend_polynom(img, 2, purpose = "ffs", parallel = 2)

## End(Not run)
```

detrendr

detrendr: Image detrending in R.

Description

The detrendr package gives functions for detrending images, most often used for preprocessing in fluorescence fluctuation and correlation spectroscopy (FFS and FCS).

References

Rory Nolan, Luis A. J. Alvarez, Jonathan Elegheert, Maro Iliopoulou, G. Maria Jakobsdottir, Marina Rodriguez-Muñoz, A. Radu Aricescu, Sergi Padilla-Parra; nandb—number and brightness in R with a novel automatic detrending algorithm, *Bioinformatics*, <https://doi.org/10.1093/bioinformatics/btx434>.

mean_frames	<i>Get the sums/means of frames in a 3-dimensional array.</i>
-------------	---

Description

Frame i of a 3-dimensional array `arr3d` is defined as `arr3d[, , i]`.

Usage

```
mean_frames(arr3d, na_rm = FALSE)
```

```
sum_frames(arr3d, na_rm = FALSE)
```

Arguments

<code>arr3d</code>	A 3-dimensional numeric array.
<code>na_rm</code>	Do you want NA values to be excluded from calculations?

Value

A numeric vector.

Examples

```
a <- array(seq_len(2^3), dim = rep(2, 3))
sum_frames(a)
mean_frames(a)
```

pillar-stats	<i>Get the sums/means/medians/variances of pillars of an ijtiff_img-style array.</i>
--------------	--

Description

For an [ijtiff_img](#)-style array `img` (indexed as `img[y, x, channel, frame]`), pillar xy of channel ch is defined as `img[y, x, ch,]`. These functions compute the mean, median and variance of each pillar for each channel.

Usage

```
sum_pillars(img, parallel = FALSE)
```

```
mean_pillars(img, parallel = FALSE)
```

```
median_pillars(img, parallel = FALSE)
```

```
var_pillars(img, parallel = FALSE)
```

Arguments

img	A 4-dimensional array in the style of an ijtiff_img (indexed by <code>img[y, x, channel, frame]</code>) or a 3-dimensional array which is a single channel of an ijtiff_img (indexed by <code>img[y, x, frame]</code>).
parallel	Would you like to use multiple cores to speed up this function? If so, set the number of cores here, or to use all available cores, use <code>parallel = TRUE</code> .

Value

An [ijtiff_img](#)-style array `arr` with one frame. `arr[y, x, ch, 1]` is equal to `mean(img[y, x, ch,])`, `median(img[y, x, ch,])`, or `var(img[y, x, ch,])`.

Examples

```
aaa <- array(seq_len(2^4), dim = rep(2, 4)) # a 2-channel, 2-frame array
sum_pillars(aaa)
mean_pillars(aaa)
median_pillars(aaa)
var_pillars(aaa)
```

rfromboxes

Randomly draw balls from boxes.

Description

Given a number of boxes with a specified number of balls in each, randomly draw a number of balls from these boxes, recording how many balls was drawn from each. An empty box cannot be drawn from.

Usage

```
rfromboxes(n, balls, weights = NULL)
```

Arguments

n	A natural number. The number of balls to draw.
balls	A vector of natural numbers. The number of balls in each box to begin with.
weights	A non-negative numeric vector the same length as <code>balls</code> . The relative probabilities of drawing a ball from each box. Default is each box is equally likely to be drawn from.

Value

A vector of natural numbers with the same length as `balls`. The number of balls drawn from each box.

See Also

rtoboxes

Examples

```
balls <- 1:10
rfromboxes(40, balls)
rfromboxes(40, balls, weights = c(rep(1, 9), 0))
```

rtoboxes	<i>Randomly place balls in boxes.</i>
----------	---------------------------------------

Description

Given a number of boxes, randomly distribute n balls into these boxes.

Usage

```
rtoboxes(n, boxes, weights = NULL, capacities = NULL)
```

Arguments

n	A natural number. The number of balls to put into the boxes.
boxes	A natural number. The number of boxes.
weights	A non-negative numeric vector. The relative probabilities of putting a ball in each box. Default is each box is equally likely.
capacities	A vector of natural numbers. The capacity of each box. Default is each box has infinite capacity.

Value

A vector of natural numbers with the same length as boxes. The number of balls placed in each box.

See Also

rfromboxes

Examples

```
rtoboxes(30, 7)
rtoboxes(30, 7, capacities = c(rep(1, 3), rep(7, 4)))
rtoboxes(30, 7,
  capacities = c(rep(1, 3), rep(70, 4)),
  weights = c(rep(0.1, 6), 1)
)
```


Index

apply_on_pillars, 2
autothresholdr::mean_stack_thresh(), 8

best_degree, 3
best_l, 4
best_swaps, 5
best_tau, 6
brightness_pillars, 7

detrend-directory, 8
detrended_img, 10, 10, 12
detrending, 10, 11
detrendr, 13
detrendr-package (detrendr), 13
dir_detrend_boxcar (detrend-directory), 8
dir_detrend_exp (detrend-directory), 8
dir_detrend_polynom (detrend-directory), 8
dir_detrend_rh (detrend-directory), 8
dir_detrend_robinhood (detrend-directory), 8

ijtiff_img, 3–7, 10, 11, 14, 15
img_detrend_boxcar, 9
img_detrend_boxcar (detrending), 11
img_detrend_exp, 9
img_detrend_exp (detrending), 11
img_detrend_polynom, 9
img_detrend_polynom (detrending), 11
img_detrend_rh (detrending), 11
img_detrend_robinhood (detrending), 11

mean_frames, 14
mean_pillars (pillar-stats), 14
median_pillars (pillar-stats), 14

pillar-stats, 14

rfromboxes, 15
rtoboxes, 16

sum_frames (mean_frames), 14
sum_pillars (pillar-stats), 14
var_pillars (pillar-stats), 14