

# Package ‘eha’

December 19, 2019

**Encoding** UTF-8

**Version** 2.8.0

**Date** 2019-12-19

**Title** Event History Analysis

**Description** Sampling of risk sets in Cox regression, selections in the Lexis diagram, bootstrapping. Parametric proportional hazards fitting with left truncation and right censoring for common families of distributions, piecewise constant hazards, and discrete models. Parametric accelerated failure time models for left truncated and right censored data.

**BugReports** <https://github.com/goranbrostrom/eha/issues>

**License** GPL (>= 2)

**LazyData** yes

**ByteCompile** yes

**Depends** R (>= 3.0.0), survival (>= 2.42-5)

**Imports** stats, graphics

**NeedsCompilation** yes

**Maintainer** Göran Broström <goran.brostrom@umu.se>

**RoxygenNote** 7.0.2

**Suggests** knitr, rmarkdown

**VignetteBuilder** knitr

**Author** Göran Broström [aut, cre],  
Jianming Jin [ctb]

**Repository** CRAN

**Date/Publication** 2019-12-19 22:40:06 UTC

**R topics documented:**

eha-package	3
aftreg	4
aftreg.fit	7
age.window	8
cal.window	9
check.dist	10
check.surv	11
coxreg	12
coxreg.fit	15
cro	17
eha-defunct	18
EV	19
fert	20
frail.fit	21
geome.fit	21
Gompertz	22
infants	24
join.spells	25
Loglogistic	26
Lognormal	27
logrye	28
ltx	29
make.communal	30
makeham	31
male.mortality	32
mlreg	33
mort	37
oe	38
oldmort	38
Pch	39
perstat	40
phfunc	41
phreg	42
phreg.fit	46
piecewise	47
plot.aftreg	48
plot.coxreg	49
plot.hazdata	50
plot.phreg	52
plot.tpchreg	53
plot.weibreg	54
print.aftreg	56
print.coxreg	57
print.phreg	57
print.risksets	58
print.tpchreg	59

print.weibreg . . . . .	60
risksets . . . . .	60
scania . . . . .	62
summary.aftreg . . . . .	63
summary.coxreg . . . . .	63
summary.phreg . . . . .	64
summary.weibreg . . . . .	65
SurvSplit . . . . .	66
swe07 . . . . .	67
table.events . . . . .	68
toBinary . . . . .	69
toDate . . . . .	70
toTime . . . . .	71
toTpch . . . . .	72
tpchreg . . . . .	73
weibreg . . . . .	74
weibreg.fit . . . . .	76
Weibull . . . . .	77
wfunk . . . . .	78
<b>Index</b>	<b>80</b>

---

 eha-package

*eha: Event History Analysis*


---

## Description

Sampling of risk sets in Cox regression, selections in the Lexis diagram, bootstrapping. Parametric proportional hazards fitting with left truncation and right censoring for common families of distributions, piecewise constant hazards, and discrete models. Parametric accelerated failure time models for left truncated and right censored data.

## Details

Eha enhances the recommended **survival** package in several ways, see the description. The main applications in mind are demography and epidemiology. For standard Cox regression analysis the function `coxph` in **survival** is still recommended. The function `coxreg` in **eha** in fact calls `coxph` for the standard kind of analyses.

## Author(s)

**Maintainer:** Göran Broström <goran.brostrom@umu.se>

Other contributors:

- Jianming Jin [contributor]

## References

Broström, G. (2012). *Event History Analysis with R*, Chapman and Hall/CRC Press, Boca Raton, FL.

## See Also

Useful links:

- Report bugs at <https://github.com/goranbrostrom/eha/issues>

---

aftreg

*Accelerated Failure Time Regression*

---

## Description

The accelerated failure time model with parametric baseline hazard(s). Allows for stratification with different scale and shape in each stratum, and left truncated and right censored data.

## Usage

```
aftreg(
  formula = formula(data),
  data = parent.frame(),
  na.action = getOption("na.action"),
  dist = "weibull",
  init,
  shape = 0,
  id,
  param = c("lifeAcc", "lifeExp"),
  control = list(eps = 1e-08, maxiter = 20, trace = FALSE),
  singular.ok = TRUE,
  model = FALSE,
  x = FALSE,
  y = TRUE
)
```

## Arguments

formula	a formula object, with the response on the left of a ~ operator, and the terms on the right. The response must be a survival object as returned by the Surv function.
data	a data.frame in which to interpret the variables named in the formula.
na.action	a missing-data filter function, applied to the model.frame, after any subset argument has been used. Default is options()\$na.action.
dist	Which distribution? Default is "weibull", with the alternatives "gompertz", "ev", "loglogistic" and "lognormal". A special case like the exponential can be obtained by choosing "weibull" in combination with shape = 1.

<code>init</code>	vector of initial values of the iteration. Default initial value is zero for all variables.
<code>shape</code>	If positive, the shape parameter is fixed at that value. If zero or negative, the shape parameter is estimated. Stratification is now regarded as a meaningful option even if shape is fixed.
<code>id</code>	If there are more than one spell per individual, it is essential to keep spells together by the <code>id</code> argument. This allows for time-varying covariates.
<code>param</code>	Which parametrization should be used? The <code>lifeAcc</code> uses the parametrization given in the vignette, while the <code>lifeExp</code> uses the same as in the <code>survreg</code> function.
<code>control</code>	a list with components <code>eps</code> (convergence criterion), <code>maxiter</code> (maximum number of iterations), and <code>trace</code> (logical, debug output if TRUE). You can change any component without mention the other(s).
<code>singular.ok</code>	Not used.
<code>model</code>	Not used.
<code>x</code>	Return the design matrix in the model object?
<code>y</code>	Return the response in the model object?

### Details

The parameterization is different from the one used by `survreg`, when `param = "lifeAcc"`. The result is then true acceleration of time. Then the model is

$$S(t; a, b, \beta, z) = S_0((t/\exp(b - z\beta))^{\exp(a)})$$

$$S(t; a, b, \beta, z) = S_0((t/\exp(b - z\beta))^{\exp(a)})$$

where  $S_0$  is some standardized survivor function. The baseline parameters  $a$  and  $b$  are log shape and log scale, respectively. This is for the default parametrization. With the `lifeExp` parametrization, some signs are changed:

$$b - z\beta$$

is changed to

$$b + z\beta$$

. For the Gompertz distribution, the base parametrization is canonical, a necessity for consistency with the shape/scale paradigm (this is new in 2.3).

### Value

A list of class `c("aftreg", "coxreg")` with components

<code>coefficients</code>	Fitted parameter estimates.
<code>var</code>	Covariance matrix of the estimates.
<code>loglik</code>	Vector of length two; first component is the value at the initial parameter values, the second component is the maximized value.
<code>score</code>	The score test statistic (at the initial value).

<code>linear.predictors</code>	The estimated linear predictors.
<code>means</code>	Means of the columns of the design matrix.
<code>w.means</code>	Weighted (against exposure time) means of covariates; weighted relative frequencies of levels of factors.
<code>n</code>	Number of spells in indata (possibly after removal of cases with NA's).
<code>events</code>	Number of events in data.
<code>terms</code>	Used by extractor functions.
<code>assign</code>	Used by extractor functions.
<code>wald.test</code>	The Wald test statistic (at the initial value).
<code>y</code>	The Surv vector.
<code>isF</code>	Logical vector indicating the covariates that are factors.
<code>covars</code>	The covariates.
<code>ttr</code>	Total Time at Risk.
<code>levels</code>	List of levels of factors.
<code>formula</code>	The calling formula.
<code>call</code>	The call.
<code>method</code>	The method.
<code>convergence</code>	Did the optimization converge?
<code>fail</code>	Did the optimization fail? (Is NULL if not).
<code>pfixed</code>	TRUE if shape was fixed in the estimation.
<code>param</code>	The parametrization.

**Author(s)**

Göran Broström

**See Also**

[coxreg](#), [phreg](#), [survreg](#)

**Examples**

```
data(mort)
aftreg(Surv(enter, exit, event) ~ ses, param = "lifeExp", data = mort)
```

---

 aftreg.fit

*Parametric proportional hazards regression*


---

### Description

This function is called by [aftreg](#), but it can also be directly called by a user.

### Usage

```
aftreg.fit(X, Y, dist, param, strata, offset, init, shape, id, control, pfixed)
```

### Arguments

X	The design (covariate) matrix.
Y	A survival object, the response.
dist	Which baseline distribution?
param	Which parametrization?
strata	A stratum variable.
offset	Offset.
init	Initial regression parameter values.
shape	If positive, a fixed value of the shape parameter in the distribution. Otherwise, the shape is estimated.
id	See corresponding argument to <a href="#">aftreg</a> .
control	Controls convergence and output.
pfixed	A logical indicating fixed shape parameter(s).

### Details

See [aftreg](#) for more detail.

### Value

coefficients	Estimated regression coefficients plus estimated scale and shape coefficients, sorted by strata, if present.
df	Degrees of freedom; No. of regression parameters.
var	Variance-covariance matrix
loglik	Vector of length 2. The first component is the maximized loglikelihood with only scale and shape in the model, the second the final maximum.
conver	TRUE if convergence
fail	TRUE if failure
iter	Number of Newton-Raphson iterates.
n.strata	The number of strata in the data.

**Author(s)**

Göran Broström

**See Also**[aftreg](#)

---

age.window	<i>Age cut of survival data</i>
------------	---------------------------------

---

**Description**

For a given age interval, each spell is cut to fit into the given age interval.

**Usage**

```
age.window(dat, window, surv = c("enter", "exit", "event"))
```

**Arguments**

dat	Input data frame. Must contain survival data.
window	Vector of length two; the age interval.
surv	Vector of length three giving the names of the central variables in 'dat'.

**Details**

The window must be in the order (begin, end)

**Value**

A data frame of the same form as the input data frame, but 'cut' as desired. Intervals exceeding window[2] will be given event = 0

**Author(s)**

Göran Broström

**See Also**[cal.window](#), [coxreg](#), [aftreg](#)**Examples**

```
dat <- data.frame(enter = 0, exit = 5.731, event = 1, x = 2)
window <- c(2, 5.3)
dat.trim <- age.window(dat, window)
```



---

cal.window	<i>Calendar time cut of survival data</i>
------------	---

---

**Description**

For a given time interval, each spell is cut so that it fully lies in the given time interval

**Usage**

```
cal.window(dat, window, surv = c("enter", "exit", "event", "birthdate"))
```

**Arguments**

dat	Input data frame. Must contain survival data and a birth date.
window	Vector of length two; the time interval
surv	Vector of length four giving the names of the central variables in 'dat'.

**Details**

The window must be in the order (begin, end)

**Value**

A data frame of the same form as the input data frame, but 'cut' as desired. Intervals exceeding window[2] will be given event = 0

**Author(s)**

Göran Broström

**See Also**

[age.window](#), [coxreg](#), [aftreg](#)

**Examples**

```
dat <- data.frame(enter = 0, exit = 5.731, event = 1,  
birthdate = 1962.505, x = 2)  
window <- c(1963, 1965)  
dat.trim <- cal.window(dat, window)
```

---

check.dist	<i>Graphical goodness-of-fit test</i>
------------	---------------------------------------

---

### Description

Comparison of the cumulative hazards functions for a semi-parametric and a parametric model.

### Usage

```
check.dist(sp, pp, main = NULL, col = NULL, printLegend = TRUE)
```

### Arguments

sp	An object of type "coxreg", typically output from <a href="#">coxreg</a>
pp	An object of type "phreg", typically output from <a href="#">phreg</a>
main	Header for the plot. Default is distribution and "cumulative hazard function"
col	Line colors. should be NULL (black lines) or of length 2
printLegend	Should a legend be printed? Default is TRUE.

### Details

For the moment only a graphical comparison. The arguments sp and pp may be swapped.

### Value

No return value.

### Author(s)

Göran Broström

### See Also

[coxreg](#) and [phreg](#).

### Examples

```
data(mort)
oldpar <- par(mfrow = c(2, 2))
fit.cr <- coxreg(Surv(enter, exit, event) ~ ses, data = mort)
fit.w <- phreg(Surv(enter, exit, event) ~ ses, data = mort)
fit.g <- phreg(Surv(enter, exit, event) ~ ses, data = mort,
  dist = "gompertz")
fit.pch <- phreg(Surv(enter, exit, event) ~ ses, data = mort,
  dist = "pch", cuts = c(5, 10, 15))
fit.ev <- phreg(Surv(enter, exit, event) ~ ses, data = mort,
  dist = "ev")
```

```
check.dist(fit.cr, fit.w)
check.dist(fit.cr, fit.g)
check.dist(fit.cr, fit.pch)
check.dist(fit.cr, fit.ev)
par(oldpar)
```

---

check.surv

*Check the integrity of survival data.*

---

## Description

Check that exit occurs after enter, that spells from an individual do not overlap, and that each individual experiences at most one event.

## Usage

```
check.surv(enter, exit, event, id = NULL, eps = 1e-08)
```

## Arguments

enter	Left truncation time.
exit	Time of exit.
event	Indicator of event. Zero means 'no event'.
id	Identification of individuals.
eps	The smallest allowed spell length or overlap.

## Details

Interval lengths must be strictly positive.

## Value

A vector of id's for the insane individuals. Of zero length if no errors.

## Author(s)

Göran Broström

## See Also

[join.spells](#), [coxreg](#), [aftreg](#)

## Examples

```
xx <- data.frame(enter = c(0, 1), exit = c(1.5, 3), event = c(0, 1), id =
c(1,1))
check.surv(xx$enter, xx$exit, xx$event, xx$id)
```

coxreg

*Cox regression***Description**

Performs Cox regression with some special attractions, especially *sampling of risksets* and *the weird bootstrap*.

**Usage**

```
coxreg(formula = formula(data), data = parent.frame(), weights,
subset, t.offset, na.action = getOption("na.action"), init = NULL, method =
c("efron", "breslow", "mpropl", "ml"), control = list(eps = 1e-08, maxiter =
25, trace = FALSE), singular.ok = TRUE, model = FALSE, center = TRUE, x =
FALSE, y = TRUE, hazards = TRUE, boot = FALSE, efrac = 0, geometric = FALSE,
rs = NULL, frailty = NULL, max.survs = NULL)
```

**Arguments**

formula	a formula object, with the response on the left of a ~ operator, and the terms on the right. The response must be a survival object as returned by the Surv function.
data	a data.frame in which to interpret the variables named in the formula.
weights	Case weights; time-fixed or time-varying.
subset	An optional vector specifying a subset of observations to be used in the fitting process.
t.offset	Case offsets; time-varying.
na.action	a missing-data filter function, applied to the model.frame, after any subset argument has been used. Default is options()\$na.action.
init	vector of initial values of the iteration. Default initial value is zero for all variables.
method	Method of treating ties, "efron" (default), "breslow", "mpropl" (maximum partial partial likelihood), or "ml" (maximum likelihood).
control	a list with components eps (convergence criterion), maxiter (maximum number of iterations), and silent (logical, controlling amount of output). You can change any component without mention the other(s).
singular.ok	Not used
model	Not used
center	Logical. If center = TRUE (default), the baseline hazards are calculated at the means of the covariates and for the reference category for factors, otherwise at the value zero. See Details.
x	Return the design matrix in the model object?
y	return the response in the model object?

hazards	Calculate baseline hazards? Default is TRUE.
boot	Number of boot replicates. Defaults to FALSE, no boot samples.
efrac	Upper limit of fraction failures in 'mopl'.
geometric	If TRUE, forces an 'ml' model with constant riskset probability. Default is FALSE.
rs	Risk set?
frailty	Grouping variable for frailty analysis. Not in use yet.
max.survs	Sampling of risk sets? If given, it should be (the upper limit of) the number of survivors in each risk set.

### Details

The default method, `efron`, and the alternative, `breslow`, are both the same as in `coxph` in package `survival`. The methods `mopl` and `ml` are maximum likelihood, discrete-model, based.

If `center = TRUE` (default), graphs show the "baseline" distribution at the means of (continuous) covariates, and for the reference category in case of factors (avoiding representing "flying pigs"). If `center = FALSE` the baseline distribution is at the value zero of all covariates. It is usually a good idea to use `center = FALSE` in combination with "precentering" of covariates, that is, subtracting a reference value, ideally close to the center of the covariate distribution. In that way, the "reference" will be the same for all subsets of the data.

### Value

A list of class `c("coxreg", "coxph")` with components

<code>coefficients</code>	Fitted parameter estimates.
<code>var</code>	Covariance matrix of the estimates.
<code>loglik</code>	Vector of length two; first component is the value at the initial parameter values, the second component is the maximized value.
<code>score</code>	The score test statistic (at the initial value).
<code>linear.predictors</code>	The estimated linear predictors.
<code>residuals</code>	The martingale residuals.
<code>hazard</code>	The estimated baseline hazard, calculated at the means of the covariates (rather, columns of the design matrix). Is a list, with one component per stratum. Each component is a matrix with two columns, the first contains risktimes, the second the corresponding hazard atom.
<code>means</code>	Means of the columns of the design matrix corresponding to covariates, if <code>center = TRUE</code> . Columns corresponding to factor levels give a zero in the corresponding position in means. If <code>center = FALSE</code> , means are all zero.
<code>w.means</code>	Weighted (against exposure time) means of covariates; weighted relative frequencies of levels of factors.
<code>n</code>	Number of spells in indata (possibly after removal of cases with NA's).
<code>events</code>	Number of events in data.

terms	Used by extractor functions.
assign	Used by extractor functions.
y	The Surv vector.
isF	Logical vector indicating the covariates that are factors.
covars	The covariates.
ttr	Total Time at Risk.
levels	List of levels of factors.
formula	The calling formula.
bootstrap	The (matrix of) bootstrap replicates, if requested on input. It is up to the user to do whatever desirable with this sample.
boot.sd	The estimated standard errors of the bootstrap replicates.
call	The call.
method	The method.
convergence	Did the optimization converge?
fail	Did the optimization fail? (Is NULL if not).

### Warning

The use of `rs` is dangerous, see note. It can however speed up computing time considerably for huge data sets.

### Note

This function starts by creating risksets, if no riskset is supplied via `rs`, with the aid of [risksets](#). Supplying output from `risksets` via `rs` fails if there are any NA's in the data! Note also that it depends on stratification, so `rs` contains information about stratification. Giving another strata variable in the formula is an error. The same is ok, for instance to supply stratum interactions.

### Author(s)

Göran Broström

### References

Broström, G. and Lindkvist, M. (2008). Partial partial likelihood. *Communications in Statistics: Simulation and Computation* 37:4, 679-686.

### See Also

[coxph](#), [risksets](#)

**Examples**

```

dat <- data.frame(time= c(4, 3,1,1,2,2,3),
                  status=c(1,1,1,0,1,1,0),
                  x=     c(0, 2,1,1,1,0,0),
                  sex=   c(0, 0,0,0,1,1,1))
coxreg( Surv(time, status) ~ x + strata(sex), data = dat) #stratified model
# Same as:
rs <- risksets(Surv(dat$time, dat$status), strata = dat$sex)
coxreg( Surv(time, status) ~ x, data = dat, rs = rs) #stratified model

```

---

coxreg.fit

*Cox regression*


---

**Description**

Called by `coxreg`, but a user can call it directly.

**Usage**

```

coxreg.fit(
  X,
  Y,
  rs,
  weights,
  t.offset = NULL,
  strats,
  offset,
  init,
  max.survs,
  method = "breslow",
  center = TRUE,
  boot = FALSE,
  efrac = 0,
  calc.hazards = TRUE,
  calc.martres = TRUE,
  control,
  verbose = TRUE
)

```

**Arguments**

X	The design matrix.
Y	The survival object.
rs	The risk set composition. If absent, calculated.
weights	Case weights; time-fixed or time-varying.

t.offset	Case offset; time-varying.
strats	The stratum variable. Can be absent.
offset	Offset. Can be absent.
init	Start values. If absent, equal to zero.
max.survs	Sampling of risk sets? If so, gives the maximum number of survivors in each risk set.
method	Either "efron" (default) or "breslow".
center	See <a href="#">coxreg</a> .
boot	Number of bootstrap replicates. Defaults to FALSE, no bootstrapping.
efrac	Upper limit of fraction failures in 'mppl'.
calc.hazards	Should estimates of baseline hazards be calculated?
calc.martres	Should martingale residuals be calculated?
control	See <a href="#">coxreg</a>
verbose	Should Warnings about convergence be printed?

### Details

rs is dangerous to use when NA's are present.

### Value

A list with components

coefficients	Estimated regression parameters.
var	Covariance matrix of estimated coefficients.
loglik	First component is value at <code>init</code> , second at maximum.
score	Score test statistic, at initial value.
linear.predictors	Linear predictors.
residuals	Martingale residuals.
hazard	Estimated baseline hazard. At value zero of 'design' variables.
means	Means of the columns of the design matrix.
bootstrap	The bootstrap replicates, if requested on input.
conver	TRUE if convergence.
f.conver	TRUE if variables converged.
fail	TRUE if failure.
iter	Number of performed iterations.

### Note

It is the user's responsibility to check that `indata` is sane.



**Author(s)**

Göran Broström

**See Also**[coxreg](#), [risksets](#)**Examples**

```
X <- as.matrix(data.frame(
  x=      c(0, 2,1,4,1,0,3),
  sex=    c(1, 0,0,0,1,1,1)))
time <- c(1,2,3,4,5,6,7)
status <- c(1,1,1,0,1,1,0)
stratum <- rep(1, length(time))

coxreg.fit(X, Surv(time, status), strats = stratum, max.survs = 6,
  control = list(eps=1.e-4, maxiter = 10, trace = FALSE))
```

cro

*Creates a minimal representation of a data frame.***Description**

Given a data frame with a defined response variable, this function creates a unique representation of the covariates in the data frame, vector (matrix) of responses, and a pointer vector, connecting the responses with the corresponding covariates.

**Usage**

```
cro(dat, response = 1)
```

**Arguments**

dat	A data frame
response	The column(s) where the response resides.

**Details**

The rows in the data frame are converted to text strings with `paste` and compared with `match`.

**Value**

A list with components

y	The response.
covar	A data frame with unique rows of covariates.
keys	Pointers from y to covar, connecting each response with its covariate vector.

**Note**

This function is based on suggestions by Anne York and Brian Ripley.

**Author(s)**

Göran Broström

**See Also**

[match](#), [paste](#)

**Examples**

```
dat <- data.frame(y = c(1.1, 2.3, 0.7), x1 = c(1, 0, 1), x2 = c(0, 1, 0))
cro(dat)
```

---

eha-defunct

*Defunct functions*

---

**Description**

These functions were duplicates of functions in the package **glimmML**.

**Usage**

```
ghq(...)
```

```
glimmboot(...)
```

```
glimmbootFit(...)
```

```
glimmML(...)
```

```
glimmML.fit(...)
```

**Arguments**

...           input parameters

**Details**

Instead of using these functions, use the corresponding functions in **glimmML** with the same name

**Description**

Density, distribution function, quantile function, hazard function, cumulative hazard function, and random generation for the EV distribution with parameters shape and scale.

**Usage**

```
dEV(x, shape = 1, scale = 1, log = FALSE)
pEV(q, shape = 1, scale = 1, lower.tail = TRUE, log.p = FALSE)
qEV(p, shape = 1, scale = 1, lower.tail = TRUE, log.p = FALSE)
hEV(x, shape = 1, scale = 1, log = FALSE)
HEV(x, shape = 1, scale = 1, log.p = FALSE)
rEV(n, shape = 1, scale = 1)
```

**Arguments**

shape, scale	shape and scale parameters, both defaulting to 1.
lower.tail	logical; if TRUE (default), probabilities are $P(X \leq x)$ , otherwise, $P(X > x)$ .
x, q	vector of quantiles.
p	vector of probabilities.
n	number of observations. If $\text{length}(n) > 1$ , the length is taken to be the number required.
log, log.p	logical; if TRUE, probabilities p are given as $\log(p)$ .

**Details**

The EV distribution with scale parameter  $a$  and shape parameter  $\sigma$  has hazard function given by

$$h(x) = (b/\sigma)(x/\sigma)^{b-1} \exp(-(x/\sigma)^b)$$

for  $x \geq 0$ .

**Value**

dEV gives the density, pEV gives the distribution function, qEV gives the quantile function, hEV gives the hazard function, HEV gives the cumulative hazard function, and rEV generates random deviates.

Invalid arguments will result in return value NaN, with a warning.

---

fert

*Marital fertility nineteenth century*

---

### Description

Birth intervals for married women with at least one birth, 19th northern Sweden

### Usage

```
data(fert)
```

### Format

A data frame with 12169 observations the lengths (in years) of birth intervals for 1859 married women with at least one birth. The first interval (`parity = 0`) is the interval from marriage to first birth.

`id` Personal identification number for mother.

`parity` Time order of birth interval for the present mother. The interval with `parity = 0` is the first, from marriage to first birth.

`age` The age of mother at start of interval.

`year` The calendar year at start of interval.

`next.ivl` The length of the coming time interval.

`event` An indicator for whether the `next.ivl` ends in a new birth (`event = 1`) or is right censored (`event = 0`). Censoring occurs when the woman ends her fertility period within her first marriage (marriage dissolution or reaching the age of 48).

`prev.ivl` The length of the previous time interval. May be used as explanatory variable in a Cox regression of birth intervals.

`ses` Socio-economic status, a factor with levels `lower`, `upper`, `farmer`, and `unknown`.

`parish` The Skelleftea region consists of three parishes, `Jorn`, `Norsjo`, and `Skelleftea`.

### Details

The data set contain clusters of dependent observations defined by mother's `id`.

### Source

Data is coming from The Demographic Data Base, Umea University, Umea, Sweden.

### References

<http://www.ddb.umu.se>

**Examples**

```
data(fert)
fit <- coxreg(Surv(next.ivl, event) ~ ses + prev.ivl, data = fert, subset =
(parity == 1))
drop1(fit, test = "Chisq")
```

---

frail.fit	<i>Frailty experiment</i>
-----------	---------------------------

---

**Description**

Utilizing GLMM models: Experimental, not exported (yet).

**Usage**

```
frail.fit(X, Y, rs, strats, offset, init, max.survs, frailty, control)
```

**Arguments**

X	design matrix
Y	survival object
rs	output from <a href="#">risksets</a>
strats	strata
offset	offset
init	start values
max.survs	for sampling of riskset survivors
frailty	grouping variable
control	control of optimization

---

geome.fit	<i>Constant intensity discrete time proportional hazards</i>
-----------	--

---

**Description**

This function is called from coxreg. A user may call it directly.

**Usage**

```
geome.fit(X, Y, rs, strats, offset, init, max.survs, method = "ml", control)
```

**Arguments**

<code>X</code>	The design matrix
<code>Y</code>	Survival object
<code>rs</code>	risk set produced by <a href="#">risksets</a>
<code>strats</code>	Stratum indicator
<code>offset</code>	Offset
<code>init</code>	Initial values
<code>max.survs</code>	Maximal survivors
<code>method</code>	"ml", always, i.e., this argument is ignored.
<code>control</code>	See <code>coxreg</code> .

**Value**

See the code.

**Note**

Nothing special  
`coxreg` is a defunct function

**Author(s)**

Göran Broström

**References**

See [coxreg](#).

**See Also**

[coxreg](#)

---

Gompertz

*The Gompertz Distribution*

---

**Description**

Density, distribution function, quantile function, hazard function, cumulative hazard function, and random generation for the Gompertz distribution with parameters shape and scale.

**Usage**

```

dgomperz(x, shape = 1, scale = 1, log = FALSE,
param = c("default", "canonical"))
pgomperz(q, shape = 1, scale = 1, lower.tail = TRUE, log.p = FALSE,
param = c("default", "canonical"))
qgomperz(p, shape = 1, scale = 1, lower.tail = TRUE, log.p = FALSE,
param = c("default", "canonical"))
hgomperz(x, shape = 1, scale = 1, log = FALSE,
param = c("default", "canonical"))
Hgomperz(x, shape = 1, scale = 1, log.p = FALSE,
param = c("default", "canonical"))
rgomperz(n, shape = 1, scale = 1, param = c("default", "canonical"))

```

**Arguments**

shape, scale	shape and scale parameters, both defaulting to 1.
lower.tail	logical; if TRUE (default), probabilities are $P(X \leq x)$ , otherwise, $P(X > x)$ .
param	default or canonical.
x, q	vector of quantiles.
p	vector of probabilities.
n	number of observations. If $\text{length}(n) > 1$ , the length is taken to be the number required.
log, log.p	logical; if TRUE, probabilities p are given as $\log(p)$ .

**Details**

The Gompertz distribution with scale parameter  $a$  and shape parameter  $\sigma$  has hazard function given by

$$h(x) = a \exp(x/\sigma)$$

for  $x \geq 0$ . If `param = "canonical"`, then then  $a \rightarrow a/b$ , so that  $b$  is a true scale parameter (for any fixed  $a$ ), and  $b$  is an 'AFT parameter'.

**Value**

`dgomperz` gives the density, `pgomperz` gives the distribution function, `qgomperz` gives the quantile function, `hgomperz` gives the hazard function, `Hgomperz` gives the cumulative hazard function, and `rgomperz` generates random deviates.

Invalid arguments will result in return value NaN, with a warning.

---

 infants
 

---



---

*Infant mortality and maternal death, Sweeden 1821–1894.*


---

**Description**

Matched data on infant mortality, from seven parishes in Sweden, 1821–1894.

**Usage**

```
data(infants)
```

**Format**

A data frame with 80 rows and five variables.

`stratum` Triplet No. Each triplet consist of one infant whose mother died (a case), and two controls, i.e, infants whose mother did not die. Matched on covariates below.

`enter` Age (in days) of case when its mother died.

`exit` Age (in days) at death or right censoring (at age 365 days).

`event` Follow-up ends with death (1) or right censoring (0).

`mother` dead for cases, alive for controls.

`age` Mother's age at infant's birth.

`sex` The infant's sex.

`parish` Birth parish, either Nedertornea or not Nedertornea.

`civst` Civil status of mother, married or unmarried.

`ses` Socio-economic status of mother, either farmer or not farmer.

`year` Year of birth of the infant.

**Details**

From 5641 first-born in seven Swedish parishes 1820-1895, from Fleninge in the very south to Nedertorneå in the very north, those whose mother died during their first year of life were selected, in all 35 infants. To each of them, two cotrols were selected by matching on the given covariates.

**Source**

Data originate from The Demographic Data Base, Umeå University, Umeå, Sweden, <http://www.ddb.umu.se>.

**References**

Broström, G. (1987). The influence of mother's death on infant mortality: A case study in matched data survival analysis. *Scandinavian Journal of Statistics* 14, 113-123.



**Examples**

```

data(infants)
fit <- coxreg(Surv(enter, exit, event) ~ strata(stratum) + mother, data
= infants)
fit
fit.w <- phreg(Surv(enter, exit, event) ~ mother + parish + ses, data =
infants)
fit.w ## Weibull proportional hazards model.

```

---

join.spells

*Straighten up a survival data frame*


---

**Description**

Unnecessary cut spells are glued together, overlapping spells are "polished", etc.

**Usage**

```
join.spells(dat, strict = FALSE, eps = 1e-08)
```

**Arguments**

dat	A data frame with names enter, exit, event, id.
strict	If TRUE, nothing is changed if errors in spells (non-positive length, overlapping intervals, etc.) are detected. Otherwise (the default), bad spells are removed, with "earlier life" having higher priority.
eps	Tolerance for equality of two event times. Should be kept small.

**Details**

In case of overlapping intervals (i.e., a data error), the appropriate id's are returned if strict is TRUE.

**Value**

A data frame with the same variables as the input, but individual spells are joined, if possible (identical covariate values, and adjacent time intervals).

**Author(s)**

Göran Broström

**References**

Therneau, T.M. and Grambsch, P.M. (2000). *Modeling Survival Data: Extending the Cox model*. Springer.

**See Also**

[coxreg](#), [aftreg](#), [check.surv](#)

Loglogistic

*The Loglogistic Distribution***Description**

Density, distribution function, quantile function, hazard function, cumulative hazard function, and random generation for the Loglogistic distribution with parameters shape and scale.

**Usage**

```
dlllogis(x, shape = 1, scale = 1, log = FALSE)
pllogis(q, shape = 1, scale = 1, lower.tail = TRUE, log.p = FALSE)
qllogis(p, shape = 1, scale = 1, lower.tail = TRUE, log.p = FALSE)
hllogis(x, shape = 1, scale = 1, prop = 1, log = FALSE)
Hllogis(x, shape = 1, scale = 1, prop = 1, log.p = FALSE)
rllogis(n, shape = 1, scale = 1)
```

**Arguments**

shape, scale	shape and scale parameters, both defaulting to 1.
lower.tail	logical; if TRUE (default), probabilities are $P(X \leq x)$ , otherwise, $P(X > x)$ .
x, q	vector of quantiles.
p	vector of probabilities.
n	number of observations. If $\text{length}(n) > 1$ , the length is taken to be the number required.
log, log.p	logical; if TRUE, probabilities p are given as $\log(p)$ .
prop	proportionality constant in the extended Loglogistic distribution.

**Details**

The Loglogistic distribution with scale parameter  $a$  and shape parameter  $\sigma$  has hazard function given by

$$h(x) = (b/\sigma)(x/\sigma)^{b-1} \exp(-(x/\sigma)^b)$$

for  $x \geq 0$ .

**Value**

`dlllogis` gives the density, `pllogis` gives the distribution function, `qllogis` gives the quantile function, `hllogis` gives the hazard function, `Hllogis` gives the cumulative hazard function, and `rllogis` generates random deviates.

Invalid arguments will result in return value NaN, with a warning.

**Description**

Density, distribution function, quantile function, hazard function, cumulative hazard function, and random generation for the Lognormal distribution with parameters shape and scale.

**Usage**

```
hlnorm(x, meanlog = 0, sdlog = 1, shape = 1 / sdlog, scale = exp(meanlog),
prop = 1, log = FALSE)
Hlnorm(x, meanlog = 0, sdlog = 1, shape = 1 / sdlog, scale = exp(meanlog),
prop = 1, log.p = FALSE)
```

**Arguments**

x	vector of quantiles.
meanlog	mean in the Normal distribution.
sdlog, shape	sdlog is standard deviation in the Normal distribution, shape = 1/sdlog.
scale	is exp(meanlog).
prop	proportionality constant in the extended Lognormal distribution.
log, log.p	logical; if TRUE, probabilities p are given as log(p).

**Details**

The Lognormal distribution with scale parameter  $a$  and shape parameter  $\sigma$  has hazard function given by

$$h(x) = (b/\sigma)(x/\sigma)^{b-1} \exp(-(x/\sigma)^b)$$

for  $x \geq 0$ .

**Value**

dlnorm gives the density, plnorm gives the distribution function, qlnorm gives the quantile function, hlnorm gives the hazard function, Hlnorm gives the cumulative hazard function, and rlnorm generates random deviates.

Invalid arguments will result in return value NaN, with a warning.

---

logrye

*Rye prices, Scania, southern Sweden, 1801-1894.*

---

### **Description**

The data consists of yearly rye prices from 1801 to 1894. Logged and detrended, so the time series is supposed to measure short term fluctuations in rye prices.

### **Usage**

```
data(scania)
```

### **Format**

A data frame with 94 observations in two columns on the following 2 variables.

year The year the price is recorded.

foodprices Detrended log rye prices.

### **Details**

The Scanian area in southern Sweden was during the 19th century a mainly rural area.

### **Source**

The Scanian Economic Demographic Database.

### **References**

Jörberg, L. (1972). A History of Prices in Sweden 1732-1914, CWK Gleerup, Lund.

### **Examples**

```
data(logrye)  
summary(logrye)
```

---

ltx *LaTeX printing of coxreg results.*

---

### Description

This (generic) function prints the LaTeX code of the results of a fit from [coxreg](#), [phreg](#), or [aftreg](#), similar to what `xtable` does for fits from other functions.

### Usage

```
ltx(  
  x,  
  caption = NULL,  
  label = NULL,  
  dr = NULL,  
  digits = max(options()$digits - 4, 3),  
  ...  
)
```

### Arguments

<code>x</code>	The output from a call to <code>coxreg</code> , <code>coxreg</code> , or <code>aftreg</code>
<code>caption</code>	A suitable caption for the table.
<code>label</code>	A label used in the LaTeX code.
<code>dr</code>	Output from a <code>drop1</code> call.
<code>digits</code>	Number of digits to be printed.
<code>...</code>	Not used.

### Details

The result is a printout which is (much) nicer than the standard printed output from `glm` and friends,

### Value

LaTeX code version of the results from a run with [coxreg](#), [phreg](#), or [aftreg](#).

### Note

There is no method in `xtable` for `coxreg`.

### Author(s)

Göran Broström.

### See Also

`xtable`, [coxreg](#)

## Examples

```
data(oldmort)
fit <- coxreg(Surv(enter, exit, event) ~ civ + sex, data = oldmort)
dr <- drop1(fit, test = "Chisq")
ltx(fit, dr = dr, caption = "A test example.", label = "tab:test1")
```

---

```
make.communal
```

```
Put communals in "fixed" data frame
```

---

## Description

Given an ordinary data frame suitable for survival analysis, and a data frame with "communal" time series, this function includes the communal covariates as fixed, by the "cutting spells" method.

## Usage

```
make.communal(
  dat,
  com.dat,
  communal = TRUE,
  start,
  period = 1,
  lag = 0,
  surv = c("enter", "exit", "event", "birthdate"),
  tol = 1e-04,
  fortran = TRUE
)
```

## Arguments

<code>dat</code>	A data frame containing interval specified survival data and covariates, of which one must give a "birth date", the connection between duration and calendat time
<code>com.dat</code>	Data frame with communal covariates. They must have the same start year and periodicity, given by <code>com.ins</code>
<code>communal</code>	Boolean; if TRUE, then it is a true communal (default), otherwise a fixed. The first component is the first year (start date in decimal form), and the second component is the period length. The third is lag and the fourth is scale.
<code>start</code>	Start date in decimal form.
<code>period</code>	Period length. Defaults to one.
<code>lag</code>	The lag of the effect. Defaults to zero.
<code>surv</code>	Character vector of length 4 giving the names of interval start, interval end, event indicator, birth date, in that order. These names must correspond to names in <code>dat</code>

tol	Largest length of an interval considered to be of zero length. The cutting sometimes produces zero length intervals, which we want to discard.
fortran	If TRUE, then a Fortran implementation of the function is used. This is the default. This possibility is only for debugging purposes. You should of course get identical results with the two methods.

### Details

The main purpose of this function is to prepare a data file for use with [coxreg](#), [aftreg](#), and [coxph](#).

### Value

The return value is a data frame with the same variables as in the combination of `dat` and `com.dat`. Therefore it is an error to have common name(s) in the two data frames.

### Note

Not very vigorously tested.

### Author(s)

Göran Broström

### See Also

[coxreg](#), [aftreg](#), [coxph](#), [cal.window](#)

### Examples

```
dat <- data.frame(enter = 0, exit = 5.731, event = 1,
  birthdate = 1962.505, x = 2)
## Birth date: July 2, 1962 (approximately).
com.dat <- data.frame(price = c(12, 3, -5, 6, -8, -9, 1, 7))
dat.com <- make.communal(dat, com.dat, start = 1962.000)
```

### Description

Density, distribution function, quantile function, hazard function, cumulative hazard function, and random generation for the Gompertz-Makeham distribution with parameters `shape` and `scale`.

**Usage**

```

dmakeham(x, shape = c(1, 1), scale = 1, log = FALSE)
pmakeham(q, shape = c(1, 1), scale = 1, lower.tail = TRUE, log.p = FALSE)
qmakeham(p, shape = c(1, 1), scale = 1, lower.tail = TRUE, log.p = FALSE)
hmakeham(x, shape = c(1, 1), scale = 1, log = FALSE)
Hmakeham(x, shape = c(1, 1), scale = 1, log.p = FALSE)
rmakeham(n, shape = c(1, 1), scale = 1)

```

**Arguments**

shape	A vector, default value c(1, 1).
scale	defaulting to 1.
lower.tail	logical; if TRUE (default), probabilities are $P(X \leq x)$ , otherwise, $P(X > x)$ .
x, q	vector of quantiles.
p	vector of probabilities.
n	number of observations. If length(n) > 1, the length is taken to be the number required.
log, log.p	logical; if TRUE, probabilities p are given as log(p).

**Details**

The Gompertz-Makeham distribution with scale parameter  $a$  and shape parameter  $\sigma$  has hazard function given by

$$h(x) = a[1] + a[2] \exp(x/\sigma)$$

for  $x \geq 0$ .

**Value**

dmakeham gives the density, pmakeham gives the distribution function, qmakeham gives the quantile function, hmakeham gives the hazard function, Hmakeham gives the cumulative hazard function, and rmakeham generates random deviates.

Invalid arguments will result in return value NaN, with a warning.

---

male.mortality

*Male mortality in ages 40-60, nineteenth century*


---

**Description**

Males born in the years 1800-1820 and surviving at least 40 years in the parish Skellefteå in northern Sweden are followed from their fortieth birthday until death or the sixtieth birthday, whichever comes first.

**Usage**

```
data(male.mortality)
```



**Format**

A data frame with 2058 observations on the following 6 variables.

`id` Personal identification number.  
`enter` Start of duration. Measured in years since the fortieth birthday.  
`exit` End of duration. Measured in years since the fortieth birthday.  
`event` a logical vector indicating death at end of interval.  
`birthdate` The birthdate in decimal form.  
`ses` Socio-economic status, a factor with levels lower, upper

**Details**

The interesting explanatory covariate is `ses` (socioeconomic status), which is a time-varying covariate. This explains why several individuals are represented by more than one record each. Left truncation and right censoring are introduced this way.

**Note**

This data set is also known, and accessible, as `mort`.

**Source**

Data is coming from The Demographic Data Base, Umea University, Umeå, Sweden.

**References**

<http://www.ddb.umu.se>

**Examples**

```
data(male.mortality)
coxreg(Surv(enter, exit, event) ~ ses, data = male.mortality)
```

---

mlreg

*ML proportional hazards regression*

---

**Description**

Maximum Likelihood estimation of proportional hazards models. Is deprecated, use `coxreg` instead.

**Usage**

```
mlreg(
  formula = formula(data),
  data = parent.frame(),
  na.action = getOption("na.action"),
  init = NULL,
  method = c("ML", "MPPL"),
  control = list(eps = 1e-08, maxiter = 10, n.points = 12, trace = FALSE),
  singular.ok = TRUE,
  model = FALSE,
  center = TRUE,
  x = FALSE,
  y = TRUE,
  boot = FALSE,
  geometric = FALSE,
  rs = NULL,
  frailty = NULL,
  max.survs = NULL
)
```

**Arguments**

formula	a formula object, with the response on the left of a ~ operator, and the terms on the right. The response must be a survival object as returned by the Surv function.
data	a data.frame in which to interpret the variables named in the formula.
na.action	a missing-data filter function, applied to the model.frame, after any subset argument has been used. Default is options()\$na.action.
init	vector of initial values of the iteration. Default initial value is zero for all variables.
method	Method of treating ties, "ML", the default, means pure maximum likelihood, i.e., data are treated as discrete. The choice "MPPL" implies that risk sets with no tied events are treated as in ordinary Cox regression. This is a cameleont that adapts to data, part discrete and part continuous.
control	a list with components eps (convergence criterion), maxiter (maximum number of iterations), and silent (logical, controlling amount of output). You can change any component without mention the other(s).
singular.ok	Not used.
model	Not used.
center	Should covariates be centered? Default is TRUE
x	Return the design matrix in the model object?
y	return the response in the model object?
boot	No. of bootstrap replicates. Defaults to FALSE, i.e., no bootstrapping.
geometric	If TRUE, the intensity is assumed constant within strata.

rs	Risk set? If present, speeds up calculations considerably.
frailty	A grouping variable for frailty analysis. Full name is needed.
max.survs	Sampling of risk sets?

### Details

Method ML performs a true discrete analysis, i.e., one parameter per observed event time. Method MPPL is a compromise between the discrete and continuous time approaches; one parameter per observed event time with multiple events. With no ties in data, an ordinary Cox regression (as with [coxreg](#)) is performed.

### Value

A list of class `c("mlreg", "coxreg", "coxph")` with components

coefficients	Fitted parameter estimates.
var	Covariance matrix of the estimates.
loglik	Vector of length two; first component is the value at the initial parameter values, the second component is the maximized value.
score	The score test statistic (at the initial value).
linear.predictors	The estimated linear predictors.
residuals	The martingale residuals.
hazard	The estimated baseline hazard.
means	Means of the columns of the design matrix.
w.means	Weighted (against exposure time) means of covariates; weighted relative frequencies of levels of factors.
n	Number of spells in indata (possibly after removal of cases with NA's).
events	Number of events in data.
terms	Used by extractor functions.
assign	Used by extractor functions.
wald.test	The Wald test statistic (at the initial value).
y	The Surv vector.
isF	Logical vector indicating the covariates that are factors.
covars	The covariates.
ttr	Total Time at Risk.
levels	List of levels of factors.
formula	The calling formula.
call	The call.
bootstrap	The bootstrap sample, if requested on input.
sigma	Present if a frailty model is fitted. Equals the estimated frailty standard deviation.

<code>sigma.sd</code>	The standard error of the estimated frailty standard deviation.
<code>method</code>	The method.
<code>convergence</code>	Did the optimization converge?
<code>fail</code>	Did the optimization fail? (Is NULL if not).

**Warning**

The use of `rs` is dangerous, see note above. It can however speed up computing time.

**Note**

This function starts by creating risksets, if no riskset is supplied via `rs`, with the aid of [risksets](#). This latter mechanism fails if there are any NA's in the data! Note also that it depends on stratification, so `rs` contains information about stratification. Giving another strata variable in the formula is an error. The same is ok, for instance to supply stratum interactions.

Note further that `mlreg` is deprecated. [coxreg](#) should be used instead.

**Author(s)**

Göran Broström

**References**

Broström, G. (2002). Cox regression; Ties without tears. *Communications in Statistics: Theory and Methods* **31**, 285–297.

**See Also**

[coxreg](#), [risksets](#)

**Examples**

```
dat <- data.frame(time= c(4, 3,1,1,2,2,3),
                 status=c(1,1,1,0,1,1,0),
                 x=     c(0, 2,1,1,1,0,0),
                 sex=   c(0, 0,0,0,1,1,1))
mlreg( Surv(time, status) ~ x + strata(sex), data = dat) #stratified model
# Same as:
rs <- risksets(Surv(dat$time, dat$status), strata = dat$sex)
mlreg( Surv(time, status) ~ x, data = dat, rs = rs) #stratified model
```

---

`mort`*Male mortality in ages 40-60, nineteenth century*

---

**Description**

Males born in the years 1800-1820 and surviving at least 40 years in the parish Skellefteå in northern Sweden are followed from their fortieth birthday until death or the sixtieth birthday, whichever comes first.

**Usage**

```
data(mort)
```

**Format**

A data frame with 2058 observations on the following 6 variables.

`id` Personal identification number.

`enter` Start of duration. Measured in years since the fortieth birthday.

`exit` End of duration. Measured in years since the fortieth birthday.

`event` a logical vector indicating death at end of interval.

`birthdate` The birthdate in decimal form.

`ses` Socio-economic status, a factor with levels lower, upper

**Details**

The interesting explanatory covariate is `ses` (socioeconomic status), which is a time-varying covariate. This explains why several individuals are represented by more than one record each. Left truncation and right censoring are introduced this way.

**Note**

This data set is also known, and accessible, as `male.mortality`

**Source**

Data is coming from The Demographic Data Base, Umea University, Umeå, Sweden.

**References**

<http://www.ddb.umu.se>

**Examples**

```
data(mort)
coxreg(Surv(enter, exit, event) ~ ses, data = mort)
```

---

oe *Create an oe object*

---

### Description

Create an *oe* ("occurrence/exposure") object, used as a response variable in a model formula specifically in *tpchreg*.

### Usage

```
oe(count, exposure)
```

### Arguments

`count` Number of events, a non-negative integer.  
`exposure` exposure time corresponding to count. A positive numeric vector.

### See Also

[tpchreg](#).

---

oldmort *Old age mortality, Sundsvall, Sweden, 1860-1880.*

---

### Description

The data consists of old age life histories from 1 January 1860 to 31 december 1880, 21 years. Only (parts of) life histories above age 60 is considered.

### Usage

```
data(oldmort)
```

### Format

A data frame with 6508 observations from 4603 persons on the following 13 variables.

`id` Identification number.  
`enter` Start age for the interval.  
`exit` Stop age for the interval.  
`event` Indicator of death; equals TRUE if the person died at the end of the interval, FALSE otherwise.  
`birthdate` Birthdate as a real number (i.e., "1765-06-27" is 1765.490).  
`m.id` Mother's identification number.  
`f.id` Father's identification number.

sex Gender, a factor with levels male female  
 civ Civil status, a factor with levels unmarried married widow  
 ses.50 Socio-economic status at age 50, a factor with levels middle unknown upper farmer lower  
 birthplace a factor with levels parish region remote  
 imr.birth Infant mortality rate at birth in the region of birth  
 region Subregion of Sundsvall, a factor with levels town industry rural

### Details

The Sundsvall area in mid-Sweden was during the 19th century a fast growing forest industry. At the end of the century, it was one of the largest sawmill area in Europe. The town Sundsvall is fast growing part of the region and center for the commerce.

### Source

The Demographic Data Base, Umeå University, Sweden.

### References

Edvinsson, S. (2000). The Demographic Data Base at Umeå University: A resource for historical studies. In Hall, McKaa, and Thorvaldsen (eds), "Handbook of International Historical Microdata for Population Research", Minnesota Population Center, Minneapolis.

### Examples

```
data(oldmort)
summary(oldmort)
## maybe str(oldmort) ; plot(oldmort) ...
```

---

Pch

*The Piecewise Constant Hazards distribution.*

---

### Description

Density, distribution function, quantile function, hazard function, cumulative hazard function, mean, and random generation for the Piecewise Constant Hazards (pch) distribution.

### Usage

```
ppch(q, cuts, levels, lower.tail = TRUE, log.p = FALSE)
dpch(x, cuts, levels, log = FALSE)
hpch(x, cuts, levels, log = FALSE)
Hpch(x, cuts, levels, log.p = FALSE)
qpch(p, cuts, levels, lower.tail = TRUE, log.p = FALSE)
mpch(cuts, levels)
rpch(n, cuts, levels)
```

**Arguments**

cuts	Vector of cut points defining the intervals where the hazard function is constant.
levels	Vector of levels (values of the hazard function).
lower.tail	logical; if TRUE (default), probabilities are $P(X \leq x)$ , otherwise, $P(X > x)$ .
x, q	vector of quantiles.
p	vector of probabilities.
log, log.p	logical; if TRUE, probabilities p are given as log(p).
n	number of observations. If $\text{length}(n) > 1$ , the length is taken to be the number required.

**Details**

The pch distribution has a hazard function that is piecewise constant on intervals defined by cut-points

$$0 < c_1 < \dots < c_n < \infty, n \geq 0$$

If  $n = 0$ , this reduces to an exponential distribution.

**Value**

dpch gives the density, ppch gives the distribution function, qpch gives the quantile function, hpch gives the hazard function, Hpch gives the cumulative hazard function, mpch gives the mean, and rpch generates random deviates.

**Note**

the parameter levels must have length at least 1, and the number of cut points must be one less than the number of levels.

---

perstat

*Period statistics*


---

**Description**

Calculates occurrence / exposure rates for time periods given by period and for ages given by age.

**Usage**

```
perstat(surv, period, age = c(0, 200))
```

**Arguments**

surv	An (extended) surv object (4 columns with enter, exit, event, birthdate)
period	A vector of dates (in decimal form)
age	A vector of length 2; lowest and highest age



**Value**

A list with components

events	No. of events in each time period.
exposure	Exposure times in each period.
intensity	events / exposure

**Author(s)**

Göran Broström

**See Also**

[piecewise](#)

---

phfunc

*Loglikelihood function of a proportional hazards regression*

---

**Description**

Calculates minus the log likelihood function and its first and second order derivatives for data from a Weibull regression model.

**Usage**

```
phfunc(
  beta = NULL,
  lambda,
  p,
  X = NULL,
  Y,
  offset = rep(0, length(Y)),
  ord = 2,
  pfixed = FALSE,
  dist = "weibull"
)
```

**Arguments**

beta	Regression parameters
lambda	The scale parameter
p	The shape parameter
X	The design (covariate) matrix.
Y	The response, a survival object.
offset	Offset.

ord	ord = 0 means only loglikelihood, 1 means score vector as well, 2 loglikelihood, score and hessian.
pfixed	Logical, if TRUE the shape parameter is regarded as a known constant in the calculations, meaning that it is not considered in the partial derivatives.
dist	Which distribution? The default is "weibull", with the alternatives "loglogistic" and "lognormal".

### Details

Note that the function returns log likelihood, score vector and minus hessian, i.e. the observed information. The model is

$$S(t; p, \lambda, \beta, z) = S_0((t/\lambda)^p) e^{z\beta}$$

### Value

A list with components

f	The log likelihood. Present if ord >= 0
fp	The score vector. Present if ord >= 1
fpp	The negative of the hessian. Present if ord >= 2

### Author(s)

Göran Broström

### See Also

[phreg](#)

---

phreg

*Parametric Proportional Hazards Regression*

---

### Description

Proportional hazards model with parametric baseline hazard(s). Allows for stratification with different scale and shape in each stratum, and left truncated and right censored data.

### Usage

```
phreg(
  formula = formula(data),
  data = parent.frame(),
  na.action = getOption("na.action"),
  dist = "weibull",
  cuts = NULL,
  init,
  shape = 0,
```

```

param = c("canonical", "rate"),
control = list(eps = 1e-08, maxiter = 20, trace = FALSE),
singular.ok = TRUE,
model = FALSE,
x = FALSE,
y = TRUE,
center = TRUE
)

```

## Arguments

formula	a formula object, with the response on the left of a ~ operator, and the terms on the right. The response must be a survival object as returned by the Surv function.
data	a data.frame in which to interpret the variables named in the formula.
na.action	a missing-data filter function, applied to the model.frame, after any subset argument has been used. Default is options()\$na.action.
dist	Which distribution? Default is "weibull", with the alternatives "ev" (Extreme value), "gompertz", "pch" (piecewise constant hazards function), "loglogistic" and "lognormal". A special case like the exponential can be obtained by choosing "weibull" in combination with shape = 1, or "pch" without cuts.
cuts	Only used with dist = "pch". Specifies the points in time where the hazard function jumps. If omitted, an exponential model is fitted.
init	vector of initial values of the iteration. Default initial value is zero for all variables.
shape	If positive, the shape parameter is fixed at that value (in each stratum). If zero or negative, the shape parameter is estimated. If more than one stratum is present in data, each stratum gets its own estimate.
param	Applies only to the Gompertz distribution: "canonical" is defined in the description of the <a href="#">Gompertz</a> distribution; "rate" transforms scale to 1/log(scale), giving the same parametrization as in Stata and SAS. The latter thus allows for a negative rate, or a "cure" (Gompertz) model. The default is "canonical"; if this results in extremely large scale and/or shape estimates, consider trying "rate".
control	a list with components eps (convergence criterion), maxiter (maximum number of iterations), and silent (logical, controlling amount of output). You can change any component without mention the other(s).
singular.ok	Not used.
model	Not used.
x	Return the design matrix in the model object?
y	Return the response in the model object?
center	Logical, only affects plotting. Results are reported as is, without centering. See Details.

## Details

The parameterization is the same as in `coxreg` and `coxph`, but different from the one used by `survreg` (which is not a proportional hazards modelling function). The model is

$$S(t; a, b, \beta, z) = S_0((t/b)^a)^{\exp((z - \text{mean}(z))\beta)}$$

where  $S_0$  is some standardized survivor function.

If `center = TRUE` (default), graphs show the "baseline" distribution at the means of (continuous) covariates, and for the reference category in case of factors (avoiding representing "flying pigs"). If `center = FALSE` the baseline distribution is at the value zero of all covariates. It is usually a good idea to use `center = FALSE` in combination with "precentering" of covariates, that is, subtracting a reference value, ideally close to the center of the covariate distribution. In that way, the "reference" will be the same for all subsets of the data.

## Value

A list of class `c("phreg", "coxreg")` with components

<code>coefficients</code>	Fitted parameter estimates.
<code>cuts</code>	Cut points for the "pch" distribution. NULL otherwise.
<code>hazards</code>	The estimated constant levels in the case of the "pch" distribution. NULL otherwise.
<code>var</code>	Covariance matrix of the estimates.
<code>loglik</code>	Vector of length two; first component is the value at the initial parameter values, the second component is the maximized value.
<code>score</code>	The score test statistic (at the initial value).
<code>linear.predictors</code>	The estimated linear predictors.
<code>means</code>	Means of the columns of the design matrix, except those columns corresponding to a factor level, if <code>center = TRUE</code> . Otherwise all zero.
<code>w.means</code>	Weighted (against exposure time) means of covariates; weighted relative frequencies of levels of factors.
<code>n</code>	Number of spells in <code>indata</code> (possibly after removal of cases with NA's).
<code>events</code>	Number of events in data.
<code>terms</code>	Used by extractor functions.
<code>assign</code>	Used by extractor functions.
<code>wald.test</code>	The Wald test statistic (at the initial value).
<code>y</code>	The <code>Surv</code> vector.
<code>isF</code>	Logical vector indicating the covariates that are factors.
<code>covars</code>	The covariates.
<code>ttr</code>	Total Time at Risk.
<code>levels</code>	List of levels of factors.

formula	The calling formula.
call	The call.
method	The method.
convergence	Did the optimization converge?
fail	Did the optimization fail? (Is NULL if not).
pfixed	TRUE if shape was fixed in the estimation.

### Warning

The lognormal and loglogistic distributions are included on an experimental basis for the moment. Use with care, results may be unreliable!

The gompertz distribution has an exponentially increasing hazard function under the canonical parametrization. This may cause instability in the convergence of the fitting algorithm in the case of near-exponential data. It may be resolved by using `param = "rate"`.

### Note

The lognormal and loglogistic baseline distributions are extended to a three-parameter family by adding a "proportionality" parameter (multiplying the baseline hazard function). The log of the estimated parameter turns up as '(Intercept)' in the printed output. The reason for this extension is that the standard lognormal and loglogistic distributions are not closed under proportional hazards.

### Author(s)

Göran Broström

### See Also

[coxreg](#), [check.dist](#), [link{aftreg}](#).

### Examples

```
data(mort)
fit <- phreg(Surv(enter, exit, event) ~ ses, data = mort)
fit
plot(fit)
fit.cr <- coxreg(Surv(enter, exit, event) ~ ses, data = mort)
check.dist(fit.cr, fit)
```

---

 phreg.fit

*Parametric proportional hazards regression*


---

### Description

This function is called by [phreg](#), but it can also be directly called by a user.

### Usage

```
phreg.fit(X, Y, dist, strata, offset, init, shape, control, center = NULL)
```

### Arguments

X	The design (covariate) matrix.
Y	A survival object, the response.
dist	Which baseline distribution?
strata	A stratum variable.
offset	Offset.
init	Initial regression parameter values.
shape	If positive, a fixed value of the shape parameter in the distribution. Otherwise, the shape is estimated.
control	Controls convergence and output.
center	Deprecated (not used). Kept for backward copability. Results are reported as is, no centering.

### Details

See [phreg](#) for more detail.

### Value

coefficients	Estimated regression coefficients plus estimated scale and shape coefficients, sorted by strata, if present.
var	Variance-covariance matrix
loglik	Vector of length 2. The first component is the maximized loglikelihood with only scale and shape in the model, the second the final maximum.
score	Score test statistic at initial values
linear.predictors	Linear predictors for each interval.
means	Means of the covariates
conver	TRUE if convergence
fail	TRUE if failure
iter	Number of Newton-Raphson iterates.
n.strata	The number of strata in the data.

**Author(s)**

Göran Broström

**See Also**[phreg](#)

---

`piecewise`*Piecewise hazards*

---

**Description**

Calculate piecewise hazards, no. of events, and exposure times in each interval indicated by cutpoints.

**Usage**

```
piecewise(enter, exit, event, cutpoints)
```

**Arguments**

<code>enter</code>	Left interval endpoint
<code>exit</code>	Right interval endpoint
<code>event</code>	Indicator of event
<code>cutpoints</code>	Vector of cutpoints

**Details**

Exact calculation.

**Value**

A list with components

<code>events</code>	Vector of number of events
<code>exposure</code>	Vector of total exposure time
<code>intensity</code>	Vector of hazards, $\text{intensity} == \text{events} / \text{exposure}$

**Author(s)**

Göran Broström

**See Also**[perstat](#)

---

plot.aftreg                      *Plots output from an AFT regression*

---

### Description

Just a simple plot of the hazard (cumulative hazard, density, survival) functions for each stratum.

### Usage

```
## S3 method for class 'aftreg'
plot(
  x,
  fn = c("haz", "cum", "den", "sur"),
  main = NULL,
  xlim = NULL,
  ylim = NULL,
  xlab = "Duration",
  ylab = "",
  col,
  lty,
  printLegend = TRUE,
  new.data = x$means,
  ...
)
```

### Arguments

x	A aftreg object
fn	Which functions should be plotted! Default is all. They will scroll by, so you have to take care of explicitly what you want to be produced. See, eg, par(mfrow = ...)
main	Header for the plot
xlim	x limits
ylim	y limits
xlab	x label
ylab	y label
col	Colors?
lty	Line types?
printLegend	Should legend be printed? Default is yes.
new.data	At which covariate values?
...	Extra parameters passed to 'plot'

### Details

The plot is drawn at the mean values of the covariates, by default.



**Value**

No return value.

**Author(s)**

Göran Broström

**See Also**

[aftreg](#)

**Examples**

```
y <- rlllogis(40, shape = 1, scale = 1)
x <- rep(c(1,1,2,2), 10)
fit <- aftreg(Surv(y, rep(1, 40)) ~ x, dist = "loglogistic")
plot(fit)
```

---

plot.coxreg

*Plot method for coxreg objects*

---

**Description**

A plot of a baseline function of a coxreg fit is produced, one curve for each stratum.

**Usage**

```
## S3 method for class 'coxreg'
plot(
  x,
  fn = c("cum", "surv", "log", "loglog"),
  fig = TRUE,
  xlim = NULL,
  ylim = NULL,
  main = NULL,
  xlab = "Duration",
  ylab = "",
  col,
  lty,
  printLegend = TRUE,
  newdata = NULL,
  ...
)
```

**Arguments**

x	A coxreg object
fn	What should be plotted? Default is "cumhaz", and the other choices are "surv", "log", and "loglog".
fig	logical. If TRUE the plot is actually drawn, otherwise only the coordinates of the curve(s) are returned.
xlim	Start and end of the x axis.
ylim	Start and end of the y axis.
main	A headline for the plot
xlab	Label on the x axis.
ylab	Label on the y axis.
col	Color of the curves. Defaults to 'black'.
lty	Line type(s).
printLegend	Either a logical or a text string; if TRUE, a legend is printed at a default place, if FALSE, no legend is printed. Otherwise, if a text string, it should be one of "bottomleft", "bottomright", "topleft", etc., see <a href="#">legend</a> for all possible choices.
newdata	Not used
...	Other parameters to pass to the plot.

**Value**

An object of class hazdata containing the coordinates of the curve(s).

---

plot.hazdata	<i>Plots of survivor functions.</i>
--------------	-------------------------------------

---

**Description**

Baseline hazards estimates.

**Usage**

```
## S3 method for class 'hazdata'
plot(
  x,
  strata = NULL,
  fn = c("cum", "surv", "log", "loglog"),
  fig = TRUE,
  xlim = NULL,
  ylim = NULL,
  main = NULL,
  xlab = NULL,
  ylab = NULL,
```

```

    col = "black",
    lty = 1,
    printLegend = TRUE,
    where = NULL,
    ...
)

```

### Arguments

x	A hazdata object, typically the 'hazards' element in the output from <code>link{coxreg}</code> with <code>hazards = TRUE</code> .
strata	Stratum names if there are strata present.
fn	Which type of plot?
fig	Should a plot actually be produced? Default is TRUE.
xlim	Horizontal plot limits. If NULL, calculated by the function.
ylim	Vertical plot limits. If NULL, set to <code>c(0, 1)</code>
main	A heading for the plot.
xlab	Label on the x axis.
ylab	Label on the y-axis.
col	Color of the lines. May be a vector of length equal to No. of strata.
lty	Line type(s). May be a vector of length equal to No. of strata.
printLegend	Logical; should a legend be produced? Defaults to TRUE.
where	Where should the legend be placed (if(printLegend))? If NULL, "bottomleft" for <code>fn = "surv"</code> , otherwise "bottomright".
...	Anything that <code>plot.default</code> likes...

### Details

It is also possible to have as first argument an object of type "coxreg", given that it contains a component of type "hazdata".

### Value

A list where the elements are two-column matrices, one for each stratum in the model. The first column contains risktimes, and the second the y coordinates for the requested curve(s).

### Author(s)

Göran Broström

**Examples**

```

time0 <- numeric(50)
group <- c(rep(0, 25), rep(1, 25))
time1 <- rexp( 50, exp(group) )
event <- rep(1, 50)
fit <- coxreg(Surv(time0, time1, event) ~ strata(group), hazards = TRUE)
plot(fit$hazards)

```

---

plot.phreg

*Plots output from a phreg regression*


---

**Description**

Plot(s) of the hazard, density, cumulative hazards, and/or the survivor function(s) for each stratum.

**Usage**

```

## S3 method for class 'phreg'
plot(
  x,
  fn = c("haz", "cum", "den", "sur"),
  main = NULL,
  xlim = NULL,
  ylim = NULL,
  xlab = "Duration",
  ylab = "",
  col,
  lty,
  printLegend = TRUE,
  new.data = NULL,
  ...
)

```

**Arguments**

x	A phreg object
fn	Which functions should be plotted! Default is all. They will scroll by, so you have to take care explicitly what you want to be produced. See, eg, par(mfrow = ...)
main	Header for the plot
xlim	x limits
ylim	y limits
xlab	x label

ylab	y label
col	Color(s) for the curves. Defaults to black.
lty	Line type for the curve(s). Defaults to 1:(No. of strata).
printLegend	Logical, or character ("topleft", "bottomleft", "topright" or "bottomright"); if TRUE or character, a legend is added to the plot if the number of strata is two or more.
new.data	Now deprecated; reference hazard is given by the fit; either zero or the means all covariates, and (always) the reference category for factors.
...	Extra parameters passed to 'plot' and 'lines'.

**Value**

No return value.

**Author(s)**

Göran Broström

**See Also**

[phreg](#)

**Examples**

```
y <- rlllogis(40, shape = 1, scale = 1)
x <- rep(c(1,1,2,2), 10)
fit <- phreg(Surv(y, rep(1, 40)) ~ x, dist = "loglogistic")
plot(fit)
```

---

plot.tpchreg

*Plots output from a tpchreg regression*

---

**Description**

Plot(s) of the hazard, cumulative hazards, and/or the survivor function(s) for each stratum.

**Usage**

```
## S3 method for class 'tpchreg'
plot(
  x,
  fn = c("haz", "cum", "sur"),
  main = NULL,
  xlim = NULL,
  ylim = NULL,
```

```

    xlab = "Duration",
    ylab = "",
    col,
    lty,
    printLegend = TRUE,
    ...
)

```

### Arguments

x	A tpchreg object
fn	Which functions should be plotted! Default is the hazard function.
main	Header for the plot
xlim	x limits
ylim	y limits
xlab	x label
ylab	y label
col	Color(s) for the curves. Defaults to black.
lty	Line type for the curve(s). Defaults to 1:(No. of strata).
printLegend	Logical, or character ("topleft", "bottomleft", "topright" or "bottomright"); if TRUE or character, a legend is added to the plot if the number of strata is two or more.
...	Extra parameters passed to 'plot' and 'lines'.

### Value

No return value.

### Author(s)

Göran Broström

### See Also

[tpchreg](#)

---

plot.weibreg

*Plots output from a Weibull regression*

---

### Description

Plot(s) of the hazard, density, cumulative hazards, and/or the survivor function(s) for each stratum.

**Usage**

```
## S3 method for class 'weibreg'
plot(
  x,
  fn = c("haz", "cum", "den", "sur"),
  main = NULL,
  xlim = NULL,
  ylim = NULL,
  xlab = NULL,
  ylab = NULL,
  new.data = x$means,
  ...
)
```

**Arguments**

x	A weibreg object
fn	Which functions should be plotted! Default is all. They will scroll by, so you have to take care explicitly what you want to be produced. See, eg, <code>par(mfrow = ...)</code>
main	Header for the plot
xlim	x limits
ylim	y limits
xlab	x label
ylab	y label
new.data	At which covariate values?
...	Extra parameters passed to 'plot'

**Details**

The plot is drawn at the mean values of the covariates.

**Value**

No return value

**Author(s)**

Göran Broström

**See Also**

[phreg](#), [weibreg](#)

## Examples

```
y <- rweibull(4, shape = 1, scale = 1)
x <- c(1,1,2,2)
fit <- weibreg(Surv(y, c(1,1,1,1)) ~ x)
plot(fit)
```

---

print.aftreg	<i>Prints aftreg objects</i>
--------------	------------------------------

---

## Description

The hazard, the cumulative hazard, the density, and the survivor baseline functions are plotted.

## Usage

```
## S3 method for class 'aftreg'
print(x, digits = max(options())$digits - 4, 3), ...)
```

## Arguments

x	A aftreg object
digits	Precision in printing
...	Not used.

## Value

No value is returned.

## Note

Doesn't work for threeway or higher order interactions. Use [print.coxph](#) in that case.

## Author(s)

Göran Broström

## See Also

[phreg](#), [print.coxph](#)



---

print.coxreg	<i>Prints coxreg objects</i>
--------------	------------------------------

---

**Description**

More "pretty-printing" than `print.coxph`, which is a fall-back for 'difficult' objects.

**Usage**

```
## S3 method for class 'coxreg'  
print(x, digits = max(options())$digits - 4, 3), ...)
```

**Arguments**

<code>x</code>	A coxreg object, typically the result of running <code>coxreg</code>
<code>digits</code>	Output format.
<code>...</code>	Other arguments.

**Details**

Doesn't work with three-way and higher interactions, in which case `print.coxph` is used.

**Value**

No value is returned.

**Author(s)**

Göran Broström

**See Also**

[coxreg](#), [print.coxph](#)

---

print.phreg	<i>Prints phreg objects</i>
-------------	-----------------------------

---

**Description**

The hazard, the cumulative hazard, the density, and the survivor baseline functions are plotted.

**Usage**

```
## S3 method for class 'phreg'  
print(x, digits = max(options())$digits - 4, 3), ...)
```

**Arguments**

x	A phreg object
digits	Precision in printing
...	Not used.

**Value**

No value is returned.

**Note**

Doesn't work for threeway or higher order interactions. Use [print.coxph](#) in that case.

**Author(s)**

Göran Broström

**See Also**

[phreg](#), [print.coxph](#)

---

print.risksets

*Prints a summary of the content of a set of risk sets.*

---

**Description**

Given the output from risksets, summary statistics are given for it.

**Usage**

```
## S3 method for class 'risksets'  
print(x, ...)
```

**Arguments**

x	An object of class 'risksets'.
...	Not used for the moment.

**Value**

No value is returned; the function prints summary statistics of risk sets.

**Note**

There is no `summary.risksets` yet. On the TODO list.

**Author(s)**

Göran Broström

**See Also**

risksets

**Examples**

```
rs <- with(mort, risksets(Surv(enter, exit, event)))
print(rs)
```

---

print.tpchreg	<i>Prints tpchreg objects</i>
---------------	-------------------------------

---

**Description**

More "pretty-printing"

**Usage**

```
## S3 method for class 'tpchreg'
print(x, digits = max(options())$digits - 4, 3), ...)
```

**Arguments**

x	A tpchreg object, typically the result of running tpchreg
digits	Output format.
...	Other arguments.

**Details**

Doesn't work with three-way or higher interactions.

**Value**

No value is returned.

**Author(s)**

Göran Broström

**See Also**[tpchreg](#), [print.coxreg](#)

`print.weibreg`            *Prints weibreg objects*

---

### Description

The hazard, the cumulative hazard, the density, and the survivor baseline functions are plotted.

### Usage

```
## S3 method for class 'weibreg'  
print(x, digits = max(options())$digits - 4, 3), ...)
```

### Arguments

<code>x</code>	A weibreg object
<code>digits</code>	Precision in printing
<code>...</code>	Not used.

### Value

No value is returned.

### Note

Doesn't work for threeway or higher order interactions. Use [print.coxph](#) in that case.

### Author(s)

Göran Broström

### See Also

[weibreg](#), [print.coxph](#)

---

`risksets`            *Finds the compositions and sizes of risk sets*

---

### Description

Focus is on the risk set composition just prior to a failure.

### Usage

```
risksets(x, strata = NULL, max.survs = NULL, members = TRUE)
```

**Arguments**

x	A Surv object.
strata	Stratum indicator.
max.survs	Maximum number of survivors in each risk set. If smaller than the 'natural number', survivors are sampled from the present ones. No sampling if missing.
members	If TRUE, all members of all risk sets are listed in the resulting list, see below.

**Details**

If the input argument max.survs is left alone, all survivors are accounted for in all risk sets.

**Value**

A list with components

antrs	No. of risk sets in each stratum. The number of strata is given by length(antrs).
risktimes	Ordered distinct failure time points.
eventset	If 'members' is TRUE, a vector of pointers to events in each risk set, else NULL.
riskset	If 'members' is TRUE, a vector of pointers to the members of the risk sets, in order. The 'n.events' first are the events. If 'members' is FALSE, 'riskset' is NULL.
size	The sizes of the risk sets.
n.events	The number of events in each risk set.
sample_fraction	The sampling fraction of survivors in each risk set.

**Note**

can be used to "sample the risk sets".

**Author(s)**

Göran Broström

**See Also**

[table.events](#), [coxreg](#).

**Examples**

```
enter <- c(0, 1, 0, 0)
exit <- c(1, 2, 3, 4)
event <- c(1, 1, 1, 0)
risksets(Surv(enter, exit, event))
```

---

scania

*Old age mortality, Scania, southern Sweden, 1813-1894.*

---

### Description

The data consists of old age life histories from 1 January 1813 to 31 december 1894. Only (parts of) life histories above age 50 is considered.

### Usage

```
data(scania)
```

### Format

A data frame with 1931 observations from 1931 persons on the following 9 variables.

`id` Identification number (enumeration).

`enter` Start age for the interval.

`exit` Stop age for the interval.

`event` Indicator of death; equals TRUE if the person died at the end of the interval, FALSE otherwise.

`birthdate` Birthdate as a real number (i.e., "1765-06-27" is 1765.490).

`sex` Gender, a factor with levels male female.

`parish` One of five parishes in Scania, coded 1, 2, 3, 4, 5. Factor.

`ses` Socio-economic status at age 50, a factor with levels upper and lower.

`immigrant` a factor with levels no region and yes.

### Details

The Scanian area in southern Sweden was during the 19th century a mainly rural area.

### Source

The Scanian Economic Demographic Database, Lund University, Sweden.

### References

<http://www.ed.lu.se/databases>

### Examples

```
data(scania)
summary(scania)
```

---

summary.aftreg	<i>Prints aftreg objects</i>
----------------	------------------------------

---

**Description**

This is the same as [print.aftreg](#)

**Usage**

```
## S3 method for class 'aftreg'  
summary(object, ...)
```

**Arguments**

object	A aftreg object
...	Additional ...

**Author(s)**

Göran Broström

**See Also**

[print.coxreg](#)

**Examples**

```
## The function is currently defined as  
function (object, ...)  
print(object)
```

---

summary.coxreg	<i>Prints coxreg objects</i>
----------------	------------------------------

---

**Description**

This is the same as [print.coxreg](#)

**Usage**

```
## S3 method for class 'coxreg'  
summary(object, ...)
```

**Arguments**

object	A coxreg object
...	Additional ...

**Author(s)**

Göran Broström

**See Also**

[print.coxreg](#)

**Examples**

```
## The function is currently defined as
function (object, ...)
print(object)
```

---

summary.phreg

*Prints phreg objects*

---

**Description**

This is the same as [print.phreg](#)

**Usage**

```
## S3 method for class 'phreg'
summary(object, ...)
```

**Arguments**

object	A phreg object
...	Additional ...

**Author(s)**

Göran Broström

**See Also**

[print.coxreg](#)



## Examples

```
## The function is currently defined as
function (object, ...)
print(object)
```

---

summary.weibreg	<i>Prints a weibreg object</i>
-----------------	--------------------------------

---

## Description

This is the same as [print.weibreg](#)

## Usage

```
## S3 method for class 'weibreg'
summary(object, ...)
```

## Arguments

object	A weibreg object
...	Additional ...

## Author(s)

Göran Broström

## See Also

[print.weibreg](#)

## Examples

```
## The function is currently defined as
function (object, ...)
print(object)
```

SurvSplit

*Split a survival object at specified durations.***Description**

Given a survival object, (a matrix with two or three columns) and a set of specified cut times, split each record into multiple subrecords at each cut time. The new survival object will be in 'counting process' format, with an enter time, exit time, and event status for each record.

**Usage**

```
SurvSplit(Y, cuts)
```

**Arguments**

Y	A survival object, a matrix with two or three columns.
cuts	The cut points, must be strictly positive and distinct.

**Value**

A list with components

Y	The new survival object with three columns, i.e., in 'counting process' form.
ivl	Interval No., starting from leftmost, (0, cuts[1]) or similar.
idx	Row number for original Y row.

**Note**

This function is used in [phreg](#) for the piecewise constant hazards model. It uses [age.window](#) for each interval.

**Author(s)**

Göran Broström

**See Also**

[survSplit](#), [age.window](#).

**Examples**

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.

## The function is currently defined as
function(Y, cuts){
```

```

if (NCOL(Y) == 2) Y <- cbind(rep(0, NROW(Y)), Y)
indat <- cbind(Y, 1:NROW(Y), rep(-1, NROW(Y)))
colnames(indat) <- c("enter", "exit", "event", "idx", "ivl")
n <- length(cuts)
cuts <- sort(cuts)
if ((cuts[1] <= 0) || (cuts[n] == Inf))
  stop("'cuts' must be positive and finite.")
cuts <- c(0, cuts, Inf)
n <- n + 1
out <- list()
indat <- as.data.frame(indat)
for (i in 1:n){
  out[[i]] <- age.window(indat, cuts[i:(i+1)])
  out[[i]]$ivl <- i
  out[[i]] <- t(out[[i]])
}
Y <- matrix(unlist(out), ncol = 5, byrow = TRUE)
colnames(Y) <- colnames(indat)
list(Y = Y[, 1:3],
      ivl = Y[, 5],
      idx = Y[, 4]
    )
}

```

swe07

*Swedish population and deaths in ages 61–80, 2007.***Description**

The Swedish population and No. of deaths by age and sex in the ages 61–80. Data from the year 2007.

**Usage**

```
data(swe07)
```

**Format**

A data frame with 80 rows and five variables.

pop Average population size during the year 2007 by age and sex.

deaths Number of deaths by age and sex during the year 2007.

sex Sex.

age Age.

log.pop The logarithm of the first variable, pop. Included for convenience, may be used as an offset in a Poisson regression.

**Details**

The average population is calculated as the mean of the population 1 January 2007 and 1 January 2008.

**Source**

Data is taken from Statistics Sweden.

**References**

<http://www.scb.se>

**Examples**

```
data(swe07)
fit <- glm(deaths ~ offset(log.pop) + sex * as.factor(age), family = poisson, data = swe07)
drop1(fit, test = "Chisq") ## Proportional hazards?
```

---

table.events	<i>Calculating failure times, risk set sizes and No. of events in each risk set</i>
--------------	---

---

**Description**

From input data of the 'interval' type, with an event indicator, summary statistics for each risk set (at an event time point) are calculated.

**Usage**

```
table.events(enter = rep(0, length(exit)), exit, event, strict = TRUE)
```

**Arguments**

enter	Left truncation time point.
exit	End time point, an event or a right censoring.
event	Event indicator.
strict	If TRUE, then tabulating is not done after a time point where all individuals in a riskset failed.

**Value**

A list with components

times	Ordered distinct event time points.
events	Number of events at each event time point.
riskset.sizes	Number at risk at each event time point.

**Author(s)**

Göran Broström

**See Also**[risksets](#)**Examples**

```
exit = c(1,2,3,4,5)
event = c(1,1,0,1,1)
table.events(exit = exit, event = event)
```

---

toBinary	<i>Transforms a "survival" data frame into a data frame suitable for binary (logistic) regression</i>
----------	---

---

**Description**

The result of the transformation can be used to do survival analysis via logistic regression. If the cloglog link is used, this corresponds to a discrete time analogue to Cox's proportional hazards model.

**Usage**

```
toBinary(
  dat,
  surv = c("enter", "exit", "event"),
  strats,
  max.survs = NROW(dat)
)
```

**Arguments**

dat	A data frame with three variables representing the survival response. The default is that they are named enter, exit, and event
surv	A character vector with the names of the three variables representing survival.
strats	An eventual stratification variable.
max.survs	Maximal number of survivors per risk set. If set to a (small) number, survivors are sampled from the risk sets.

**Details**

toBinary calls risksets in the eha package.

**Value**

Returns a data frame expanded risk set by risk set. The three "survival variables" are replaced by a variable named event (which overwrites an eventual variable by that name in the input). Two more variables are created, riskset and orig.row.

event	Indicates an event in the corresponding risk set.
riskset	Factor (with levels 1, 2, ...) indicating risk set.
risktime	The 'risktime' (age) in the corresponding riskset.
orig.row	The row number for this item in the original data frame.

**Note**

The survival variables must be three. If you only have *exit* and *event*, create a third containing all zeros.

**Author(s)**

Göran Broström

**See Also**

[coxreg.glm](#).

**Examples**

```
enter <- rep(0, 4)
exit <- 1:4
event <- rep(1, 4)
z <- rep(c(-1, 1), 2)
dat <- data.frame(enter, exit, event, z)
binDat <- toBinary(dat)
dat
binDat
coxreg(Surv(enter, exit, event) ~ z, method = "ml", data = dat)
## Same as:
summary(glm(event ~ z + riskset, data = binDat, family = binomial(link = cloglog)))
```

---

toDate

*Convert time in years since "0000-01-01" to a date.*

---

**Description**

This function uses `as.Date` and a simple linear transformation.

**Usage**

```
toDate(times)
```

**Arguments**

times            a vector of durations

**Value**

A vector of dates as character strings of the type "1897-05-21".

**Author(s)**

Göran Broström

**See Also**

[toTime](#)

**Examples**

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.  
toDate(1897.357)
```

---

toTime

*Calculate duration in years from "0000-01-01" to a given date*

---

**Description**

Given a vector of dates, the output is a vector of durations in years since "0000-01-01".

**Usage**

```
toTime(dates)
```

**Arguments**

dates            A vector of dates in character form or of class Date

**Value**

A vector of durations, as described above.

**Author(s)**

Göran Broström

**See Also**[toDate](#)**Examples**

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.

## The function is currently defined as
toTime(c("1897-05-16", "1901-11-21"))
```

---

toTpch

*Transform a "survival" data frame Surv(enter, exit, event) to tabular form with 'event' and 'exposure' and aggregating*

---

**Description**

Transform a "survival" data frame Surv(enter, exit, event) to tabular form with 'event' and 'exposure' and aggregating

**Usage**

```
toTpch(dat, cuts)
```

**Arguments**

dat            The survival data frame.

cuts           Vector defining the age periods of constant hazard.



---

tpchreg	<i>Proportional hazards regression with piecewise constant hazards and tabular data.</i>
---------	--

---

**Description**

Proportional hazards regression with piecewise constant hazards and tabular data.

**Usage**

```
tpchreg(
  formula,
  data,
  time,
  pieces,
  subset,
  na.action,
  contrasts = NULL,
  start.coef = NULL,
  control = list(epsilon = 1e-08, maxit = 200, trace = FALSE)
)
```

**Arguments**

formula	a formula with 'oe(count, exposure) ~ x1 + ...'
data	a data frame with event, exposure, age plus covariates
time	the time variable, a factor indicating time intervals.
pieces	numeric vector of length 1 or length(levels(time)): The length(s) of timeintervals.
subset	subset of data, not implemented yet.
na.action	Not implemented yet.
contrasts	Not implemented yet.
start.coef	For themoment equal to zero.
control	list of control parameters for the optimization.

**Note**

This function is under development and not well documented for the time being. Use it with care, but it should work with standard (default) settings.

**See Also**

[oe.](#)

weibreg

*Weibull Regression***Description**

Proportional hazards model with baseline hazard(s) from the Weibull family of distributions. Allows for stratification with different scale and shape in each stratum, and left truncated and right censored data.

**Usage**

```
weibreg(
  formula = formula(data),
  data = parent.frame(),
  na.action = getOption("na.action"),
  init,
  shape = 0,
  control = list(eps = 1e-04, maxiter = 10, trace = FALSE),
  singular.ok = TRUE,
  model = FALSE,
  x = FALSE,
  y = TRUE,
  center = TRUE
)
```

**Arguments**

formula	a formula object, with the response on the left of a ~ operator, and the terms on the right. The response must be a survival object as returned by the Surv function.
data	a data.frame in which to interpret the variables named in the formula.
na.action	a missing-data filter function, applied to the model.frame, after any subset argument has been used. Default is options()\$na.action.
init	vector of initial values of the iteration. Default initial value is zero for all variables.
shape	If positive, the shape parameter is fixed at that value (in each stratum). If zero or negative, the shape parameter is estimated. If more than one stratum is present in data, each stratum gets its own estimate.
control	a list with components eps (convergence criterion), maxiter (maximum number of iterations), and silent (logical, controlling amount of output). You can change any component without mention the other(s).
singular.ok	Not used.
model	Not used.
x	Return the design matrix in the model object?
y	Return the response in the model object?
center	Deprecated, and not used. Will be removed in the future.

**Details**

The parameterization is the same as in `coxreg` and `coxph`, but different from the one used by `survreg`. The model is

$$h(t; a, b, \beta, z) = (a/b)(t/b)^{a-1} \exp(z\beta)$$

This is in correspondence with `Weibull`. To compare regression coefficients with those from `survreg` you need to divide by estimated shape ( $\hat{a}$ ) and change sign. The p-values and test statistics are however the same, with one exception; the score test is done at maximized scale and shape in `weibreg`.

This model is a Weibull distribution with shape parameter  $a$  and scale parameter  $b \exp(-z\beta/a)$

**Value**

A list of class `c("weibreg", "coxreg")` with components

<code>coefficients</code>	Fitted parameter estimates.
<code>var</code>	Covariance matrix of the estimates.
<code>loglik</code>	Vector of length two; first component is the value at the initial parameter values, the second component is the maximized value.
<code>score</code>	The score test statistic (at the initial value).
<code>linear.predictors</code>	The estimated linear predictors.
<code>means</code>	Means of the columns of the design matrix.
<code>w.means</code>	Weighted (against exposure time) means of covariates; weighted relative frequencies of levels of factors.
<code>n</code>	Number of spells in <code>indata</code> (possibly after removal of cases with NA's).
<code>events</code>	Number of events in data.
<code>terms</code>	Used by extractor functions.
<code>assign</code>	Used by extractor functions.
<code>wald.test</code>	The Wald test statistic (at the initial value).
<code>y</code>	The <code>Surv</code> vector.
<code>isF</code>	Logical vector indicating the covariates that are factors.
<code>covars</code>	The covariates.
<code>ttr</code>	Total Time at Risk.
<code>levels</code>	List of levels of factors.
<code>formula</code>	The calling formula.
<code>call</code>	The call.
<code>method</code>	The method.
<code>convergence</code>	Did the optimization converge?
<code>fail</code>	Did the optimization fail? (Is NULL if not).
<code>pfixed</code>	TRUE if shape was fixed in the estimation.

**Warning**

The print method `print.weibreg` doesn't work if threeway or higher order interactions are present.

Note further that covariates are internally centered, if `center = TRUE`, by this function, and this is not corrected for in the output. This affects the estimate of  $\log(\text{scale})$ , but nothing else. If you don't like this, set `center = FALSE`.

**Note**

This function is not maintained, and may behave in unpredictable ways. Use `phreg` with `dist = "weibull"` (the default) instead! Will soon be declared deprecated.

**Author(s)**

Göran Broström

**See Also**

`phreg`, `coxreg`, `print.weibreg`

**Examples**

```
dat <- data.frame(time = c(4, 3, 1, 1, 2, 2, 3),
                  status = c(1, 1, 1, 0, 1, 1, 0),
                  x = c(0, 2, 1, 1, 1, 0, 0),
                  sex = c(0, 0, 0, 0, 1, 1, 1))
weibreg( Surv(time, status) ~ x + strata(sex), data = dat) #stratified model
```

---

weibreg.fit

*Weibull regression*

---

**Description**

This function is called by `weibreg`, but it can also be directly called by a user.

**Usage**

```
weibreg.fit(X, Y, strata, offset, init, shape, control, center = TRUE)
```

**Arguments**

X	The design (covariate) matrix.
Y	A survival object, the response.
strata	A stratum variable.
offset	Offset.

<code>init</code>	Initial regression parameter values.
<code>shape</code>	If positive, a fixed value of the shape parameter in the Weibull distribution. Otherwise, the shape is estimated.
<code>control</code>	Controls convergence and output.
<code>center</code>	Should covariates be centered?

**Details**

See [weibreg](#) for more detail.

**Value**

<code>coefficients</code>	Estimated regression coefficients plus estimated scale and shape coefficients, sorted by strata, if present.
<code>var</code>	
<code>loglik</code>	Vector of length 2. The first component is the maximized loglikelihood with only scale and shape in the model, the second the final maximum.
<code>score</code>	Score test statistic at initial values
<code>linear.predictors</code>	Linear predictors for each interval.
<code>means</code>	Means of the covariates
<code>conver</code>	TRUE if convergence
<code>fail</code>	TRUE if failure
<code>iter</code>	Number of Newton-Raphson iterates.
<code>n.strata</code>	The number of strata in the data.

**Author(s)**

Göran Broström

**See Also**

[weibreg](#)

---

Weibull

*The (Cumulative) Hazard Function of a Weibull Distribution*

---

**Description**

`hweibull` calculates the hazard function of a Weibull distribution, and `Hweibull` calculates the corresponding cumulative hazard function.

**Usage**

```
hweibull(x, shape, scale = 1, log = FALSE)
```

**Arguments**

x	Vector of quantiles.
shape	The shape parameter.
scale	The scale parameter, defaults to 1.
log	logical; if TRUE, the log of the hazard function is given.

**Details**

See [dweibull](#).

**Value**

The (cumulative) hazard function, evaluated at x.

**Author(s)**

Göran Broström

**See Also**

[pweibull](#)

**Examples**

```
hweibull(3, 2, 1)
dweibull(3, 2, 1) / pweibull(3, 2, 1, lower.tail = FALSE)
Hweibull(3, 2, 1)
-pweibull(3, 2, 1, log.p = TRUE, lower.tail = FALSE)
```

---

wfunk

*Loglikelihood function of a Weibull regression*

---

**Description**

Calculates minus the log likelihood function and its first and second order derivatives for data from a Weibull regression model. Is called by [weibreg](#).

**Usage**

```
wfunk(  
  beta = NULL,  
  lambda,  
  p,  
  X = NULL,  
  Y,
```

```

offset = rep(0, length(Y)),
ord = 2,
pfixed = FALSE
)

```

### Arguments

beta	Regression parameters
lambda	The scale parameter
p	The shape parameter
X	The design (covariate) matrix.
Y	The response, a survival object.
offset	Offset.
ord	ord = 0 means only loglikelihood, 1 means score vector as well, 2 loglikelihood, score and hessian.
pfixed	Logical, if TRUE the shape parameter is regarded as a known constant in the calculations, meaning that it is not considered in the partial derivatives.

### Details

Note that the function returns log likelihood, score vector and minus hessian, i.e. the observed information. The model is

$$h(t; p, \lambda, \beta, z) = p/\lambda(t/\lambda)^{(p-1)} \exp(-(t/\lambda)^p) \exp(z\beta)$$

This is in correspondence with [dweibull](#).

### Value

A list with components

f	The log likelihood. Present if ord >= 0
fp	The score vector. Present if ord >= 1
fpp	The negative of the hessian. Present if ord >= 2

### Author(s)

Göran Broström

### See Also

[weibreg](#)

# Index

- \*Topic **cluster**
  - toBinary, 69
- \*Topic **datasets**
  - fert, 20
  - infants, 24
  - logrye, 28
  - male.mortality, 32
  - mort, 37
  - oldmort, 38
  - scania, 62
  - swe07, 67
- \*Topic **distribution**
  - check.dist, 10
  - EV, 19
  - Gompertz, 22
  - Loglogistic, 26
  - Lognormal, 27
  - makeham, 31
  - Pch, 39
  - phfunc, 41
  - wfunk, 78
- \*Topic **dplot**
  - plot.aftreg, 48
  - plot.phreg, 52
  - plot.tpchreg, 53
  - plot.weibreg, 54
- \*Topic **manip**
  - check.surv, 11
  - cro, 17
  - join.spells, 25
  - SurvSplit, 66
- \*Topic **nonparametric**
  - perstat, 40
  - piecewise, 47
- \*Topic **printing**
  - ltx, 29
- \*Topic **print**
  - summary.aftreg, 63
  - summary.coxreg, 63
  - summary.phreg, 64
  - summary.weibreg, 65
- \*Topic **regression**
  - aftreg, 4
  - aftreg.fit, 7
  - coxreg, 12
  - coxreg.fit, 15
  - mlreg, 33
  - phreg, 42
  - phreg.fit, 46
  - print.aftreg, 56
  - print.phreg, 57
  - print.weibreg, 60
  - weibreg, 74
  - weibreg.fit, 76
- \*Topic **summary**
  - print.risksets, 58
- \*Topic **survival**
  - aftreg, 4
  - aftreg.fit, 7
  - age.window, 8
  - cal.window, 9
  - check.surv, 11
  - coxreg, 12
  - coxreg.fit, 15
  - geome.fit, 21
  - join.spells, 25
  - make.communal, 30
  - mlreg, 33
  - perstat, 40
  - phfunc, 41
  - phreg, 42
  - phreg.fit, 46
  - piecewise, 47
  - plot.aftreg, 48
  - plot.hazdata, 50
  - plot.phreg, 52
  - plot.tpchreg, 53
  - plot.weibreg, 54



- print.aftreg, 56
  - print.coxreg, 57
  - print.phreg, 57
  - print.tpchreg, 59
  - print.weibreg, 60
  - risksets, 60
  - summary.aftreg, 63
  - summary.coxreg, 63
  - summary.phreg, 64
  - summary.weibreg, 65
  - table.events, 68
  - toBinary, 69
  - toDate, 70
  - toTime, 71
  - weibreg, 74
  - weibreg.fit, 76
  - Weibull, 77
  - wfunk, 78
- aftreg, 4, 7–9, 11, 26, 29, 31, 49
- aftreg.fit, 7
- age.window, 8, 9, 66
- cal.window, 8, 9, 31
- check.dist, 10, 45
- check.surv, 11, 26
- coxph, 3, 13, 14, 31, 44, 75
- coxreg, 3, 6, 8–11, 12, 15–17, 22, 26, 29, 31, 35, 36, 44, 45, 57, 61, 70, 75, 76
- coxreg.fit, 15
- cro, 17
- dEV (EV), 19
- dgomertz (Gompertz), 22
- dllogis (Loglogistic), 26
- dlnorm (Lognormal), 27
- dmakeham (makeham), 31
- dpch (Pch), 39
- dweibull, 78, 79
- eha (eha-package), 3
- eha-defunct, 18
- eha-package, 3
- EV, 19
- fert, 20
- frail.fit, 21
- geome.fit, 21
- ghq (eha-defunct), 18
- glm, 70
- glmboot (eha-defunct), 18
- glmbootFit (eha-defunct), 18
- glmML (eha-defunct), 18
- Gompertz, 22, 43
- gomertz (Gompertz), 22
- HEV (EV), 19
- hEV (EV), 19
- Hgomertz (Gompertz), 22
- hgomertz (Gompertz), 22
- Hllogis (Loglogistic), 26
- hllogis (Loglogistic), 26
- Hlnorm (Lognormal), 27
- hlnorm (Lognormal), 27
- Hmakeham (makeham), 31
- hmakeham (makeham), 31
- Hpch (Pch), 39
- hpch (Pch), 39
- Hweibull (Weibull), 77
- hweibull (Weibull), 77
- infants, 24
- join.spells, 11, 25
- legend, 50
- Llogis (Loglogistic), 26
- Lnorm (Lognormal), 27
- Loglogistic, 26
- Lognormal, 27
- logrye, 28
- ltx, 29
- make.communal, 30
- makeham, 31
- male.mortality, 32
- match, 18
- mlreg, 33
- mort, 37
- mpch (Pch), 39
- oe, 38, 73
- oldmort, 38
- paste, 18
- Pch, 39
- pch (Pch), 39
- perstat, 40, 47
- pEV (EV), 19

pgompertz (Gompertz), 22  
phfunc, 41  
phreg, 6, 10, 29, 42, 42, 46, 47, 53, 55, 56, 58, 66, 76  
phreg.fit, 46  
piecewise, 41, 47  
pllogis (Loglogistic), 26  
plnorm (Lognormal), 27  
plot.aftreg, 48  
plot.coxreg, 49  
plot.default, 51  
plot.hazdata, 50  
plot.phreg, 52  
plot.tpchreg, 53  
plot.weibreg, 54  
pmakeham (makeham), 31  
ppch (Pch), 39  
print.aftreg, 56, 63  
print.coxph, 56–58, 60  
print.coxreg, 57, 59, 63, 64  
print.phreg, 57, 64  
print.risksets, 58  
print.tpchreg, 59  
print.weibreg, 60, 65, 76  
pweibull, 78

qEV (EV), 19  
qgompertz (Gompertz), 22  
qlllogis (Loglogistic), 26  
qlnorm (Lognormal), 27  
qmakeham (makeham), 31  
qpch (Pch), 39

rEV (EV), 19  
rgompertz (Gompertz), 22  
risksets, 14, 17, 21, 22, 36, 60, 69  
rllogis (Loglogistic), 26  
rlnorm (Lognormal), 27  
rmakeham (makeham), 31  
rpch (Pch), 39

scania, 62  
summary.aftreg, 63  
summary.coxreg, 63  
summary.phreg, 64  
summary.weibreg, 65  
survreg, 5, 6, 44, 75  
SurvSplit, 66  
survSplit, 66

swe07, 67

table.events, 61, 68  
toBinary, 69  
toDate, 70, 72  
toTime, 71, 71  
toTpch, 72  
tpchreg, 38, 54, 59, 73

weibreg, 55, 60, 74, 76–79  
weibreg.fit, 76  
Weibull, 75, 77  
wfunk, 78