

Package ‘pbdSLAP’

January 12, 2020

Version 0.2-8

Date 2020-01-04

Title Programming with Big Data -- Scalable Linear Algebra Packages

Depends R (>= 3.6.0), methods, rlecuyer, pbdMPI (>= 0.3-1)

LazyLoad yes

LazyData yes

Copyright See 'pbdSLAP/inst/ScaLAPACK_LICENSE.txt' for the files in 'src/BLACS/', 'src/PBLAS/', 'src/REDIST/', 'src/ScaLAPACK/', and 'src/TOOLS/'.

Description Utilizing scalable linear algebra packages mainly including 'BLACS', 'PBLAS', and 'ScaLAPACK' in double precision via 'pbdMPI' based on 'ScaLAPACK' version 2.0.2.

SystemRequirements 'OpenMPI' (>= 1.5.4) on Solaris, Linux, Mac, and FreeBSD. 'MS-MPI' (Microsoft HPC Pack 2012 R2 MS-MPI Redistributable Package) on Windows.

License Mozilla Public License 2.0

URL <http://r-pbd.org/>

BugReports <https://github.com/snoweyepbdSLAP/issues>

MailingList Please send questions and comments regarding pbdR to RBigData@gmail.com

NeedsCompilation yes

Maintainer Wei-Chen Chen <wccsnow@gmail.com>

Author Wei-Chen Chen [aut, cre],
Drew Schmidt [aut],
George Ostrouchov [aut],
Pragneshkumar Patel [aut],
Brian Ripley [ctb] (Solaris & Mac)

Repository CRAN

Date/Publication 2020-01-12 06:00:10 UTC

R topics documented:

pbdSLAP-package	2
SLAP Grid Information	3

Index	5
--------------	----------

pbdSLAP-package	<i>Programming with Big Data – Scalable Linear Algebra Packages</i>
-----------------	---

Description

pbdSLAP utilizes scalable linear algebra packages mainly including BLACS, PBLAS, and ScaLAPACK in double precision via pbdMPI based on ScaLAPACK version 2.0.2.

Details

Package:	pbdSLAP
Type:	Package
License:	MPL2
LazyLoad:	yes

This package requires **pbdMPI** and MPI system. The main purpose of **pbdSLAP** is to provide several scalable linear algebra packages containing double precision libraries for **pbdDMAC** or other useful packages.

Author(s)

Wei-Chen Chen <wccsnow@gmail.com>, Drew Schmidt, George Ostrouchov, and Pragneshkumar Patel.

References

Programming with Big Data in R Website: <http://r-pbd.org/>
 ScaLAPACK Website: <http://www.netlib.org/scalapack/>
 ScaLAPACK Block Cyclic Data Distribution Website: <http://icl.cs.utk.edu/lapack-forum/viewtopic.php?f=5&t=4922>

Examples

```
## Not run:
### Under command mode, run the demo with 2 processors by
### (Use Rscript.exe for windows system)

mpiexec -np 2 Rscript -e "demo(gridinfo,'pbdSLAP',ask=F,echo=F)"

## End(Not run)
```

Description

These functions initialize a grid of pbdSLAP, assign the information to a global object, and free the grid.

Usage

```
slap.init.grid(nprow, npcol = 1, ictxt = 0)
slap.exit.grid(ictxt)
slap.finalize(quit.mpi = FALSE)
```

Arguments

<code>nprow</code>	number of row processors.
<code>npcol</code>	number of column processors.
<code>ictxt</code>	the grid id
<code>quit.mpi</code>	if finalize MPI.

Details

This function arranges all processors in a (`nprow * npcol`) grid and the grid will map the big data matrix.

Value

`slap.init.grid` assigns a global object `__grid_info_0` for `ictxt = 0` containing the grid information. `slap.exit.grid` free the grid. `slap.finalize` free all memory.

Author(s)

Wei-Chen Chen <wccsnow@gmail.com>, Drew Schmidt, George Ostrouchov, and Pragneshkumar Patel.

References

Programming with Big Data in R Website: <http://r-pbd.org/>

ScaLAPACK Website: <http://www.netlib.org/scalapack/>

ScaLAPACK Block Cyclic Data Distribution Website: <http://icl.cs.utk.edu/lapack-forum/viewtopic.php?f=5&t=4922>

Examples

```
## Not run:  
### Under command mode, run the demo with 2 processors by  
### (Use Rscript.exe for windows system)  
  
mpiexec -np 2 Rscript -e "demo(gridinfo,'pbdSLAP',ask=F,echo=F)"  
  
## End(Not run)
```

Index

*Topic **package**

 pbdSLAP-package, [2](#)

*Topic **programming**

 SLAP Grid Information, [3](#)

pbdSLAP (pbdSLAP-package), [2](#)

pbdSLAP-package, [2](#)

SLAP Grid Information, [3](#)

slap.exit.grid(SLAP Grid Information),
[3](#)

slap.finalize(SLAP Grid Information), [3](#)

slap.init.grid(SLAP Grid Information),
[3](#)