

# Package ‘renv’

December 9, 2019

**Type** Package

**Title** Project Environments

**Version** 0.9.2

**Description** A dependency management toolkit for R. Using 'renv', you can create and manage project-local R libraries, save the state of these libraries to a 'lockfile', and later restore your library as required. Together, these tools can help make your projects more isolated, portable, and reproducible.

**License** MIT + file LICENSE

**URL** <https://rstudio.github.io/renv>

**BugReports** <https://github.com/rstudio/renv/issues>

**Imports** utils

**Suggests** covr, knitr, packrat, remotes, reticulate, rmarkdown, rstudioapi, testthat

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 7.0.2

**VignetteBuilder** knitr

**NeedsCompilation** no

**Author** Kevin Ushey [aut, cre],  
RStudio [cph]

**Maintainer** Kevin Ushey <kevin@rstudio.com>

**Repository** CRAN

**Date/Publication** 2019-12-09 22:50:02 UTC

## R topics documented:

|              |   |
|--------------|---|
| renv-package | 2 |
| activate     | 3 |
| bootstrap    | 4 |

|                        |           |
|------------------------|-----------|
| clean . . . . .        | 5         |
| config . . . . .       | 6         |
| consent . . . . .      | 8         |
| deactivate . . . . .   | 8         |
| dependencies . . . . . | 9         |
| diagnostics . . . . .  | 11        |
| equip . . . . .        | 11        |
| history . . . . .      | 12        |
| hydrate . . . . .      | 13        |
| init . . . . .         | 14        |
| install . . . . .      | 16        |
| isolate . . . . .      | 17        |
| load . . . . .         | 18        |
| lockfile . . . . .     | 19        |
| lockfiles . . . . .    | 20        |
| migrate . . . . .      | 22        |
| modify . . . . .       | 23        |
| paths . . . . .        | 24        |
| project . . . . .      | 26        |
| purge . . . . .        | 26        |
| rebuild . . . . .      | 27        |
| record . . . . .       | 29        |
| refresh . . . . .      | 30        |
| rehash . . . . .       | 31        |
| remote . . . . .       | 31        |
| remove . . . . .       | 32        |
| restore . . . . .      | 33        |
| revert . . . . .       | 35        |
| run . . . . .          | 36        |
| settings . . . . .     | 36        |
| snapshot . . . . .     | 38        |
| status . . . . .       | 40        |
| update . . . . .       | 41        |
| upgrade . . . . .      | 42        |
| use_python . . . . .   | 43        |
| <b>Index</b>           | <b>46</b> |

---

renv-package

*Project-local Environments for R*


---

## Description

Project-local environments for R.

## Details

You can use `renv` to construct isolated, project-local R libraries. Each project using `renv` will share package installations from a global cache of packages, helping to avoid wasting disk space on multiple installations of a package that might otherwise be shared across projects.

## Author(s)

**Maintainer:** Kevin Ushey <kevin@rstudio.com>

Other contributors:

- RStudio [copyright holder]

## See Also

Useful links:

- <https://rstudio.github.io/renv>
- Report bugs at <https://github.com/rstudio/renv/issues>

---

activate

*Activate a Project*

---

## Description

Use `activate()` to write the infrastructure needed to ensure that newly-launched R projects will load the project's private library on launch, alongside any other project-specific state recorded for the project.

## Usage

```
activate(project = NULL)
```

## Arguments

`project` The project directory. If `NULL`, then the active project will be used. If no project is currently active, then the current working directory is used instead.

## Value

The project directory, invisibly. Note that this function is normally called for its side effects.

## See Also

Other `renv`: [deactivate\(\)](#)

## Examples

```
## Not run:  
  
# activate the current project  
renv::activate()  
  
# activate a separate project  
renv::activate("~/projects/analysis")  
  
## End(Not run)
```

---

bootstrap

*Bootstrap an renv Installation*

---

## Description

Bootstrap an renv installation, making the requested version of renv available for projects on the system.

## Usage

```
bootstrap(project = NULL, version = NULL)
```

## Arguments

|         |   |
|---------|---|
| project | The project directory. If NULL, then the active project will be used. If no project is currently active, then the current working directory is used instead.  |
| version | The version of renv to install. If NULL, the version of renv currently installed will be used. The requested version of renv will be retrieved from the renv public GitHub repository, at <a href="https://github.com/rstudio/renv">https://github.com/rstudio/renv</a> . |

## Details

Normally, this function does not need to be called directly by the user; it will be invoked as required by `init()` and `activate()`.

## Value

The project directory, invisibly. Note that this function is normally called for its side effects.

---

|       |                        |
|-------|------------------------|
| clean | <i>Clean a Project</i> |
|-------|------------------------|

---

### Description

Clean up a project and its associated R libraries.

### Usage

```
clean(project = NULL, ..., confirm = interactive())
```

### Arguments

|         |  |
|---------|--|
| project | The project directory. If NULL, then the active project will be used. If no project is currently active, then the current working directory is used instead. |
| ...     | Optional arguments; reserved for future expansion.   |
| confirm | Boolean; prompt the user before taking any action?   |

### Details

The following actions will be taken:

- Stale lockfiles (00LOCK-) will be removed.
- Leftover temporary directories in the project library will be removed.
- Non-system packages installed in the system library will be removed.
- Unused packages within the project will be removed.
- Packages within the cache that are no longer used will be removed.

### Value

The project directory, invisibly. Note that this function is normally called for its side effects.

### Examples

```
## Not run:  
  
# clean the current project  
renv::clean()  
  
## End(Not run)
```

config

*User-Level Configuration of renv***Description**

Configure different behaviors of renv.

**Details**

For a given configuration option:

1. If an R option of the form `renv.config.<name>` is available, then that option's value will be used;
2. If an environment variable of the form `RENV_CONFIG_<NAME>` is available, then that option's value will be used;
3. Otherwise, the default for that particular configuration value is used.

Any periods (.)s in the option name are transformed into underscores (\_) in the environment variable name, and vice versa. For example, the configuration option `auto.snapshot` could be configured as:

- `options(renv.config.auto.snapshot = <...>)`
- `Sys.setenv(RENV_CONFIG_AUTO_SNAPSHOT = <...>)`

Note that if both the R option and the environment variable are defined, the R option will be used instead. Environment variables can be more useful when you want a particular configuration to be automatically inherited by child processes; if that behavior is not desired, then the R option may be preferred.

If you want to set and persist these options across multiple projects, it is recommended that you set them in your user startup files (e.g. in `~/.Rprofile` or `~/.Renviron`).

**Configuration**

The following renv configuration options are available:

| <b>Name</b>                     | <b>Type</b>  | <b>Default</b>           | <b>Description</b>   |
|---------------------------------|--------------|--------------------------|--|
| <code>auto.snapshot</code>      | logical[1]   | FALSE                    | Automatically snapshot changes to the project library after a new project is created.  |
| <code>copy.method</code>        | character[1] | "auto"                   | The method to use when attempting to copy directories. See <b>Copy</b> .   |
| <code>connect.timeout</code>    | integer[1]   | 20L                      | The amount of time to spend (in seconds) when attempting to download a file.   |
| <code>connect.retry</code>      | integer[1]   | 3L                       | The number of times to attempt re-downloading a file, when transferring fails.   |
| <code>external.libraries</code> | character[*] | <code>character()</code> | A character vector of external libraries, to be used in tandem with <code>install.staged</code> .  |
| <code>install.staged</code>     | logical[1]   | TRUE                     | Perform a staged install of packages during install and restore? When active, renv will attempt to install packages in a temporary directory before copying them to the project library. |
| <code>repos.override</code>     | character[*] | NULL                     | Override the R package repositories used during <b>restore</b> . Primarily useful for testing.   |
| <code>sandbox.enabled</code>    | logical[1]   | FALSE                    | Enable sandboxing for renv projects? When active, renv will attempt to install packages in a temporary directory before copying them to the project library.                             |
| <code>shims.enabled</code>      | logical[1]   | TRUE                     | Should renv shims be installed on package load? When enabled, renv will attempt to install shims for packages that are not installed on the system.                                      |
| <code>snapshot.validate</code>  | logical[1]   | TRUE                     | Validate R package dependencies when calling snapshot? When TRUE, renv will attempt to validate the dependencies of the project library.   |
| <code>updates.check</code>      | logical[1]   | FALSE                    | Check for package updates when the session is initialized? This can be useful for ensuring that the project library is up-to-date.   |

|                  |            |       |  |
|------------------|------------|-------|--|
| updates.parallel | integer[1] | 2L    | Check for package updates in parallel? This can be useful when a     |
| user.library     | logical[1] | FALSE | Include the user library on the library paths for your projects? Not |
| user.profile     | logical[1] | FALSE | Load the user R profile (typically located at ~/.Rprofile) when ren  |

## Copy Methods

If you find that `renv` is unable to copy some directories in your environment, you may want to try setting the `copy.method` option. By default, `renv` will try to choose a system tool that is likely to succeed in copying files on your system – `robocopy` on Windows, and `cp` on Unix. `renv` will also instruct these tools to preserve timestamps and attributes when copying files. However, you can select a different method as appropriate.

The following methods are supported:

|          |   |
|----------|---|
| R        | Use R's built-in <code>file.copy()</code> function.                   |
| cp       | Use <code>cp</code> to copy files.                                    |
| robocopy | Use <code>robocopy</code> to copy files. (Only available on Windows.) |
| rsync    | Use <code>rsync</code> to copy files.                                 |

You can also provide a custom copy method if required; e.g.

```
options(renv.config.copy.method = function(src, dst) {
  # copy a file from 'src' to 'dst'
})
```

Note that `renv` will always first attempt to copy a directory first to a temporary path within the target folder, and then rename that temporary path to the final target destination. This helps avoid issues where a failed attempt to copy a directory could leave a half-copied directory behind in the final location.

## Project-Local Settings

For settings that should persist alongside a particular project, the various settings available in [settings](#) can be used.

## Examples

```
# disable automatic snapshots
options(renv.config.auto.snapshot = FALSE)

# disable with environment variable
Sys.setenv(RENV_CONFIG_AUTO_SNAPSHOT = "FALSE")
```

---

|         |                                 |
|---------|---------------------------------|
| consent | <i>Consent to usage of renv</i> |
|---------|---------------------------------|

---

### Description

Provide consent to renv, allowing it to write and update certain files on your filesystem.

### Usage

```
consent(provided = FALSE)
```

### Arguments

|          |  |
|----------|--|
| provided | The default provided response. If you need to provide consent from a non-interactive R session, you can invoke <code>renv::consent(provided = TRUE)</code> explicitly. |
|----------|--|

### Details

As part of its normal operation, renv will write and update some files in your project directory, as well as an application-specific cache directory. These paths are documented within [paths](#).

In accordance with the [CRAN Repository Policy](#), renv must first obtain consent from you, the user, before these actions can be taken. Please call `renv::consent()` first to provide this consent.

You can also set the R option:

```
options(renv.consent = TRUE)
```

to implicitly provide consent for e.g. non-interactive R sessions.

### Value

TRUE if consent is provided, or an R error otherwise.

---

|            |                             |
|------------|-----------------------------|
| deactivate | <i>Deactivate a Project</i> |
|------------|-----------------------------|

---

### Description

Use `deactivate()` to remove the infrastructure used by renv to activate projects for newly-launched R sessions. In particular, this implies removing the requisite code from the project `.Rprofile` that automatically activates the project when new R sessions are launched in the project directory.

### Usage

```
deactivate(project = NULL)
```



**Arguments**

`project` The project directory. If NULL, then the active project will be used. If no project is currently active, then the current working directory is used instead.

**Value**

The project directory, invisibly. Note that this function is normally called for its side effects.

**See Also**

Other renv: [activate\(\)](#)

**Examples**

```
## Not run:  
  
# deactivate the currently-activated project  
renv::deactivate()  
  
## End(Not run)
```

---

dependencies

*Find R Package Dependencies in a Project*

---

**Description**

Find R packages used within a project.

**Usage**

```
dependencies(path = getwd(), root = NULL, quiet = FALSE, dev = FALSE)
```

**Arguments**

`path` The path to a (possibly multi-mode) R file, or a directory containing such files.

`root` The root directory to be used for dependency discovery. Defaults to the active project directory. You may need to set this explicitly to ensure that your project's `.renvignore`s (if any) are properly handled.

`quiet` Boolean; report problems discovered (if any) during dependency discovery?

`dev` Boolean; include 'development' dependencies as well? That is, packages which may be required during development but are unlikely to be required during runtime for your project. By default, only runtime dependencies are returned.

## Details

`dependencies()` will crawl files within your project, looking for R files and the packages used within those R files. This is done primarily by parsing the code and looking for calls of the form:

- `library(package)`
- `require(package)`
- `requireNamespace("package")`
- `package::method()`

For R package projects, dependencies expressed in the DESCRIPTION file will also be discovered. Note that the `rmarkdown` package is required in order to crawl dependencies in R Markdown files.

## Value

An R data.frame of discovered dependencies, mapping inferred package names to the files in which they were discovered.

## Ignoring Files

By default, `renv` will read your project's `.gitignores` (if any) to determine whether certain files or folders should be included when traversing directories. If preferred, you can also create a `.renvignore` file (with entries of the same format as a standard `.gitignore` file) to tell `renv` which files to ignore within a directory. If both `.renvignore` and `.gitignore` exist within a folder, the `.renvignore` will be used in lieu of the `.gitignore`.

See <https://git-scm.com/docs/gitignore> for documentation on the `.gitignore` format. Some simple examples here:

```
# ignore all R Markdown files
*.Rmd

# ignore all data folders
data/

# ignore only data folders from the root of the project
/data/
```

## Development Dependencies

`renv` attempts to distinguish between 'development' dependencies and 'runtime' dependencies. For example, you might rely on e.g. `devtools` and `roxygen2` during development for a project, but may not actually require these packages at runtime.

## Examples

```
## Not run:

# find R package dependencies in the current directory
renv::dependencies()
```

```
## End(Not run)
```

---

|             |                                   |
|-------------|-----------------------------------|
| diagnostics | <i>Print a Diagnostics Report</i> |
|-------------|-----------------------------------|

---

**Description**

Print a diagnostics report, summarizing the state of a project using `renv`. This report can occasionally be useful when diagnosing issues with `renv`.

**Usage**

```
diagnostics(project = NULL)
```

**Arguments**

|         |  |
|---------|--|
| project | The project directory. If <code>NULL</code> , then the active project will be used. If no project is currently active, then the current working directory is used instead. |
|---------|--|

**Value**

This function is normally called for its side effects.

---

|       |  |
|-------|--|
| equip | <i>Install Required System Libraries</i> |
|-------|--|

---

**Description**

Equip your system with libraries commonly-used during compilation of `R` packages. Currently only supported on Windows.

**Usage**

```
equip()
```

**Value**

This function is normally called for its side effects.

**Examples**

```
## Not run:  
  
# download useful build tools  
renv::equip()  
  
## End(Not run)
```

---

`history`*View Lockfile History*

---

### Description

Use your version control system to find prior versions of the `renv.lock` file that have been used in your project.

### Usage

```
history(project = NULL)
```

### Arguments

`project` The project directory. If `NULL`, then the active project will be used. If no project is currently active, then the current working directory is used instead.

### Details

The `history()` function is currently only implemented for projects using `git` for version control.

### Value

An R `data.frame`, summarizing the commits in which `renv.lock` has been mutated.

### Examples

```
## Not run:  
  
# get history of previous versions of renv.lock in VCS  
db <- renv::history()  
  
# choose an older commit  
commit <- db$commit[5]  
  
# revert to that version of the lockfile  
renv::revert(commit = commit)  
  
## End(Not run)
```

---

|         |                          |
|---------|--------------------------|
| hydrate | <i>Hydrate a Project</i> |
|---------|--------------------------|

---

### Description

Discover the R packages used within a project, and then install those packages into the active library. This effectively allows you to clone the state of your system R libraries for use within a project library.

### Usage

```
hydrate/packages = NULL, ..., library = NULL, project = NULL)
```

### Arguments

|          |  |
|----------|--|
| packages | The set of R packages to install. When NULL, the set of packages as reported by <code>dependencies()</code> is used.   |
| ...      | Optional arguments; reserved for future expansion.   |
| library  | The R library to be hydrated. When NULL, the active library as reported by <code>.libPaths()</code> is used.   |
| project  | The project directory. If NULL, then the active project will be used. If no project is currently active, then the current working directory is used instead. |

### Details

`hydrate()` attempts to re-use packages already installed on your system, to avoid unnecessary attempts to download and install packages from remote sources. `hydrate()` will attempt to discover R packages from the following sources (in order):

- The user library,
- The site library,
- The system library,
- The renv cache.

If package is discovered in one of these locations, renv will attempt to copy or link that package into the requested library as appropriate.

### Value

A named R list, giving the packages that were used for hydration as well as the set of packages which were not found.

### Missing Packages

If renv discovers that your project depends on R packages not currently installed in your user library, then it will attempt to install those packages from the active R repositories.

## Examples

```
## Not run:  
  
# hydrate the active library  
renv::hydrate()  
  
## End(Not run)
```

---

init

*Initialize a Project*

---

## Description

Discover packages used within the current project, and then initialize a project-local private R library with those packages. The currently-installed versions of any packages in use (as detected within the default R libraries) are then installed to the project's private library.

## Usage

```
init(  
  project = NULL,  
  ...,  
  settings = NULL,  
  bare = FALSE,  
  force = FALSE,  
  restart = interactive()  
)
```

## Arguments

|          |   |
|----------|---|
| project  | The project directory. The R working directory will be changed to match the requested project directory.  |
| ...      | Optional arguments; reserved for future expansion.  |
| settings | A list of <a href="#">settings</a> to be used with the newly-initialized project.   |
| bare     | Boolean; initialize the project without attempting to discover and install R package dependencies?  |
| force    | Boolean; force initialization? By default, renv will refuse to initialize the home directory as a project, to defend against accidental misuses of <code>init()</code> .    |
| restart  | Boolean; attempt to restart the R session after initializing the project? A session restart will be attempted if the "restart" R option is set by the frontend embedding R. |

## Details

The primary steps taken when initializing a new project are:

1. R package dependencies are discovered within the R files used within the project with `dependencies()`;
2. Discovered packages are copied into the renv global package cache, so these packages can be re-used across future projects as necessary;
3. Any missing R package dependencies discovered are then installed into the project's private library;
4. A lockfile capturing the state of the project's library is created with `snapshot()`;
5. The project is activated with `activate()`.

This mimics the workflow provided by `packrat:::init()`, but with a few differences – in particular, renv does not attempt to download and store package sources, and renv will re-use packages that have already been installed whenever possible.

If renv sees that the associated project has already been initialized and has a lockfile, then it will attempt to infer the appropriate action to take based on the presence of a private library. If no library is available, renv will restore the private library from the lockfile; if one is available, renv will ask if you want to perform a 'standard' init, restore from the lockfile, or activate the project without taking any further action.

## Value

The project directory, invisibly. Note that this function is normally called for its side effects.

## Infrastructure

renv will write or amend the following files in the project:

- `.Rprofile`: An auto-loader will be installed, so that new R sessions launched within the project are automatically loaded.
- `renv/activate.R`: This script is run by the previously-mentioned `.Rprofile` to load the project.
- `renv/.gitignore`: This is used to instruct Git to ignore the project's private library, as it does not need to be
- `.Rbuildignore`: to ensure that the renv directory is ignored during package development; e.g. when attempting to build or install a package using renv.

## Examples

```
## Not run:  
  
# disable automatic snapshots  
auto.snapshot <- getOption("renv.config.auto.snapshot")  
options(renv.config.auto.snapshot = FALSE)  
  
# initialize a new project (with an empty R library)  
renv::init(bare = TRUE)
```

```
# install digest 0.6.19
renv::install("digest@0.6.19")

# save library state to lockfile
renv::snapshot()

# remove digest from library
renv::remove("digest")

# check library status
renv::status()

# restore lockfile, thereby reinstalling digest 0.6.19
renv::restore()

# restore automatic snapshots
options(renv.config.auto.snapshot = auto.snapshot)

## End(Not run)
```

---

install

*Install Packages*

---

## Description

Install one or more R packages from a variety of remote sources.

## Usage

```
install(
  packages = NULL,
  ...,
  library = NULL,
  rebuild = FALSE,
  confirm = interactive(),
  project = NULL
)
```

## Arguments

|          |   |
|----------|---|
| packages | A character vector of R packages to install. Required package dependencies (Depends, Imports, LinkingTo) will be installed as required. |
| ...      | Optional arguments; reserved for future expansion.  |
| library  | The R library to be used. When NULL, the active project library will be used instead.   |



|         |  |
|---------|--|
| rebuild | Force packages to be rebuilt, thereby bypassing any installed versions of the package available in the cache? This can either be a boolean (indicating that the requested package(s) should be rebuilt), or a vector of package names indicating which packages should be rebuilt. |
| confirm | Boolean; prompt the user before taking any action?   |
| project | The project directory. If NULL, then the active project will be used. If no project is currently active, then the current working directory is used instead.   |

### Details

`install()` uses the same machinery as `restore()` when installing packages. In particular, this means that the local cache of package installations is used when possible. This helps to avoid re-downloading packages that have already been downloaded before, and re-compiling packages from source when a binary copy of that package is already available.

Note that this interface is subject to change – the goal is to hook into separate package installation backends in the future.

### Value

A named list of package records which were installed by `renv`.

### Examples

```
## Not run:

# install the latest version of 'digest'
renv::install("digest")

# install an old version of 'digest' (using archives)
renv::install("digest@0.6.18")

# install 'digest' from GitHub (latest dev. version)
renv::install("eddelbuettel/digest")

# install a package from local sources
renv::install("~/path/to/package")

## End(Not run)
```

---

isolate

*Isolate a Project*

---

### Description

Copy packages from the `renv` cache directly into the project library, so that the project can continue to function independently of the `renv` cache.

**Usage**

```
isolate(project = NULL)
```

**Arguments**

**project**            The project directory. If NULL, then the active project will be used. If no project is currently active, then the current working directory is used instead.

**Value**

The project directory, invisibly. Note that this function is normally called for its side effects.

**Examples**

```
## Not run:

# isolate a project
renv::isolate()

## End(Not run)
```

---

load

*Load a Project*


---

**Description**

Load a project.

**Usage**

```
load(project = getwd(), quiet = FALSE)
```

**Arguments**

**project**            The project directory. If NULL, then the active project will be used. If no project is currently active, then the current working directory is used instead.

**quiet**              Boolean; be quiet during load?

**Details**

Normally, this is done automatically on session startup by the infrastructure generated by [activate\(\)](#) – users should not need to call this function directly.

**Value**

The project directory, invisibly. Note that this function is normally called for its side effects.

## Examples

```
## Not run:  
  
# load a project -- note that this is normally done automatically  
# when the R session is started in an renv project after calling  
# renv::activate()  
renv::load()  
  
## End(Not run)
```

---

lockfile

*Programmatically Create and Modify a Lockfile*

---

## Description

This function provides an API for creating and modifying renv lockfiles. This can be useful when you'd like to programmatically generate or modify a lockfile – for example, because you want to update or change a package record in an existing lockfile.

## Usage

```
lockfile(file = NULL, project = NULL)
```

## Arguments

|         |   |
|---------|---|
| file    | The path to an existing lockfile. When no lockfile is provided, a new one will be created based on the current project context. If you want to create a blank lockfile, use <code>file = NA</code> instead. |
| project | The project directory. If <code>NULL</code> , then the active project will be used. If no project is currently active, then the current working directory is used instead.                                  |

## See Also

[lockfiles](#), for a description of the structure of an renv lockfile.

## Examples

```
## Not run:  
  
lock <- lockfile("renv.lock")  
  
# set the repositories for a lockfile  
lock$repos(CRAN = "https://cran.r-project.org")  
  
# depend on digest 0.6.22  
lock$add(digest = "digest@0.6.22")
```

```
# write to file
lock$write("renv.lock")

## End(Not run)
```

---

lockfiles

*Lockfiles*


---

## Description

A **lockfile** records the state of a project at some point in time.

## Details

A lockfile captures the state of a project's library at some point in time. In particular, the package names, their versions, and their sources (when known) are recorded in the lockfile.

Projects can be restored from a lockfile using the `restore()` function. This implies re-installing packages into the project's private library, as encoded within the lockfile.

While lockfiles are normally generated and used with `snapshot()` / `restore()`, they can also hand-edited if so desired. Lockfiles are written as `.json`, to allow for easy consumption by other tools.

An example lockfile follows:

```
{
  "renv": {
    "Version": "1.0.0"
  },
  "R": {
    "Version": "3.6.1",
    "Repositories": [
      {
        "Name": "CRAN",
        "URL": "https://cloud.r-project.org"
      }
    ]
  },
  "Packages": {
    "markdown": {
      "Package": "markdown",
      "Version": "1.0",
      "Source": "Repository",
      "Repository": "CRAN",
      "Hash": "4584a57f565dd7987d59dda3a02cfb41"
    },
    "mime": {
```

```

    "Package": "mime",
    "Version": "0.7",
    "Source": "Repository",
    "Repository": "CRAN",
    "Hash": "908d95ccbfd1dd274073ef07a7c93934"
  }
}
}

```

The sections used within a lockfile are described next.

### [renv]

Information about the version of `renv` used to manage this project.

**Version** The version of the `renv` package used with this project.

### [R]

Properties related to the version of `R` associated with this project.

**Version** The version of `R` used.  
**Repositories** The `R` repositories used in this project.

### [Packages]

`R` package records, capturing the packages used or required by a project at the time when the lockfile was generated.

**Package** The package name.  
**Version** The package version.  
**Source** The location from which this package was retrieved.  
**Repository** The name of the repository (if any) from which this package was retrieved.  
**Hash** (Optional) A unique hash for this package, used for package caching.

Additional remote fields, further describing how the package can be retrieved from its corresponding source, will also be included as appropriate (e.g. for packages installed from GitHub).

### [Python]

Metadata related to the version of `Python` used with this project (if any).

**Version** The version of `Python` being used.  
**Type** The type of `Python` environment being used ("virtualenv", "conda", "system")  
**Name** The (optional) name of the environment being used.

Note that the Name field may be empty. In that case, a project-local Python environment will be used instead (when not directly using a system copy of Python).

### See Also

Other reproducibility: [restore\(\)](#), [snapshot\(\)](#)

---

|         |   |
|---------|---|
| migrate | <i>Migrate a Project from Packrat to renv</i> |
|---------|---|

---

### Description

Migrate a project's infrastructure from Packrat to renv.

### Usage

```
migrate(
  project = NULL,
  packrat = c("lockfile", "sources", "library", "options", "cache")
)
```

### Arguments

|         |   |
|---------|---|
| project | The project directory. If NULL, then the active project will be used. If no project is currently active, then the current working directory is used instead.  |
| packrat | Components of the Packrat project to migrate. See the default argument list for components of the Packrat project that can be migrated. Select a subset of those components for migration as appropriate. |

### Value

The project directory, invisibly. Note that this function is normally called for its side effects.

### Migration

When migrating Packrat projects to renv, the set of components migrated can be customized using the packrat argument. The set of components that can be migrated are as follows:

| Name     | Description  |
|----------|--|
| lockfile | Migrate the Packrat lockfile (packrat/packrat.lock) to the renv lockfile (renv.lock).  |
| sources  | Migrate package sources from the packrat/src folder to the renv sources folder. Currently, only CRAN packages are supported. |
| library  | Migrate installed packages from the Packrat library to the renv project library.   |
| options  | Migrate compatible Packrat options to the renv project.  |
| cache    | Migrate packages from the Packrat cache to the renv cache.   |

**Examples**

```
## Not run:  
  
# migrate Packrat project infrastructure to renv  
renv::migrate()  
  
## End(Not run)
```

---

modify

*Open the Lockfile for Editing*

---

**Description**

Open a project's lockfile (if any) for editing. After edit, if the lockfile edited is associated with the active project, any state-related changes (e.g. to R repositories) will be updated in the current session.

**Usage**

```
modify(project = NULL)
```

**Arguments**

**project** The project directory. If NULL, then the active project will be used. If no project is currently active, then the current working directory is used instead.

**Value**

The project directory, invisibly. Note that this function is normally called for its side effects.

**Examples**

```
## Not run:  
  
# modify an existing lockfile  
if (interactive())  
  renv::modify()  
  
## End(Not run)
```

---

paths *Path Customization*

---

### Description

Access the paths that renv uses for global state storage.

### Usage

paths

### Format

An object of class `list` of length 3.

### Details

By default, renv collects state into these folders:

| Platform | Location                           |
|----------|------------------------------------|
| Linux    | ~/local/share/renv                 |
| macOS    | ~/Library/Application Support/renv |
| Windows  | %LOCALAPPDATA%/renv                |

If desired, this path can be adjusted by setting the `RENV_PATHS_ROOT` environment variable. This can be useful if you'd like, for example, multiple users to be able to share a single global cache.

The various state sub-directories can also be individually adjusted, if so desired (e.g. you'd prefer to keep the cache of package installations on a separate volume). The various environment variables that can be set are enumerated below:

| Environment Variable            | Description   |
|---------------------------------|---|
| <code>RENV_PATHS_ROOT</code>    | The root path used for global state storage.  |
| <code>RENV_PATHS_LIBRARY</code> | The root path containing different R libraries.   |
| <code>RENV_PATHS_LOCAL</code>   | The path containing local package sources.  |
| <code>RENV_PATHS_SOURCE</code>  | The path containing downloaded package sources.   |
| <code>RENV_PATHS_BINARY</code>  | The path containing downloaded package binaries.  |
| <code>RENV_PATHS_CACHE</code>   | The path containing cached package installations.   |
| <code>RENV_PATHS_RTOOLS</code>  | (Windows only) The path to <b>Rtools</b> .  |
| <code>RENV_PATHS_EXTSOFT</code> | (Windows only) The path containing external software needed for compilation of Windows source p |

Note that renv will append platform-specific and version-specific entries to the set paths as appropriate. For example, if you have set:

```
Sys.setenv(RENV_PATHS_CACHE = "/mnt/shared/renv/cache")
```



then the directory used for the cache will still depend on the R version (e.g. 3.5) and the renv cache version (e.g. v2). For example:

```
/mnt/shared/renv/cache/R-3.5/v2
```

This ensures that you can set a single `RENV_PATHS_CACHE` environment variable globally without worry that it may cause collisions or errors if multiple versions of R needed to interact with the same cache.

If reproducibility of a project is desired on a particular machine, it is highly recommended that the renv cache of installed packages + binary packages is stored, so that packages can be easily restored in the future – installation of packages from source can often be arduous.

If you want these settings to persist in your project, it is recommended that you add these to an appropriate R startup file. For example, these could be set in:

- A project-local `.Renvi`;
- The user-level `.Renvi`;
- A file at `$(R RHOME)/etc/Renvi.site`.

Please see [?Startup](#) for more details.

## Local Sources

If your project depends on one or R packages that are not available in any remote location, you can still provide a locally-available tarball for renv to use during restore. By default, these packages should be made available in the folder as specified by the `RENV_PATHS_LOCAL` environment variable. The package sources should be placed in a file at one of these locations:

- `${RENV_PATHS_LOCAL}/<package>_<version>.<ext>`
- `${RENV_PATHS_LOCAL}/<package>/<package>_<version>.<ext>`
- `<project>/renv/local/<package>_<version>.<ext>`
- `<project>/renv/local/<package>/<package>_<version>.<ext>`

where `<ext>` is `.tar.gz` for source packages, or `.tgz` for binaries on macOS and `.zip` for binaries on Windows. During a `restore()`, packages installed from an unknown source will be searched for in this location.

## Projects

In order to determine whether a package can safely be removed from the cache, renv needs to know which projects are using packages from the cache. Since packages may be symlinked from the cache, and symlinks are by nature a one-way link, projects need to also report that they're using the renv cache.

To accomplish this, whenever renv is used with a project, it will record itself as being used within a file located at:

- `${RENV_PATHS_ROOT}/projects`

This file is list of projects currently using the renv cache. With this, renv can crawl projects registered with renv and use that to determine if any packages within the cache are no longer in use, and can be removed.

**Examples**

```
# get the path to the project library
path <- renv::paths$library()
```

---

|         |                                    |
|---------|------------------------------------|
| project | <i>Retrieve the Active Project</i> |
|---------|------------------------------------|

---

**Description**

Retrieve the path to the active project (if any).

**Usage**

```
project(default = NULL)
```

**Arguments**

default            The value to return when no project is currently active. Defaults to NULL.

**Value**

The active project directory, as a length-one character vector.

**Examples**

```
## Not run:

# get the currently-active renv project
renv::project()

## End(Not run)
```

---

|       |                                      |
|-------|--------------------------------------|
| purge | <i>Purge Packages from the Cache</i> |
|-------|--------------------------------------|

---

**Description**

Purge packages from the cache. This can be useful if a package which had previously been installed in the cache has become corrupted or unusable, and needs to be reinstalled.

**Usage**

```
purge(package, ..., version = NULL, hash = NULL, confirm = interactive())
```

### Arguments

|         |  |
|---------|--|
| package | A single package to be removed from the cache.   |
| ...     | Optional arguments; reserved for future expansion.   |
| version | The package version to be removed. When NULL, all versions of the requested package will be removed.                     |
| hash    | The specific hashes to be removed. When NULL, all hashes associated with a particular package's version will be removed. |
| confirm | Boolean; prompt the user before taking any action?   |

### Details

`purge()` is an inherently destructive option. It removes packages from the cache, and so any project which had symlinked that package into its own project library would find that package now unavailable. These projects would hence need to reinstall any purged packages. Take heed of this in case you're looking to purge the cache of a package which is difficult to install, or if the original sources for that package are no longer available!

### Value

The set of packages removed from the `renv` global cache, as a character vector of file paths.

### Examples

```
## Not run:  
  
# remove all versions of 'digest' from the cache  
renv::purge("digest")  
  
# remove only a particular version of 'digest' from the cache  
renv::purge("digest", version = "0.6.19")  
  
## End(Not run)
```

---

rebuild

*Rebuild the Packages in your Project Library*

---

### Description

Rebuild and reinstall packages in your library. This can be useful as a diagnostic tool – for example, if you find that one or more of your packages fail to load, and you want to ensure that you are starting from a clean slate.

## Usage

```
rebuild(  
  packages = NULL,  
  recursive = TRUE,  
  ...,  
  confirm = interactive(),  
  library = NULL,  
  project = NULL  
)
```

## Arguments

|           |  |
|-----------|--|
| packages  | The package(s) to be rebuilt. When NULL, all packages in the library will be installed.  |
| recursive | Boolean; should dependencies of packages be rebuilt recursively? Defaults to TRUE.   |
| ...       | Optional arguments; reserved for future expansion.   |
| confirm   | Boolean; prompt the user before taking any action?   |
| library   | The R library to be used. When NULL, the active project library will be used instead.  |
| project   | The project directory. If NULL, then the active project will be used. If no project is currently active, then the current working directory is used instead. |

## Details

Note that binaries will be used when appropriate and available for your platform. If you'd like to force packages to be rebuilt from sources, you can set `options(pkgType = "source")`.

## Value

A named list of package records which were installed by `renv`.

## Examples

```
## Not run:  
  
# rebuild the 'dplyr' package + all of its dependencies  
renv::rebuild("dplyr", recursive = TRUE)  
  
# rebuild only 'dplyr'  
renv::rebuild("dplyr", recursive = FALSE)  
  
## End(Not run)
```

---

`record`*Update Package Records in a Lockfile*

---

## Description

Use `record()` to record a new entry within an existing `renv` lockfile.

## Usage

```
record(records, lockfile = file.path(project, "renv.lock"), project = NULL)
```

## Arguments

|                       |  |
|-----------------------|--|
| <code>records</code>  | A list of named records, mapping package names to a definition of their source. See <b>Records</b> for more details.   |
| <code>lockfile</code> | The path to a lockfile. By default, the project lockfile is used.  |
| <code>project</code>  | The project directory. If <code>NULL</code> , then the active project will be used. If no project is currently active, then the current working directory is used instead. |

## Details

This function can be useful when you need to change one or more of the package records within an `renv` lockfile – for example, because a recorded package cannot be restored in a particular environment, and you know of a suitable alternative.

## Records

Records can be provided either using the **remotes** short-hand syntax, or by using an `R` list of entries to record within the lockfile. See `?lockfiles` for more information on the structure of a package record.

## Examples

```
## Not run:

# use digest 0.6.22 from package repositories -- different ways
# of specifying the remote. use whichever is most natural
renv::record("digest@0.6.22")
renv::record(list(digest = "0.6.22"))
renv::record(list(digest = "digest@0.6.22"))

# alternatively, provide a full record as a list
digest_record <- list(
  Package = "digest",
  Version = "0.6.22",
  Source = "Repository",
  Repository = "CRAN"
```

```
)  
renv::record(list(digest = digest_record))  
  
## End(Not run)
```

---

refresh

*Refresh the Local Cache of Available Packages*

---

### Description

Query the active R package repositories for available packages, and update the in-memory cache of those packages.

### Usage

```
refresh()
```

### Details

Note that R also maintains its own on-disk cache of available packages, which is used by `available.packages()`. Calling `refresh()` will force an update of both types of caches. `renv` prefers using an in-memory cache as on occasion the temporary directory can be slow to access (e.g. when it is a mounted network filesystem).

### Value

A list of package databases, invisibly – one for each repository currently active in the R session. Note that this function is normally called for its side effects.

### Examples

```
## Not run:  
  
# check available packages  
db <- available.packages()  
  
# wait some time (suppose packages are uploaded / changed in this time)  
Sys.sleep(5)  
  
# refresh the local available packages database  
# (the old locally cached db will be removed)  
db <- renv::refresh()  
  
## End(Not run)
```

---

`rehash`*Re-Hash Packages in the renv Cache*

---

**Description**

Re-hash packages in the renv cache, ensuring that any previously-cached packages are copied to a new cache location appropriate for this version of renv. This can be useful if the cache scheme has changed in a new version of renv, but you'd like to preserve your previously-cached packages.

**Usage**

```
rehash(confirm = interactive())
```

**Arguments**

`confirm` Boolean; prompt the user before taking any action?

**Details**

Any packages which are re-hashed will retain links to the location of the newly-hashed package, ensuring that prior installations of renv can still function as expected.

---

`remote`*Resolve a Remote*

---

**Description**

Given a remote specification, resolve it into an renv package record that can be used for download and installation (e.g. with [install](#)).

**Usage**

```
remote(spec)
```

**Arguments**

`spec` A remote specification.

---

|        |                        |
|--------|------------------------|
| remove | <i>Remove Packages</i> |
|--------|------------------------|

---

### Description

Remove (uninstall) R packages.

### Usage

```
remove(packages, ..., library = NULL, project = NULL)
```

### Arguments

|          |  |
|----------|--|
| packages | A character vector of R packages to remove.  |
| ...      | Optional arguments; reserved for future expansion.   |
| library  | The library from which packages should be removed. When NULL, the active library (that is, the first entry reported in <code>.libPaths()</code> ) is used instead. |
| project  | The project directory. If NULL, then the active project will be used. If no project is currently active, then the current working directory is used instead.       |

### Value

A vector of package records, describing the packages (if any) which were successfully removed.

### Examples

```
## Not run:

# disable automatic snapshots
auto.snapshot <- getOption("renv.config.auto.snapshot")
options(renv.config.auto.snapshot = FALSE)

# initialize a new project (with an empty R library)
renv::init(bare = TRUE)

# install digest 0.6.19
renv::install("digest@0.6.19")

# save library state to lockfile
renv::snapshot()

# remove digest from library
renv::remove("digest")

# check library status
renv::status()
```



```
# restore lockfile, thereby reinstalling digest 0.6.19
renv::restore()

# restore automatic snapshots
options(renv.config.auto.snapshot = auto.snapshot)

## End(Not run)
```

---

restore

*Restore a Project*


---

### Description

Restore a project's dependencies from a lockfile, as previously generated by `snapshot()`.

### Usage

```
restore(
  project = NULL,
  ...,
  library = NULL,
  lockfile = NULL,
  packages = NULL,
  repos = NULL,
  clean = FALSE,
  confirm = interactive()
)
```

### Arguments

|          |   |
|----------|---|
| project  | The project directory. If NULL, then the active project will be used. If no project is currently active, then the current working directory is used instead.  |
| ...      | Optional arguments; reserved for future expansion.  |
| library  | The library paths to be used during restore. See <b>Library</b> for details.  |
| lockfile | The lockfile to be used for restoration of the associated project. When NULL, the most recently generated lockfile for this project is used.  |
| packages | A subset of packages recorded in the lockfile to restore. When NULL (the default), all packages available in the lockfile will be restored. Any required recursive dependencies of the requested packages will be restored as well.   |
| repos    | The repositories to use during restore, for packages installed from CRAN or another similar R package repository. When set, this will override any repositories declared in the lockfile. See also the <code>repos.override</code> option in <code>config</code> for an alternate way to provide a repository override. |
| clean    | Boolean; remove packages not recorded in the lockfile from the target library? Use <code>clean = TRUE</code> if you'd like the library state to exactly reflect the lockfile contents after <code>restore()</code> .  |
| confirm  | Boolean; prompt the user before taking any action?  |

**Value**

A named list of package records which were installed by `renv`.

**Library**

When `renv::restore()` is called, packages from the lockfile are compared against packages currently installed in the library paths specified by `library`. Any packages which have changed will then be installed into the default library. If `clean = TRUE`, then packages that exist within the default library, but aren't recorded in the lockfile, will be removed as well.

**See Also**

Other reproducibility: [lockfiles](#), [snapshot\(\)](#)

**Examples**

```
## Not run:

# disable automatic snapshots
auto.snapshot <- getOption("renv.config.auto.snapshot")
options(renv.config.auto.snapshot = FALSE)

# initialize a new project (with an empty R library)
renv::init(bare = TRUE)

# install digest 0.6.19
renv::install("digest@0.6.19")

# save library state to lockfile
renv::snapshot()

# remove digest from library
renv::remove("digest")

# check library status
renv::status()

# restore lockfile, thereby reinstalling digest 0.6.19
renv::restore()

# restore automatic snapshots
options(renv.config.auto.snapshot = auto.snapshot)

## End(Not run)
```

---

|        |                        |
|--------|------------------------|
| revert | <i>Revert Lockfile</i> |
|--------|------------------------|

---

### Description

Revert the lockfile to its contents at a prior commit.

### Usage

```
revert(commit = "HEAD", ..., project = NULL)
```

### Arguments

|         |  |
|---------|--|
| commit  | The commit associated with a prior version of the lockfile.  |
| ...     | Optional arguments; currently unused.  |
| project | The project directory. If NULL, then the active project will be used. If no project is currently active, then the current working directory is used instead. |

### Details

The `revert()` function is currently only implemented for projects using `git` for version control.

### Value

The commit used when reverting `renv.lock`. Note that this function is normally called for its side effects.

### Examples

```
## Not run:  
  
# get history of previous versions of renv.lock in VCS  
db <- renv::history()  
  
# choose an older commit  
commit <- db$commit[5]  
  
# revert to that version of the lockfile  
renv::revert(commit = commit)  
  
## End(Not run)
```

---

|     |                     |
|-----|---------------------|
| run | <i>Run a Script</i> |
|-----|---------------------|

---

**Description**

Run an R script, in the context of a project using renv. The script will be run within an R subprocess.

**Usage**

```
run(script, ..., job = NULL, name = NULL, project = NULL)
```

**Arguments**

|         |  |
|---------|--|
| script  | The path to an R script.   |
| ...     | Optional arguments; reserved for future expansion.   |
| job     | Run the requested script as an RStudio job? Requires a recent version of both RStudio and the rstudioapi packages. When NULL, the script will be run as a job if possible, and as a regular R process launched by <code>system2()</code> if not. |
| name    | The name to associate with the job, for scripts run as a job.  |
| project | The path to the renv project. This project will be loaded before the requested script is executed. When NULL (the default), renv will automatically determine the project root for the associated script if possible.                            |

**Value**

The project directory, invisibly. Note that this function is normally called for its side effects.

---

|          |                         |
|----------|-------------------------|
| settings | <i>Project Settings</i> |
|----------|-------------------------|

---

**Description**

Define project-local settings that can be used to adjust the behavior of renv with your particular project.

**Usage**

```
settings
```

**Format**

An object of class `list` of length 5.

## Settings

`ignored.packages` A vector of packages, which should be ignored when attempting to snapshot the project's private library. Note that if a package has already been added to the lockfile, that entry in the lockfile will not be ignored.

`external.libraries` A vector of library paths, to be used in addition to the project's own private library. This can be useful if you have a package available for use in some global library, but for some reason `renv` is not able to install that package (e.g. sources or binaries for that package are not publicly available, or you have been unable to orchestrate the pre-requisites for installing some packages from source on your machine).

`snapshot.type` The type of snapshot to perform by default. See [snapshot](#) for more details.

`use.cache` Use a global cache of R packages. When active, `renv` will install packages into a global cache, and link packages from the cache into your `renv` projects as appropriate. This can greatly save on disk space and install time when for R packages which are used across multiple projects in the same environment.

`vcs.ignore.library` Set whether the `renv` project library is excluded from version control.

## Defaults

You can change the default values of these settings for newly-created `renv` projects by setting R options for `renv.settings` or `renv.settings.<name>`. For example:

```
options(renv.settings = list(snapshot.type = "simple"))
options(renv.settings.snapshot.type = "simple")
```

If both of the `renv.settings` and `renv.settings.<name>` options are set for a particular key, the option associated with `renv.settings.<name>` is used instead. We recommend setting these in an appropriate startup profile, e.g. `~/Rprofile` or similar.

## Examples

```
## Not run:

# view currently-ignored packaged
renv::settings$ignored.packages()

# ignore a set of packages
renv::settings$ignored.packages("devtools", persist = FALSE)

## End(Not run)
```

---

snapshot

*Snapshot a Project*

---

## Description

Call `snapshot()` to create a **lockfile** capturing the state of a project's R package dependencies. The lockfile can be used to later restore these project's dependencies as required. See the [lockfile](#) documentation for more details on the structure of a lockfile.

## Usage

```
snapshot(  
  project = NULL,  
  ...,  
  library = NULL,  
  lockfile = file.path(project, "renv.lock"),  
  type = settings$snapshot.type(project = project),  
  confirm = interactive(),  
  force = FALSE  
)
```

## Arguments

|                       |   |
|-----------------------|---|
| <code>project</code>  | The project directory. If <code>NULL</code> , then the active project will be used. If no project is currently active, then the current working directory is used instead.  |
| <code>...</code>      | Optional arguments; reserved for future expansion.  |
| <code>library</code>  | The R libraries to snapshot. When <code>NULL</code> , the active R libraries (as reported by <code>.libPaths()</code> ) are used.   |
| <code>lockfile</code> | The location where the generated lockfile should be written. By default, the lockfile is written to a file called <code>renv.lock</code> in the project directory. When <code>NULL</code> , the lockfile (as an R object) is returned directly instead. |
| <code>type</code>     | The type of snapshot to perform. See <b>Snapshot Type</b> for more details. When <code>NULL</code> (the default), a "packrat"-style snapshot is performed.  |
| <code>confirm</code>  | Boolean; prompt the user before taking any action?  |
| <code>force</code>    | Boolean; force generation of a lockfile even when preflight validation checks have failed?  |

## Value

The generated lockfile, as an R object (invisibly). Note that this function is normally called for its side effects.

## Snapshot Type

Depending on how you prefer to manage dependencies, you might prefer selecting a different snapshot mode. The modes available are as follows:

"simple" Capture all packages within the active R libraries in the lockfile. This is the quickest and simplest method, but may lead to undesired packages (e.g. development dependencies) entering the lockfile.

"packrat" Perform a Packrat-style snapshot. The intersection of packages discovered in your R libraries, alongside those discovered in your R code by `renv::dependencies()`, will enter the lockfile. This helps ensure that only the packages you are using will enter the lockfile, but may be slower if your project contains a large number of files. If this becomes an issue, you might consider using `.renvignore` files to limit which files `renv` uses for dependency discovery, or explicitly declaring your required dependencies in a `DESCRIPTION` file.

"custom" Like "packrat", but use a custom user-defined filter instead. The filter should be specified by the R option `renv.snapshot.filter`, and should either be a character vector naming a function (e.g. "package::method"), or be a function itself. The function should only accept one argument (the project directory), and should return a vector of package names to include in the lockfile.

By default, "packrat"-style snapshots are used. The snapshot type can be configured on a project-specific basis using the `renv` project [settings](#) mechanism.

## See Also

Other reproducibility: [lockfiles](#), [restore\(\)](#)

## Examples

```
## Not run:

# disable automatic snapshots
auto.snapshot <- getOption("renv.config.auto.snapshot")
options(renv.config.auto.snapshot = FALSE)

# initialize a new project (with an empty R library)
renv::init(bare = TRUE)

# install digest 0.6.19
renv::install("digest@0.6.19")

# save library state to lockfile
renv::snapshot()

# remove digest from library
renv::remove("digest")

# check library status
renv::status()
```

```
# restore lockfile, thereby reinstalling digest 0.6.19
renv::restore()

# restore automatic snapshots
options(renv.config.auto.snapshot = auto.snapshot)

## End(Not run)
```

---

status

*Status*

---

## Description

Report differences between the project's lockfile and the current state of the project's library (if any).

## Usage

```
status(project = NULL, ..., library = NULL, lockfile = NULL)
```

## Arguments

|          |  |
|----------|--|
| project  | The project directory. If NULL, then the active project will be used. If no project is currently active, then the current working directory is used instead. |
| ...      | Optional arguments; reserved for future expansion.   |
| library  | The library paths. By default, the library paths associated with the requested project are used.   |
| lockfile | The path to a lockfile. By default, the project lockfile (called <code>renv.lock</code> ) is used.   |

## Value

This function is normally called for its side effects.

## Examples

```
## Not run:

# disable automatic snapshots
auto.snapshot <- getOption("renv.config.auto.snapshot")
options(renv.config.auto.snapshot = FALSE)

# initialize a new project (with an empty R library)
renv::init(bare = TRUE)

# install digest 0.6.19
```



```
renv::install("digest@0.6.19")

# save library state to lockfile
renv::snapshot()

# remove digest from library
renv::remove("digest")

# check library status
renv::status()

# restore lockfile, thereby reinstalling digest 0.6.19
renv::restore()

# restore automatic snapshots
options(renv.config.auto.snapshot = auto.snapshot)

## End(Not run)
```

---

update

*Update Packages*

---

## Description

Update packages which are currently out-of-date. Currently, only CRAN and GitHub package sources are supported.

## Usage

```
update(
  packages = NULL,
  ...,
  library = NULL,
  rebuild = FALSE,
  check = FALSE,
  confirm = interactive(),
  project = NULL
)
```

## Arguments

|          |  |
|----------|--|
| packages | A character vector of R packages to update. When NULL, all packages within the required libraries will be updated. |
| ...      | Optional arguments; reserved for future expansion.   |
| library  | The R library to be used. When NULL, the active project library will be used instead.                              |

|         |  |
|---------|--|
| rebuild | Force packages to be rebuilt, thereby bypassing any installed versions of the package available in the cache? This can either be a boolean (indicating that the requested package(s) should be rebuilt), or a vector of package names indicating which packages should be rebuilt. |
| check   | Boolean; check for package updates without actually installing available updates?  |
| confirm | Boolean; prompt the user before taking any action?   |
| project | The project directory. If NULL, then the active project will be used. If no project is currently active, then the current working directory is used instead.   |

### Details

Updates will only be checked from the same source – for example, if a package was installed from GitHub, but a newer version is available on CRAN, that updated version will not be seen.

### Value

A named list of package records which were installed by renv.

### Examples

```
## Not run:

# update the 'dplyr' package
renv::update("dplyr")

## End(Not run)
```

---

upgrade

*Upgrade renv*

---

### Description

Upgrade the version of renv associated with a project.

### Usage

```
upgrade(project = NULL, version = NULL, reload = NULL, confirm = interactive())
```

### Arguments

|         |  |
|---------|--|
| project | The project directory. If NULL, then the active project will be used. If no project is currently active, then the current working directory is used instead. |
| version | The version of renv to be installed. By default, the latest version of renv as available on the active R package repositories is used.                       |

|         |   |
|---------|---|
| reload  | Boolean; reload renv after install? When NULL (the default), renv will be reloaded only if updating renv for the active project. Note that this may fail if you've loaded packages which also depend on renv. |
| confirm | Boolean; confirm upgrade before proceeding?   |

### Details

By default, this function will attempt to install the latest version of renv as available on the active R package repositories. If you'd instead like to try out a development version of renv, you can explicitly request a different version of renv and that version of the package will be downloaded and installed from GitHub. Use `version = "master"` to install the latest development version of renv, as from the renv project's [GitHub page](#).

### Value

A boolean value, indicating whether the requested version of renv was successfully installed. Note that this function is normally called for its side effects.

### Examples

```
## Not run:  
  
# upgrade to the latest version of renv  
renv::upgrade()  
  
# upgrade to the latest version of renv on GitHub (development version)  
renv::upgrade(version = "master")  
  
## End(Not run)
```

---

use\_python

*Use Python*

---

### Description

Associate a version of Python with your project.

### Usage

```
use_python(  
  python = NULL,  
  ...,  
  type = c("auto", "virtualenv", "conda", "system"),  
  name = NULL,  
  project = NULL  
)
```

**Arguments**

|         |   |
|---------|---|
| python  | The path to a Python binary. This can be the path to a Python binary on the system, or the path to a Python binary within an already-existing Python environment. If NULL, the RETICULATE_PYTHON environment variable is checked; if that is not set, then the default version of python on the PATH is used instead. As a special case, use_python(FALSE) can be used to deactivate Python integration with a project. |
| ...     | Optional arguments; currently unused.   |
| type    | The type of Python environment to use. When "auto" (the default), a project-local environment (virtual environments on Linux / macOS; conda environments on Windows) will be created. Ignored if the requested version of python lives within a pre-existing Python environment.  |
| name    | The name or path that should be used for the associated Python environment. If NULL and python points to a Python executable living within a pre-existing virtual environment, that environment will be used. Otherwise, a project-local environment will be created instead.   |
| project | The project directory. If NULL, then the active project will be used. If no project is currently active, then the current working directory is used instead.  |

**Details**

When Python integration is active, renv will:

- Save metadata about the requested version of Python in `renv.lock` – in particular, the Python version, and the Python type ("virtualenv", "conda", "system"),
- On load, set the RETICULATE\_PYTHON environment variable, so that the reticulate package can automatically use the requested copy of Python as appropriate,
- Capture the set of installed Python packages during `renv::snapshot()`,
- Reinstall the set of recorded Python packages during `renv::restore()`.

**Value**

TRUE, indicating that the requested version of Python has been successfully activated. Note that this function is normally called for its side effects.

**Examples**

```
## Not run:

# use python with a project
renv::use_python()

# use virtualenv python with a project
renv::use_python(type = "virtualenv")

# use conda python with a project
renv::use_python(type = "conda")
```

*use\_python*

45

## End(Not run)

# Index

## \*Topic **datasets**

- paths, [24](#)
- settings, [36](#)
- .expand\_R\_libs\_env\_var, [6](#)
  
- activate, [3](#), [9](#)
- activate(), [4](#), [15](#), [18](#)
  
- bootstrap, [4](#)
  
- clean, [5](#)
- config, [6](#), [33](#)
- consent, [8](#)
  
- deactivate, [3](#), [8](#)
- dependencies, [9](#)
- dependencies(), [13](#), [15](#)
- diagnostics, [11](#)
  
- equip, [11](#)
  
- history, [12](#)
- hydrate, [13](#)
  
- init, [14](#)
- init(), [4](#)
- install, [16](#), [31](#)
- isolate, [17](#)
  
- load, [18](#)
- lockfile, [19](#), [38](#)
- lockfiles, [19](#), [20](#), [34](#), [39](#)
  
- migrate, [22](#)
- modify, [23](#)
  
- paths, [8](#), [24](#)
- project, [26](#)
- purge, [26](#)
  
- rebuild, [27](#)
- record, [29](#)
  
- refresh, [30](#)
- rehash, [31](#)
- remote, [31](#)
- remove, [32](#)
- renv (renv-package), [2](#)
- renv-package, [2](#)
- restore, [6](#), [22](#), [33](#), [39](#)
- restore(), [17](#), [20](#)
- revert, [35](#)
- run, [36](#)
  
- settings, [7](#), [14](#), [36](#), [39](#)
- snapshot, [22](#), [34](#), [37](#), [38](#)
- snapshot(), [15](#), [20](#), [33](#)
- Startup, [25](#)
- status, [40](#)
- system2(), [36](#)
  
- update, [41](#)
- upgrade, [42](#)
- use\_python, [43](#)