

Package ‘rggobi’

July 7, 2018

Version 2.1.22

Title Interface Between R and 'GGobi'

Author Duncan Temple Lang <duncan@research.bell-labs.com>,
Debby Swayne <dfs@research.att.com>,
Hadley Wickham <h.wickham@gmail.com>,
Michael Lawrence <michafla@gene.com>

Maintainer Hadley Wickham <h.wickham@gmail.com>

Description A command-line interface to 'GGobi', an interactive and dynamic graphics package. 'Rggobi' complements the graphical user interface of 'GGobi' providing a way to fluidly transition between analysis and exploration, as well as automating common tasks.

Depends R (>= 2.5.1)

Suggests reshape, nlme

Imports RGtk2, utils

SystemRequirements GGobi

License BSD_3_clause + file LICENSE

LazyData true

Acknowledgments Di Cook, Nicholas Lewin-Koh, Xuejing Chen.

URL <https://github.com/ggobi/rggobi>, <http://www.ggobi.org/rggobi>

BugReports <https://github.com/ggobi/rggobi/issues>

NeedsCompilation yes

Repository CRAN

Date/Publication 2018-07-07 16:20:03 UTC

R topics documented:

"colorscheme<-"	3
"edges<-.GGobi"	3
"edges<-.GGobiData"	4
"edges<-.GGobiDisplay"	5

"excluded<-".GGobiData"	6
"glyph_colour<-".GGobiData"	6
"glyph_size<-".GGobiData"	7
"glyph_type<-".GGobiData"	8
"ids<-".GGobiData"	8
"shadowed<-".GGobiData"	9
"variables<-".GGobiDisplay"	10
"[.GGobi"	11
"[.GGobiData"	12
"[<-.GGobi"	13
.check_versions	13
close.GGobi	14
colorscheme	14
connecting_edges	15
dataset.GGobiDisplay	15
display.GGobiData	16
displays.GGobi	17
edges	18
excluded.GGobiData	18
ggobi.default	19
ggobi_count	20
ggobi_display_get_tour_projection	21
ggobi_display_save_picture	22
ggobi_display_set_tour_projection	22
ggobi_get	23
ggobi_longitudinal	24
ggobi_version	25
glyph_colour.GGobiData	25
glyph_size.GGobiData	26
glyph_type.GGobiData	27
ids.GGobiData	28
imode	28
names.GGobi	29
pmode	30
selected.GGobiData	30
shadowed.GGobiData	31
Storm tracks data	32
summary.GGobi	33
summary.GGobiData	33
variables.GGobiDisplay	34

"colorscheme<-" *Set active colour scheme.*

Description

Specify the active color scheme in a GGobi instance or the session options.

Usage

```
"colorscheme<-"(x, value)
```

Arguments

x	GGobi object
value	colour scheme to make active

Details

This makes a particular color scheme active within a GGobi instance.

Value

The name of the previously active color scheme.

Author(s)

Hadley Wickham <h.wickham@gmail.com>

Examples

```
if (interactive()) {  
  g <- ggobi(mtcars)  
  colorscheme(g) <- "Set1 8"  
  colorscheme(g) <- 1}  
}
```

"edges<- .GGobi" *Set edges*

Description

Create a new edges dataset and add to GGobi

Usage

```
## S3 replacement method for class 'GGobi'  
edges(x) <- value
```

Arguments

x	GGobi dataset
value	new edges

Details

@arguments GGobi dataset @arguments new edges

Author(s)

Hadley Wickham <h.wickham@gmail.com>

"edges<-.GGobiData" *Set edges*

Description

Set edges for a dataset.

Usage

```
## S3 replacement method for class 'GGobiData'
edges(x) <- value
```

Arguments

x	GGobiData
value	matrix, data frame, or graph containing of edges. First column should be from edge, second column to edge.

Details

In GGobi, and edge dataset is a special type of dataset that has two additional (hidden) columns which specification source and destination row names. These rownames are compared to the row names of the dataset in the current plot, and if any match, it is possible to specify this dataset as an edge set to the plotted dataset. When this is done, edges will be drawn between points specified by the edge dataset.

To remove edges, set edges to NULL.

Author(s)

Hadley Wickham <h.wickham@gmail.com>

See Also

[ggobi_longitudinal](#) for creating edges which simulate time series plots

Examples

```
if (interactive()) {
  cc<-cor(t(swiss),use="p", method="s")
  ccd<-sqrt(2*(1-cc))
  a <- which(lower.tri(ccd), arr.ind=TRUE)
  src <- row.names(swiss)[a[,2]]
  dest <- row.names(swiss)[a[,1]]
  weight <- as.vector(as.dist(ccd))
  gg <- ggobi(swiss)
  gg$cor <- data.frame(weight)
  edges(gg$cor) <- cbind(src, dest)
  edges(gg$cor)
  edges(gg$cor) <- NULL}
```

"edges<-.GGobiDisplay"

Set edges

Description

Set edges for a display

Usage

```
## S3 replacement method for class 'GGobiDisplay'
edges(x) <- value
```

Arguments

x	GGobiDisplay object
value	GGobiData object that contains edges

Details

This sets the dataset that a GGobiDisplay uses to display edges.

Author(s)

Hadley Wickham <h.wickham@gmail.com>

```
"excluded<-.GGobiData"
```

Set excluded status

Description

Set the exclusion status of points.

Usage

```
## S3 replacement method for class 'GGobiData'  
excluded(x) <- value
```

Arguments

x	GGobiData
value	logical vector

Details

If a point is excluded it is not drawn.

Author(s)

Hadley Wickham <h.wickham@gmail.com>

See Also

[excluded](#)

```
"glyph_colour<-.GGobiData"
```

Set glyph colour

Description

Set glyph colour

Usage

```
## S3 replacement method for class 'GGobiData'  
glyph_colour(x) <- value
```

Arguments

x	GGobiData
value	vector of new colours

Author(s)

Hadley Wickham <h.wickham@gmail.com>

See Also

[glyph_colour](#)

"glyph_size<-.GGobiData"
Set glyph size

Description

Set glyph size

Usage

```
## S3 replacement method for class 'GGobiData'  
glyph_size(x) <- value
```

Arguments

x	GGobiData
value	vector of new sizes

Details

Glyph size is an integer between 1 and 6.

Author(s)

Hadley Wickham <h.wickham@gmail.com>

See Also

[glyph_size](#)

```
"glyph_type<-GGobiData"
```

Set glyph type

Description

Set glyph type

Usage

```
## S3 replacement method for class 'GGobiData'  
glyph_type(x) <- value
```

Arguments

<code>x</code>	GGobiData
<code>value</code>	vector of new types

Author(s)

Hadley Wickham <h.wickham@gmail.com>

See Also

[glyph_type](#)

```
"ids<-GGobiData"
```

Set row ids

Description

Set row ids from a GGobiData

Usage

```
## S3 replacement method for class 'GGobiData'  
ids(x) <- value
```

Arguments

<code>x</code>	GGobiData
<code>value</code>	new values

Author(s)

Hadley Wickham <h.wickham@gmail.com>

See Also

[ids](#)

"shadowed<- .GGobiData"

Set shadowed status

Description

Set the exclusion status of points.

Usage

```
## S3 replacement method for class 'GGobiData'  
shadowed(x) <- value
```

Arguments

x	GGobiData
value	logical vector

Details

If a point is shadowed it is drawn in a dark gray colour, behind all non-shadowed points. It cannot be selected.

Author(s)

Hadley Wickham <h.wickham@gmail.com>

See Also

[shadowed](#)

```
"variables<-.GGobiDisplay"  
      Set display variables
```

Description

Set display variables with a list of x, y, and z component variable indices.

Usage

```
## S3 replacement method for class 'GGobiDisplay'  
variables(x) <- value
```

Arguments

x	GGobiDisplay object
value	list with X, Y and Z components listing the variable indices to display, either as numeric position or character variable name

Details

There are three types of variables in GGobi displays: x, y, z, which correspond to the labels on the toggle buttons in GGobi. Most plots have a constrained set of possible options. For example, in tours you can only set x variables, and you must have at least three. Or in the rotation plot, you need exactly one x, y, and z variable.

Currently, there is no checking done to ensure that you are sending a sensible set of variables for the given display type. Generally, any invalid choices will be silently ignored.

Author(s)

Hadley Wickham <h.wickham@gmail.com>

Examples

```
if (interactive()) {  
  g <- ggobi(mtcars)  
  d <- display(g[1], "Parallel Coordinates Display")  
  variables(d)  
  variables(d) <- list(X=1:8)  
  variables(d) <- list(X=c("mpg", "cyl"))  
  variables(d)}
```

"[.GGobi" *Get ggobi data.*

Description

Conveniently retrieve ggobi dataset.

Usage

```
## S3 method for class 'GGobi'  
x[i, ..., drop=TRUE]
```

Arguments

x	GGobi object
i	name of dataset to retrieve
...	ignored
drop	if TRUE, return vector is possible

Details

It is convenient to be able to refer to and operate on a ggobi dataset as if it were a regular R dataset. This function allows one to get an GGobiData object that represents a particular dataset.

Author(s)

Hadley Wickham <h.wickham@gmail.com>

Examples

```
if (interactive()) {  
  g <- ggobi(ChickWeight)  
  g["cars"] <- mtcars  
  g[1:2]  
  g["ChickWeight"]  
  g["cars"]  
  g$cars}  
}
```

"[.GGobiData"] *Subsetting*

Description

Subsetting for ggobi datasets

Usage

```
## S3 method for class 'GGobiData'  
x[i, j, drop=FALSE]
```

Arguments

x	ggobi dataset
i	rows
j	cols
drop	drop dimensions?

Details

This functions allow one to treat a ggobi dataset as if it were a local data.frame. One can extract and assign elements within the dataset.

This method works by retrieving the entire dataset into R, and then subsetting with R.

Value

desired subset from data.frame

Author(s)

Hadley Wickham <h.wickham@gmail.com>

Examples

```
if (interactive()) {  
  
  g <- ggobi(mtcars)  
  x <- g$mtcars  
  x[1:5, 1:5]  
  x[[1]]  
  x$cy1}  
}
```

```
"[-.GGobi"      [-.GGobi
```

Description

Add data to ggobi instance.

Usage

```
## S3 replacement method for class 'GGobi'
x[i] <- value
```

Arguments

x	ggobi instance
i	name of data frame
value	data.frame, or string to path of file to load

Details

This function allows you to add (and eventually) replace GGobiData objects in a GGobi instance.

Author(s)

Hadley Wickham <h.wickham@gmail.com>

Examples

```
if (interactive()) {
  g <- ggobi()
  g["a"] <- mtcars
  g$b <- mtcars}
```

```
.check_versions      check that rggobi and GGobi by major:minor versions are the same
```

Description

to ensure binary compatibility

Usage

```
.check_versions()
```

Author(s)

Hadley Wickham <h.wickham@gmail.com>

close.GGobi *Close GGobi instance*

Description

Terminates and discards a ggobi instance

Usage

```
## S3 method for class 'GGobi'  
close(con, ...)
```

Arguments

con ggobi object to close
... ignored and for compatability generic function.

Details

This allows the caller to close a ggobi instance and discard the resources it uses. The function closes the display windows and variable panel window associated with this ggobi instance. It also resets the default ggobi instance to be the last one created.

Author(s)

Hadley Wickham <h.wickham@gmail.com>

Examples

```
if (interactive()) {  
  g1 <- ggobi(mtcars)  
  g2 <- ggobi(mtcars)  
  close(g2)  
  close(ggobi_get())}
```

colorscheme *Get active colour scheme*

Description

Get name of the active colour scheme

Usage

```
colorscheme(x)
```

Arguments

x GGobi object

Author(s)

Hadley Wickham <h.wickham@gmail.com>

Examples

```
if (interactive()) {  
  g <- ggobi(mtcars)  
  colorscheme(g)}
```

connecting_edges *Get connecting edges*

Description

Get actual edges from application of edges dataset to target dataset.

Usage

```
connecting_edges(x, y)
```

Arguments

x target ggobi dataset
y ggobi dataset containing edges

Author(s)

Hadley Wickham <h.wickham@gmail.com>

dataset.GGobiDisplay *Get display dataset*

Description

Returns a link to the GGobiData (dataset) object associated with this display.

Usage

```
## S3 method for class 'GGobiDisplay'  
dataset(x, .gobi=ggobi(x))
```

Arguments

x	GGobiDisplay object
.gobi	ggobi reference

Details

See [\[.GGobi\]](#) for more information on

Author(s)

Hadley Wickham <h.wickham@gmail.com>

Examples

```
if (interactive()) {
  g <- ggobi(mtcars)
  d <- displays(g)[[1]]
  dataset(d)}
```

display.GGobiData	<i>Create a new display</i>
-------------------	-----------------------------

Description

Create a new display for the GGobiData object.

Usage

```
## S3 method for class 'GGobiData'
display(x, pmode="Scatterplot Display", vars=list(X=names(x)), embed=FALSE, ...)
```

Arguments

x	GGobiData object
pmode	projection mode to use
vars	variables to display, see variables.GGobiDisplay for details
embed	If TRUE, returns widget for use with RGtk2
...	ignored

Details

This function allows you to create a new display from a GGobiData object. You will need to specify the type of display you want ("Scatterplot Display", "Scatterplot Matrix" and "Parallel Coordinates Display" are the most common), and which variables the plot should be initialised with. Specifying more than two variables only makes sense for scatterplot matrices and pcps.

Many of the plots used in GGobi (eg. the tours and densities plots) are special modes of the scatterplot display. You will need to create a new scatterplot display, change the projection mode to what you want, and then set the variables. Hopefully this will be improved in a future version of rggobi.

Author(s)

Hadley Wickham <h.wickham@gmail.com>

See Also

[ggobi_display_types](#) for a list of display types

Examples

```
if (interactive()) {
  g <- ggobi(mtcars)
  display(g[1])
  display(g[1], vars=list(X=4, Y=5))
  display(g[1], vars=list(X="drat", Y="hp"))
  display(g[1], "Parallel Coordinates Display")
}
## Not run:
display(g[1], "2D Tour")
display(g[1], "2x1D Tour", list(X=c(1,2,3), Y=c(4,5,6)))
display(g[1], "Scatterplot Matrix")
## End(Not run)
```

displays.GGobi

Get GGobi displays

Description

Gets list of displays in the specified GGobi instance

Usage

```
## S3 method for class 'GGobi'
displays(x)
```

Arguments

x GGobi object

Details

A display basically corresponds to a window in GGobi. A display may contain multiple plots within it. For example, the scatterplot matrix contains $p * p$ plots.

Use this function to obtain a reference to a display (they are numbered in the order they are created) so you can change display mode, set variables ([variables<- .GGobiDisplay](#)), or save a static image to disk.

Author(s)

Hadley Wickham <h.wickham@gmail.com>

See Also

[display](#) to create displays

Examples

```
if (interactive()) {  
  g <- ggobi(mtcars)  
  displays(g)  
  display(g[1])  
  displays(g)}
```

edges	<i>Get edges</i>
-------	------------------

Description

Get edges for a dataset

Usage

```
edges(x)
```

Arguments

x ggobi dataset

Value

A matrix of edge pairs

Author(s)

Hadley Wickham <h.wickham@gmail.com>

excluded.GGobiData	<i>Get excluded status</i>
--------------------	----------------------------

Description

Get the exclusion status of points.

Usage

```
## S3 method for class 'GGobiData'  
excluded(x)
```

Arguments

x ggobiDataget

Details

If a point is excluded it is not drawn.

Author(s)

Hadley Wickham <h.wickham@gmail.com>

See Also

[excluded<-](#)

ggobi.default

New ggobi

Description

Creates a new ggobi instance

Usage

```
## Default S3 method:
ggobi(data, args=character(0), mode=character(0), name = deparse(sys.call()[[2]]), ...)
```

Arguments

data	the name of a file containing the data, or a data frame or matrix containing the values
args	a character vector of command-line arguments
mode	data format GGobi should expect to read the data from, if reading from a file.
name	the name to use in GGobi for the dataset, if one is specified
...	ignored

Details

This function creates a new instance of GGobi with or without new data. Use this function whenever you want to create a new GGobi independent of the others—they will not share linked plots. If you want to add another dataset to an existing ggobi, please see [\[<- .GGobi](#)

There are currently three basic types of functions that you can use with rggobi:

- Data getting and setting: see [\[.GGobi](#), and [\[.GGobiData](#)
- "Automatic" brushing: see [glyph_colour](#), [glyph_size](#), [glyph_type](#), [shadowed](#), [excluded](#), and the associated setter functions.

- Edge modification: see [edges](#), [edges<-](#), [ggobi_longitudinal](#)

You will generally spend most of your time working with ggobdatas, you retrieve using `$.GGobiData`, `[.GGobiData`, or `[[.GGobiData`. Most of the time these will operate like normal R datasets while pointing to the data in GGobi so that all changes are kept in sync. If you need to force a ggobiDataset to be an R data.frame use `as.data.frame`.

Value

A ggobi object

Author(s)

Hadley Wickham <h.wickham@gmail.com>

Examples

```
if (interactive()) {
  ggobi(ggobi_find_file("data", "flea.csv"))
  ggobi(ggobi_find_file("data", "flea.xml"))
  ggobi(mtcars)
  mtcarsg <- ggobi_get()$mtcars
  glyph_colour(mtcarsg)
  glyph_colour(mtcarsg) <- ifelse(mtcarsg$cyl < 4, 1, 2)
  glyph_size(mtcarsg) <- mtcarsg$cyl}

```

ggobi_count

Get number of GGobis

Description

Retrieves the number of ggobi instances within this session

Usage

```
ggobi_count()
```

Details

One or more ggobi instances can be created within an R session so that one can simultaneously look at different datasets or have different views of the same dataset. This function returns the number of ggobis in existence.

The different ggobi instances are maintained as C level structures. This function accesses a variable that stores how many are in existence when the function is invoked.

Author(s)

Hadley Wickham <h.wickham@gmail.com>

Examples

```
if (interactive()) {  
  ggobi_count()  
}
```

```
ggobi_display_get_tour_projection  
  Get tour projection
```

Description

Get the tour projection from a GGobi tour.

Usage

```
ggobi_display_get_tour_projection(gd)
```

Arguments

gd GGobiDisplay object running tour

Details

This function retrieves the current projection matrix from a paused tour. (The tour must be paused so that R can run commands).

This can be used to record interesting projections of your data for later analysis.

Author(s)

Hadley Wickham <h.wickham@gmail.com>

Examples

```
if (interactive()) {  
  g <- ggobi(mtcars)  
  d <- displays(g)[[1]]  
}  
## Not run:  
pmode(d) <- "2D Tour"  
ggobi_display_get_tour_projection(d)  
variables(d) <- list(X=names(mtcars))  
ggobi_display_get_tour_projection(d)  
MASS::eqscplot(as.matrix(mtcars) %*% ggobi_display_get_tour_projection(d))  
  
## End(Not run)
```

`ggobi_display_save_picture`*Save picture of plot (and window) to disk*

Description

This allows you to make a static copy of a GGobiDisplay.

Usage

```
ggobi_display_save_picture(display=displays(ggobi_get())[1]),  
  path="ggobi_display.png", filetype="png", plot.only = FALSE)
```

Arguments

<code>display</code>	GGobiDisplay to save
<code>path</code>	path to save to
<code>filetype</code>	type of file to save
<code>plot.only</code>	if TRUE, save only plot, otherwise save surrounding GUI elements as well

Details

If you want to make publication quality graphics, you should probably use the DescribeDisplay plugin and package. This will recreate a GGobiDisplay in R, and so can produce high-quality vector (eg. pdf) output. See <http://www.ggobi.org/describe-display> for more information

Author(s)

Hadley Wickham <h.wickham@gmail.com>

`ggobi_display_set_tour_projection`*Set tour projection*

Description

Set the tour projection from a GGobi tour.

Usage

```
ggobi_display_set_tour_projection(gd, value)
```

Arguments

<code>gd</code>	GGobiDisplay object running tour
<code>value</code>	tour projection

Details

If you know the projection you would like to see in the tour, you can use this function to set it. The example illustrates setting the projection to show the first two principle components.

Author(s)

Hadley Wickham <h.wickham@gmail.com>

Examples

```
if (interactive()) {
  g <- ggobi(mtcars)
  d <- displays(g)[[1]]
}
## Not run:
pmode(d) <- "2D Tour"
variables(d) <- list(X=names(mtcars))
ggobi_display_get_tour_projection(d)
pc <- princomp(as.matrix(mtcars))$loadings[,1:2]
ggobi_display_set_tour_projection(d, pc)
pc <- princomp(as.matrix(mtcars), cor=T)$loadings
ggobi_display_set_tour_projection(d, pc)[,1:2]

## End(Not run)
```

ggobi_get

Get GGobi

Description

Returns a ggobi reference

Usage

```
ggobi_get(id = ggobi_count(), drop=TRUE)
```

Arguments

id	numeric vector indicating which ggobi instances to retrieve. Use default if none specified
drop	drop if possible?

Details

This allows one to get a list of all the ggobi instances currently in existence in the R session. Also, one can fetch particular instances.

Author(s)

Hadley Wickham <h.wickham@gmail.com>

Examples

```
if (interactive()) {  
  ggobi(mtcars)  
  ggobi(Nile)  
  ggobi_get(1)  
  ggobi_get(1:2)}
```

ggobi_longitudinal *Create longitudinal dataset.*

Description

Instantiate new ggobi with a longitudinal data set.

Usage

```
ggobi_longitudinal(data, time=1:rows, id=rep(1, rows), g = NULL)
```

Arguments

data	data frame
time	time variable
id	id variable
g	ggobi instance, if you don't want to create a new one

Details

This function allows you to load longitudinal data in to GGobi and display it as a line plot. This is achieved by creating edges between adjacent time points, for a given id variable.

For best viewing, we recommend that you turn the show points off in the options menu. When brushing, you may also want to use categorical brushing on the id variable, so that the entire series is selected for an observation.

Author(s)

Hadley Wickham <h.wickham@gmail.com>

Examples

```
data(Oxboys, package="nlme")  
if (interactive()) {  
  ggobi_longitudinal(Oxboys, Occasion, Subject)  
  ggobi_longitudinal(stormtracks, seasday, id)  
  ggobi_longitudinal(data.frame(x=1:100, y=sin(1:100)))}
```

ggobi_version	<i>Get version</i>
---------------	--------------------

Description

GGobi version information

Usage

```
ggobi_version()
```

Details

Return an object that describes the version of the ggobi library being used. This allows code to execute conditionally on certain version numbers, etc.

Value

date	the release date of the ggobi library
version	a vector of 3 integers containing the major, minor and patch-level numbers.
versionstring	a string version of the major, minor and patch-level numbers,

Author(s)

Hadley Wickham <h.wickham@gmail.com>

Examples

```
ggobi_version()
```

glyph_colour.GGobiData	<i>Get glyph colour</i>
------------------------	-------------------------

Description

Get glyph colour

Usage

```
## S3 method for class 'GGobiData'  
glyph_colour(x)
```

Arguments

x	GGobiData
---	-----------

Author(s)

Hadley Wickham <h.wickham@gmail.com>

See Also

[glyph_colour<-](#)

glyph_size.GGobiData *Get glyph size*

Description

Get glyph size

Usage

```
## S3 method for class 'GGobiData'  
glyph_size(x)
```

Arguments

x GGobiData

Details

Glyph size is an integer between 1 and 6.

Author(s)

Hadley Wickham <h.wickham@gmail.com>

See Also

[glyph_size<-](#)

glyph_type.GGobiData *Get glyph type.*

Description

Get glyph type.

Usage

```
## S3 method for class 'GGobiData'  
glyph_type(x)
```

Arguments

x GGobiData

Details

Glyph type refers to the shape of the glyph, one of:

- a filled circle
- an empty circle
- a filled square
- an empty square
- a single pixel
- a plus sign
- a cross

Author(s)

Hadley Wickham <h.wickham@gmail.com>

See Also

[glyph_type<-](#)

ids.GGobiData	<i>Row ids</i>
---------------	----------------

Description

Retrive row ids from a GGobiData

Usage

```
## S3 method for class 'GGobiData'  
ids(x)
```

Arguments

x GGobiData

Author(s)

Hadley Wickham <h.wickham@gmail.com>

See Also

[ids<-](#)

imode	<i>Interaction mode</i>
-------	-------------------------

Description

Functions to get and set interaction mode

Usage

```
imode(x)
```

Arguments

x GGobiDisplay object

Details

In GGobi, the interaction mode determines the how you interact with a plot: brushing, identify etc. Each projection mode also has a default interaction mode that allows you to select variables and control other parameters of the display

You can see the list of available interaction modes using the [imodes](#) function. This accepts either a GGobiDisplay, or the name of the display type.

Author(s)

Hadley Wickham <h.wickham@gmail.com>

Examples

```
if (interactive()) {  
  g <- ggobi(mtcars)  
  d <- displays(g)[[1]]  
  imode(d)  
  imodes(d)  
  imode(d) <- "Brush"}  

```

names.GGobi

GGobi names

Description

Get dataset names

Usage

```
## S3 method for class 'GGobi'  
names(x)
```

Arguments

x ggobi instance

Author(s)

Hadley Wickham <h.wickham@gmail.com>

Examples

```
if (interactive()) {  
  g <- ggobi(mtcars)  
  names(g)}  

```

`pmode` *Projection mode*

Description

Functions to get and set projection mode

Usage

```
pmode(x)
```

Arguments

`x` GGobiDisplay object

Details

In GGobi, the projection mode determines the type of plot that is displayed. For example, a 1D ASH plot, or a 2D tour.

You can see the list of available projection modes using the `pmodes` function. This accepts either a GGobiDisplay, or the name of the display type.

Author(s)

Hadley Wickham <h.wickham@gmail.com>

Examples

```
if (interactive()) {
  g <- ggobi(mtcars)
  d <- displays(g)[[1]]
  pmode(d)
  pmodes(d)
  pmode(d) <- "1D Plot"}
```

`selected.GGobiData` *Get selection status*

Description

Returns logical vector indicating if each point is under the brush

Usage

```
## S3 method for class 'GGobiData'
selected(x)
```

Arguments

x GGobiData
 logical vector

Author(s)

Hadley Wickham <h.wickham@gmail.com>

shadowed.GGobiData *Get shadowed status*

Description

Get the exclusion status of points.

Usage

```
## S3 method for class 'GGobiData'  
shadowed(x)
```

Arguments

x ggobiDataget

Details

If a point is shadowed it is drawn in a dark gray colour, behind all non-shadowed points. It cannot be selected.

Author(s)

Hadley Wickham <h.wickham@gmail.com>

See Also

[shadowed<-](#)

Storm tracks data *Storm tracks in the Caribbean*

Description

The data consist of tropical cyclone tracks through the Atlantic Ocean, Caribbean Sea and Gulf of Mexico from 1995 to 2005. Only “named” storms, those which reached tropical storm status or stronger, are included.

The data originated from the National Hurricane Center’s archive of Tropical Cyclone Reports (<http://www.nhc.noaa.gov/pastall.shtml>). From the NHC, the reports "contain comprehensive information on each tropical cyclone, including synoptic history, meteorological statistics, casualties and damages, and the post-analysis best track (six-hourly positions and intensities)."

This dataset is taken from the post-analysis best track information, which are presented in tabular form in the Tropical Cyclone Reports and came in a variety of electronic formats (PDF, HTML and Microsoft Word documents). The best track tables were then copied to text files and parsed into the comma-separated format in which they currently reside.

The variables are as follows:

- Name: Storm Name
- Year: Year of report
- Month: Month of report
- Day: Day of report (day of the month)
- Hour: Hour of report (0, 6, 12 or 18 in UTC time)
- Latitude: Latitude of the storm’s center (degrees North)
- Longitude: Longitude of the storm’s center (degrees West)
- Pressure: Air pressure at the storm’s center (millibars)
- Wind: Storm’s maximum sustained wind speed (knots or nautical miles per hour)
- Type: Storm classification (Tropical Depression, Tropical Storm, Hurricane, Extratropical)
- SeasDay: Day of the hurricane season (days since June 1)

The Tropical Cyclone Reports had a variety of storm type designations and there appeared to be no consistent naming convention for cyclones that were not hurricanes, tropical depressions, or tropical storms. Many of these designations have been combined into the "Extratropical" category in this dataset.

This data was put together by Jon Hobbs, a PhD student at Iowa State. Thanks Jon!

Usage

```
data(stormtracks)
```

Format

A data frame with 5519 rows and 24 variables

summary.GGobi	<i>GGobi summary</i>
---------------	----------------------

Description

Get a description of the global state of the GGobi session.

Usage

```
## S3 method for class 'GGobi'  
summary(object, ...)
```

Arguments

object	ggobi object
...	ignored

Author(s)

Hadley Wickham <h.wickham@gmail.com>

Examples

```
if (interactive()) {  
  g <- ggobi(mtcars)  
  summary(g)}  
}
```

summary.GGobiData	<i>Summarise GGobiData.</i>
-------------------	-----------------------------

Description

Summarise a GGobiData with dimensions, mode and variable names.

Usage

```
## S3 method for class 'GGobiData'  
summary(object, ...)
```

Arguments

object	GGobiData
...	ignored

Author(s)

Hadley Wickham <h.wickham@gmail.com>

variables.GGobiDisplay

Get display variables

Description

List the variables used in a given display

Usage

```
## S3 method for class 'GGobiDisplay'  
variables(x)
```

Arguments

x GGobiDisplay object

Details

There are three types of variables in GGobi displays: X, Y, Z, which correspond to the labels on the toggle buttons in GGobi. Most plots have a constrained set of possible options. For example, in tours you can only set X variables, and you must have at least three. Or in the rotation plot, you need exactly one X, Y, and Z variable. You can figure out what these conditions are by using the toggle buttons in GGobi.

Author(s)

Hadley Wickham <h.wickham@gmail.com>

See Also

[variables<- .GGobiDisplay](#) for examples

Index

- *Topic **attribute**
 - summary.GGobiData, 33
- *Topic **color**
 - colorscheme, 14
- *Topic **datasets**
 - Storm tracks data, 32
- *Topic **dynamic**
 - close.GGobi, 14
 - display.GGobiData, 16
 - displays.GGobi, 17
 - excluded.GGobiData, 18
 - ggobi.default, 19
 - ggobi_count, 20
 - ggobi_display_get_tour_projection, 21
 - ggobi_display_set_tour_projection, 22
 - ggobi_get, 23
 - ggobi_longitudinal, 24
 - ggobi_version, 25
 - glyph_colour.GGobiData, 25
 - glyph_size.GGobiData, 26
 - glyph_type.GGobiData, 27
 - imode, 28
 - names.GGobi, 29
 - pmode, 30
 - selected.GGobiData, 30
 - shadowed.GGobiData, 31
 - summary.GGobi, 33
 - variables.GGobiDisplay, 34
- *Topic **hplot**
 - ggobi_display_save_picture, 22
- *Topic **manip**
 - connecting_edges, 15
 - dataset.GGobiDisplay, 15
 - edges, 18
 - ids.GGobiData, 28
 - .check_versions, 13
 - [.GGobi, 16, 19
 - [.GGobiData, 19, 20
 - [[.GGobiData, 20
 - \$.GGobiData, 20
 - as.data.frame, 20
 - close.GGobi, 14
 - colorscheme, 14
 - connecting_edges, 15
 - dataset.GGobiDisplay, 15
 - display, 18
 - display.GGobiData, 16
 - displays.GGobi, 17
 - edges, 18, 20
 - excluded, 6, 19
 - excluded.GGobiData, 18
 - ggobi (ggobi.default), 19
 - ggobi.default, 19
 - ggobi_count, 20
 - ggobi_display_get_tour_projection, 21
 - ggobi_display_save_picture, 22
 - ggobi_display_set_tour_projection, 22
 - ggobi_display_types, 17
 - ggobi_get, 23
 - ggobi_longitudinal, 4, 20, 24
 - ggobi_version, 25
 - glyph_color (glyph_colour.GGobiData), 25
 - glyph_colour, 7, 19
 - glyph_colour (glyph_colour.GGobiData), 25
 - glyph_colour.GGobiData, 25
 - glyph_size, 7, 19
 - glyph_size (glyph_size.GGobiData), 26
 - glyph_size.GGobiData, 26
 - glyph_type, 8, 19
 - glyph_type (glyph_type.GGobiData), 27
 - glyph_type.GGobiData, 27

ids, [9](#)
ids (ids.GGobiData), [28](#)
ids.GGobiData, [28](#)
imode, [28](#)
imode<- (imode), [28](#)
imodes, [28](#)

names.GGobi, [29](#)

pmode, [30](#)
pmode<- (pmode), [30](#)
pmodes, [30](#)

rggobi (ggobi.default), [19](#)

selected (selected.GGobiData), [30](#)
selected.GGobiData, [30](#)
shadowed, [9](#), [19](#)
shadowed (shadowed.GGobiData), [31](#)
shadowed.GGobiData, [31](#)
Storm tracks data, [32](#)
stormtracks (Storm tracks data), [32](#)
summary.GGobi, [33](#)
summary.GGobiData, [33](#)

variables.GGobiDisplay, [16](#), [34](#)