

Package ‘rsleep’

July 28, 2019

Type Package

Title Analysis of Sleep Data

Version 1.0.1

Author Paul Bouchequet <paul.bouchequet@frenchkpi.com>

Maintainer Paul Bouchequet <paul.bouchequet@frenchkpi.com>

Description Provides users functions for sleep data management and analysis such as European Data Format (EDF) to Morpheo Data Format (MDF) conversion: P.Bouchequet, D.Jin, G.Solelhac, M.Chennaoui, D.Leger (2018) <doi:10.1016/j.msom.2018.01.130> ``Morpheo Data Format (MDF), un nouveau format de donnees simple, robuste et performant pour stocker et analyser les enregistrements de sommeil''. Provides hypnogram statistics computing and visualisation functions from the American Academy of Sleep Medicine (AASM) manual ``The AASM Manual for the Scoring of Sleep and Associated Events" <<https://aasm.org/clinical-resources/scoring-manual/>>.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Imports edfReader, jsonlite, ggplot2, signal, phonTools

Suggests testthat

RoxygenNote 6.1.1

NeedsCompilation no

Depends R (>= 3.5.0)

Repository CRAN

Date/Publication 2019-07-28 11:10:02 UTC

R topics documented:

bands_power	2
check_events	2
detect_rpeaks	3
epochs	4
example_ecg_200hz	4

example_hypnogram_30s	5
hypnogram	5
normalize_cycles	6
plot_hypnogram	6
read_events_noxturnal	7
read_mdf	8
spectrogram	9
stages_stats	10
write_channel	10
write_mdf	11

bands_power	<i>Computes spectral power of bands listed in the bands argument.</i>
-------------	---

Description

‘bands_power‘ calculates power spectral densities estimates using Welch’s method on bands. Bands are computed from spectrogram bands equal or greater than lower limit and inferior to the upper limit.

Usage

```
bands_power(bands, signal, sRate, broadband = c(0.5, 40))
```

Arguments

bands	A list of bands to compute with lower and upper limits in the form ‘list(c(0,4),c(4,8))‘
signal	Numerical vector of the signal.
sRate	Signal sample rate in Hertz.
broadband	The broadband to normalize by.

Value

A list of bands powers.

Examples

```
bands_power(bands = list(c(0,4),c(4,8)), signal = sin(c(1:10000)), sRate = 200)
```

check_events	<i>Check events dataframe.</i>
--------------	--------------------------------

Description

Check events dataframe.

Usage

```
check_events(e)
```

Arguments

e	Events dataframe. Dataframe must have begin (POSIXt), end (POSIXt) and event (character) columns.
---	---

detect_rpeaks	<i>Detects R peaks in raw ECG signal.</i>
---------------	---

Description

Implements the first part of the Pan & Tompkins algorithms to detect R peaks from a raw ECG signal. Inspiration from <https://zenodo.org/record/826614>.

Usage

```
detect_rpeaks(signal, sRate, lowcut = 0, highcut = 15,
              filter_order = 1, integration_window = 15, refractory = 200)
```

Arguments

signal	Numerical vector of ECG signal.
sRate	ECG signal sample rate.
lowcut	Butterworth bandpass filter low cut value.
highcut	Butterworth bandpass filter high cut value.
filter_order	Butterworth bandpass filter order value.
integration_window	Convolution window size.
refractory	Minimal space between peaks in milliseconds.

Value

A vector of each detected R peaks in seconds from the start.

References

Pan, Jiapu, and Willis J. Tompkins. "A real-time QRS detection algorithm." IEEE Trans. Biomed. Eng 32, no. 3 (1985): 230-236.

Examples

```
data("example_ecg_200hz")
detect_rpeaks(example_ecg_200hz, 200)
```

epochs	<i>Split signals into a list of epochs according to an events dataframe or an epoch duration.</i>
--------	---

Description

Split signals into a list of epochs according to an events dataframe or an epoch duration.

Usage

```
epochs(signals, sRates, resample = 100, epoch = 30, startTime = 0)
```

Arguments

signals	A list of numeric vectors containing signals.
sRates	A vector or list of integer values of the signals sample rates.
resample	The sample rate to resample all signals. Defaults to 100.
epoch	Epochs reference. Can be an events dataframe or the number of seconds of each epoch. Defaults to 30.
startTime	The start timestamp of the signal, used to join events to epoch.

Value

A list of signal chunks

Examples

```
epochs(list(c(1:1000), c(1:1000)), 100, 2)
```

example_ecg_200hz *Sample electrocardiogram signal*

Description

10 seconds of ECG from Resmed Nox A1 polysomnograph sampled at 200 Hz expressed in Volts.

Usage

```
example_ecg_200hz
```

Format

A vector of 2000 values.

Source

```
http://www.sommeil-vigilance.fr/
```

example_hypnogram_30s
Example hypnogram scored on 30 seconds.

Description

Example hypnogram scored on 30 seconds.

Usage

```
example_hypnogram_30s
```

Format

Dataframe

Source

```
http://cloud.frenchkpi.com/s/wreGqkitWNnWwnP/download
```

hypnogram	<i>Filter and reorder an events dataframe to keep only sleep stages related-events.</i>
-----------	---

Description

Remove non-sleep stages events and reorder dataframe rows using the `begin` column.

Usage

```
hypnogram(events, labels = c("N3", "N2", "N1", "REM", "AWA"))
```

Arguments

<code>events</code>	Events dataframe. Dataframe must have <code>begin</code> (POSIXt), <code>end</code> (POSIXt) and <code>event</code>
<code>labels</code>	Sleep stages labels. Defaults to <code>c("N3", "N2", "N1", "REM", "AWA")</code> .

Value

hypnogram dataframe.

Examples

```
e <- data.frame(begin = as.POSIXlt(c(1536967800,1536967860,1536967830),origin = "1970-01-01")
e$end <- as.POSIXlt(c(1536967830,1536967890,1536967860), origin = "1970-01-01")
e$event = c("back-position", "N3", "REM")
hypnogram(e)
```

normalize_cycles	<i>Normalize sleep cycles scored on Noxturnal software from start and stop flags to unique events.</i>
------------------	--

Description

Normalize sleep cycles scored on Noxturnal software from start and stop flags to unique events.

Usage

```
normalize_cycles(events)
```

Arguments

<code>events</code>	Events dataframe. Dataframe must have <code>begin</code> (POSIXt), <code>end</code> (POSIXt) and <code>event</code> . Cycles flags must be named <code>Activity-CLASSICstart</code> , <code>Activity-BNstart</code> , <code>Activity-BNend</code> , <code>Activity-REMstart</code> , <code>Activity-REmend</code> , <code>Activity-ENstart</code> or <code>Activity-ENend</code> .
---------------------	--

Examples

```
cycles <- data.frame(event = c("Activity-CLASSICstart", "Activity-CLASSICend"))
cycles$begin <- as.POSIXct(c("2016-01-16 01:13:30", "2016-01-16 01:15:30"))
cycles$end <- as.POSIXct(c("2016-01-16 01:13:30", "2016-01-16 01:15:30"))
normalize_cycles(cycles)
```

plot_hypnogram *Draw a hypnogram with ggplot2.*

Description

A hypnogram represents the stages of sleep as a function of time. `plot_hypnogram()` plot a hypnogram using the `ggplot2` library from stages sleep in an event dataframe. REM stage is highlighted in red.

Usage

```
plot_hypnogram(events, labels = c("N3", "N2", "N1", "REM", "AWA"))
```

Arguments

events	Events dataframe. Dataframe must have begin (POSIXt), end (POSIXt) and event
labels	Sleep stages labels. Defaults to <code>c("N3", "N2", "N1", "REM", "AWA")</code> .

Value

a ggplot object.

References

Silber MH, Ancoli-Israel S, Bonnet MH, Chokroverty S, Grigg-Damberger MM, et al. (2007). "The visual scoring of sleep in adults". *Journal of Clinical Sleep Medicine*. 3 (2): 121–31. PMID 17557422

Examples

```
e <- data.frame(begin = as.POSIXlt(c(1536967800, 1536967830, 1536967860), origin = "1970-01-01"),
e$end <- as.POSIXlt(c(1536967830, 1536967860, 1536967890), origin = "1970-01-01")
e$event = c("N3", "N3", "REM")
plot_hypnogram(e)
```

```
read_events_noxturnal
```

Read a Noxturnal events file (Unicode CSV format)

Description

Read a Noxturnal events file (Unicode CSV format)

Usage

```
read_events_noxturnal(dir)
```

Arguments

`dir` Noxturnal events file path.

Value

A dataframe of scored events.

```
read_mdf
```

Read a Morpheo Data Format (MDF) directory to a list.

Description

Read a Morpheo Data Format (MDF) directory to a list.

Usage

```
read_mdf(mdfPath, channels = c(NA), metadata = TRUE)
```

Arguments

`mdfPath` character. MDF path.
`channels` character. Channels to read.
`metadata` boolean. Read or not the metadata.

Value

A list.

References

P. Bouchequet, D. Jin, G. Solelhac, M. Chennaoui, D. Leger, "Morpheo Data Format (MDF), un nouveau format de données simple, robuste et performant pour stocker et analyser les enregistrements de sommeil", *Médecine du Sommeil*, vol. 15, n 1, p. 48/49, march 2018.

Examples

```
download.file("http://cloud.frenchkpi.com/s/65cm6DMq7SYKQ6J/download",
paste0(tempdir(), "/15012016HD.edf"))
download.file("http://cloud.frenchkpi.com/s/wreGqkitWNnWwnP/download",
paste0(tempdir(), "15012016HD.csv"))
mdfPath = paste0(tempdir(), "/15012016HD/")
channels = c("C3-M2", "ECG")
events = read_events_noxturnal(paste0(tempdir(), "15012016HD.csv"))
write_mdf(paste0(tempdir(), "/15012016HD.edf"),
          mdfPath,
          channels,
          events
)
mdf <- read_mdf(paste0(tempdir(), "/15012016HD.edf"))
```

spectrogram

Plot the spectrogram of signal.

Description

‘spectrogram’ resamples signal and use the ‘specgram’ function from the ‘signal’ library to compute the spectrogram. Results resolution can be then reduced to quickly plot large signals.

Usage

```
spectrogram(signal, sRate, maxFreq = 25, n = 1024, window = n * 2,
            overlap = 0, cols = c(rep("#3B9AB2", 9), "#78B7C5", "#EBCC2A",
            "#E1AF00", rep("#F21A00", 6)), freq = 4, plot = TRUE,
            startTime = as.POSIXct("1970/01/01 00:00:00"))
```

Arguments

signal	Numerical vector of the signal.
sRate	Signal sample rate in Hertz.
maxFreq	Maximal frequency to plot in Hertz. Signal will be resampled at maxFreq*2 sample rate.
n	The size of the Fourier transform window.
window	Shape of the fourier transform window, defaults to n*2.
overlap	Overlap with previous window, defaults to 0.
cols	Color scale used for the underlying plot function.
freq	Aggregate frequency used to lower spectrogram resolution. Defaults to 4.
plot	Boolean, plot or not the spectrogram.
startTime	Posixct of the signal start. Adjust the x axis labels accordingly.

Value

A spectrogram.

Examples

```
library(signal)
spectrogram(chirp(seq(-2, 15, by = 0.001), 400, 10, 100, 'quadratic'),20,n=1024)
```

stages_stats	<i>Get stages events related stats in a named vector.</i>
--------------	---

Description

stages_stats computes stages related stats.

Usage

```
stages_stats(e)
```

Arguments

e Events dataframe. Dataframe must have begin (POSIXt), end (POSIXt) and event (character) columns.

Value

stages vector

Examples

```
e <- data.frame(begin = as.POSIXlt(seq(from = 0, to = 30*10, by = 30),origin = "1970-01-01"))
e$end <- as.POSIXlt(seq(from = 30, to = 30*11, by = 30), origin = "1970-01-01")
e$event = c("AWA", "N1", "N2", "N3", "N3", "REM", "N2", "REM", "N2", "REM", "AWA")
stages_stats(e)
```

write_channel	<i>Write a timeserie to disk using Morpheo Data Format (MDF) guidelines.</i>
---------------	--

Description

Write a timeserie to disk using Morpheo Data Format (MDF) guidelines.

Usage

```
write_channel(channel, signals, headers, mdfPath, endian = "little")
```

Arguments

channel	character. Channel name.
signals	list. European Data Format (EDF) signals list.
headers	list. European Data Format (EDF) file headers.
mdfPath	character. Morpheo Data Format (MDF) directory path.
endian	character. Endianess. "big" or "little". Defaults to "little".

References

P. Bouchequet, D. Jin, G. Solelhac, M. Chennaoui, D. Leger, "Morpheo Data Format (MDF), un nouveau format de données simple, robuste et performant pour stocker et analyser les enregistrements de sommeil", *Médecine du Sommeil*, vol. 15, n 1, p. 48-49, march 2018.

write_mdf	<i>Write a European Data Format (EDF) record file to disk using Morpheo Data Format (MDF) guidelines. Target directory is erased if it already exists. Signals are stored in binary file, events and metadata in JavaScript Object Notation (JSON) files.</i>
-----------	---

Description

Write a European Data Format (EDF) record file to disk using Morpheo Data Format (MDF) guidelines. Target directory is erased if it already exists. Signals are stored in binary file, events and metadata in JavaScript Object Notation (JSON) files.

Usage

```
write_mdf(edfPath, mdfPath, channels = c(NA), events = c(),
  endian = "little")
```

Arguments

edfPath	character. European Data Format (EDF) file path.
mdfPath	character. Morpheo Data Format (MDF) directory path.
channels	character. Vector of channels labels to write.
events	dataframe. Events dataframe to write. Events dataframe. Dataframe must contain begin (POSIXt), end (POSIXt) and event (character) columns.
endian	character. Endianess. "big" or "little". Defaults to "little".

References

P. Bouchequet, D. Jin, G. Solelhac, M. Chennaoui, D. Leger, "Morpheo Data Format (MDF), un nouveau format de données simple, robuste et performant pour stocker et analyser les enregistrements de sommeil", *Médecine du Sommeil*, vol. 15, n 1, p. 48/49, march 2018.

Examples

```
download.file("http://cloud.frenchkpi.com/s/65cm6DMq7SYKQ6J/download",
paste0(tempdir(), "/15012016HD.edf"))
download.file("http://cloud.frenchkpi.com/s/wreGqkitWNnWwnP/download",
paste0(tempdir(), "15012016HD.csv"))
mdfPath = paste0(tempdir(), "/15012016HD/")
channels = c("C3-M2", "ECG")
events = read_events_noxturnal(paste0(tempdir(), "15012016HD.csv"))
write_mdf(paste0(tempdir(), "/15012016HD.edf"),
          mdfPath,
          channels,
          events
)
```