

# Package ‘RobStatTM’

March 3, 2020

**Version** 1.0.2

**Date** 2020-03-02

**Title** Robust Statistics: Theory and Methods

**Description** Companion package for the book: “Robust Statistics: Theory and Methods, second edition”, <<http://www.wiley.com/go/maronna/robust>>. This package contains code that implements the robust estimators discussed in the recent second edition of the book above, as well as the scripts reproducing all the examples in the book.

**Depends** R (>= 3.5.0), fit.models

**Imports** stats, graphics, utils, methods, DEoptimR, pyinit, rrcov, robustbase, shiny, shinyjs, PerformanceAnalytics, DT, ggplot2, gridExtra, xts

**Suggests** knitr, R.rsp

**LazyData** yes

**License** GPL (>= 3)

**RoxygenNote** 6.1.1

**Encoding** UTF-8

**VignetteBuilder** knitr, R.rsp

**NeedsCompilation** yes

**Author** Matias Salibian-Barrera [cre],  
Victor Yohai [aut],  
Ricardo Maronna [aut],  
Doug Martin [aut],  
Gregory Brownson [aut] (ShinyUI),  
Kjell Konis [aut],  
Kjell Konis [cph] (erfi),  
Christophe Croux [ctb] (WBYlogreg, BYlogreg),  
Gentiane Haesbroeck [ctb] (WBYlogreg, BYlogreg),  
Martin Maechler [cph] (lmrob.fit, lmrob.M..fit, lmrob.S),  
Manuel Koller [cph] (lmrob.fit, .vcov.avar1, lmrob.S, lmrob.lar),  
Matias Salibian-Barrera [aut]

**Maintainer** Matias Salibian-Barrera <matias@stat.ubc.ca>

**Repository** CRAN

**Date/Publication** 2020-03-03 00:30:02 UTC

**R topics documented:**

alcohol . . . . .	3
algae . . . . .	4
biochem . . . . .	5
bisquare . . . . .	5
bus . . . . .	6
cov.dcml . . . . .	7
covClassic . . . . .	7
covRob . . . . .	9
covRobMM . . . . .	10
covRobRocke . . . . .	11
DCML . . . . .	13
drop1.lmrobdetMM . . . . .	14
fastmve . . . . .	15
flour . . . . .	16
glass . . . . .	17
hearing . . . . .	17
image . . . . .	18
initPP . . . . .	19
INVTR2 . . . . .	20
lmrobdet.control . . . . .	21
lmrobdetDCML . . . . .	23
lmrobdetMM . . . . .	25
lmrobdetMM.RFPE . . . . .	27
lmrobLinTest . . . . .	28
lmrobM . . . . .	29
lmrobM.control . . . . .	31
locScaleM . . . . .	32
logregBY . . . . .	33
logregWBY . . . . .	34
logregWML . . . . .	35
mineral . . . . .	36
MMPY . . . . .	37
mopt . . . . .	38
neuralgia . . . . .	38
oats . . . . .	39
opt . . . . .	40
pcaRobS . . . . .	40
prcompRob . . . . .	42
refine.sm . . . . .	43
resex . . . . .	44
rho . . . . .	45
rhoprime . . . . .	46
rhoprime2 . . . . .	47
scaleM . . . . .	48
ShinyUI . . . . .	49
shock . . . . .	49

<i>alcohol</i>	3
skin . . . . .	50
SMPY . . . . .	51
stackloss . . . . .	52
step.lmrobdet . . . . .	52
vehicle . . . . .	54
waste . . . . .	55
wine . . . . .	56
<b>Index</b>	<b>57</b>

---

<i>alcohol</i>	<i>Alcohol data</i>
----------------	---------------------

---

### Description

This data set contains physicochemical characteristics of 44 aliphatic alcohols. The aim of the experiment was the prediction of the solubility on the basis of molecular descriptors.

### Usage

```
data(alcohol)
```

### Format

An object of class "data.frame".

### Details

Format: 44 cases and 7 continuous variables. The columns are: 1. SAG=solvent accessible surface-bounded molecular volume 2. V=volume 3. log PC (PC=octanol-water partitions coefficient) 4. P=polarizability 5. RM=molar refractivity 6. Mass 7. log(Solubility) (response)

### Source

Romanelli, G.P., Martino, C.M. and Castro, E.A. (2001), Modeling the solubility of aliphatic alcohols via molecular descriptors, *Journal of the Chemical Society of Pakistan*, 23, 195-199.

### Examples

```
data(alcohol)
```

---

algae

*Algae data*

---

### Description

Each row of the data set is a set of 90 measurements at a river in some place in Europe. There are 11 predictors. The response is the logarithm of the abundance of a certain class of algae. Description: The columns are: 1. season, categorical (1,2,3,4 for winter, spring, summer and autumn) 2. river size (categorical) (1,2,3 for small, medium and large) 3. fluid velocity (categorical) (1,2,3 for low, medium and high) 4-11 (numeric): content of nitrogen in the form of nitrates, nitrites and ammonia, and other chemical compounds. Col. 12 is the response: abundance of a type of algae (type 6 in the complete file). For simplicity we deleted the rows with missing values and took the logarithm of the response.

### Usage

```
data(algae)
```

### Format

An object of class "data.frame".

### Details

Format 90 rows, 12 columns (3 categorical, 9 numeric)

### Source

Hettich, S. and Bay, S.D. (1999), The UCI KDD Archive <http://kdd.ics.uci.edu>. Irvine, CA: University of California, Department of Information and Computer Science.

### References

References go here.

### Examples

```
data(algae)
```

---

biochem

*Biochem data*

---

**Description**

Two biochemical measurements on 12 men with similar weights.

**Usage**

```
data(biochem)
```

**Format**

An object of class "data.frame".

**Details**

Format: Numeric, 12 rows, two columns

**Source**

Seber, G.A.F. (1984), *Multivariate Observations*. New York: John Wiley.

**Examples**

```
data(biochem)
```

---

bisquare

*Tuning parameter the rho loss functions*

---

**Description**

This function computes the tuning constant that yields an MM-regression estimator with a desired asymptotic efficiency when computed with a rho function in the corresponding family. The output of this function can be passed to the functions [lmrobdet.control](#), [mscale](#) and [rho](#).

**Usage**

```
bisquare(e)
```

**Arguments**

**e** the desired efficiency of the corresponding regression estimator for Gaussian errors

**Value**

A length-1 vector with the corresponding tuning constant.

**Author(s)**

Kjell Konis

**Examples**

```
# Tuning parameters for an 85%-efficient M-estimator at a Gaussian model
bisquare(.85)
```

---

bus

*Bus data*

---

**Description**

This data set corresponds to a study in automatic vehicle recognition. Each of the 218 rows corresponds to a view of a bus silhouette, and contains 18 attributes of the image. It was decided to exclude variable 9 and divide the remaining variables by their MADN's.

**Usage**

```
data(bus)
```

**Format**

An object of class "data.frame".

**Details**

Description: The following features were extracted from the silhouettes. 1. compactness 2. circularity 3. distance circularity 4. radius ratio 5. principal axis aspect ratio 6. maximum length aspect ratio 7. scatter ratio 8. elongatedness 9. principal axis rectangularity 10. maximum length rectangularity 11. scaled variance along major axis 12. scaled variance along minor axis 13. scaled radius of gyration 14. skewness about major axis 15. skewness about minor axis 16. kurtosis about minor axis 17. kurtosis about major axis 18. hollows ratio

Format: Numeric, 218 rows and 18 columns.

**Source**

Hettich, S. and Bay, S.D. (1999), The UCI KDD Archive <http://kdd.ics.uci.edu>. Irvine, CA: University of California, Department of Information and Computer Science.

**Examples**

```
data(bus)
```

---

cov.dcm1	<i>Approximate covariance matrix of the DCML regression estimator.</i>
----------	--

---

**Description**

The estimated covariance matrix of the DCML regression estimator. This function is used internally and not meant to be used directly.

**Usage**

```
cov.dcm1(res.LS, res.R, CC, sig.R, t0, p, n, control)
```

**Arguments**

res.LS	vector of residuals from the least squares fit
res.R	vector of residuals from the robust regression fit
CC	estimated covariance matrix of the robust regression estimator
sig.R	robust estimate of the scale of the residuals
t0	mixing parameter
p, n	the dimensions of the problem, needed for the finite sample correction of the tuning constant of the M-scale
control	a list of control parameters as returned by <a href="#">lmrobdet.control</a>

**Value**

The covariance matrix estimate.

**Author(s)**

Victor Yohai, <victoryohai@gmail.com>

---

covClassic	<i>Classical Covariance Estimation</i>
------------	--

---

**Description**

Compute an estimate of the covariance/correlation matrix and location vector using classical methods.

**Usage**

```
covClassic(data, corr = FALSE, center = TRUE, distance = TRUE,
  na.action = na.fail, unbiased = TRUE)
```

**Arguments**

<code>data</code>	a numeric matrix or data frame containing the data.
<code>corr</code>	a logical flag. If <code>corr = TRUE</code> then the estimated correlation matrix is computed.
<code>center</code>	a logical flag or a numeric vector of length $p$ (where $p$ is the number of columns of $x$ ) specifying the center. If <code>center = TRUE</code> then the center is estimated. Otherwise the center is taken to be 0.
<code>distance</code>	a logical flag. If <code>distance = TRUE</code> the Mahalanobis distances are computed.
<code>na.action</code>	a function to filter missing data. The default <code>na.fail</code> produces an error if missing values are present. An alternative is <code>na.omit</code> which deletes observations that contain one or more missing values.
<code>unbiased</code>	a logical flag. If <code>TRUE</code> the unbiased estimator is returned (computed with denominator equal to $n-1$ ), else the MLE (computed with denominator equal to $n$ ) is returned.

**Details**

Its main intention is to return an object compatible to that produced by `covRob`, but fit using classical methods.

**Value**

a list with class “covClassic” containing the following elements:

<code>call</code>	an image of the call that produced the object with all the arguments named.
<code>cov</code>	a numeric matrix containing the estimate of the covariance/correlation matrix.
<code>center</code>	a numeric vector containing the estimate of the location vector.
<code>dist</code>	a numeric vector containing the squared Mahalanobis distances. Only present if <code>distance = TRUE</code> in the call.
<code>corr</code>	a logical flag. If <code>corr = TRUE</code> then <code>cov</code> contains an estimate of the correlation matrix of $x$ .

**Note**

Originally, and in S-PLUS, this function was called `cov`; it has been renamed, as that did mask the function in the standard package **stats**.

**Examples**

```
data(wine)
round( covClassic(wine)$cov, 2)
```



---

covRob	<i>Robust multivariate location and scatter estimators</i>
--------	--

---

### Description

This function computes robust estimators for multivariate location and scatter.

### Usage

```
covRob(X, type = "auto", maxit = 50, tol = 1e-04, cor = FALSE)
```

### Arguments

X	a data matrix with observations in rows.
type	a string indicating which estimator to compute. Valid options are "Rocke" for Rocke's S-estimator, "MM" for an MM-estimator with a SHR rho function, or "auto" (default) which selects "Rocke" if the number of variables is greater than or equal to 10, and "MM" otherwise.
maxit	Maximum number of iterations, defaults to 50.
tol	Tolerance for convergence, defaults to 1e-4.
cor	A logical value. If TRUE a correlation matrix is included in the element cor of the returned object. Defaults to FALSE.

### Details

This function computes robust estimators for multivariate location and scatter. The default behaviour (type = "auto") computes a "Rocke" estimator (as implemented in [covRobRocke](#)) if the number of variables is greater than or equal to 10, and an MM-estimator with a SHR rho function (as implemented in [covRobMM](#)) otherwise.

### Value

A list with class "covClassic" with the following components:

mu	The location estimate
V	The scatter matrix estimate, scaled for consistency at the normal distribution
center	The location estimate. Same as mu above.
cov	The scatter matrix estimate, scaled for consistency at the normal distribution. Same as V above.
cor	The correlation matrix estimate, if the argument cor equals TRUE. Otherwise it is set to NULL.
dist	Robust Mahalanobis distances

### Author(s)

Ricardo Maronna, <[rmaronna@retina.ar](mailto:rmaronna@retina.ar)>

## References

<http://www.wiley.com/go/maronna/robust>

## See Also

[covRobRocke](#), [covRobMM](#)

## Examples

```
data(bus)
X0 <- as.matrix(bus)
X1 <- X0[,-9]
tmp <- covRob(X1)
round(tmp$cov[1:10, 1:10], 3)
tmp$mu
```

---

covRobMM

*MM robust multivariate location and scatter estimator*

---

## Description

This function computes an MM robust estimator for multivariate location and scatter with the "SHR" loss function.

## Usage

```
covRobMM(X, maxit = 50, tolpar = 1e-04, cor = FALSE)
```

## Arguments

X	a data matrix with observations in rows.
maxit	Maximum number of iterations.
tolpar	Tolerance to decide convergence.
cor	A logical value. If TRUE a correlation matrix is included in the element cor of the returned object. Defaults to FALSE.

## Details

This function computes an MM robust estimator for multivariate location and scatter with the "SHR" loss function.

**Value**

A list with class “covRob” containing the following elements

mu	The location estimate
V	The scatter or correlation matrix estimate, scaled for consistency at the normal distribution
center	The location estimate. Same as mu above.
cov	The scatter matrix estimate, scaled for consistency at the normal distribution. Same as V above.
cor	The correlation matrix estimate, if the argument cor equals TRUE. Otherwise it is set to NULL.
dista	Robust Mahalanobis distances

**Author(s)**

Ricardo Maronna, <rmaronna@retina.ar>

**References**

<http://www.wiley.com/go/maronna/robust>

**Examples**

```
data(bus)
X0 <- as.matrix(bus)
X1 <- X0[,-9]
tmp <- covRobMM(X1)
round(tmp$cov[1:10, 1:10], 3)
tmp$mu
```

---

covRobRocke

*Rocke's robust multivariate location and scatter estimator*

---

**Description**

This function computes Rocke's robust estimator for multivariate location and scatter.

**Usage**

```
covRobRocke(X, initial = "K", maxsteps = 5, propmin = 2, qs = 2,
  maxit = 50, tol = 1e-04, cor = FALSE)
```

**Arguments**

<code>X</code>	a data matrix with observations in rows.
<code>initial</code>	A character indicating the initial estimator. Valid options are 'K' (default) for the Pena-Prieto 'KSD' estimate, and 'mve' for the Minimum Volume Ellipsoid.
<code>maxsteps</code>	Maximum number of steps for the line search section of the algorithm.
<code>propmin</code>	Regulates the proportion of weights computed from the initial estimator that will be different from zero. The number of observations with initial non-zero weights will be at least $p$ (the number of columns of $X$ ) times <code>propmin</code> .
<code>qs</code>	Tuning parameter for Rocke's loss functions.
<code>maxit</code>	Maximum number of iterations.
<code>tol</code>	Tolerance to decide convergence.
<code>cor</code>	A logical value. If TRUE a correlation matrix is included in the element <code>cor</code> of the returned object. Defaults to FALSE.

**Details**

This function computes Rocke's robust estimator for multivariate location and scatter.

**Value**

A list with class "covRob" containing the following elements:

<code>mu</code>	The location estimate
<code>V</code>	The scatter (or correlation) matrix estimate, scaled for consistency at the normal distribution
<code>center</code>	The location estimate. Same as <code>mu</code> above.
<code>cov</code>	The scatter matrix estimate, scaled for consistency at the normal distribution. Same as <code>V</code> above.
<code>cor</code>	The correlation matrix estimate, if the argument <code>cor</code> equals TRUE. Otherwise it is set to NULL.
<code>dista</code>	Robust Mahalanobis distances.
<code>w</code>	weights
<code>gamma</code>	Final value of the constant $\gamma$ that regulates the efficiency.

**Author(s)**

Ricardo Maronna, <[rmaronna@retina.ar](mailto:rmaronna@retina.ar)>

**References**

<http://www.wiley.com/go/maronna/robust>

**Examples**

```
data(bus)
X0 <- as.matrix(bus)
X1 <- X0[,-9]
tmp <- covRobRocke(X1)
round(tmp$cov[1:10, 1:10], 3)
tmp$mu
```

---

DCML

*DCML regression estimator*

---

**Description**

This function computes the DCML regression estimator. This function is used internally by `lmrobdetDCML`, and not meant to be used directly.

**Usage**

```
DCML(x, y, z, z0, control)
```

**Arguments**

x	design matrix
y	response vector
z	robust fit as returned by <code>MMPY</code> or <code>SMPY</code>
z0	least squares fit as returned by <code>lm.fit</code>
control	a list of control parameters as returned by <code>lmrobdet.control</code>

**Value**

a list with the following components

coefficients	the vector of regression coefficients
cov	the estimated covariance matrix of the DCML regression estimator
residuals	the vector of regression residuals from the DCML fit
scale	a robust residual (M-)scale estimate
t0	the mixing proportion between the least squares and robust regression estimators

**Author(s)**

Victor Yohai, <victoryohai@gmail.com>, Matias Salibian-Barrera, <matias@stat.ubc.ca>

**References**

<http://www.wiley.com/go/maronna/robust>

**See Also**

[DCML](#), [MMPY](#), [SMPY](#)

---

drop1.lmrobdetMM      *RFPE of submodels of an [lmrobdetMM](#) fit*

---

**Description**

This function computes the RFPE for the MM-estimators obtained with [lmrobdetMM](#) by recomputing it, successively removing each of a number of specified terms. It is used internally by [step.lmrobdetMM](#) and not meant to be used directly.

**Usage**

```
## S3 method for class 'lmrobdetMM'
drop1(object, scope, scale, keep, ...)
```

**Arguments**

object	the MM element (of class <a href="#">lmrob</a> ) in an object of class <a href="#">lmrobdetMM</a> .
scope	an optional formula giving the terms to be considered for dropping. Typically this argument is omitted, in which case all possible terms are dropped (without breaking hierarchy rules). The scope can also be a character vector of term labels. If the argument is supplied as a formula, any <code>.</code> is interpreted relative to the formula implied by the object argument.
scale	an optional residual scale estimate. If missing the residual scale estimate in object is used.
keep	a character vector of names of components that should be saved for each subset model. Only names from the set "coefficients", "fitted" and "residuals" are allowed. If <code>keep == TRUE</code> , the complete set is saved. The default behavior is not to keep anything.
...	additional parameters to match generic method <code>drop1</code>

**Value**

An anova object consisting of the term labels, the degrees of freedom, and Robust Final Prediction Errors (RFPE) for each subset model. If `keep` is missing, the anova object is returned. If `keep` is present, a list with components "anova" and "keep" is returned. In this case, the "keep" component is a matrix of mode "list", with a column for each subset model, and a row for each component kept.

**Author(s)**

Victor Yohai, <[victoryohai@gmail.com](mailto:victoryohai@gmail.com)>, Matias Salibian-Barrera, <[matias@stat.ubc.ca](mailto:matias@stat.ubc.ca)>

**References**

<http://www.wiley.com/go/maronna/robust>

**See Also**

[lmrobdetMM](#)

---

fastmve

*Minimum Volume Ellipsoid covariance estimator*

---

**Description**

This function uses a fast algorithm to compute the Minimum Volume Ellipsoid (MVE) for multivariate location and scatter.

**Usage**

```
fastmve(x, nsamp = 500)
```

**Arguments**

x	data matrix (n x p) with cases stored in rows.
nsamp	number of random starts for the iterative algorithm, these are constructed using subsamples of the data.

**Details**

This function computes the Minimum Volume Ellipsoid (MVE) for multivariate location and scatter, using a fast algorithm related to the fast algorithm for S-regression estimators (see [lmrob](#)).

**Value**

A list with the following components:

center	a vector with the robust multivariate location estimate
cov	a matrix with the robust covariance / scatter matrix estimate
scale	A scalar that equals the median of the mahalanobis distances of the data to the center, multiplied by the determinant of the covariance matrix to the power 1/p
best	Indices of the observations that correspond to the MVE estimator
nsamp	Number of random starts used for the iterative algorithm
nsing	Number of random subsamples (among the nsamp attempted) that failed (resulting in singular initial values)

**Author(s)**

Matias Salibian-Barrera, <matias@stat.ubc.ca>

**References**

<http://www.wiley.com/go/maronna/robust>

**Examples**

```
data(bus)
X0 <- as.matrix(bus)
X1 <- X0[,-9]
tmp <- fastmve(X1)
round(tmp$cov[1:10, 1:10], 3)
tmp$center
```

---

flour

*Flour data*

---

**Description**

Determinations of the copper content in wholemeal flour (in parts per million), sorted in ascending order. Format: numeric vector of size 24.

**Usage**

```
data(flour)
```

**Format**

An object of class "data.frame".

**Source**

Analytical Methods Committee (1989), Robust statistics-How not to reject outliers, *Analyst*, 114, 1693-1702.

**References**

References go here.

**Examples**

```
data(flour)
```



---

glass

*Glass data*

---

**Description**

Measurements of the presence of seven chemical constituents in 76 pieces of glass from nonfloat car windows.

**Usage**

```
data(glass)
```

**Format**

An object of class "data.frame".

**Details**

Format: 76 cases and 7 continuous variables. Description: The columns are: 1. RI refractive index 2. Na2O sodium oxide (unit measurement: weight percent in corresponding oxide, as are the rest of attributes) 3. MgO magnesium oxide 4. Al2O3 aluminum oxide 5. SiO2 silicon oxide 6. K2O potassium oxide 7. CaO calcium oxide

**Source**

Hettich, S. and Bay, S.D. (1999), The UCI KDD Archive <http://kdd.ics.uci.edu>, Irvine, CA: University of California, Department of Information and Computer Science.

**Examples**

```
data(glass)
```

---

hearing

*Hearing data*

---

**Description**

Prevalence rates in percent for men aged 55–64 with hearing levels 16 decibels or more above the audiometric zero.

**Usage**

```
data(hearing)
```

**Format**

An object of class "data.frame".

**Details**

Format: Two-way ANOVA. Description: The rows correspond to different frequencies and to normal speech. 1. 500 hertz 2. 1000 hertz 3. 2000 hertz 4. 3000 hertz 5. 4000 hertz 6. 6000 hertz 7. Normal speech The columns classify the data in seven occupational groups: 1. professional–managerial 2. farm 3. clerical sales 4. craftsmen 5. operatives 6. service 7. laborers

**Source**

Roberts, J. and Cohns, J. (1968), Hearing levels of adults, US National Center for Health Statistics Publications, Series 11, No. 31

**Examples**

```
data(hearing)
```

---

image

*Image data*

---

**Description**

These data are part of a synthetic aperture satellite radar image corresponding to a suburb of Munich, and contain the values corresponding to three frequency bands for each of 1573 pixels of a radar image.

**Usage**

```
data(image)
```

**Format**

An object of class "data.frame".

**Details**

Format: 1573 cases and 3 variables.

**Source**

Source: Frery, A. (2005), Personal communication.

**Examples**

```
data(image)
```

---

`initPP`*Robust multivariate location and scatter estimators*

---

**Description**

This function computes robust multivariate location and scatter estimators using both random and deterministic starting points.

**Usage**

```
initPP(X, muldirand = 20, muldifix = 10, dirmin = 1000)
```

**Arguments**

<code>X</code>	a data matrix with observations in rows.
<code>muldirand</code>	used to determine the number of random directions (candidates), which is $\max(p \cdot \text{muldirand}, \text{dirmin})$ , where $p$ is the number of columns in $X$ .
<code>muldifix</code>	used to determine the number of random directions (candidates), which is $\min(n, 2 \cdot \text{muldifix} \cdot p)$ .
<code>dirmin</code>	minimum number of random directions

**Details**

This function computes robust multivariate location and scatter using both Pen~a-Prieto and random candidates.

**Value**

A list with the following components:

<code>idx</code>	A zero/one vector with ones in the positions of the suspected outliers
<code>disma</code>	Robust squared Mahalanobis distances
<code>center</code>	Robust mean estimate
<code>cova</code>	Robust covariance matrix estimate
<code>t</code>	Outlyingness of data points

**Author(s)**

Ricardo Maronna, <[rmaronna@retina.ar](mailto:rmaronna@retina.ar)>, based on original code by D. Pen~a and J. Prieto

**References**

<http://www.wiley.com/go/maronna/robust>

**Examples**

```
data(bus)
X0 <- as.matrix(bus)
X1 <- X0[,-9]
tmp <- initPP(X1)
round(tmp$cov[1:10, 1:10], 3)
tmp$center
```

---

**INVTR2***Robust R<sup>2</sup> coefficient of determination*

---

**Description**

This function computes a robust version of the R<sup>2</sup> coefficient of determination. It is used internally by [lmrobdetMM](#), and not meant to be used directly.

**Usage**

```
INVTR2(RR2, family, cc)
```

**Arguments**

RR2	the proportional difference in loss functions (a naive robust R <sup>2</sup> coefficient).
family	family string specifying the name of the family of loss function to be used (current valid options are "bisquare", "opt" and "mopt").
cc	tuning parameters to be computed according to efficiency and / or breakdown considerations. See <a href="#">lmrobdet.control</a> , <a href="#">bisquare</a> , <a href="#">mopt</a> and <a href="#">opt</a> .

**Details**

This function computes a robust version of the R<sup>2</sup> coefficient. It is used internally by [lmrobdetMM](#), and not meant to be used directly.

**Value**

An unbiased version of the robust R<sup>2</sup> coefficient of determination.

**Author(s)**

Victor Yohai, <[victoryohai@gmail.com](mailto:victoryohai@gmail.com)>

**References**

<http://www.wiley.com/go/maronna/robust>

---

lmrobdet.control      *Tuning parameters for lmrobdetMM and lmrobdetDCML*

---

### Description

This function sets tuning parameters for the MM estimator implemented in `lmrobdetMM` and the Distance Constrained Maximum Likelihood regression estimators computed by `lmrobdetDCML`.

### Usage

```
lmrobdet.control(bb = 0.5, efficiency = 0.95, family = "mopt",
  tuning.psi, tuning.chi, compute.rd = FALSE, corr.b = TRUE,
  split.type = "f", initial = "S", max.it = 100,
  refine.tol = 1e-07, rel.tol = 1e-07, refine.PY = 10,
  solve.tol = 1e-07, trace.lev = 0, psc_keep = 0.5,
  resid_keep_method = "threshold", resid_keep_thresh = 2,
  resid_keep_prop = 0.2, py_maxit = 20, py_eps = 1e-05,
  mscale_maxit = 50, mscale_tol = 1e-06, mscale_rho_fun = "bisquare")
```

### Arguments

<code>bb</code>	tuning constant (between 0 and 1/2) for the M-scale used to compute the initial S-estimator. It determines the robustness (breakdown point) of the resulting MM-estimator, which is <code>bb</code> . Defaults to 0.5.
<code>efficiency</code>	desired asymptotic efficiency of the final regression M-estimator. Defaults to 0.95.
<code>family</code>	string specifying the name of the family of loss function to be used (current valid options are "bisquare", "opt" and "mopt"). Incomplete entries will be matched to the current valid options. Defaults to "mopt".
<code>tuning.psi</code>	tuning parameters for the regression M-estimator computed with a rho function as specified with argument <code>family</code> . If missing, it is computed inside <code>lmrobdet.control</code> to match the value of <code>efficiency</code> according to the family of rho functions specified in <code>family</code> . Appropriate values for <code>tuning.psi</code> for a given desired efficiency for Gaussian errors can be constructed using the functions <a href="#">bisquare</a> , <a href="#">mopt</a> and <a href="#">opt</a> .
<code>tuning.chi</code>	tuning constant for the function used to compute the M-scale used for the initial S-estimator. If missing, it is computed inside <code>lmrobdet.control</code> to match the value of <code>bb</code> according to the family of rho functions specified in <code>family</code> .
<code>compute.rd</code>	logical value indicating whether robust leverage distances need to be computed.
<code>corr.b</code>	logical value indicating whether a finite-sample correction should be applied to the M-scale parameter <code>bb</code> .
<code>split.type</code>	determines how categorical and continuous variables are split. See <a href="#">splitFrame</a> .
<code>initial</code>	string specifying the initial value for the M-step of the MM-estimator. Valid options are 'S', for an S-estimator and 'MS' for an M-S estimator which is appropriate when there are categorical explanatory variables in the model.

<code>max.it</code>	maximum number of IRWLS iterations for the MM-estimator
<code>refine.tol</code>	relative coverage tolerance for the S-estimator
<code>rel.tol</code>	relative coverage tolerance for the IRWLS iterations for the MM-estimator
<code>refine.PY</code>	number of refinement steps for the Pen-a-Yohai candidates
<code>solve.tol</code>	(for the S algorithm): relative tolerance for matrix inversion. Hence, this corresponds to <code>solve.default</code> 's tol.
<code>trace.lev</code>	positive values (increasingly) provide details on the progress of the MM-algorithm
<code>psc_keep</code>	For <code>pyinit</code> , proportion of observations to remove based on PSCs. The effective proportion of removed observations is adjusted according to the sample size to be <code>prosac*(1-p/n)</code> . See <code>pyinit</code> .
<code>resid_keep_method</code>	For <code>pyinit</code> , how to clean the data based on large residuals. If "threshold", all observations with scaled residuals larger than <code>C.res</code> will be removed, if "proportion", observations with the largest prop residuals will be removed. See <code>pyinit</code> .
<code>resid_keep_thresh</code>	See parameter <code>resid_keep_method</code> above. See <code>pyinit</code> .
<code>resid_keep_prop</code>	See parameter <code>resid_keep_method</code> above. See <code>pyinit</code> .
<code>py_maxit</code>	Maximum number of iterations. See <code>pyinit</code> .
<code>py_eps</code>	Relative tolerance for convergence. See <code>pyinit</code> .
<code>mscale_maxit</code>	Maximum number of iterations for the M-scale algorithm. See <code>pyinit</code> and <code>mscale</code> .
<code>mscale_tol</code>	Convergence tolerance for the M-scale algorithm. See <code>mscale</code> and <code>mscale</code> .
<code>mscale_rho_fun</code>	String indicating the loss function used for the M-scale. See <code>pyinit</code> .

### Details

The argument `family` specifies the name of the family of loss function to be used. Current valid options are "bisquare", "opt" and "mopt"—"opt" refers to the optimal psi function defined in Section 5.8.1. of the book *Robust Statistics: Theory and Methods (with R)* by Maronna, Martin, Yohai and Salibian-Barrera, "mopt" is a modified version of the optimal psi function to make it strictly increasing close to 0, and to make the corresponding weight function non-increasing near 0.

### Value

A list with the necessary tuning parameters.

### Author(s)

Matias Salibian-Barrera, <matias@stat.ubc.ca>

### See Also

`pyinit`, `mscale`.

**Examples**

```
data(coleman, package='robustbase')
m2 <- lmrobdetMM(Y ~ ., data=coleman, control=lmrobdet.control(refine.PY=50))
m2
summary(m2)
```

---

lmrobdetDCML	<i>Robust Distance Constrained Maximum Likelihood estimators for linear regression</i>
--------------	--

---

**Description**

This function computes robust Distance Constrained Maximum Likelihood estimators for linear models.

**Usage**

```
lmrobdetDCML(formula, data, subset, weights, na.action, model = TRUE,
  x = !control$compute.rd, y = FALSE, singular.ok = TRUE,
  contrasts = NULL, offset = NULL, control = lmrobdet.control())
```

**Arguments**

formula	a symbolic description of the model to be fit.
data	an optional data frame, list or environment containing the variables in the model. If not found in data, model variables are taken from environment(formula), which usually is the root environment of the current R session.
subset	an optional vector specifying a subset of observations to be used.
weights	an optional vector of weights to be used in the fitting process.
na.action	a function to indicate what should happen when the data contain NAs. The default is set by the <a href="#">na.action</a> setting of <a href="#">options</a> , and is <code>na.fail</code> if that is unset.
model	logical value indicating whether to return the model frame
x	logical value indicating whether to return the model matrix
y	logical value indicating whether to return the vector of responses
singular.ok	logical value. If FALSE a singular fit produces an error.
contrasts	an optional list. See the <code>contrasts.arg</code> of <a href="#">model.matrix.default</a> .
offset	this can be used to specify an a priori known component to be included in the linear predictor during fitting. An offset term can be included in the formula instead or as well, and if both are specified their sum is used.
control	a list specifying control parameters as returned by the function <a href="#">lmrobdet.control</a> .

**Details**

This function computes Distance Constrained Maximum Likelihood regression estimators computed using an MM-regression estimator based on Pen-a-Yohai candidates (instead of subsampling ones). This function makes use of the functions `lmrob.fit`, `lmrob.M.fit`, `.vcov.avar1`, `lmrob.S` and `lmrob.lar`, from `robustbase`, along with utility functions used by these functions, modified so as to include use of the analytic form of the optimal psi and rho functions (for the optimal psi function, see Section 5.8.1 of Maronna, Martin, Yohai and Salibian Barrera, 2019)

**Value**

A list with the following components:

<code>coefficients</code>	The estimated vector of regression coefficients
<code>scale</code>	The estimated scale of the residuals
<code>residuals</code>	The vector of residuals associated with the robust fit
<code>converged</code>	Logical value indicating whether IRWLS iterations for the MM-estimator have converged
<code>iter</code>	Number of IRWLS iterations for the MM-estimator
<code>rweightsMM</code>	Robustness weights for the MM-estimator
<code>fitted.values</code>	Fitted values associated with the robust fit
<code>rank</code>	Numeric rank of the fitted linear model
<code>cov</code>	The estimated covariance matrix of the regression estimates
<code>df.residual</code>	The residual degrees of freedom
<code>contrasts</code>	(only where relevant) the contrasts used
<code>xlevels</code>	(only where relevant) a record of the levels of the factors used in fitting
<code>call</code>	the matched call
<code>model</code>	if requested, the model frame used
<code>x</code>	if requested, the model matrix used
<code>y</code>	if requested, the response vector used
<code>na.action</code>	(where relevant) information returned by <code>model.frame</code> on the special handling of NAs

**Author(s)**

Matias Salibian-Barrera, <matias@stat.ubc.ca>, based on `lmrob`

**References**

<http://www.wiley.com/go/maronna/robust>

**See Also**

[DCML](#), [MMPY](#), [SMPY](#)



**Examples**

```
data(coleman, package='robustbase')
m1 <- lmrobdetDCML(Y ~ ., data=coleman)
m1
summary(m1)
```

lmrobdetMM

*Robust linear regression estimators***Description**

This function computes an MM-regression estimators for linear models using deterministic starting points.

**Usage**

```
lmrobdetMM(formula, data, subset, weights, na.action, model = TRUE,
  x = !control$compute.rd, y = FALSE, singular.ok = TRUE,
  contrasts = NULL, offset = NULL, control = lmrobdet.control())
```

**Arguments**

formula	a symbolic description of the model to be fit.
data	an optional data frame, list or environment containing the variables in the model. If not found in data, model variables are taken from environment(formula), which usually is the root environment of the current R session.
subset	an optional vector specifying a subset of observations to be used.
weights	an optional vector of weights to be used in the fitting process.
na.action	a function to indicates what should happen when the data contain NAs. The default is set by the <a href="#">na.action</a> setting of <a href="#">options</a> , and is <code>na.fail</code> if that is unset.
model	logical value indicating whether to return the model frame
x	logical value indicating whether to return the model matrix
y	logical value indicating whether to return the vector of responses
singular.ok	logical value. If FALSE a singular fit produces an error.
contrasts	an optional list. See the <code>contrasts.arg</code> of <a href="#">model.matrix.default</a> .
offset	this can be used to specify an a priori known component to be included in the linear predictor during fitting. An offset term can be included in the formula instead or as well, and if both are specified their sum is used.
control	a list specifying control parameters as returned by the function <a href="#">lmrobdet.control</a> .

**Details**

This function computes MM-regression estimators computed using Pen-a-Yohai candidates (instead of subsampling ones). This function makes use of the functions `lmrob.fit`, `lmrob.MM.fit`, `.vcov.avar1`, `lmrob.S` and `lmrob.lar`, from `robustbase`, along with utility functions used by these functions, modified so as to include use of the analytic form of the optimal psi and rho functions (for the optimal psi function, see Section 5.8.1 of Maronna, Martin, Yohai and Salibián Barrera, 2019)

**Value**

A list with the following components:

<code>coefficients</code>	The estimated vector of regression coefficients
<code>scale</code>	The estimated scale of the residuals
<code>residuals</code>	The vector of residuals associated with the robust fit
<code>converged</code>	Logical value indicating whether IRWLS iterations for the MM-estimator have converged
<code>iter</code>	Number of IRWLS iterations for the MM-estimator
<code>rweights</code>	Robustness weights for the MM-estimator
<code>fitted.values</code>	Fitted values associated with the robust fit
<code>rank</code>	Numeric rank of the fitted linear model
<code>cov</code>	The estimated covariance matrix of the regression estimates
<code>df.residual</code>	The residual degrees of freedom
<code>contrasts</code>	(only where relevant) the contrasts used
<code>xlevels</code>	(only where relevant) a record of the levels of the factors used in fitting
<code>call</code>	the matched call
<code>model</code>	if requested, the model frame used
<code>x</code>	if requested, the model matrix used
<code>y</code>	if requested, the response vector used
<code>na.action</code>	(where relevant) information returned by <code>model.frame</code> on the special handling of NAs

**Author(s)**

Matias Salibián-Barrera, <matias@stat.ubc.ca>, based on `lmrob` from package `robustbase`

**References**

<http://www.wiley.com/go/maronna/robust>

**See Also**

[DCML](#), [MMPY](#), [SMPY](#)

## Examples

```
data(coleman, package='robustbase')
m2 <- lmrobdetMM(Y ~ ., data=coleman)
m2
summary(m2)
```

---

lmrobdetMM.RFPE      *Robust Final Prediction Error*

---

## Description

This function computes the robust Final Prediction Errors (RFPE) for a robust regression fit using M-estimates. It is used internally by [step.lmrobdetMM](#) and not meant to be used directly.

## Usage

```
lmrobdetMM.RFPE(object, scale = NULL)
```

## Arguments

object	the MM element (of class <a href="#">lmrob</a> ) in an object of class <a href="#">lmrobdetMM</a> .
scale	a numeric value specifying the scale estimate used to compute the RFPE. Usually this should be the scale estimate from an encompassing model. If NULL, the scale estimate in object is used.

## Value

the robust final prediction error (numeric).

## Author(s)

Victor Yohai, <[victoryohai@gmail.com](mailto:victoryohai@gmail.com)>, Matias Salibian-Barrera, <[matias@stat.ubc.ca](mailto:matias@stat.ubc.ca)>

## References

<http://www.wiley.com/go/maronna/robust>

## See Also

[lmrobdetMM](#)

---

lmrobLinTest	<i>Robust likelihood ratio test for linear hypotheses</i>
--------------	---

---

### Description

This function computes a robust likelihood ratio test for linear hypotheses.

### Usage

```
lmrobLinTest(object1, object2)
```

### Arguments

object1	an lmrob object with the fit corresponding to the complete model
object2	an lmrob object with the fit corresponding to the model restricted under the null linear hypothesis.

### Value

A list with the following components: c("test", "chisq.pvalue", "f.pvalue", "df")

test	The value of the F-statistic
f.pvalue	p-value based on the F distribution
chisq.pvalue	p-value based on the chi-squared distribution
df	degrees of freedom

### Author(s)

Victor Yohai, <vyohai@gmail.com>

### References

<http://www.wiley.com/go/maronna/robust>

### Examples

```
data(oats)
cont <- lmrobdet.control(bb = 0.5, efficiency = 0.85, family = "bisquare")
oats1M <- lmrobM(response1 ~ variety+block, control=cont, data=oats)
oats1M_var <- lmrobM(response1 ~ block, control=cont, data=oats)
( anov1M_var <- rob.linear.test(oats1M, oats1M_var) )
```

lmrobM

*Robust estimators for linear regression with fixed designs***Description**

This function computes a robust regression estimator for a linear models with fixed designs.

**Usage**

```
lmrobM(formula, data, subset, weights, na.action, model = TRUE,
        x = FALSE, y = FALSE, singular.ok = TRUE, contrasts = NULL,
        offset = NULL, control = lmrobM.control())
```

**Arguments**

formula	a symbolic description of the model to be fit.
data	an optional data frame, list or environment containing the variables in the model. If not found in data, model variables are taken from environment(formula), which usually is the root environment of the current R session.
subset	an optional vector specifying a subset of observations to be used.
weights	an optional vector of weights to be used in the fitting process.
na.action	a function to indicates what should happen when the data contain NAs. The default is set by the <a href="#">na.action</a> setting of <a href="#">options</a> , and is <code>na.fail</code> if that is unset.
model	logical value indicating whether to return the model frame
x	logical value indicating whether to return the model matrix
y	logical value indicating whether to return the vector of responses
singular.ok	logical value. If FALSE a singular fit produces an error.
contrasts	an optional list. See the <code>contrasts.arg</code> of <a href="#">model.matrix.default</a> .
offset	this can be used to specify an a priori known component to be included in the linear predictor during fitting. An offset term can be included in the formula instead or as well, and if both are specified their sum is used.
control	a list specifying control parameters as returned by the function <a href="#">lmrobM.control</a> .

**Details**

This function computes robust regression estimators for linear models with fixed designs. It computes an L1 estimator, and uses it as a starting point to find a minimum of a re-descending M estimator. The scale is set to a quantile of the absolute residuals from the L1 estimator. This function makes use of the functions `lmrob.fit`, `lmrob.M.fit`, `.vcov.avar1`, `lmrob.S` and `lmrob.lar`, from `robustbase`, along with utility functions used by these functions, modified so as to include use of the analytic form of the optimal  $\psi$  and  $\rho$  functions (for the optimal  $\psi$  function, see Section 5.8.1 of Maronna, Martin, Yohai and Salibián Barrera, 2019)

**Value**

A list with the following components:

coefficients	The estimated vector of regression coefficients
scale	The estimated scale of the residuals
residuals	The vector of residuals associated with the robust fit
converged	Logical value indicating whether IRWLS iterations for the MM-estimator have converged
iter	Number of IRWLS iterations for the MM-estimator
rweights	Robustness weights for the MM-estimator
fitted.values	Fitted values associated with the robust fit
rank	Numeric rank of the fitted linear model
cov	The estimated covariance matrix of the regression estimates
df.residual	The residual degrees of freedom
contrasts	(only where relevant) the contrasts used
xlevels	(only where relevant) a record of the levels of the factors used in fitting
call	the matched call
model	if requested, the model frame used
x	if requested, the model matrix used
y	if requested, the response vector used
na.action	(where relevant) information returned by model.frame on the special handling of NAs

**Author(s)**

Victor Yohai, <vyohai@gmail.com>, based on lmrob

**References**

<http://www.wiley.com/go/maronna/robust>

**Examples**

```
data(shock)
cont <- lmrobM.control(bb = 0.5, efficiency = 0.85, family = "bisquare")
shockrob <- lmrobM(time ~ n.shocks, data = shock, control=cont)
shockrob
summary(shockrob)
```

---

lmrobM.control                      *Tuning parameters for lmrobM*

---

### Description

This function sets tuning parameters for the M estimators of regression implemented in [lmrobM](#).

### Usage

```
lmrobM.control(bb = 0.5, efficiency = 0.99, family = "opt",
  tuning.chi, tuning.psi, max.it = 100, rel.tol = 1e-07,
  mscale_tol = 1e-06, mscale_maxit = 50, trace.lev = 0)
```

### Arguments

bb	tuning constant (between 0 and 1/2) for the M-scale used to compute the residual scale estimator. Defaults to 0.5.
efficiency	desired asymptotic efficiency of the final regression M-estimator. Defaults to 0.85.
family	string specifying the name of the family of loss function to be used (current valid options are "bisquare", "opt" and "mopt"). Incomplete entries will be matched to the current valid options.
tuning.chi	tuning constant for the function used to compute the M-scale used for the residual scale estimator. If missing, it is computed inside <code>lmrobdet.control</code> to match the value of <code>bb</code> according to the family of rho functions specified in <code>family</code> .
tuning.psi	tuning parameters for the regression M-estimator computed with a rho function as specified with argument <code>family</code> . If missing, it is computed inside <code>lmrobdet.control</code> to match the value of <code>efficiency</code> according to the family of rho functions specified in <code>family</code> . Appropriate values for <code>tuning.psi</code> for a given desired efficiency for Gaussian errors can be constructed using the functions <a href="#">bisquare</a> , <a href="#">mopt</a> and <a href="#">opt</a> .
max.it	maximum number of IRWLS iterations for the M-estimator
rel.tol	relative convergence tolerance for the IRWLS iterations for the M-estimator
mscale_tol	Convergence tolerance for the M-scale algorithm. See <a href="#">mscale</a> .
mscale_maxit	Maximum number of iterations for the M-scale algorithm. See <a href="#">mscale</a> .
trace.lev	positive values (increasingly) provide details on the progress of the M-algorithm

### Value

A list with the necessary tuning parameters.

### Author(s)

Matias Salibian-Barrera, <matias@stat.ubc.ca>

**Examples**

```
data(coleman, package='robustbase')
m2 <- lmrobM(Y ~ ., data=coleman, control=lmrobM.control())
m2
summary(m2)
```

locScaleM

*Robust univariate location and scale M-estimators***Description**

This function computes M-estimators for location and scale.

**Usage**

```
locScaleM(x, psi = "mopt", eff = 0.95, maxit = 50, tol = 1e-04,
na.rm = FALSE)
```

**Arguments**

<code>x</code>	a vector of univariate observations
<code>psi</code>	a string indicating which score function to use. Valid options are "bisquare", "huber", "opt" and "mopt".
<code>eff</code>	desired asymptotic efficiency. Valid options are 0.85, 0.9 and 0.95 (default) when <code>psi = "bisquare"</code> or <code>"huber"</code> , and 0.85, 0.9, 0.95 (default) and 0.99 when <code>psi = "opt"</code> or <code>"mopt"</code> .
<code>maxit</code>	maximum number of iterations allowed.
<code>tol</code>	tolerance to decide convergence of the iterative algorithm.
<code>na.rm</code>	a logical value indicating whether NA values should be stripped before the computation proceeds. Defaults to FALSE

**Details**

This function computes M-estimators for location and scale.

**Value**

A list with the following components:

<code>mu</code>	The location estimate
<code>std.mu</code>	Estimated standard deviation of the location estimator <code>mu</code>
<code>disper</code>	M-scale/dispersion estimate

**Author(s)**

Ricardo Maronna, <rmaronna@retina.ar>



## References

<http://www.wiley.com/go/maronna/robust>

## Examples

```
set.seed(123)
r <- rnorm(150, sd=1.5)
locScaleM(r)
# 10% of outliers, sd of good points is 1.5
set.seed(123)
r2 <- c(rnorm(135, sd=1.5), rnorm(15, mean=-10, sd=.5))
locScaleM(r2)
```

---

logregBY

*Bianco and Yohai estimator for logistic regression*

---

## Description

This function computes the M-estimator proposed by Bianco and Yohai for logistic regression. By default, an intercept term is included and p parameters are estimated. Modified by Yohai (2018) to take as initial estimator a weighted ML estimator with weights derived from the MCD estimator. For more details we refer to Croux, C., and Haesbroeck, G. (2002), "Implementing the Bianco and Yohai estimator for Logistic Regression"

## Usage

```
logregBY(x0, y, intercept = 1, const = 0.5, kmax = 1000,
maxhalf = 10)
```

## Arguments

x0	matrix of explanatory variables;
y	vector of binomial responses (0 or 1);
intercept	1 or 0 indicating if an intercept is included or not
const	tuning constant used in the computation of the estimator (default=0.5);
kmax	maximum number of iterations before convergence (default=1000);
maxhalf	max number of step-halving (default=10).

## Value

A list with the following components:

coefficients	estimates for the regression coefficients
standard.deviation	standard deviations of the coefficients

fitted.values	fitted values
residual.deviances	residual deviances
components	logical value indicating whether convergence was achieved
objective	value of the objective function at the minimum

**Author(s)**

Christophe Croux, Gentiane Haesbroeck, Victor Yohai

**References**

<http://www.wiley.com/go/maronna/robust>

**Examples**

```
data(skin)
Xskin <- as.matrix( skin[, 1:2] )
yskin <- skin$vasoconst
skinBY <- logregBY(Xskin, yskin, intercept=1)
skinBY$coeff
skinBY$standard.deviation
```

---

logregWBY

*Bianco and Yohai estimator for logistic regression*

---

**Description**

This function computes the weighted M-estimator of Bianco and Yohai in logistic regression. By default, an intercept term is included and p parameters are estimated. Modified by Yohai (2018) to take as initial estimator a weighted ML estimator computed with weights derived from the MCD estimator of the continuous explanatory variables. The same weights are used to compute the final weighted M-estimator. For more details we refer to Croux, C., and Haesbroeck, G. (2002), "Implementing the Bianco and Yohai estimator for Logistic Regression"

**Usage**

```
logregWBY(x0, y, intercept = 1, const = 0.5, kmax = 1000,
maxhalf = 10)
```

**Arguments**

x0	matrix of explanatory variables;
y	vector of binomial responses (0 or 1);
intercept	1 or 0 indicating if an intercept is included or not
const	tuning constant used in the computation of the estimator (default=0.5);
kmax	maximum number of iterations before convergence (default=1000);
maxhalf	max number of step-halving (default=10).

**Value**

A list with the following components:

coefficients	estimates for the regression coefficients
standard.deviation	standard deviations of the coefficients
fitted.values	fitted values
residual.deviances	residual deviances
components	logical value indicating whether convergence was achieved
objective	value of the objective function at the minimum

**Author(s)**

Christophe Croux, Gentiane Haesbroeck, Victor Yohai

**References**

<http://www.wiley.com/go/maronna/robust>

**Examples**

```
data(skin)
Xskin <- as.matrix( skin[, 1:2] )
yskin <- skin$vasoconst
skinWBY <- logregWBY(Xskin, yskin, intercept=1)
skinWBY$coeff
skinWBY$standard.deviation
```

---

logregWML

*Weighted likelihood estimator for the logistic model*

---

**Description**

This function computes a weighted likelihood estimator for the logistic model, where the weights penalize high leverage observations. In this version the weights are zero or one.

**Usage**

```
logregWML(x0, y, intercept = 1)
```

**Arguments**

x0	p x n matrix of explanatory variables, p is the number of explanatory variables, n is the number of observations
y	response vector
intercept	1 or 0 indicating if an intercept is included or not

**Value**

A list with the following components:

coefficients	vector of regression coefficients
standard.deviation	standard deviations of the regression coefficient estimators
fitted.values	vector with the probabilities of success
residual.deviances	residual deviances
cov	covariance matrix of the regression estimates
objective	value of the objective function at the minimum
xweights	vector of zeros and ones used to compute the weighted maximum likelihood estimator

**Author(s)**

Victor Yohai

**References**

<http://www.wiley.com/go/maronna/robust>

**Examples**

```
data(skin)
Xskin <- as.matrix( skin[, 1:2] )
yskin <- skin$vasoconst
skinWML <- logregWML(Xskin, yskin, intercept=1)
skinWML$coeff
skinWML$standard.deviation
```

---

mineral

*Mineral data*

---

**Description**

Contents (in parts per million) of 22 chemical elements in 53 samples of rocks in Western Australia. Two columns (8 and 9) were selected for use in this book.

**Usage**

```
data(mineral)
```

**Format**

An object of class "data.frame".

**Details**

Format: Numeric with 53 rows and 2 columns:

**Source**

Smith, R.E., Campbell, N.A. and Lichfield, A. (1984), Multivariate statistical techniques applied to pisolitic laterite geochemistry at Golden Grove, Western Australia, *Journal of Geochemical Exploration*, 22, 193-216.

**Examples**

```
data(mineral)
```

---

MMPY

*MM regression estimator using Pen~a-Yohai candidates*

---

**Description**

This function computes MM-regression estimator using Pen~a-Yohai candidates for the initial S-estimator. This function is used internally by `lmrobdetMM`, and not meant to be used directly.

**Usage**

```
MMPY(X, y, control, mf)
```

**Arguments**

X	design matrix
y	response vector
control	a list of control parameters as returned by <code>lmrobdet.control</code>
mf	model frame

**Value**

an `lmrob` object with the M-estimator obtained starting from the S-estimator computed with the Pen~a-Yohai initial candidates. The properties of the final estimator (efficiency, etc.) are determined by the tuning constants in the argument `control`.

**Author(s)**

Victor Yohai, <victoryohai@gmail.com>, Matias Salibian-Barrera, <matias@stat.ubc.ca>

**References**

<http://www.wiley.com/go/maronna/robust>

**See Also**

`DCML`, `MMPY`, `SMPY`

---

mopt	<i>Tuning parameter for a rho function in the modified (asymptotic bias-) optimal family</i>
------	--

---

**Description**

This function computes the tuning constant that yields an MM-regression estimator with a desired asymptotic efficiency when computed with a rho function in the corresponding family. The output of this function can be passed to the functions [lmrobdet.control](#), [mscale](#) and [rho](#).

**Usage**

```
mopt(e)
```

**Arguments**

e                    the desired efficiency of the corresponding regression estimator for Gaussian errors

**Value**

A vector with named elements containing the corresponding tuning parameters.

**Author(s)**

Kjell Konis

**Examples**

```
# Tuning parameters for an 85%-efficient M-estimator at a Gaussian model  
mopt(.85)
```

---

neuralgia	<i>Neuralgia data</i>
-----------	-----------------------

---

**Description**

Neuralgia data. More details [here](#).

**Usage**

```
data(neuralgia)
```

**Format**

An object of class "data.frame".

**Source**

Source goes here.

**References**

References go here.

**Examples**

```
data(neuralgia)
```

---

oats

*Oats data*

---

**Description**

Yield of grain for eight varieties of oats in five replications of a randomized-block experiment

**Usage**

```
data(oats)
```

**Format**

An object of class "data.frame".

**Details**

Format: Two-way ANOVA table with 8 rows and 5 columns.

**Source**

Scheffe, H. (1959), Analysis of Variance. New York: John Wiley.

**References**

References go here.

**Examples**

```
data(oats)
```

---

opt	<i>Tuning parameter for a rho function in the (asymptotic bias-) optimal family</i>
-----	---

---

**Description**

This function computes the tuning constant that yields an MM-regression estimator with a desired asymptotic efficiency when computed with a rho function in the corresponding family. The output of this function can be passed to the functions [lmrobdet.control](#), [mscale](#) and [rho](#).

**Usage**

```
opt(e)
```

**Arguments**

e	the desired efficiency of the corresponding regression estimator for Gaussian errors
---	--

**Value**

A vector with named elements containing the corresponding tuning parameters.

**Author(s)**

Kjell Konis

**Examples**

```
# Tuning parameters for an 85%-efficient M-estimator at a Gaussian model
opt(.85)
```

---

pcaRobS	<i>Robust principal components</i>
---------	------------------------------------

---

**Description**

This function computes robust principal components based on the minimization of the "residual" M-scale.

**Usage**

```
pcaRobS(X, ncomp, desprop = 0.9, deltasca = 0.5, maxit = 100)
```



**Arguments**

X	a data matrix with observations in rows.
ncomp	desired (maximum) number of components
desprop	desired (minimum) proportion of explained variability (default = 0.9)
deltasca	"delta" parameter of the scale M-estimator (default=0.5)
maxit	maximum number of iterations (default= 100)

**Value**

A list with the following components:

q	The actual number of principal components
propex	The actual proportion of unexplained variability
eigvec	Eigenvectors, in a $p \times q$ matrix
fit	an $n \times p$ matrix with the rank- $q$ approximation to $X$
repre	An $n \times q$ matrix with representation of data in $R^q$ (scores)
propSPC	A vector of length $p$ with the cumulative explained variance from initial SPC

**Author(s)**

Ricardo Maronna, <rmaronna@retina.ar>, based on original code by D. Pen-a and J. Prieto

**References**

<http://www.wiley.com/go/maronna/robust>

**Examples**

```
data(bus)
X0 <- as.matrix(bus)
X1 <- X0[,-9]
ss <- apply(X1, 2, mad)
mu <- apply(X1, 2, median)
X <- scale(X1, center=mu, scale=ss)
q <- 3 #compute three components
rr <- pcaRobS(X, q, 0.99)
round(rr$eigvec, 3)
```

---

`prcompRob`*Robust Principal Components Cont'd*

---

**Description**

This function uses the `pcaRobS` function to compute all principal components while behaving similarly to the `prcomp` function

**Usage**

```
prcompRob(x, rank. = NULL, delta.scale = 0.5, max.iter = 100L)
```

**Arguments**

<code>x</code>	data matrix with observations in rows
<code>rank.</code>	Maximal number of principal components to be used (optional)
<code>delta.scale</code>	"delta" parameter of the scale M-estimator (default = 0.5)
<code>max.iter</code>	maximum number of iterations (default = 100)

**Value**

<code>sdev</code>	the standard deviation of the principal components
<code>rotation</code>	matrix containing the factor loadings
<code>x</code>	matrix containing the rotated data
<code>center</code>	the centering used

**Author(s)**

Gregory Brownson, <gregory.brownson@gmail.com>

**Examples**

```
data(wine)

p.wine <- prcompRob(wine)
summary(p.wine)

## Choose only 5
p5.wine <- prcompRob(wine, rank. = 5)
summary(p5.wine)
```

---

refine.sm	<i>IRWLS iterations for S- or M-estimators</i>
-----------	--

---

### Description

This function performs iterative improvements for S- or M-estimators.

### Usage

```
refine.sm(x, y, initial.beta, initial.scale, k = 50, conv = 1, b, cc,
         family, step = "M")
```

### Arguments

<code>x</code>	design matrix
<code>y</code>	vector of responses
<code>initial.beta</code>	vector of initial regression estimates
<code>initial.scale</code>	initial residual scale estimate. If missing the (scaled) median of the absolute residuals is used.
<code>k</code>	maximum number of refining steps to be performed
<code>conv</code>	an integer indicating whether to check for convergence (1) at each step, or to force running k steps (0)
<code>b</code>	tuning constant for the M-scale estimator, used if iterations are for an S-estimator.
<code>cc</code>	tuning constant for the rho function.
<code>family</code>	string specifying the name of the family of loss function to be used (current valid options are "bisquare", "opt" and "mopt")
<code>step</code>	a string indicating whether the iterations are to compute an S-estimator ('S') or an M-estimator ('M')

### Details

This function performs iterative improvements for S- or M-estimators. Both iterations are formally the same, the only difference is that for M-iterations the residual scale estimate remains fixed, while for S-iterations it is updated at each step. In this case, we follow the Fast-S algorithm of Salibián-Barrera and Yohai and use one step updates for the M-scale, as opposed to a full computation. This is an internal function.

### Value

A list with the following components:

<code>beta.rw</code>	The updated vector of regression coefficients
<code>scale.rw</code>	The corresponding estimated residual scale
<code>converged</code>	A logical value indicating whether the algorithm converged

**Author(s)**

Matias Salibian-Barrera, <matias@stat.ubc.ca>.

---

resex

*Resex data*

---

**Description**

A monthly series of inward movement of residential telephone extensions in a fixed geographic area from January 1966 to May 1973.

**Usage**

data(resex)

**Format**

An object of class "data.frame".

**Details**

Format: numeric vector of size 89.

**Source**

Source Engineering, 2nd. Edition, New York, John Wiley.

**References**

Brubacher. S.R. (1974), Time series outlier detection and modeling with interpolation, Bell Laboratories Technical Memo.

**Examples**

data(resex)

---

rho	<i>Rho functions</i>
-----	----------------------

---

### Description

This function returns the value of the "rho" loss function used to compute either an M-scale estimator or a robust regression estimator. It currently can be used to compute the bisquare, optimal and modified optimal loss functions.

### Usage

```
rho(u, family = "bisquare", cc, standardize = TRUE)
```

### Arguments

u	point or vector at which rho is to be evaluated
family	family string specifying the name of the family of loss function to be used (current valid options are "bisquare", "opt" and "mopt").
cc	tuning parameters to be computed according to efficiency and / or breakdown considerations. See <a href="#">lmrobdet.control</a> , <a href="#">bisquare</a> , <a href="#">mopt</a> and <a href="#">opt</a> .
standardize	logical value determining whether the rho function is to be standardized so that its maximum value is 1. See <a href="#">Mpsi</a> .

### Value

The value(s) of rho at u

### Author(s)

Matias Salibian-Barrera, <matias@stat.ubc.ca>

### Examples

```
# Evaluate rho tuned for 85% efficiency
rho(u=1.1, family='bisquare', cc=bisquare(.85))
# Evaluate rho tuned for 50% breakdown
rho(u=1.1, family='opt', cc=lmrobdet.control(bb=.5, family='opt')$tuning.chi)
```

---

rho prime	<i>The first derivative of the rho function</i>
-----------	---

---

## Description

The first derivative of the rho function

## Usage

```
rho prime(u, family, cc, standardize = FALSE)
```

## Arguments

u	point or vector at which rho is to be evaluated
family	family string specifying the name of the family of loss function to be used (current valid options are "bisquare", "opt" and "mopt").
cc	tuning parameters to be computed according to efficiency and / or breakdown considerations. See <a href="#">lmrobdet.control</a> , <a href="#">bisquare</a> , <a href="#">mopt</a> and <a href="#">opt</a> .
standardize	logical value determining whether the rho function is to be standardized so that its maximum value is 1. See <a href="#">Mpsi</a> .

## Value

The value of the first derivative rho evaluated at u

## Author(s)

Matias Salibian-Barrera, <matias@stat.ubc.ca>

## Examples

```
# Evaluate the derivative of a rho function tuned for 85% efficiency
rho prime(u=1.1, family='bisquare', cc=bisquare(.85))
# Evaluate the derivative of a rho function tuned for 50% breakdown
rho prime(u=1.1, family='opt', cc=lmrobdet.control(bb=.5, family='opt')$tuning.chi)
```

---

rhoprime2                      *The second derivative of the rho function*

---

## Description

The second derivative of the rho function

## Usage

```
rhoprime2(u, family, cc, standardize = FALSE)
```

## Arguments

u	point or vector at which rho is to be evaluated
family	family string specifying the name of the family of loss function to be used (current valid options are "bisquare", "opt" and "mopt").
cc	tuning parameters to be computed according to efficiency and / or breakdown considerations. See <a href="#">lmrobdet.control</a> , <a href="#">bisquare</a> , <a href="#">mopt</a> and <a href="#">opt</a> .
standardize	logical value determining whether the rho function is to be standardized so that its maximum value is 1. See <a href="#">Mpsi</a> .

## Value

The value of the second derivative of rho evaluated at u

## Author(s)

Matias Salibian-Barrera, <matias@stat.ubc.ca>

## Examples

```
# Evaluate the 2nd derivative of a rho function tuned for 85% efficiency
rhoprime2(u=1.1, family='bisquare', cc=bisquare(.85))
# Evaluate the 2nd derivative of a rho function tuned for 50% breakdown
rhoprime2(u=1.1, family='opt', cc=lmrobdet.control(bb=.5, family='opt')$tuning.chi)
```

scaleM

*M-scale estimator***Description**

This function computes an M-scale, which is a robust scale (spread) estimator. M-estimators of scale are a robust alternative to the sample standard deviation. Given a vector of residuals  $r$ , the M-scale estimator  $s$  solves the non-linear equation  $\text{mean}(\rho(r/s, cc))=b$ , where  $b$  and  $cc$  are user-chosen tuning constants. In this package the function  $\rho$  is one of Tukey's bisquare family. The breakdown point of the estimator is  $\min(b, 1-b)$ , so the optimal choice for  $b$  is 0.5. To obtain a consistent estimator the constant  $cc$  should be chosen such that  $E(\rho(Z, cc)) = b$ , where  $Z$  is a standard normal random variable.

**Usage**

```
scaleM(u, delta = 0.5, tuning.chi = 1.547645, family = "bisquare",
       max.it = 100, tol = 1e-06, tolerancezero = .Machine$double.eps)
```

**Arguments**

<code>u</code>	vector of residuals
<code>delta</code>	the right hand side of the M-scale equation
<code>tuning.chi</code>	the tuning object for the $\rho$ function as returned by <code>lmrobdet.control</code> , <code>bisquare</code> , <code>mopt</code> or <code>opt</code> . It should correspond to the family of $\rho$ functions specified in the argument family.
<code>family</code>	string specifying the name of the family of loss function to be used (current valid options are "bisquare", "opt" and "mopt").
<code>max.it</code>	maximum number of iterations allowed
<code>tol</code>	relative tolerance for convergence
<code>tolerancezero</code>	smallest (in absolute value) non-zero value accepted as a scale. Defaults to <code>.Machine\$double.eps</code>

**Details**

The iterative algorithm starts from the scaled median of the absolute values of the input vector, and then cycles through the equation  $s^2 = s^2 * \text{mean}(\rho(r/s, cc)) / b$ .

**Value**

The scale estimate value at the last iteration or at convergence.

**Author(s)**

Matias Salibian-Barrera, <matias@stat.ubc.ca>



**Examples**

```
set.seed(123)
r <- rnorm(150, sd=1.5)
mscale(r)
sd(r)
# 10% of outliers, sd of good points is 1.5
set.seed(123)
r2 <- c(rnorm(135, sd=1.5), rnorm(15, mean=-5, sd=.5))
mscale(r2)
sd(r2)
```

---

**ShinyUI***Open the Shiny interface for the package*

---

**Description**

This function opens the Shiny interface for the package.

**Usage**

```
ShinyUI()
```

**Author(s)**

Gregory Brownson <gsb25@uw.edu>

**References**

<http://www.wiley.com/go/maronna/robust>

---

**shock***Shock data*

---

**Description**

Times recorded for a rat to go through a shuttlebox in successive attempts. If the time exceeded 5 seconds, the rat received an electric shock for the duration of the next attempt. The data are the number of shocks received and the average time for all attempts between shocks.

**Usage**

```
data(shock)
```

**Format**

An object of class "data.frame".

**Details**

Format: Numeric matrix with 16 rows and 2 columns

**Source**

Bond, N.W. (1979), Impairment of shuttlebox avoidance-learning following repeated alcohol withdrawal episodes in rats, *Pharmacology, Biochemistry and Behavior*, 11, 589-591.

**References**

References go here.

**Examples**

```
data(shock)
```

---

skin

*Skin data*

---

**Description**

These data correspond to a study of the relationship between air inspiration and blood circulation in the skin.

**Usage**

```
data(skin)
```

**Format**

An object of class "data.frame".

**Details**

Description: The covariates are the logarithms of the volume of air inspired (log VOL) and of the inspiration rate (log RATE). The response (column 3) is the presence or absence of vasoconstriction of the skin of the digits after air inspiration. Format Numeric, 23 rows and 3 columns.

**Source**

Finney, D.J. (1947), The estimation from individual records of the relationship between dose and quantal response, *Biometrika*, 34, 320-334.

**Examples**

```
data(skin)
```

---

SMPY

*SM regression estimator using Pen~a-Yohai candidates*

---

## Description

This function computes a robust regression estimator when there are categorical / dummy explanatory variables. It uses Pen~a-Yohai candidates for the S-estimator. This function is used internally by [lmrobdetMM](#), and not meant to be used directly.

## Usage

```
SMPY(mf, y, control, split)
```

## Arguments

<code>mf</code>	model frame
<code>y</code>	response vector
<code>control</code>	a list of control parameters as returned by <a href="#">lmrobdet.control</a>
<code>split</code>	a list as returned by <a href="#">splitFrame</a> containing the continuous and dummy components of the design matrix

## Value

an [lmrob](#) object with the M-estimator obtained starting from the MS-estimator computed with the Pen~a-Yohai initial candidates. The properties of the final estimator (efficiency, etc.) are determined by the tuning constants in the argument `control`.

## Author(s)

Victor Yohai, <[victoryohai@gmail.com](mailto:victoryohai@gmail.com)>, Matias Salibian-Barrera, <[matias@stat.ubc.ca](mailto:matias@stat.ubc.ca)>

## References

<http://www.wiley.com/go/maronna/robust>

## See Also

[DCML](#), [MMPY](#), [SMPY](#)

---

stackloss

*Stackloss data*

---

### Description

Observations from 21 days operation of a plant for the oxidation of ammonia as a stage in the production of nitric acid.

### Usage

```
data(stackloss)
```

### Format

An object of class "data.frame".

### Details

Format: 21 cases and 4 continuous variables. Description: The columns are: 1. air flow 2. cooling water inlet temperature (C) 3. acid concentration ( 4. Stack loss, defined as the percentage of ingoing ammonia that escapes unabsorbed (response)

### Source

Brownlee, K.A. (1965), Statistical Theory and Methodology in Science and Engineering, 2nd Edition, New York: John Wiley & Sons, Inc.

### Examples

```
data(stackloss)
```

---

step.lmrobdet

*Robust stepwise using RFPE*

---

### Description

This function performs stepwise model selection on a robustly fitted linear model using the RFPE criterion and the robust regression estimators computed with [lmrobdetMM](#). Only backwards stepwise is currently implemented.

### Usage

```
step.lmrobdet(object, scope, direction = c("both", "backward",  
  "forward"), trace = TRUE, keep = NULL, steps = 1000,  
  whole.path = FALSE)
```

**Arguments**

object	a robust fit as returned by <code>lmrobdetMM</code>
scope	either a formula or a list with elements <code>lower</code> and <code>upper</code> each of which is a formula. The terms in the right-hand-side of <code>lower</code> are always included in the model and the additional terms in the right-hand-side of <code>upper</code> are the candidates for inclusion/exclusion from the model. If a single formula is given, it is taken to be <code>upper</code> , and <code>lower</code> is set to the empty model. The <code>.</code> operator is interpreted in the context of the formula in <code>object</code> .
direction	the direction of stepwise search. Currently only backward stepwise searches are implemented.
trace	logical. If TRUE information about each step is printed on the screen.
keep	a filter function whose input is a fitted model object and the associated AIC statistic, and whose output is arbitrary. Typically <code>keep</code> will select a subset of the components of the object and return them. The default is not to keep anything.
steps	maximum number of steps to be performed. Defaults to 1000, which should mean as many as needed.
whole.path	if FALSE (default) variables are dropped until the RFPE fails to improve. If TRUE the best variable to be dropped is removed, even if this does not improve the RFPE.

**Details**

Presently only backward stepwise selection is supported. During each step the Robust Final Prediction Error (as computed by the function `lmrobdetMM.RFPE`) is calculated for the current model and for each sub-model achievable by deleting a single term. If the argument `whole.path` is FALSE, the function steps to the sub-model with the lowest Robust Final Prediction Error or, if the current model has the lowest Robust Final Prediction Error, terminates. If the argument `whole.path` is TRUE, the function steps through all smaller submodels removing, at each step, the variable that most reduces the Robust Final Prediction Error. The scale estimate from `object` is used to compute the Robust Final Prediction Error throughout the procedure.

**Value**

If `whole.path == FALSE` the function returns the robust fit as obtained by `lmrobdetMM` using the final model. If `whole.path == TRUE` a list is returned containing the RFPE of each model on the sequence of submodels. The names of the components of this list are the formulas that corresponds to each model.

**Author(s)**

Victor Yohai, <victoryohai@gmail.com>, Matias Salibian-Barrera, <matias@stat.ubc.ca>

**References**

<http://www.wiley.com/go/maronna/robust>

**See Also**

[DCML](#), [MMPY](#), [SMPY](#)

**Examples**

```
cont <- lmrobdet.control(bb = 0.5, efficiency = 0.85, family = "bisquare")
set.seed(300)
X <- matrix(rnorm(50*6), 50, 6)
beta <- c(1,1,1,0,0,0)
y <- as.vector(X %*% beta) + 1 + rnorm(50)
y[1:6] <- seq(30, 55, 5)
for (i in 1:6) X[i,] <- c(X[i,1:3],i/2,i/2,i/2)
Z <- cbind(y,X)
Z <- as.data.frame(Z)
obj <- lmrobdetMM(y ~ ., data=Z, control=cont)
out <- step.lmrobdetMM(obj)
```

---

vehicle

*Vehicle data*

---

**Description**

The original data set contains an ensemble of shape feature extractors to the 2D silhouettes of different vehicles. The purpose is to classify a given silhouette as one of four types of vehicle, using a set of 18 features extracted from the silhouette. Here we deal with the "van" type, which has 217 cases. Description; The following features were extracted from the silhouettes. 1. compactness 2. circularity 3. distance circularity 4. radius ratio 5. principal axis aspect ratio 6. maximum length aspect ratio 7. scatter ratio 8. elongatedness 9. principal axis rectangularity 10. maximum length rectangularity 11. scaled variance along major axis 12. scaled variance along minor axis 13. scaled radius of gyration 14. skewness about major axis 15. skewness about minor axis 16. kurtosis about minor axis 17. kurtosis about major axis 18. hollows ratio

**Usage**

```
data(vehicle)
```

**Format**

An object of class "data.frame".

**Details**

Format: Numeric, 217 rows and 18 columns.

**Source**

Turing Institute, Glasgow, and are available at [https://archive.ics.uci.edu/ml/datasets/Statlog+\(Vehicle+Silhouettes\)](https://archive.ics.uci.edu/ml/datasets/Statlog+(Vehicle+Silhouettes)).

**Examples**

```
data(vehicle)
```

---

waste

*Waste data*

---

**Description**

Waste data. The original data are the result of a study on production waste and land use by Golueke and McGauhey (1970), and contain nine variables, of which we consider six.

**Usage**

```
data(waste)
```

**Format**

An object of class "data.frame".

**Details**

Format: 40 cases and 6 continuous variables. Description: The columns are 1. industrial land (acres) 2. fabricated metals (acres) 3. trucking and wholesale trade (acres) 4. retail trade (acres) 5. restaurants and hotels (acres) 6. solid waste (millions of tons), response

**Source**

Golueke, C.G. and McGauhey, P.H. (1970), Comprehensive Studies of Solid Waste Management, US Department of Health, Education and Welfare, Public Health Services Publication No. 2039.

**References**

Golueke, C.G. and McGauhey, P.H. (1970), Comprehensive Studies of Solid Waste Management, US Department of Health, Education and Welfare, Public Health Services Publication No. 2039.

**Examples**

```
data(waste)
```

---

wine

*Wine data*

---

**Description**

It contains, for each of 59 wines grown in the same region in Italy, the quantities of 13 constituents. The original purpose of the analysis was to classify wines from different cultivars by means of these measurements. In this example we treat cultivar one.

**Usage**

```
data(wine)
```

**Format**

An object of class "data.frame".

**Details**

Format: Numeric, 59 rows and 13 columns. Description: The attributes are: 1. Alcohol 2. Malic acid 3. Ash 4. Alcalinity of ash 5. Magnesium 6. Total phenols 7. Flavanoids 8. Nonflavanoid phenols 9. Proanthocyanins 10. Color intensity 11. Hue 12. OD280/OD315 of diluted wines 13. Proline

**Source**

Hettich, S. and Bay, S.D. (1999), The UCI KDD Archive <http://kdd.ics.uci.edu>. Irvine, CA: University of California, Department of Information and Computer Science.

**Examples**

```
data(wine)
```



# Index

## \*Topic **datasets**

- alcohol, 3
  - algae, 4
  - biochem, 5
  - bus, 6
  - flour, 16
  - glass, 17
  - hearing, 17
  - image, 18
  - mineral, 36
  - neuralgia, 38
  - oats, 39
  - resex, 44
  - shock, 49
  - skin, 50
  - stackloss, 52
  - vehicle, 54
  - waste, 55
  - wine, 56
- alcohol, 3
- algae, 4
- biochem, 5
- bisquare, 5, 20, 21, 31, 45–48
- bus, 6
- BYlogreg (logregBY), 33
- cov.dcm1, 7
- covClassic, 7
- covRob, 8, 9
- covRobMM, 9, 10, 10
- covRobRocke, 9, 10, 11
- DCML, 13, 14, 24, 26, 37, 51, 54
- drop1.lmrobdetMM, 14
- fastmve, 15
- flour, 16
- glass, 17
- hearing, 17
- image, 18
- initPP, 19
- INVTR2, 20
- KurtSDNew (initPP), 19
- lm.fit, 13
- lmrob, 14, 15, 27, 37, 51
- lmrobdet.control, 5, 7, 13, 20, 21, 23, 25, 37, 38, 40, 45–48, 51
- lmrobdetDCML, 13, 23
- lmrobdetMM, 14, 15, 20, 25, 27, 37, 51–53
- lmrobdetMM.RFPE, 27
- lmrobLinTest, 28
- lmrobM, 29, 31
- lmrobM.control, 29, 31
- locScaleM, 32
- logregBY, 33
- logregWBY, 34
- logregWML, 35
- mineral, 36
- MLocDis (locScaleM), 32
- MMPY, 13, 14, 24, 26, 37, 37, 51, 54
- MMultiSHR (covRobMM), 10
- model.matrix.default, 23, 25, 29
- mopt, 20, 21, 31, 38, 45–48
- Mpsi, 45–47
- mscale, 5, 22, 31, 38, 40
- mscale (scaleM), 48
- Multirobu (covRob), 9
- na.action, 23, 25, 29
- neuralgia, 38
- oats, 39
- opt, 20, 21, 31, 40, 45–48
- options, 23, 25, 29

pcaRobS, 40  
prcompRob, 42  
pyinit, 22

refine.sm, 43  
resex, 44  
rho, 5, 38, 40, 45  
rhoPrime, 46  
rhoPrime2, 47  
rob.linear.test (lmrobLinTest), 28  
RockeMulti (covRobRocke), 11

scaleM, 48  
ShinyUI, 49  
shock, 49  
skin, 50  
SMPCA (pcaRobS), 40  
SMPY, 13, 14, 24, 26, 37, 51, 51, 54  
solve.default, 22  
splitFrame, 21, 51  
stackloss, 52  
step.lmrobdet, 52  
step.lmrobdetMM, 14, 27  
step.lmrobdetMM (step.lmrobdet), 52

vehicle, 54

waste, 55  
WBYlogreg (logregWBY), 34  
wine, 56  
WMLlogreg (logregWML), 35