

Package ‘fdatest’

February 19, 2015

Type Package

Title Interval Testing Procedure for Functional Data

Version 2.1

Date 2015-02-05

Depends fda

Author Alessia Pini, Simone Vantini

Maintainer Alessia Pini <alessia.pini@polimi.it>

Description Implementation of the Interval Testing Procedure for functional data in different frameworks (i.e., one or two-population frameworks, functional linear models) by means of different basis expansions (i.e., B-spline, Fourier, and phase-amplitude Fourier). The current version of the package requires functional data evaluated on a uniform grid; it automatically projects each function on a chosen functional basis; it performs the entire family of multivariate tests; and, finally, it provides the matrix of the p-values of the previous tests and the vector of the corrected p-values. The functional basis, the coupled or uncoupled scenario, and the kind of test can be chosen by the user. The package provides also a plotting function creating a graphical output of the procedure: the p-value heat-map, the plot of the corrected p-values, and the plot of the functional data.

License GPL-2

NeedsCompilation no

Repository CRAN

Date/Publication 2015-02-05 13:00:51

R topics documented:

fdatest-package	2
ITP1bspline	4
ITP1fourier	6
ITP2bspline	7
ITP2fourier	9
ITP2pafourier	11
ITPaovbspline	13
ITPimage	16

ITPlmbspline	17
NASAtemp	20
plot.ITP1	21
plot.ITP2	22
plot.ITPaov	24
plot.ITPlm	26
summary.ITPaov	28
summary.ITPlm	29

Index	31
--------------	-----------

fdatest-package	<i>Interval Testing Procedure for Functional Data</i>
-----------------	---

Description

Implementation of the Interval Testing Procedure for functional data in different frameworks (i.e., one or two-population frameworks, functional linear models) by means of different basis expansions (i.e., B-spline, Fourier, and phase-amplitude Fourier). The current version of the package requires functional data evaluated on a uniform grid; it automatically projects each function on a chosen functional basis; it performs the entire family of multivariate tests; and, finally, it provides the matrix of the p-values of the previous tests and the vector of the corrected p-values. The functional basis, the coupled or uncoupled scenario, and the kind of test can be chosen by the user. The package provides also a plotting function creating a graphical output of the procedure: the p-value heat-map, the plot of the corrected p-values, and the plot of the functional data.

Details

Package: fdatest
 Type: Package
 Version: 2.1
 Date: 2015-02-05
 License: GPL-2

Author(s)

Alessia Pini, Simone Vantini

Maintainer: Alessia Pini <alessia.pini@polimi.it>

References

A. Pini and S. Vantini (2013). The Interval Testing Procedure: Inference for Functional Data Controlling the Family Wise Error Rate on Intervals. *MOX-report 13/2013*, Politecnico di Milano.

K. Abramowicz, S. De Luna, C. Häger, A. Pini, L. Schelin, and S. Vantini (2015). Distribution-Free Interval-Wise Inference for Functional-on-Scalar Linear Models. *MOX-report 3/2015*, Politecnico di Milano.

See Also

See also [ITP1bspline](#), [ITP1fourier](#), [ITP2bspline](#), [ITP2fourier](#), [ITP2pafourier](#), [ITPlmbspline](#), [ITPaovbspline](#), and [ITPimage](#).

Examples

```
# Importing the NASA temperatures data set
data(NASAtemp)

# Example 1:
# Performing the ITP for one population with the Fourier basis
ITP.result <- ITP1fourier(NASAtemp$milan,maxfrequency=10,B=1000)
# Plotting the results of the ITP
plot(ITP.result)

# Plotting the p-value heatmap
ITPimage(ITP.result)

# Selecting the significant coefficients
which(ITP.result$corrected.pval < 0.05)

# Example 2:
# Performing the ITP for two populations with the B-spline basis
ITP.result <- ITP2bspline(NASAtemp$milan,NASAtemp$paris,nknots=20,B=1000)
# Plotting the results of the ITP
plot(ITP.result)

# Plotting the p-values heatmap
ITPimage(ITP.result)

# Selecting the significant components for the radius at 5% level
which(ITP.result$corrected.pval < 0.05)

# Example 3:
# Fitting and testing a functional-on-scalar linear model
# Defining data and covariates
temperature <- rbind(NASAtemp$milan,NASAtemp$paris)
groups <- c(rep(0,22),rep(1,22))

# Performing the ITP
ITP.result <- ITPlmbspline(temperature ~ groups,B=1000,nknots=20,order=3)
# Summary of the ITP results
summary(ITP.result)

# Plot of the ITP results
layout(1)
```

```
plot(ITP.result,main='NASA data', plot.adjpv = TRUE,xlab='Day',xrange=c(1,365))

# All graphics on the same device
layout(matrix(1:6,nrow=3,byrow=FALSE))
plot(ITP.result,main='NASA data', plot.adjpv = TRUE,xlab='Day',xrange=c(1,365))
```

ITP1bspline

*One population Interval Testing Procedure with B-spline basis***Description**

The function implements the Interval Testing Procedure for testing the center of symmetry of a functional population evaluated on a uniform grid. Data are represented by means of the B-spline expansion and the significance of each basis coefficient is tested with an interval-wise control of the Family Wise Error Rate. The default parameters of the basis expansion lead to the piece-wise interpolating function.

Usage

```
ITP1bspline(data, mu = 0, order = 2, nknots = dim(data)[2], B = 10000)
```

Arguments

data	Pointwise evaluations of the functional data set on a uniform grid. data is a matrix of dimensions $c(n, J)$, with J evaluations on columns and n units on rows.
mu	The center of symmetry under the null hypothesis: either a constant (in this case, a constant function is used) or a J-dimensional vector containing the evaluations on the same grid which data are evaluated. The default is $\mu=0$.
order	Order of the B-spline basis expansion. The default is $order=2$.
nknots	Number of knots of the B-spline basis expansion. The default is $nknots=dim(data)[2]$.
B	The number of iterations of the MC algorithm to evaluate the p-values of the permutation tests. The default is $B=10000$.

Value

ITP1bspline returns an object of class "ITP1".

An object of class "ITP1" is a list containing at least the following components:

basis	String vector indicating the basis used for the first phase of the algorithm. In this case equal to "B-spline".
test	String vector indicating the type of test performed. In this case equal to "1pop".
mu	Center of symmetry under the null hypothesis (as entered by the user).

<code>coeff</code>	Matrix of dimensions $c(n, p)$ of the p coefficients of the B-spline basis expansion. Rows are associated to units and columns to the basis index.
<code>pval</code>	Uncorrected p-values for each basis coefficient.
<code>pval.matrix</code>	Matrix of dimensions $c(p, p)$ of the p-values of the multivariate tests. The element (i, j) of matrix <code>pval.matrix</code> contains the p-value of the joint NPC test of the components $(j, j+1, \dots, j+(p-i))$.
<code>corrected.pval</code>	Corrected p-values for each basis coefficient.
<code>labels</code>	Labels indicating the population membership of each data (in this case always equal to 1).
<code>data.eval</code>	Evaluation on a fine uniform grid of the functional data obtained through the basis expansion.
<code>heatmap.matrix</code>	Heatmap matrix of p-values (used only for plots).

Author(s)

Alessia Pini, Simone Vantini

References

A. Pini and S. Vantini (2013). The Interval Testing Procedure: Inference for Functional Data Controlling the Family Wise Error Rate on Intervals. *MOX-report 13/2013*, Politecnico di Milano.

See Also

See also [ITP1fourier](#), [ITP2bspline](#), [ITP2fourier](#), [ITP2pafourier](#), and [ITPimage](#).

Examples

```
# Importing the NASA temperatures data set
data(NASAtemp)
# Performing the ITP for two populations with the B-spline basis
ITP.result <- ITP1bspline(NASAtemp$paris,mu=4,nknots=50,B=1000)
# Plotting the results of the ITP
plot(ITP.result,xrange=c(0,12),main='Paris temperatures')

# Plotting the p-value heatmap
ITPimage(ITP.result,abscissa.range=c(0,12))

# Selecting the significant components for the radius at 5% level
which(ITP.result$corrected.pval < 0.05)
```

Description

The function implements the Interval Testing Procedure for testing the center of symmetry of a functional population evaluated on a uniform grid. Data are represented by means of the Fourier expansion and the significance of each basis coefficient is tested with an interval-wise control of the Family Wise Error Rate.

Usage

```
ITP1fourier(data, mu = 0, maxfrequency=floor(dim(data)[2]/2), B = 10000)
```

Arguments

data	Pointwise evaluations of the functional data set on a uniform grid. data is a matrix of dimensions $c(n, J)$, with J evaluations on columns and n units on rows.
mu	The center of symmetry under the null hypothesis: either a constant (in this case, a constant function is used) or a J -dimensional vector containing the evaluations on the same grid which data are evaluated. The default is $\mu=0$.
maxfrequency	The maximum frequency to be used in the Fourier basis expansion of data. The default is $\text{floor}(\text{dim}(\text{data})[2]/2)$, leading to an interpolating expansion.
B	The number of iterations of the MC algorithm to evaluate the p-values of the permutation tests. The default is $B=10000$.

Value

ITP1fourier returns an object of `class` "ITP1".

An object of class "ITP1" is a list containing at least the following components:

basis	String vector indicating the basis used for the first phase of the algorithm. In this case equal to "Fourier".
test	String vector indicating the type of test performed. In this case equal to "1pop".
mu	Center of symmetry under the null hypothesis (as entered by the user).
coeff	Matrix of dimensions $c(n, p)$ of the p coefficients of the Fourier basis expansion. Rows are associated to units and columns to the basis index: the first column is a_0 , the following $(p-1)/2$ columns are the a_k coefficients (sine coefficients) and the last $(p-1)/2$ columns the b_k coefficients (cosine coefficients).
pval	Uncorrected p-values for each frequency.
pval.matrix	Matrix of dimensions $c(p, p)$ of the p-values of the multivariate tests. The element (i, j) of matrix <code>pval.matrix</code> contains the p-value of the joint NPC test of the components $(j, j+1, \dots, j+(p-i))$.

corrected.pval Corrected p-values for each frequency.
 labels Labels indicating the population membership of each data (in this case always equal to 1).
 data.eval Evaluation on a fine uniform grid of the functional data obtained through the basis expansion.
 heatmap.matrix Heatmap matrix of p-values (used only for plots).

Author(s)

Alessia Pini, Simone Vantini

References

A. Pini and S. Vantini (2013). The Interval Testing Procedure: Inference for Functional Data Controlling the Family Wise Error Rate on Intervals. *MOX-report 13/2013*, Politecnico di Milano.

See Also

See also [ITP1bspline](#), [ITP2bspline](#), [ITP2fourier](#), [ITP2pafourier](#), and [ITPimage](#).

Examples

```
# Importing the NASA temperatures data set
data(NASAtemp)
# Performing the ITP
ITP.result <- ITP1fourier(NASAtemp$milan,maxfrequency=20,B=1000)
# Plotting the results of the ITP
plot(ITP.result,main='NASA data',xrange=c(1,365),xlab='Day')

# Plotting the p-value heatmap
ITPimage(ITP.result,abscissa.range=c(1,365))

# Selecting the significant coefficients
which(ITP.result$corrected.pval < 0.05)
```

 ITP2bspline

Two populations Interval Testing Procedure with B-spline basis

Description

The function implements the Interval Testing Procedure for testing the difference between two functional populations evaluated on a uniform grid. Data are represented by means of the B-spline basis and the significance of each basis coefficient is tested with an interval-wise control of the Family Wise Error Rate. The default parameters of the basis expansion lead to the piece-wise interpolating function.

Usage

```
ITP2bspline(data1, data2, mu = 0,
            order = 2, nknots = dim(data1)[2], B = 10000, paired = FALSE)
```

Arguments

data1	Pointwise evaluations of the first population's functional data set on a uniform grid. data1 is a matrix of dimensions $c(n1, J)$, with J evaluations on columns and $n1$ units on rows.
data2	Pointwise evaluations of the second population's functional data set on a uniform grid. data2 is a matrix of dimensions $c(n2, J)$, with J evaluations on columns and $n2$ units on rows.
mu	The difference between the first functional population and the second functional population under the null hypothesis. Either a constant (in this case, a constant function is used) or a J -dimensional vector containing the evaluations on the same grid which data are evaluated. The default is $\mu=0$.
order	Order of the B-spline basis expansion. The default is $order=2$.
nknots	Number of knots of the B-spline basis expansion. The default is $nknots=dim(data1)[2]$.
B	The number of iterations of the MC algorithm to evaluate the p-values of the permutation tests. The default is $B=10000$.
paired	A logical indicating whether the test is paired. The default is FALSE.

Value

ITP2bspline returns an object of class "ITP2".

An object of class "ITP2" is a list containing at least the following components:

basis	String vector indicating the basis used for the first phase of the algorithm. In this case equal to "B-spline".
test	String vector indicating the type of test performed. In this case equal to "2pop".
mu	Difference between the first functional population and the second functional population under the null hypothesis (as entered by the user).
paired	Logical indicating whether the test is paired (as entered by the user).
coeff	Matrix of dimensions $c(n, p)$ of the p coefficients of the B-spline basis expansion, with $n=n1+n2$. Rows are associated to units and columns to the basis index. The first $n1$ rows report the coefficients of the first population units and the following $n2$ rows report the coefficients of the second population units
pval	Uncorrected p-values for each basis coefficient.
pval.matrix	Matrix of dimensions $c(p, p)$ of the p-values of the multivariate tests. The element (i, j) of matrix <code>pval.matrix</code> contains the p-value of the joint NPC test of the components $(j, j+1, \dots, j+(p-i))$.
corrected.pval	Corrected p-values for each basis coefficient.
labels	Labels indicating the population membership of each data.
data.eval	Evaluation on a fine uniform grid of the functional data obtained through the basis expansion.
heatmap.matrix	Heatmap matrix of p-values (used only for plots).

Author(s)

Alessia Pini, Simone Vantini

References

A. Pini and S. Vantini (2013). The Interval Testing Procedure: Inference for Functional Data Controlling the Family Wise Error Rate on Intervals. *MOX-report 13/2013*, Politecnico di Milano.

See Also

For tests of comparison between two populations, see [ITP2fourier](#), [ITP2pafourier](#). For different types of ITP-based tests, see [ITP1bspline](#), [ITP1fourier](#), [ITPlmbspline](#), [ITPaovbspline](#) and [ITPimage](#).

Examples

```
# Importing the NASA temperatures data set
data(NASAtemp)
# Performing the ITP
ITP.result <- ITP2bspline(NASAtemp$milan,NASAtemp$paris,nknots=50,B=1000)

# Plotting the results of the ITP
plot(ITP.result,main='NASA data',xrange=c(1,365),xlab='Day')

# Plotting the p-values heatmap
ITPimage(ITP.result,abscissa.range=c(0,12))

# Selecting the significant components at 5% level
which(ITP.result$corrected.pval < 0.05)
```

ITP2fourier

Two populations Interval Testing Procedure with Fourier basis

Description

The function implements the Interval Testing Procedure for testing the difference between two functional populations evaluated on a uniform grid. Data are represented by means of the Fourier basis and the significance of each basis coefficient is tested with an interval-wise control of the Family Wise Error Rate.

Usage

```
ITP2fourier(data1, data2, mu = 0,
            maxfrequency=floor(dim(data1)[2]/2), B = 10000, paired = FALSE)
```

Arguments

<code>data1</code>	Pointwise evaluations of the first population's functional data set on a uniform grid. <code>data1</code> is a matrix of dimensions $c(n1, J)$, with J evaluations on columns and $n1$ units on rows.
<code>data2</code>	Pointwise evaluations of the second population's functional data set on a uniform grid. <code>data2</code> is a matrix of dimensions $c(n2, J)$, with J evaluations on columns and $n2$ units on rows.
<code>mu</code>	The difference between the first functional population and the second functional population under the null hypothesis. Either a constant (in this case, a constant function is used) or a J -dimensional vector containing the evaluations on the same grid which data are evaluated. The default is <code>mu=0</code> .
<code>maxfrequency</code>	The maximum frequency to be used in the Fourier basis expansion of data. The default is <code>floor(dim(data1)[2]/2)</code> , leading to an interpolating expansion.
<code>B</code>	The number of iterations of the MC algorithm to evaluate the p-values of the permutation tests. The default is <code>B=10000</code> .
<code>paired</code>	A logical indicating whether the test is paired. The default is <code>FALSE</code> .

Value

ITP2fourier returns an object of class "ITP2".

An object of class "ITP2" is a list containing at least the following components:

<code>basis</code>	String vector indicating the basis used for the first phase of the algorithm. In this case equal to "Fourier".
<code>test</code>	String vector indicating the type of test performed. in this case equal to "2pop".
<code>mu</code>	Difference between the first functional population and the second functional population under the null hypothesis (as entered by the user).
<code>paired</code>	Logical indicating whether the test is paired (as entered by the user).
<code>coeff</code>	Matrix of dimensions $c(n, p)$ of the p coefficients of the Fourier basis expansion. Rows are associated to units and columns to the basis index: the first $n1$ rows report the coefficients of the first population units and the following $n2$ rows report the coefficients of the second population units; the first column is a_0 , the following $(p-1)/2$ columns are the a_k coefficients (sine coefficients) and the last $(p-1)/2$ columns the b_k coefficients (cosine coefficients).
<code>pval</code>	Uncorrected p-values for each frequency.
<code>pval.matrix</code>	Matrix of dimensions $c(p, p)$ of the p-values of the multivariate tests. The element (i, j) of matrix <code>pval.matrix</code> contains the p-value of the joint NPC test of the frequencies $(j, j+1, \dots, j+(p-i))$.
<code>corrected.pval</code>	Corrected p-values for each frequency.
<code>labels</code>	Labels indicating the population membership of each data.
<code>data.eval</code>	Evaluation on a fine uniform grid of the functional data obtained through the basis expansion.
<code>heatmap.matrix</code>	Heatmap matrix of p-values (used only for plots).

Author(s)

Alessia Pini, Simone Vantini

References

A. Pini and S. Vantini (2013). The Interval Testing Procedure: Inference for Functional Data Controlling the Family Wise Error Rate on Intervals. *MOX-report 13/2013*, Politecnico di Milano.

See Also

See also [ITP2pafourier](#), [ITP2bspline](#), [ITP1fourier](#), [ITP1bspline](#), and [ITPimage](#).

Examples

```
# Importing the NASA temperatures data set
data(NASAtemp)
# Performing the ITP
ITP.result <- ITP2fourier(NASAtemp$milan,NASAtemp$paris,maxfrequency=20,B=1000,paired=TRUE)

# Plotting the results of the ITP
plot(ITP.result,main='NASA data',xrange=c(1,365),xlab='Day')

# Plotting the p-value heatmap
ITPimage(ITP.result,abscissa.range=c(1,365))

# Selecting the significant coefficients
which(ITP.result$corrected.pval < 0.05)
```

ITP2pafourier	<i>Two populations Interval Testing Procedure with Fourier basis (phase-amplitude decomposition)</i>
---------------	--

Description

The function implements the Interval Testing Procedure for testing the difference between two functional populations evaluated on a uniform grid. Data are represented by means of the Fourier basis expansion with the phase-amplitude decomposition and the significance of the amplitude and phase of each frequency is tested with an interval-wise control of the Family Wise Error Rate.

Usage

```
ITP2pafourier(data1, data2,
              maxfrequency=floor(dim(data1)[2]/2), B = 10000, paired = FALSE)
```

Arguments

data1	Pointwise evaluations of the first population's functional data set on a uniform grid. data1 is a matrix of dimensions $c(n1, J)$, with J evaluations on columns and $n1$ units on rows.
data2	Pointwise evaluations of the second population's functional data set on a uniform grid. data2 is a matrix of dimensions $c(n2, J)$, with J evaluations on columns and $n2$ units on rows.
maxfrequency	The maximum frequency to be used in the Fourier basis expansion of data. The default is $\text{floor}(\text{dim}(\text{data1})[2]/2)$, leading to an interpolating expansion.
B	The number of iterations of the MC algorithm to evaluate the p-values of the permutation tests. The default is $B=10000$.
paired	A logical indicating whether the test is paired. The default is FALSE.

Value

ITP2pafourier returns an object of class "ITP2".

An object of class "ITP2" is a list containing at least the following components:

basis	String vector indicating the basis used for the first phase of the algorithm. Equal to "paFourier".
test	String vector indicating the type of test performed. Equal to "2pop".
paired	Logical indicating whether the test is paired (as entered by the user).
coeff_phase	Matrix of dimensions $c(n, p)$ of the p phases of the Fourier basis expansion. Rows are associated to units and columns to frequencies: the first $n1$ rows report the coefficients of the first population units and the following $n2$ rows report the coefficients of the second population units.
coeff_amplitude	Matrix of dimensions $c(n, p)$ of the p amplitudes of the Fourier basis expansion. Rows are associated to units and columns to frequencies: the first $n1$ rows report the coefficients of the first population units and the following $n2$ rows report the coefficients of the second population units.
pval_phase	Uncorrected p-values of the phase tests for each frequency.
pval_amplitude	Uncorrected p-values of the amplitude tests for each frequency.
pval.matrix_phase	Matrix of dimensions $c(p, p)$ of the p-values of the multivariate tests on phase. The element (i, j) of matrix <code>pval.matrix_phase</code> contains the p-value of the joint NPC test of the frequencies $(j, j+1, \dots, j+(p-i))$.
pval.matrix_amplitude	Matrix of dimensions $c(p, p)$ of the p-values of the multivariate tests on amplitude. The element (i, j) of matrix <code>pval.matrix_amplitude</code> contains the p-value of the joint NPC test of the frequencies $(j, j+1, \dots, j+(p-i))$.
corrected.pval_phase	Corrected p-values of the phase tests for each frequency.
corrected.pval_amplitude	Corrected p-values of the amplitude tests for each frequency.

labels	Labels indicating the population membership of each data.
data.eval	Evaluation on a fine uniform grid of the functional data obtained through the basis expansion.
heatmap.matrix_phase	Heatmap matrix of p-values for phase (used only for plots).
heatmap.matrix_amplitude	Heatmap matrix of p-values for amplitude (used only for plots).

Author(s)

Alessia Pini, Simone Vantini

References

A. Pini and S. Vantini (2013). The Interval Testing Procedure: Inference for Functional Data Controlling the Family Wise Error Rate on Intervals. *MOX-report 13/2013*, Politecnico di Milano.

See Also

See also [ITP2fourier](#), [ITP2bspline](#), [ITP1fourier](#), [ITP1bspline](#), and [ITPimage](#).

Examples

```
# Importing the NASA temperatures data set
data(NASAtemp)
# Performing the ITP
ITP.result <- ITP2pafourier(NASAtemp$milan,NASAtemp$paris,maxfrequency=20,B=1000,paired=TRUE)
# Plotting the results of the ITP
plot(ITP.result,main='NASA data',xrange=c(1,365),xlab='Day')

# Plotting the p-value heatmap
ITPimage(ITP.result,abscissa.range=c(1,365))

# Selecting the significant coefficients
which(ITP.result$corrected.pval < 0.05)
```

ITPaovbspline	<i>Interval Testing Procedure for testing Functional analysis of variance with B-spline basis</i>
---------------	---

Description

ITPaovbspline is used to fit and test functional analysis of variance. The function implements the Interval Testing Procedure for testing for significant differences between several functional population evaluated on a uniform grid. Data are represented by means of the B-spline basis and the significance of each basis coefficient is tested with an interval-wise control of the Family Wise Error Rate. The default parameters of the basis expansion lead to the piece-wise interpolating function.

Usage

```
ITPaovbspline(formula, order = 2,
              nknots = dim(model.response(model.frame(formula)))[2],
              B = 10000, method = "residuals")
```

Arguments

formula	An object of class "formula" (or one that can be coerced to that class): a symbolic description of the model to be fitted.
order	Order of the B-spline basis expansion. The default is order=2.
nknots	Number of knots of the B-spline basis expansion. The default is <code>dim(model.response(model.frame(formula)))[2]</code> .
B	The number of iterations of the MC algorithm to evaluate the p-values of the permutation tests. The default is <code>B=10000</code> .
method	Permutation method used to calculate the p-value of permutation tests. Choose "residuals" for the permutations of residuals under the reduced model, according to the Freedman and Lane scheme, and "responses" for the permutation of the responses, according to the Manly scheme.

Value

ITPaovbspline returns an object of class "ITPaov".

The function summary is used to obtain and print a summary of the results.

An object of class "ITPlm" is a list containing at least the following components:

call	The matched call.
design.matrix	The design matrix of the functional-on-scalar linear model.
basis	String vector indicating the basis used for the first phase of the algorithm. In this case equal to "B-spline".
coeff	Matrix of dimensions $c(n, p)$ of the p coefficients of the B-spline basis expansion. Rows are associated to units and columns to the basis index.
coeff.regr	Matrix of dimensions $c(L+1, p)$ of the p coefficients of the B-spline basis expansion of the intercept (first row) and the L effects of the covariates specified in formula. Columns are associated to the basis index.
pval.F	Uncorrected p-values of the functional F-test for each basis coefficient.
pval.matrix.F	Matrix of dimensions $c(p, p)$ of the p-values of the multivariate F-tests. The element (i, j) of matrix <code>pval.matrix</code> contains the p-value of the joint NPC test of the components $(j, j+1, \dots, j+(p-i))$.
corrected.pval.F	Corrected p-values of the functional F-test for each basis coefficient.
pval.factors	Uncorrected p-values of the functional F-tests on each factor of the analysis of variance, separately (rows) and each basis coefficient (columns).

<code>pval.matrix.factors</code>	Array of dimensions $c(L+1, p, p)$ of the p-values of the multivariate F-tests on factors. The element (l, i, j) of array <code>pval.matrix</code> contains the p-value of the joint NPC test on factor l of the components $(j, j+1, \dots, j+(p-i))$.
<code>corrected.pval.factors</code>	Corrected p-values of the functional F-tests on each factor of the analysis of variance (rows) and each basis coefficient (columns).
<code>data.eval</code>	Evaluation on a fine uniform grid of the functional data obtained through the basis expansion.
<code>coeff.regr.eval</code>	Evaluation on a fine uniform grid of the functional regression coefficients.
<code>fitted.eval</code>	Evaluation on a fine uniform grid of the fitted values of the functional regression.
<code>residuals.eval</code>	Evaluation on a fine uniform grid of the residuals of the functional regression.
<code>R2.eval</code>	Evaluation on a fine uniform grid of the functional R-squared of the regression.
<code>heatmap.matrix.F</code>	Heatmap matrix of p-values of functional F-test (used only for plots).
<code>heatmap.matrix.factors</code>	Heatmap matrix of p-values of functional F-tests on each factor of the analysis of variance (used only for plots).

Author(s)

Alessia Pini, Simone Vantini

References

- D. Freedman and D. Lane (1983). A Nonstochastic Interpretation of Reported Significance Levels. *Journal of Business & Economic Statistics* 1.4, 292-298.
- B. F. J. Manly (2006). Randomization, *Bootstrap and Monte Carlo Methods in Biology*. Vol. 70. CRC Press.
- A. Pini and S. Vantini (2013). The Interval Testing Procedure: Inference for Functional Data Controlling the Family Wise Error Rate on Intervals. *MOX-report 13/2013*, Politecnico di Milano.
- K. Abramowicz, S. De Luna, C. Häger, A. Pini, L. Schelin, and S. Vantini (2015). Distribution-Free Interval-Wise Inference for Functional-on-Scalar Linear Models. *MOX-report 3/2015*, Politecnico di Milano.

See Also

See [summary.ITPaov](#) for summaries and [plot.ITPaov](#) for plotting the results.

See also [ITPlmbspline](#) to fit and test a functional-on-scalar linear model applying the ITP, and [ITP1bspline](#), [ITP2bspline](#), [ITP2fourier](#), [ITP2pafourier](#) for one-population and two-population tests.

Examples

```

# Importing the NASA temperatures data set
data(NASAtemp)

temperature <- rbind(NASAtemp$milan,NASAtemp$paris)
groups <- c(rep(0,22),rep(1,22))

# Performing the ITP
ITP.result <- ITPaovbspline(temperature ~ groups,B=1000,nknots=20,order=3)

# Summary of the ITP results
summary(ITP.result)

# Plot of the ITP results
layout(1)
plot(ITP.result)

# All graphics on the same device
layout(matrix(1:4,nrow=2,byrow=FALSE))
plot(ITP.result,main='NASA data', plot.adjpv = TRUE,xlab='Day',xrange=c(1,365))

```

ITPimage

*Plot of the Interval Testing Procedure results***Description**

Plotting function creating a graphical output of the ITP: the p-value heat-map, the plot of the corrected p-values, and the plot of the functional data.

Usage

```
ITPimage(ITP.result, alpha = 0.05, abscissa.range = c(0, 1), nlevel = 20)
```

Arguments

ITP.result	Results of the ITP, as created by ITP1bspline , ITP1fourier , ITP2bspline , ITP2fourier , and ITP2pafourier .
alpha	Level of the hypothesis test. The default is alpha=0.05.
abscissa.range	Range of the plot abscissa. The default is c(0, 1).
nlevel	Number of desired color levels for the p-value heatmap. The default is nlevel=20.

Value

No value returned. The function produces a graphical output of the ITP results: the p-value heatmap, a plot of the corrected p-values and the plot of the functional data. The basis components selected as significant by the test at level alpha are highlighted in the plot of the corrected p-values by a gray area.

Author(s)

Alessia pini, Simone Vantini

References

A. Pini and S. Vantini (2013). The Interval Testing Procedure: Inference for Functional Data Controlling the Family Wise Error Rate on Intervals. *MOX-report 13/2013*, Politecnico di Milano.

See Also

See [plot.ITP1](#), [plot.ITP2](#), [plot.ITPlm](#), and [plot.ITPaov](#) for the plot method applied to the ITP results of one- and two-population tests, linear models, and ANOVA, respectively.

See also [ITP1bspline](#), [ITP1fourier](#), [ITP2bspline](#), [ITP2fourier](#), and [ITP2pafourier](#) for applying the ITP.

Examples

```
# Importing the NASA temperatures data set
data(NASAtemp)

# Performing the ITP for two populations with the B-spline basis
ITP.result <- ITP2bspline(NASAtemp$milan,NASAtemp$paris,nknots=20,B=1000)

# Plotting the results of the ITP
ITPimage(ITP.result,abscissa.range=c(0,12))

# Selecting the significant components for the radius at 5% level
which(ITP.result$corrected.pval < 0.05)
```

ITPlmbspline	<i>Interval Testing Procedure for testing Functional-on-Scalar Linear Models with B-spline basis</i>
--------------	--

Description

ITPlmbspline is used to fit and test functional linear models. It can be used to carry out regression, and analysis of variance. The function implements the Interval Testing Procedure for testing the significance of the effects of scalar covariates on a functional population evaluated on a uniform grid. Data are represented by means of the B-spline basis and the significance of each basis coefficient is tested with an interval-wise control of the Family Wise Error Rate. The default parameters of the basis expansion lead to the piece-wise interpolating function.

Usage

```
ITPlmbspline(formula, order = 2,
              nknots = dim(model.response(model.frame(formula)))[2],
              B = 10000, method = "residuals")
```

Arguments

formula	An object of class "formula" (or one that can be coerced to that class): a symbolic description of the model to be fitted.
order	Order of the B-spline basis expansion. The default is order=2.
nknots	Number of knots of the B-spline basis expansion. The default is <code>dim(model.response(model.frame(formula)))[2]</code> .
B	The number of iterations of the MC algorithm to evaluate the p-values of the permutation tests. The default is <code>B=10000</code> .
method	Permutation method used to calculate the p-value of permutation tests. Choose "residuals" for the permutations of residuals under the reduced model, according to the Freedman and Lane scheme, and "responses" for the permutation of the responses, according to the Manly scheme.

Value

ITPlmbspline returns an object of class "ITPlm".

The function summary is used to obtain and print a summary of the results.

An object of class "ITPlm" is a list containing at least the following components:

call	The matched call.
design.matrix	The design matrix of the functional-on-scalar linear model.
basis	String vector indicating the basis used for the first phase of the algorithm. In this case equal to "B-spline".
coeff	Matrix of dimensions $c(n, p)$ of the p coefficients of the B-spline basis expansion. Rows are associated to units and columns to the basis index.
coeff.regr	Matrix of dimensions $c(L+1, p)$ of the p coefficients of the B-spline basis expansion of the intercept (first row) and the L effects of the covariates specified in formula. Columns are associated to the basis index.
pval.F	Uncorrected p-values of the functional F-test for each basis coefficient.
pval.matrix.F	Matrix of dimensions $c(p, p)$ of the p-values of the multivariate F-tests. The element (i, j) of matrix <code>pval.matrix</code> contains the p-value of the joint NPC test of the components $(j, j+1, \dots, j+(p-i))$.
corrected.pval.F	Corrected p-values of the functional F-test for each basis coefficient.
pval.t	Uncorrected p-values of the functional t-tests for each partial regression coefficient including the intercept (rows) and each basis coefficient (columns).
pval.matrix.t	Array of dimensions $c(L+1, p, p)$ of the p-values of the multivariate t-tests. The element (l, i, j) of array <code>pval.matrix</code> contains the p-value of the joint NPC test on covariate l of the components $(j, j+1, \dots, j+(p-i))$.
corrected.pval.t	Corrected p-values of the functional t-tests for each partial regression coefficient including the intercept (rows) and each basis coefficient (columns).
data.eval	Evaluation on a fine uniform grid of the functional data obtained through the basis expansion.

<code>coeff.regr.eval</code>	Evaluation on a fine uniform grid of the functional regression coefficients.
<code>fitted.eval</code>	Evaluation on a fine uniform grid of the fitted values of the functional regression.
<code>residuals.eval</code>	Evaluation on a fine uniform grid of the residuals of the functional regression.
<code>R2.eval</code>	Evaluation on a fine uniform grid of the functional R-squared of the regression.
<code>heatmap.matrix.F</code>	Heatmap matrix of p-values of functional F-test (used only for plots).
<code>heatmap.matrix.t</code>	Heatmap matrix of p-values of functional t-tests (used only for plots).

Author(s)

Alessia Pini, Simone Vantini

References

- D. Freedman and D. Lane (1983). A Nonstochastic Interpretation of Reported Significance Levels. *Journal of Business & Economic Statistics* 1.4, 292-298.
- B. F. J. Manly (2006). Randomization, *Bootstrap and Monte Carlo Methods in Biology*. Vol. 70. CRC Press.
- A. Pini and S. Vantini (2013). The Interval Testing Procedure: Inference for Functional Data Controlling the Family Wise Error Rate on Intervals. *MOX-report 13/2013*, Politecnico di Milano.
- K. Abramowicz, S. De Luna, C. Häger, A. Pini, L. Schelin, and S. Vantini (2015). Distribution-Free Interval-Wise Inference for Functional-on-Scalar Linear Models. *MOX-report 3/2015*, Politecnico di Milano.

See Also

See [summary.ITPlm](#) for summaries and [plot.ITPlm](#) for plotting the results.

See also [ITPaovbspline](#) to fit and test a functional analysis of variance applying the ITP, and [ITP1bspline](#), [ITP2bspline](#), [ITP2fourier](#), [ITP2pafourier](#) for one-population and two-population tests.

Examples

```
# Importing the NASA temperatures data set
data(NASAtemp)

# Defining the covariates
temperature <- rbind(NASAtemp$milan,NASAtemp$paris)
groups <- c(rep(0,22),rep(1,22))

# Performing the ITP
ITP.result <- ITP1mbspline(temperature ~ groups,B=1000,nknots=20)
# Summary of the ITP results
summary(ITP.result)

# Plot of the ITP results
```

```
layout(1)
plot(ITP.result,main='NASA data', plot.adjpv = TRUE,xlab='Day',xrange=c(1,365))

# All graphics on the same device
layout(matrix(1:6,nrow=3,byrow=FALSE))
plot(ITP.result,main='NASA data', plot.adjpv = TRUE,xlab='Day',xrange=c(1,365))
```

NASAtemp

NASA daily temperatures data set

Description

It contains the daily mean temperatures registered from July 1983 to June 2005 and stored in the NASA database Earth Surface Meteorology for Solar Energy of two different geographical locations: the region (45-46 North, 9-10 East), including the city of Milan (Italy), and the region (48-49 North, 2-3 East), including the city of Paris (France).

Usage

```
data(NASAtemp)
```

Format

List of 2 elements:

- `milan` Matrix of dimensions `c(22, 365)` containing the daily mean temperatures of the region (45-46 North, 9-10 East), including the city of Milan (Italy) registered from July 1983 to June 2005 (22 years).
- `paris` Matrix of dimensions `c(22, 365)` containing the daily mean temperatures of the region (48-49 North, 2-3 East), including the city of Paris (France) registered from July 1983 to June 2005 (22 years).

Source

These data were obtained from the NASA Langley Research Center Atmospheric Science Data Center Surface meteorological and Solar Energy (SSE) web portal supported by the NASA LaRC POWER Project. Data are freely available at: NASA Surface Meteorology and Solar Energy, A Renewable Energy Resource web site (release 6.0): <http://eosweb.larc.nasa.gov>

Examples

```
data(NASAtemp)
## Not run:

matplot(t(NASAtemp$milan), type='l')
matplot(t(NASAtemp$paris), type='l')
```

```
## End(Not run)
```

```
plot.ITP1          Plotting ITP results for one-population tests
```

Description

plot method for class "ITP1". Plotting function creating a graphical output of the ITP for the test of the mean of one population: functional data and ITP-adjusted p-values are plotted.

Usage

```
## S3 method for class 'ITP1'
plot(x, xrange = c(0, 1), alpha1 = 0.05, alpha2 = 0.01,
     ylab = "Functional Data", main = NULL, lwd = 1, col = 1,
     pch = 16, ylim = range(object$data.eval), ...)
```

Arguments

x	The object to be plotted. An object of class "ITP1", that is, a result of an ITP for comparison between two populations. Usually a call to ITP1bspline or ITP1fourier .
xrange	Range of the x axis.
alpha1	First level of significance used to select and display significant differences. Default is $\alpha_1 = 0.05$.
alpha2	Second level of significance used to select and display significant differences. Default is $\alpha_1 = 0.01$. α_1 and α_2 are s.t. $\alpha_2 < \alpha_1$. Otherwise the two values are switched.
ylab	Label of y axis of the plot of functional data. Default is "Functional Data".
main	An overall title for the plots (it will be pasted to "Functional Data" for the first plot and "adjusted p-values" for the second plot).
lwd	Line width for the plot of functional data.
col	Color used to plot the functional data.
pch	Point character for the plot of adjusted p-values.
ylim	Range of the y axis.
...	Additional plotting arguments that can be used with function plot, such as graphical parameters (see par).

Value

No value returned. The function produces a graphical output of the ITP results: the plot of the functional data and the one of the adjusted p-values. The basis components selected as significant by the test at level α_1 and α_2 are highlighted in the plot of the corrected p-values and in the one of functional data (in case the test is based on a local basis, such as B-splines) by gray areas (light and dark gray, respectively).

Author(s)

Alessia Pini, Simone Vantini

References

A. Pini and S. Vantini (2013). The Interval Testing Procedure: Inference for Functional Data Controlling the Family Wise Error Rate on Intervals. *MOX-report 13/2013*, Politecnico di Milano.

See Also

[ITPimage](#) for the plot of p-values heatmaps.

See also [ITP1bspline](#) and [ITP1fourier](#) to perform the ITP to test for the mean of a functional populations. See [plot.ITP2](#) and [plot.ITP1m](#) for the plot method applied to the ITP results of two-population tests and linear models, respectively.

Examples

```
# Importing the NASA temperatures data set
data(NASAtemp)

# Performing the ITP for one population with the B-spline basis
ITP.result.bspline <- ITP1bspline(NASAtemp$paris,mu=4,nknots=50,B=1000)
# Plotting the results of the ITP
plot(ITP.result.bspline,xlab='Day',xrange=c(0,365),main='NASA data')
# Selecting the significant components for the radius at 5% level
which(ITP.result.bspline$corrected.pval < 0.05)
```

plot.ITP2

Plotting ITP results for two-population tests

Description

plot method for class "ITP2". Plotting function creating a graphical output of the ITP for the test of comparison between two populations: functional data and ITP-adjusted p-values are plotted.

Usage

```
## S3 method for class 'ITP2'
plot(x, xrange = c(0, 1), alpha1 = 0.05, alpha2 = 0.01,
     ylab = "Functional Data", main = NULL, lwd = 1,
     col = c(1, 2), pch = 16, ylim = range(object$data.eval), ...)
```

Arguments

x	The object to be plotted. An object of class "ITP2", that is, a result of an ITP for comparison between two populations. Usually a call to ITP2bspline , ITP2fourier or ITP2pafourier .
xrange	Range of the x axis.
alpha1	First level of significance used to select and display significant differences. Default is $\alpha_1 = 0.05$.
alpha2	Second level of significance used to select and display significant differences. Default is $\alpha_1 = 0.01$. α_1 and α_2 are s.t. $\alpha_2 < \alpha_1$. Otherwise the two values are switched.
ylab	Label of y axis of the plot of functional data. Default is "Functional Data".
main	An overall title for the plots (it will be pasted to "Functional Data" for the first plot and "adjusted p-values" for the second plot).
lwd	Line width for the plot of functional data.
col	Color used to plot the functional data.
pch	Point character for the plot of adjusted p-values.
ylim	Range of the y axis.
...	Additional plotting arguments that can be used with function plot, such as graphical parameters (see par).

Value

No value returned. The function produces a graphical output of the ITP results: the plot of the functional data and the one of the adjusted p-values. The basis components selected as significant by the test at level α_1 and α_2 are highlighted in the plot of the corrected p-values and in the one of functional data (in case the test is based on a local basis, such as B-splines) by gray areas (light and dark gray, respectively). In the case of a Fourier basis with amplitude and phase decomposition, two plots of adjusted p-values are done, one for phase and one for amplitude.

Author(s)

Alessia Pini, Simone Vantini

References

A. Pini and S. Vantini (2013). The Interval Testing Procedure: Inference for Functional Data Controlling the Family Wise Error Rate on Intervals. *MOX-report 13/2013*, Politecnico di Milano.

See Also

[ITPimage](#) for the plot of p-values heatmaps.

See also [ITP2bspline](#), [ITP2fourier](#), [ITP2pafourier](#) to perform the ITP to test for differences between two populations. See [plot.ITP1](#) and [plot.ITP1m](#) for the plot method applied to the ITP results of one-population tests and a linear models, respectively.

Examples

```
# Importing the NASA temperatures data set
data(NASAtemp)

# Performing the ITP for two populations with the B-spline basis
ITP.result.bspline <- ITP2bspline(NASAtemp$milan,NASAtemp$paris,nknots=30,B=1000)
# Plotting the results of the ITP
plot(ITP.result.bspline,xlab='Day',xrange=c(1,365),main='NASA data')

# Selecting the significant components for the radius at 5% level
which(ITP.result.bspline$corrected.pval < 0.05)
```

plot.ITPaov

Plotting ITP results for functional analysis of variance testing

Description

plot method for class "ITPaov". Plotting function creating a graphical output of the ITP for the test on a functional analysis of variance: functional data, and ITP-adjusted p-values of the F-tests on the whole model and on each factor are plotted.

Usage

```
## S3 method for class 'ITPaov'
plot(x,xrange=c(0,1), alpha1=0.05, alpha2=0.01,
      plot.adjpv=FALSE,ylim=range(x$data.eval),col=1,
      ylab='Functional Data',main=NULL,lwd=1,pch=16,...)
```

Arguments

x	The object to be plotted. An object of class "ITPaov", usually, a result of a call to ITPaovbspline .
xrange	Range of the x axis.
alpha1	First level of significance used to select and display significant effects. Default is $\alpha_1 = 0.05$.
alpha2	Second level of significance used to select and display significant effects. Default is $\alpha_2 = 0.01$. α_1 and α_2 are s.t. $\alpha_2 < \alpha_1$. Otherwise the two values are switched.
plot.adjpv	A logical indicating whether the plots of adjusted p-values have to be done. Default is <code>plot.adjpv = FALSE</code> .
col	Colors for the plot of functional data. Default is <code>col = 1</code> .
ylim	Range of the y axis. Default is <code>ylim = range(x\$data.eval)</code> .
ylab	Label of y axis of the plot of functional data. Default is "Functional Data".

main	An overall title for the plots (it will be pasted to "Functional Data and F-test" for the first plot and "factor" for the other plots).
lwd	Line width for the plot of functional data. Default is lwd=16.
pch	Point character for the plot of adjusted p-values. Default is pch=16.
...	Additional plotting arguments that can be used with function plot, such as graphical parameters (see <code>par</code>).

Value

No value returned. The function produces a graphical output of the ITP results: the plot of the functional data, functional regression coefficients, and ITP-adjusted p-values of the F-tests on the whole model and on each factor. The basis components selected as significant by the tests at level `alpha1` and `alpha2` are highlighted in the plot of the corrected p-values and in the one of functional data by gray areas (light and dark gray, respectively). The first plot reports the gray areas corresponding to a significant F-test on the whole model. The remaining plots report the gray areas corresponding to significant F-tests on each factor (with colors corresponding to the levels of the factor).

Author(s)

Alessia Pini, Simone Vantini

References

- A. Pini and S. Vantini (2013). The Interval Testing Procedure: Inference for Functional Data Controlling the Family Wise Error Rate on Intervals. *MOX-report 13/2013*, Politecnico di Milano.
- K. Abramowicz, S. De Luna, C. Häger, A. Pini, L. Schelin, and S. Vantini (2015). Distribution-Free Interval-Wise Inference for Functional-on-Scalar Linear Models. *MOX-report 3/2015*, Politecnico di Milano.

See Also

See also [ITPaovbspline](#) to fit and test a functional analysis of variance applying the ITP, and [summary.ITPaov](#) for summaries. See [plot.ITPlm](#), [plot.ITP1](#), and [plot.ITP2](#) for the plot method applied to the ITP results of functional-on-scalar linear models, one-population and two-population, respectively.

Examples

```
# Importing the NASA temperatures data set
data(NASAtemp)

temperature <- rbind(NASAtemp$milan,NASAtemp$paris)
groups <- c(rep(0,22),rep(1,22))

# Performing the ITP
ITP.result <- ITPaovbspline(temperature ~ groups,B=1000,nknots=20,order=3)

# Summary of the ITP results
summary(ITP.result)
```

```

# Plot of the ITP results
layout(1)
plot(ITP.result)

# All graphics on the same device
layout(matrix(1:4,nrow=2,byrow=FALSE))
plot(ITP.result,main='NASA data', plot.adjpv = TRUE,xlab='Day',xrange=c(1,365))

```

plot.ITPlm

Plotting ITP results for functional-on-scalar linear model testing

Description

plot method for class "ITPlm". Plotting function creating a graphical output of the ITP for the test on a functional-on-scalar linear model: functional data, functional coefficients and ITP-adjusted p-values for the F-test and t-tests are plotted.

Usage

```

## S3 method for class 'ITPlm'
plot(x, xrange = c(0, 1), alpha1 = 0.05, alpha2 = 0.01,
     plot.adjpv = FALSE, col = c(1, rainbow(dim(x$corrected.pval.t)[1])),
     ylim = range(x$data.eval), ylab = "Functional Data",
     main = NULL, lwd = 1, pch = 16, ...)

```

Arguments

x	The object to be plotted. An object of class "ITPlm", usually, a result of a call to ITPlmbspline .
xrange	Range of the x axis.
alpha1	First level of significance used to select and display significant effects. Default is $\alpha_1 = 0.05$.
alpha2	Second level of significance used to select and display significant effects. Default is $\alpha_1 = 0.01$. α_1 and α_2 are s.t. $\alpha_2 < \alpha_1$. Otherwise the two values are switched.
plot.adjpv	A logical indicating whether the plots of adjusted p-values have to be done. Default is <code>plot.adjpv = FALSE</code> .
col	Vector of colors for the plot of functional data (first element), and functional coefficients (following elements). Default is <code>col = c(1, rainbow(dim(x\$corrected.pval.t)[1]))</code> .
ylim	Range of the y axis. Default is <code>ylim = range(x\$data.eval)</code> .
ylab	Label of y axis of the plot of functional data. Default is "Functional Data".
main	An overall title for the plots (it will be pasted to "Functional Data and F-test" for the first plot and "t-test" for the other plots).

lwd	Line width for the plot of functional data. Default is lwd=16.
pch	Point character for the plot of adjusted p-values. Default is pch=16.
...	Additional plotting arguments that can be used with function plot, such as graphical parameters (see par).

Value

No value returned. The function produces a graphical output of the ITP results: the plot of the functional data, functional regression coefficients, and ITP-adjusted p-values for the F-test and t-tests. The basis components selected as significant by the tests at level `alpha1` and `alpha2` are highlighted in the plot of the corrected p-values and in the one of functional data by gray areas (light and dark gray, respectively). The plot of functional data reports the gray areas corresponding to a significant F-test. The plots of functional regression coefficients report the gray areas corresponding to significant t-tests for the corresponding covariate.

Author(s)

Alessia Pini, Simone Vantini

References

- A. Pini and S. Vantini (2013). The Interval Testing Procedure: Inference for Functional Data Controlling the Family Wise Error Rate on Intervals. *MOX-report 13/2013*, Politecnico di Milano.
- K. Abramowicz, S. De Luna, C. Häger, A. Pini, L. Schelin, and S. Vantini (2015). Distribution-Free Interval-Wise Inference for Functional-on-Scalar Linear Models. *MOX-report 3/2015*, Politecnico di Milano.

See Also

See also [ITPlmbspline](#) to fit and test a functional-on-scalar linear model applying the ITP, and [summary.ITPlm](#) for summaries. See [plot.ITPaov](#), [plot.ITP1](#), and [plot.ITP2](#) for the plot method applied to the ITP results of functional analysis of variance, one-population and two-population, respectively.

Examples

```
# Importing the NASA temperatures data set
data(NASAtemp)

data <- rbind(NASAtemp$milan,NASAtemp$paris)
lab <- c(rep(0,22),rep(1,22))

# Performing the ITP
ITP.result <- ITPlmbspline(data ~ lab,B=1000,nknots=20,order=3)
# Summary of the ITP results
summary(ITP.result)

# Plot of the ITP results
layout(1)
plot(ITP.result,main='NASA data',xlab='Day',xrange=c(1,365))
```

```
# Plots of the adjusted p-values
plot(ITP.result,main='NASA data', plot.adjpv = TRUE,xlab='Day',xrange=c(1,365))

# To have all plots in one device
layout(matrix(1:6,nrow=3,byrow=FALSE))
plot(ITP.result,main='NASA data', plot.adjpv = TRUE,xlab='Day',xrange=c(1,365))
```

summary.ITPaov

Summarizing Functional Analysis of Variance Fits

Description

summary method for class "ITPaov".

Usage

```
## S3 method for class 'ITPaov'
summary(object, ...)
```

Arguments

object An object of class "ITPaov", usually, a result of a call to [ITPaovbspline](#).
... Further arguments passed to or from other methods.

Value

The function summary.ITPaov computes and returns a list of summary statistics of the fitted functional analysis of variance given in object, using the component "call" from its arguments, plus:

factors	A $L \times 1$ matrix with columns for the factors of ANOVA, and corresponding (two-sided) ITP-adjusted minimum p-values of the corresponding tests of significance (i.e., the minimum p-value over all p basis components used to describe functional data).
R2	Range of the functional R-squared.
ftest	ITP-adjusted minimum p-value of functional F-test.

Author(s)

Alessia Pini, Simone Vantini

References

A. Pini and S. Vantini (2013). The Interval Testing Procedure: Inference for Functional Data Controlling the Family Wise Error Rate on Intervals. *MOX-report 13/2013*, Politecnico di Milano.

K. Abramowicz, S. De Luna, C. Häger, A. Pini, L. Schelin, and S. Vantini (2015). Distribution-Free Interval-Wise Inference for Functional-on-Scalar Linear Models. *MOX-report 3/2015*, Politecnico di Milano.

See Also

See [ITPaovbspline](#) for fitting and testing the functional ANOVA and [plot.ITPaov](#) for plots. See also [ITPlmbspline](#), [ITP1bspline](#), [ITP2bspline](#), [ITP2fourier](#), [ITP2pafourier](#).

Examples

```
# Importing the NASA temperatures data set
data(NASAtemp)

temperature <- rbind(NASAtemp$milan,NASAtemp$paris)
groups <- c(rep(0,22),rep(1,22))

# Performing the ITP
ITP.result <- ITPaovbspline(temperature ~ groups,B=1000,nknots=20,order=3)

# Summary of the ITP results
summary(ITP.result)
```

summary.ITPlm

Summarizing Functional-on-Scalar Linear Model Fits

Description

summary method for class "ITPlm".

Usage

```
## S3 method for class 'ITPlm'
summary(object, ...)
```

Arguments

object An object of class "ITPlm", usually, a result of a call to [ITPlmbspline](#).
... Further arguments passed to or from other methods.

Value

The function `summary.ITPlm` computes and returns a list of summary statistics of the fitted functional-on-scalar linear model given in `object`, using the component "call" from its arguments, plus:

<code>ttest</code>	A $L+1 \times 1$ matrix with columns for the functional regression coefficients, and corresponding (two-sided) ITP-adjusted minimum p-values of t-tests (i.e., the minimum p-value over all p basis components used to describe functional data).
<code>R2</code>	Range of the functional R-squared.
<code>fctest</code>	ITP-adjusted minimum p-value of functional F-test.

Author(s)

Alessia Pini, Simone Vantini

References

A. Pini and S. Vantini (2013). The Interval Testing Procedure: Inference for Functional Data Controlling the Family Wise Error Rate on Intervals. *MOX-report 13/2013*, Politecnico di Milano.

K. Abramowicz, S. De Luna, C. Häger, A. Pini, L. Schelin, and S. Vantini (2015). Distribution-Free Interval-Wise Inference for Functional-on-Scalar Linear Models. *MOX-report 3/2015*, Politecnico di Milano.

See Also

See [ITPlmbspline](#) for fitting and testing the functional linear model and [plot.ITPlm](#) for plots. See also [ITPaovbspline](#), [ITP1bspline](#), [ITP2bspline](#), [ITP2fourier](#), [ITP2pafourier](#).

Examples

```
# Importing the NASA temperatures data set
data(NASAtemp)

temperature <- rbind(NASAtemp$milan,NASAtemp$paris)
groups <- c(rep(0,22),rep(1,22))

# Performing the ITP
ITP.result <- ITPlmbspline(temperature ~ groups, B=1000,nknots=20)

# Summary of the ITP results
summary(ITP.result)
```

Index

*Topic **\textasciitildekwd1**

- ITP1bspline, 4
- ITP1fourier, 6
- ITP2bspline, 7
- ITP2fourier, 9
- ITP2pafourier, 11
- ITPaovbspline, 13
- ITPimage, 16
- ITPlmbspline, 17
- plot.ITP1, 21
- plot.ITP2, 22
- plot.ITPaov, 24
- plot.ITPlm, 26
- summary.ITPaov, 28
- summary.ITPlm, 29

*Topic **\textasciitildekwd2**

- ITP1bspline, 4
- ITP1fourier, 6
- ITP2bspline, 7
- ITP2fourier, 9
- ITP2pafourier, 11
- ITPaovbspline, 13
- ITPimage, 16
- ITPlmbspline, 17
- plot.ITP1, 21
- plot.ITP2, 22
- plot.ITPaov, 24
- plot.ITPlm, 26
- summary.ITPaov, 28
- summary.ITPlm, 29

*Topic **datasets**

- NASAtemp, 20

*Topic **package**

- fdatest-package, 2

class, 4, 6, 8, 10, 12, 14, 18

fdatest (fdatest-package), 2

fdatest-package, 2

formula, 14, 18

ITP1bspline, 3, 4, 7, 9, 11, 13, 15–17, 19, 21, 22, 29, 30

ITP1fourier, 3, 5, 6, 9, 11, 13, 16, 17, 21, 22

ITP2bspline, 3, 5, 7, 7, 11, 13, 15–17, 19, 23, 29, 30

ITP2fourier, 3, 5, 7, 9, 9, 13, 15–17, 19, 23, 29, 30

ITP2pafourier, 3, 5, 7, 9, 11, 11, 15–17, 19, 23, 29, 30

ITPaovbspline, 3, 9, 13, 19, 24, 25, 28–30

ITPimage, 3, 5, 7, 9, 11, 13, 16, 22, 23

ITPlmbspline, 3, 9, 15, 17, 26, 27, 29, 30

NASAtemp, 20

par, 21, 23, 25, 27

plot.ITP1, 17, 21, 23, 25, 27

plot.ITP2, 17, 22, 22, 25, 27

plot.ITPaov, 15, 17, 24, 27, 29

plot.ITPlm, 17, 19, 22, 23, 25, 26, 30

summary.ITPaov, 15, 25, 28

summary.ITPlm, 19, 27, 29