

# Package ‘hsstan’

September 22, 2019

**Type** Package

**Title** Hierarchical Shrinkage Stan Models for Biomarker Selection

**Version** 0.6

**Date** 2019-09-14

**Description** Linear and logistic regression models penalized with hierarchical shrinkage priors for selection of biomarkers (or more general variable selection), which can be fitted using Stan (Carpenter et al. (2017) <doi:10.18637/jss.v076.i01>). It implements the horseshoe and regularized horseshoe priors (Piiironen and Vehtari (2017) <doi:10.1214/17-EJS1337SI>), as well as the projection predictive selection approach to recover a sparse set of predictive biomarkers (Piiironen, Paasiniemi and Vehtari (2018) <arXiv:1810.02406>).

**License** GPL-3

**URL** <https://github.com/mcol/hsstan>

**BugReports** <https://github.com/mcol/hsstan/issues>

**LazyData** yes

**Biarch** true

**Depends** R (>= 3.6)

**Imports** ggplot2, loo (>= 2.1.0), parallel, pROC, Rcpp, methods, rstan (>= 2.18.1), rstantools (>= 1.5.1), stats, utils

**LinkingTo** BH (>= 1.66.0.1), Rcpp (>= 0.12.15), RcppEigen (>= 0.3.3.4.0), StanHeaders (>= 2.17.2), rstan (>= 2.18.1)

**Suggests** testthat (>= 2.1.0)

**ByteCompile** yes

**NeedsCompilation** yes

**Encoding** UTF-8

**RoxygenNote** 6.1.1

**Author** Marco Colombo [aut, cre] (<<https://orcid.org/0000-0001-6672-0623>>), Paul McKeigue [aut] (<<https://orcid.org/0000-0002-5217-1034>>), Athina Spiliopoulou [ctb] (<<https://orcid.org/0000-0002-5929-6585>>)

**Maintainer** Marco Colombo <mar.colombo13@gmail.com>

**Repository** CRAN

**Date/Publication** 2019-09-22 10:40:02 UTC

## R topics documented:

hsstan-package . . . . .	2
bayes_R2.hsstan . . . . .	3
diabetes . . . . .	4
hsstan . . . . .	5
kfold.hsstan . . . . .	7
log_lik.hsstan . . . . .	8
loo.hsstan . . . . .	9
nsamples.hsstan . . . . .	10
plot.projsel . . . . .	10
posterior_interval.hsstan . . . . .	11
posterior_linpred.hsstan . . . . .	12
posterior_performance . . . . .	13
posterior_predict.hsstan . . . . .	13
posterior_summary . . . . .	14
print.hsstan . . . . .	15
projsel . . . . .	16
sampler.stats . . . . .	17
summary.hsstan . . . . .	17
<b>Index</b>	<b>19</b>

---

hsstan-package	<i>Hierarchical shrinkage Stan models for biomarker selection</i>
----------------	---

---

## Description

The **hsstan** package provides linear and logistic regression models penalized with hierarchical shrinkage priors for selection of biomarkers. Models are fitted with Stan (Carpenter et al. (2017)), which allows to perform full Bayesian inference.

## Details

The package implements the horseshoe and regularized horseshoe priors (Piironen and Vehtari (2017)), and the projection predictive selection approach to recover a sparse set of predictive biomarkers (Piironen, Paasiniemi and Vehtari (2018)).

The approach is particularly suited to selection from high-dimensional panels of biomarkers, such as those that can be measured by MSMS or similar technologies (Colombo, Valo, McGurnaghan et al. (2019)).

## References

- B. Carpenter et al. (2017), Stan: a probabilistic programming language, *Journal of Statistical Software*, 76 (1). <https://doi.org/10.18637/jss.v076.i01>
- J. Piironen and A. Vehtari (2017), Sparsity information and regularization in the horseshoe and other shrinkage priors, *Electronic Journal of Statistics*, 11 (2), 5018-5051. <https://doi.org/10.1214/17-EJS1337SI>
- J. Piironen, M. Paasiniemi and A. Vehtari (2018), Projective inference in high-dimensional problems: prediction and feature selection, *ArXiv preprint*. <https://arxiv.org/abs/1810.02406>
- M. Colombo, E. Valo, S.J. McGurnaghan et al. (2019), Biomarkers associated with progression of renal disease in type 1 diabetes, *Diabetologia*, 62 (9), 1616-1627. <https://doi.org/10.1007/s00125-019-4915-0>

---

bayes_R2.hsstan	<i>Bayesian and LOO-adjusted R-squared</i>
-----------------	--

---

## Description

Compute the Bayesian and the LOO-adjusted R-squared from the posterior samples. For Bayesian R-squared it uses the modelled residual variance (rather than the variance of the posterior distribution of the residuals). The LOO-adjusted R-squared uses Pareto smoothed importance sampling LOO residuals and Bayesian bootstrap.

## Usage

```
## S3 method for class 'hsstan'
bayes_R2(object, prob = 0.95, summary = TRUE, ...)

## S3 method for class 'hsstan'
loo_R2(object, prob = 0.95, summary = TRUE, ...)
```

## Arguments

object	An object of class <code>hsstan</code> .
prob	Width of the posterior interval (0.95, by default). It is ignored if <code>summary=FALSE</code> .
summary	Whether a summary of the distribution of the R-squared should be returned rather than the pointwise values (TRUE by default).
...	Currently ignored.

## Value

The mean, standard deviation and posterior interval of R-squared if `summary=TRUE`, or a vector of R-squared values with length equal to the size of the posterior sample if `summary=FALSE`.

## References

Andrew Gelman, Ben Goodrich, Jonah Gabry and Aki Vehtari (2019), R-squared for Bayesian regression models, *The American Statistician*, 73 (3), 307-309. <https://doi.org/10.1080/00031305.2018.1549100>

Aki Vehtari, Andrew Gelman, Ben Goodrich and Jonah Gabry (2019), Bayesian R2 and LOO-R2. [https://avehtari.github.io/bayes\\_R2/bayes\\_R2.html](https://avehtari.github.io/bayes_R2/bayes_R2.html)

## Examples

```
# continued from ?hsstan  
  
bayes_R2(hs.biom)  
loo_R2(hs.biom)
```

---

diabetes

*Diabetes data with interaction terms*

---

## Description

The dataset consists of observations on 442 individuals for which a quantitative measure of diabetes progression is recorded in variable  $Y$ . Predictors include 10 baseline measurements, 45 interactions and 9 quadratic terms, for a total of 64 variables for each individual. Each variable has been standardized by subtracting the mean and then dividing it by its standard deviation.

## Format

A data frame with 442 rows and 65 columns (centred and scaled).

## Source

B. Efron, T. Hastie, I. Johnstone and R. Tibshirani (2004), Least angle regression, *The Annals of Statistics*, 32 (2), 407-499. <https://doi.org/10.1214/009053604000000067>

The original dataset is available from <https://www.stanford.edu/~hastie/Papers/LARS/data64.txt>

## Examples

```
data(diabetes, package="hsstan")
```

---

 hsstan *Hierarchical shrinkage models*


---

**Description**

Run the No-U-Turn Sampler (NUTS) as implemented in Stan to fit a hierarchical shrinkage model.

**Usage**

```
hsstan(x, covs.model, penalized = NULL, family = gaussian,
       iter = 2000, warmup = floor(iter/2), scale.u = 2,
       regularized = TRUE, nu = ifelse(regularized, 1, 3),
       par.ratio = 0.05, global.df = 1, slab.scale = 2, slab.df = 4,
       qr = TRUE, seed = 123, adapt.delta = NULL, keep.hs.pars = FALSE,
       ...)
```

**Arguments**

x	Data frame containing outcome, covariates and penalized predictors. Continuous predictors and outcome variable should be standardized before fitting the models as priors assume them to have mean zero and unit variance.
covs.model	Formula containing the unpenalized covariates.
penalized	Names of the variables to be used as penalized predictors. If NULL or an empty vector, a model with only unpenalized covariates is fitted.
family	Type of model fitted: either <code>gaussian()</code> for linear regression (default) or <code>binomial()</code> for logistic regression.
iter	Total number of iterations in each chain, including warmup (2000 by default).
warmup	Number of warmup iterations per chain (by default, half the total number of iterations).
scale.u	Prior scale (standard deviation) for the unpenalised covariates.
regularized	If TRUE (default), the regularized horseshoe prior is used as opposed to the original horseshoe prior.
nu	Number of degrees of freedom of the half-Student-t prior on the local shrinkage parameters (by default, 1 if <code>regularized=TRUE</code> and 3 otherwise).
par.ratio	Expected ratio of non-zero to zero coefficients (ignored if <code>regularized=FALSE</code> ). The scale of the global shrinkage parameter corresponds to <code>par.ratio</code> divided by the square root of the number of observations; for linear regression only, it's further multiplied by the residual standard deviation <code>sigma</code> .
global.df	Number of degrees of freedom for the global shrinkage parameter (ignored if <code>regularized=FALSE</code> ).
slab.scale	Scale of the regularization parameter (ignored if <code>regularized=FALSE</code> ).
slab.df	Number of degrees of freedom of the regularization parameter (ignored if <code>regularized=FALSE</code> ).

qr	Whether the thin QR decomposition should be used to decorrelate the predictors (TRUE by default). This is silently set to FALSE if there are more predictors than observations.
seed	Optional integer defining the seed for the pseudo-random number generator.
adapt.delta	Target average proposal acceptance probability for adaptation, a value between 0.8 and 1 (excluded). If unspecified, it's set to 0.99 for hierarchical shrinkage models and to 0.95 for base models.
keep.hs.pars	Whether the parameters for the horseshoe prior should be kept in the stanfit object returned (FALSE by default).
...	Further arguments passed to <a href="#">sampling</a> , such as chains (4 by default), cores (the value of options("mc.cores") by default), refresh (iter / 10 by default).

### Value

An object of class `hsstan` containing the following fields:

stanfit	an object of class <code>stanfit</code> containing the output produced by Stan, including posterior samples and diagnostic summaries. It can be manipulated using methods from the <b>rstan</b> package.
betas	posterior means of the unpenalized and penalized regression parameters.
call	the matched call.
data	the dataset used in fitting the model.
model.terms	a list of names for the outcome variable, the unpenalized covariates and the penalized predictors.
family	the family object used.
qr	Whether the QR factorization was performed.

### See Also

[kfold\(\)](#) for cross-validating a fitted object.

### Examples

```
data(diabetes)

# non-default settings for speed of the example
df <- diabetes[1:50, ]
hs.biom <- hsstan(df, Y ~ age + sex, penalized=colnames(df)[5:10],
                 chains=2, iter=250)
```

---

kfold.hsstan	<i>K-fold cross-validation</i>
--------------	--------------------------------

---

## Description

Perform K-fold cross-validation using the same settings used when fitting the model on the whole data.

## Usage

```
## S3 method for class 'hsstan'
kfold(x, folds, chains = 1, store.fits = TRUE,
      cores = getOption("mc.cores", 1), ...)
```

## Arguments

x	An object of class <code>hsstan</code> .
folds	Integer vector with one element per observation indicating the cross-validation fold in which the observation should be withdrawn.
chains	Number of Markov chains to run. By default this is set to 1, independently of the number of chains used for <code>x</code> .
store.fits	Whether the fitted models for each fold should be stored in the returned object (TRUE by default).
cores	Number of cores to use for parallelization (the value of <code>options("mc.cores")</code> by default). The cross-validation folds will be distributed to the available cores, and the Markov chains for each model will be run sequentially.
...	Further arguments passed to <a href="#">sampling</a> .

## Value

An object with classes `kfold` and `loo` that has a similar structure as the objects returned by [loo\(\)](#) and [waic\(\)](#) and is compatible with the [loo\\_compare](#) function for comparing models. The object contains the following fields:

estimates	a matrix containing point estimates and standard errors of the expected log pointwise predictive density (" <code>elpd_kfold</code> "), the effective number of parameters (" <code>p_kfold</code> ", always NA) and the K-fold information criterion " <code>kfoldic</code> " (which is $-2 * \text{elpd\_kfold}$ , i.e., converted to the deviance scale).
pointwise	a matrix containing the pointwise contributions of " <code>elpd_kfold</code> ", " <code>p_kfold</code> " and " <code>kfoldic</code> ".
fits	a matrix with two columns and number of rows equal to the number of cross-validation folds. Column <code>fit</code> contains the fitted <code>hsstan</code> objects for each fold, and column <code>test.idx</code> contains the indices of the withdrawn observations for each fold. This is not present if <code>store.fits=FALSE</code> .
data	the dataset used in fitting the model (before withdrawing observations). This is not present if <code>store.fits=FALSE</code> .

**Examples**

```
# continued from ?hsstan

# only 2 folds for speed of example
folds <- rep(1:2, length.out=length(df$Y))
cv.biom <- kfold(hs.biom, folds=folds, cores=2)
```

---

log_lik.hsstan	<i>Pointwise log-likelihood</i>
----------------	---------------------------------

---

**Description**

Compute the pointwise log-likelihood.

**Usage**

```
## S3 method for class 'hsstan'
log_lik(object, newdata = NULL, ...)
```

**Arguments**

object	An object of class hsstan.
newdata	Optional data frame to use to evaluate the log-likelihood. If NULL (default), the model matrix is used.
...	Currently ignored.

**Value**

A matrix of size S by N, where S is number of draws from the posterior distribution, and N is the number of data points.

**Examples**

```
# continued from ?hsstan
log_lik(hs.biom)
```

---

`loo.hsstan`*Predictive information criteria for Bayesian models*

---

## Description

Compute an efficient approximate leave-one-out cross-validation using Pareto smoothed importance sampling (PSIS-LOO), or the widely applicable information criterion (WAIC), also known as the Watanabe-Akaike information criterion.

## Usage

```
## S3 method for class 'hsstan'  
loo(x, cores = getOption("mc.cores"), ...)  
  
## S3 method for class 'hsstan'  
waic(x, cores = getOption("mc.cores"), ...)
```

## Arguments

<code>x</code>	An object of class <code>hsstan</code> .
<code>cores</code>	Number of cores used for parallelisation (the value of <code>options("mc.cores")</code> by default).
<code>...</code>	Currently ignored.

## Value

A `loo` object.

## Examples

```
# continued from ?hsstan  
  
loo(hs.biom)  
waic(hs.biom)
```

---

nsamples.hsstan	<i>Number of posterior samples</i>
-----------------	------------------------------------

---

**Description**

Extracts the number of posterior samples stored in a fitted model.

**Usage**

```
## S3 method for class 'hsstan'
nsamples(object, ...)
```

**Arguments**

object	An object of class hsstan.
...	Currently ignored.

**Value**

The total number of posterior samples across the chains after discarding the warmup iterations.

**Examples**

```
# continued from ?hsstan
nsamples(hs.biom)
```

---

plot.projsel	<i>Plot of relative explanatory power of predictors</i>
--------------	---

---

**Description**

The function plots the relative explanatory power of each predictor in order of selection. The relative explanatory power of predictors is computed according to the KL divergence from the full model to each submodel, scaled in such a way that the baseline model (either the null model or the model containing only unpenalized covariates) is at 0, while the full model is at 1.

**Usage**

```
## S3 method for class 'projsel'
plot(x, title = NULL, max.points = NULL,
     max.labels = NULL, from.covariates = TRUE, font.size = 12,
     hadj = 0.05, vadj = 0, ...)
```

**Arguments**

<code>x</code>	A data frame created by <code>projssel()</code> .
<code>title</code>	Title of the plot. If NULL, no title is displayed.
<code>max.points</code>	Maximum number of predictors to be plotted. If NULL (default) or 0, all points are plotted.
<code>max.labels</code>	Maximum number of predictors to be labelled. If NULL (default), all predictor labels present in <code>x</code> are displayed, which may result in overprinting.
<code>from.covariates</code>	Whether the plotting should start from the unpenalized covariates (TRUE by default). If set to FALSE, the plot includes a point for the null (intercept-only) model.
<code>font.size</code>	Size of the textual elements (labels and axes).
<code>hadj, vadj</code>	Horizontal and vertical adjustment for the labels.
<code>...</code>	Currently ignored.

**Value**

A **ggplot2** object showing the relative incremental contribution of each predictor starting from the initial set of unpenalized covariates.

---

```
posterior_interval.hsstan
      Posterior uncertainty intervals
```

---

**Description**

Compute posterior uncertainty intervals for `hsstan` objects.

**Usage**

```
## S3 method for class 'hsstan'
posterior_interval(object, pars = NULL, prob = 0.95,
  ...)
```

**Arguments**

<code>object</code>	An object of class <code>hsstan</code> .
<code>pars</code>	Names of parameters for which posterior intervals should be returned, which can be specified as regular expressions. If NULL (default) then this refers to the set of predictors used in the model.
<code>prob</code>	A value between 0 and 1 indicating the desired probability to be covered by the uncertainty intervals (0.95, by default).
<code>...</code>	Currently ignored.

**Value**

A matrix with lower and upper interval bounds as columns and as many rows as selected parameters.

**Examples**

```
# continued from ?hsstan
posterior_interval(hs.biom)
```

---

```
posterior_linpred.hsstan
```

*Posterior distribution of the linear predictor*

---

**Description**

Extract the posterior draws of the linear predictor, possibly transformed by the inverse-link function.

**Usage**

```
## S3 method for class 'hsstan'
posterior_linpred(object, transform = FALSE,
  newdata = NULL, ...)
```

**Arguments**

object	An object of class hsstan.
transform	Whether the linear predictor should be transformed using the inverse-link function (FALSE by default).
newdata	Optional data frame containing the variables to use to predict. If NULL (default), the model matrix is used. If specified, its continuous variables should be standardized, since the model coefficients are learnt on standardized data.
...	Currently ignored.

**Value**

A matrix of size S by N, where S is the number of draws from the posterior distribution of the (transformed) linear predictor, and N is the number of data points.

**Examples**

```
# continued from ?hsstan
posterior_linpred(hs.biom)
```

---

posterior\_performance *Posterior measures of performance*

---

### Description

Compute the log-likelihood and a relevant measure of performance (R-squared or AUC) from the posterior samples.

### Usage

```
posterior_performance(obj, prob = 0.95, summary = TRUE,
  cores = getOption("mc.cores", 1))
```

### Arguments

obj	An object of class <code>hsstan</code> or <code>kfold</code> .
prob	Width of the posterior interval (0.95, by default). It is ignored if <code>summary=FALSE</code> .
summary	Whether a summary of the distribution of the performance measure should be returned rather than the pointwise values (TRUE by default).
cores	Number of cores to use for parallelization (the value of <code>options("mc.cores")</code> by default).

### Value

The mean, standard deviation and posterior interval of the performance measure (R-squared or AUC) if `summary=TRUE`, or a vector of values of the performance measure with length equal to the size of the posterior sample if `summary=FALSE`. Attribute `type` reports whether the performance measures are cross-validated or not.

### Examples

```
# continued from ?hsstan
posterior_performance(hs.biom, cores=1)
```

---

posterior\_predict.hsstan

*Posterior predictive distribution*

---

### Description

Draw from the posterior predictive distribution of the outcome.

**Usage**

```
## S3 method for class 'hsstan'
posterior_predict(object, newdata = NULL,
  nsamples = NULL, seed = NULL, ...)
```

**Arguments**

object	An object of class hsstan.
newdata	Optional data frame containing the variables to use to predict. If NULL (default), the model matrix is used. If specified, its continuous variables should be standardized, since the model coefficients are learnt on standardized data.
nsamples	A positive integer indicating the number of posterior samples to use. If NULL (default) all samples are used.
seed	Optional integer defining the seed for the pseudo-random number generator.
...	Currently ignored.

**Value**

A matrix of size S by N, where S is the number of simulations from the posterior predictive distribution, and N is the number of data points.

**Examples**

```
# continued from ?hsstan
posterior_predict(hs.biom)
```

---

posterior\_summary      *Posterior summary*

---

**Description**

Produce a summary of the posterior samples for the quantities of interest.

**Usage**

```
posterior_summary(x, prob, ...)

## Default S3 method:
posterior_summary(x, prob = 0.95, ...)

## S3 method for class 'hsstan'
posterior_summary(x, prob = 0.95, pars = NULL, ...)
```

**Arguments**

x	An object containing or representing posterior samples. If x is a matrix, it should have size S by Q, where S is the number of posterior samples, and Q is the number of quantities of interest.
prob	Width of the posterior intervals (0.95, by default).
...	Further arguments passed to or from other methods.
pars	Vector of parameter names to be extracted. If NULL (default) then this refers to the set of predictors used in the model.

**Value**

A matrix with columns containing mean, standard deviation and posterior intervals for the given quantities.

**See Also**

[summary\(\)](#) to produce summaries of hsstan objects that include the number of effective samples and the split-Rhat diagnostic.

**Examples**

```
# continued from ?hsstan
posterior_summary(hs.biom)
```

---

```
print.hsstan          Print a summary for the fitted model
```

---

**Description**

Print a summary for the fitted model

**Usage**

```
## S3 method for class 'hsstan'
print(x, ...)
```

**Arguments**

x	An object of class hsstan.
...	Further arguments to <a href="#">summary()</a> .

---

 projssel

*Forward selection minimizing KL-divergence in projection*


---

**Description**

Forward selection minimizing KL-divergence in projection

**Usage**

```
projssel(obj, max.iters = 30, out.csv = NULL)
```

**Arguments**

<code>obj</code>	Object of class <code>hsstan</code> .
<code>max.iters</code>	Maximum number of iterations (number of predictors selected) after which the selection procedure should stop.
<code>out.csv</code>	If not <code>NULL</code> , the name of a CSV file to save the output to.

**Value**

A data frame of class `projssel` where each row corresponds to a forward-selected submodel that contains all variables listed up to that row. The data frame contains the following columns:

<code>var</code>	names of the variables selected.
<code>kl</code>	KL-divergence from the full model to the submodel.
<code>rel.kl.null</code>	relative explanatory power of predictors starting from the intercept-only model.
<code>rel.kl</code>	relative explanatory power of predictors starting from the model containing unpenalized covariates.
<code>elpd</code>	the expected log predictive density of the submodels.
<code>delta.elpd</code>	the difference in elpd from the full model.

**Examples**

```
# continued from ?hsstan

sel <- projssel(hs.biom, max.iters=3)
plot(sel)
```

---

sampler.stats	<i>Sampler statistics</i>
---------------	---------------------------

---

**Description**

Report statistics on the parameters used in the sampler, the sampler behaviour and the sampling time.

**Usage**

```
sampler.stats(object)
```

**Arguments**

object            An object of class hsstan.

**Value**

A matrix with  $C + 1$  rows, where  $C$  is the number of Markov chains, reporting average acceptance probability, average stepsize, number of divergent transitions, maximum tree depth, total number of gradient evaluations, warmup and sampling times in seconds.

**Examples**

```
# continued from ?hsstan  
sampler.stats(hs.biom)
```

---

summary.hsstan	<i>Summary for the fitted model</i>
----------------	-------------------------------------

---

**Description**

Summary for the fitted model

**Usage**

```
## S3 method for class 'hsstan'  
summary(object, pars = NULL, prob = 0.95,  
      digits = 2, sort = NULL, decreasing = TRUE, max.rows = NULL, ...)
```

**Arguments**

object	An object of class hsstan.
pars	Vector of parameter names to be extracted. If NULL (default) then this refers to the set of predictors used in the model.
prob	Width of the posterior intervals (0.95, by default).
digits	Number of decimal places to be reported (2 by default).
sort	Column name used to sort the results according to the absolute value of the column. If NULL (default) or the column name cannot be found, no sorting occurs.
decreasing	Whether the results should be sorted in decreasing order when a valid column name is specified in sort (TRUE by default).
max.rows	Maximum number of rows to be returned. If NULL (default) or 0, all results are returned.
...	Currently ignored.

**Value**

A matrix with summaries from the posterior distribution of the parameters of interest.

**Examples**

```
# continued from ?hsstan
summary(hs.biom)
```

# Index

## \*Topic **datasets**

- diabetes, [4](#)
- bayes\_R2 (bayes\_R2.hsstan), [3](#)
- bayes\_R2.hsstan, [3](#)
- diabetes, [4](#)
- hsstan, [5](#)
- hsstan-package, [2](#)
- kfold (kfold.hsstan), [7](#)
- kfold(), [6](#)
- kfold.hsstan, [7](#)
- log\_lik (log\_lik.hsstan), [8](#)
- log\_lik.hsstan, [8](#)
- loo (loo.hsstan), [9](#)
- loo(), [7](#)
- loo.hsstan, [9](#)
- loo\_compare, [7](#)
- loo\_R2 (bayes\_R2.hsstan), [3](#)
- nsamples (nsamples.hsstan), [10](#)
- nsamples.hsstan, [10](#)
- plot.projsel, [10](#)
- posterior\_interval
  - (posterior\_interval.hsstan), [11](#)
- posterior\_interval.hsstan, [11](#)
- posterior\_linpred
  - (posterior\_linpred.hsstan), [12](#)
- posterior\_linpred.hsstan, [12](#)
- posterior\_performance, [13](#)
- posterior\_predict
  - (posterior\_predict.hsstan), [13](#)
- posterior\_predict.hsstan, [13](#)
- posterior\_summary, [14](#)
- print.hsstan, [15](#)
- projsel, [16](#)
- projsel(), [11](#)
- sampler.stats, [17](#)
- sampling, [6, 7](#)
- summary(), [15](#)
- summary.hsstan, [17](#)
- waic (loo.hsstan), [9](#)
- waic(), [7](#)