

Package ‘portfolioBacktest’

October 7, 2019

Title Automated Backtesting of Portfolios over Multiple Datasets

Version 0.2.1

Date 2019-10-07

Description Automated backtesting of multiple portfolios over multiple datasets of stock prices in a rolling-window fashion. Intended for researchers and practitioners to backtest a set of different portfolios, as well as by a course instructor to assess the students in their portfolio design in a fully automated and convenient manner, with results conveniently formatted in tables and plots. Each portfolio design is easily defined as a function that takes as input a window of the stock prices and outputs the portfolio weights. Multiple portfolios can be easily specified as a list of functions or as files in a folder. Multiple datasets can be conveniently extracted randomly from different markets, different time periods, and different subsets of the stock universe. The results can be later assessed and ranked with tables based on a number of performance criteria (e.g., expected return, volatility, Sharpe ratio, drawdown, turnover rate, return on investment, computational time, etc.), as well as plotted in a number of ways with nice barplots and boxplots.

Maintainer Daniel P. Palomar <daniel.p.palomar@gmail.com>

URL <https://CRAN.R-project.org/package=portfolioBacktest>,
<https://github.com/dppalomar/portfolioBacktest>

BugReports <https://github.com/dppalomar/portfolioBacktest/issues>

License GPL-3 | file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 6.1.1

Depends R (>= 2.10)

Imports digest, doSNOW, evaluate, foreach, ggplot2,
PerformanceAnalytics, quantmod, R.utils, rlang, snow, utils,
xts, zoo

Suggests CVXR, DT, gfortify, gridExtra, knitr, prettydoc, readtext,
rmarkdown, R.rsp, stringi, testthat

VignetteBuilder knitr, rmarkdown, R.rsp

NeedsCompilation no

Author Daniel P. Palomar [cre, aut],
Rui Zhou [aut]

Repository CRAN

Date/Publication 2019-10-07 15:20:02 UTC

R topics documented:

portfolioBacktest-package	2
backtestBoxPlot	3
backtestChartCumReturns	4
backtestChartDrawdown	5
backtestChartStackedBar	7
backtestLeaderboard	8
backtestSelector	10
backtestSummary	11
backtestTable	12
dataset10	14
genRandomFuns	14
plotPerformanceVsParams	16
portfolioBacktest	17
SP500_symbols	20
stockDataDownload	20
stockDataResample	21
summaryBarPlot	22
summaryTable	24
Index	26

portfolioBacktest-package

portfolioBacktest: Automated Backtesting of Portfolios over Multiple Datasets

Description

Automated backtesting of multiple portfolios over multiple datasets of stock prices in a rolling-window fashion. Intended for researchers and practitioners to backtest a set of different portfolios, as well as by a course instructor to assess the students in their portfolio design in a fully automated and convenient manner, with results conveniently formatted in tables and plots. Each portfolio design is easily defined as a function that takes as input a window of the stock prices and outputs the portfolio weights. Multiple portfolios can be easily specified as a list of functions or as files in a folder. Multiple datasets can be conveniently extracted randomly from different markets, different time periods, and different subsets of the stock universe. The results can be later assessed and ranked with tables based on a number of performance criteria (e.g., expected return, volatility,

Sharpe ratio, drawdown, turnover rate, return on investment, computational time, etc.), as well as plotted in a number of ways with nice barplots and boxplots.

Functions

[stockDataDownload](#), [stockDataResample](#), [portfolioBacktest](#), [backtestSelector](#), [backtestTable](#), [backtestBoxPlot](#), [backtestLeaderboard](#), [backtestChartCumReturns](#), [backtestChartDrawdown](#), [backtestChartStackedBar](#) [backtestSummary](#), [summaryTable](#), [summaryBarPlot](#)

Data

[dataset10](#), [SP500_symbols](#)

Help

For a quick help see the README file: [GitHub-README](#).

For more details see the vignette: [CRAN-vignette](#).

Author(s)

Daniel P. Palomar and Rui ZHOU

backtestBoxPlot	<i>Create boxplot from backtest results</i>
-----------------	---

Description

Create boxplot from a portfolio backtest obtained with the function [portfolioBacktest](#). By default the boxplot is based on the package [ggplot2](#) (also plots a dot for each single backtest), but the user can also specify a simple base plot.

Usage

```
backtestBoxPlot(bt, measure = "Sharpe ratio", type = c("ggplot2",
  "simple"), ...)
```

Arguments

bt	Backtest results as produced by the function portfolioBacktest .
measure	String to select a performane measure from "Sharpe ratio", "max drawdown", "annual return", "annual volatility", "Sterling ratio", "Omega ratio", and "ROT bps". Default is "Sharpe ratio".
type	Type of plot. Valid options: "ggplot2", "simple". Default is "ggplot2".
...	Additional parameters. For example: mar for margins as in <code>par()</code> (for the case of plot type = "simple"); and alpha for the alpha of each backtest dot (for the case of plot type = "ggplot2"), set to 0 to remove the dots.

Author(s)

Daniel P. Palomar and Rui Zhou

See Also

[summaryBarPlot](#), [backtestChartCumReturns](#), [backtestChartDrawdown](#), [backtestChartStackedBar](#)

Examples

```
library(portfolioBacktest)
data(dataset10) # load dataset

# define your own portfolio function
quintile_portfolio <- function(data) {
  X <- diff(log(data$adjusted))[-1]
  N <- ncol(X)
  ranking <- sort(colMeans(X), decreasing = TRUE, index.return = TRUE)$ix
  w <- rep(0, N)
  w[ranking[1:round(N/5)]] <- 1/round(N/5)
  return(w)
}

# do backtest
bt <- portfolioBacktest(list("Quintile" = quintile_portfolio), dataset10,
  benchmark = c("uniform", "index"))

# now we can plot
backtestBoxPlot(bt, "Sharpe ratio")
backtestBoxPlot(bt, "Sharpe ratio", type = "simple")
```

backtestChartCumReturns

Chart of the cumulative returns or wealth for a single backtest

Description

Create chart of the cumulative returns or wealth for a single backtest obtained with the function [portfolioBacktest](#). By default the chart is based on the package `ggplot2`, but the user can also specify a plot based on `PerformanceAnalytics`.

Usage

```
backtestChartCumReturns(bt, portfolios = names(bt), dataset_num = 1,
  type = c("ggplot2", "simple"), ...)
```

Arguments

bt	Backtest results as produced by the function portfolioBacktest .
portfolios	String with portfolio names to be charted. Default charts all portfolios in the backtest.
dataset_num	Dataset index to be charted. Default is dataset_num = 1.
type	Type of plot. Valid options: "ggplot2", "simple". Default is "ggplot2".
...	Additional parameters.

Author(s)

Daniel P. Palomar and Rui Zhou

See Also

[summaryBarPlot](#), [backtestBoxPlot](#), [backtestChartDrawdown](#), [backtestChartStackedBar](#)

Examples

```
library(portfolioBacktest)
data(dataset10) # load dataset

# define your own portfolio function
quintile_portfolio <- function(data) {
  X <- diff(log(data$adjusted))[-1]
  N <- ncol(X)
  ranking <- sort(colMeans(X), decreasing = TRUE, index.return = TRUE)$ix
  w <- rep(0, N)
  w[ranking[1:round(N/5)]] <- 1/round(N/5)
  return(w)
}

# do backtest
bt <- portfolioBacktest(list("Quintile" = quintile_portfolio), dataset10,
  benchmark = c("uniform", "index"))

# now we can chart
backtestChartCumReturns(bt)
```

backtestChartDrawdown *Chart of the drawdown for a single backtest*

Description

Create chart of the drawdown for a single backtest obtained with the function [portfolioBacktest](#). By default the chart is based on the package `ggplot2`, but the user can also specify a plot based on `PerformanceAnalytics`.

Usage

```
backtestChartDrawdown(bt, portfolios = names(bt), dataset_num = 1,
  type = c("ggplot2", "simple"), ...)
```

Arguments

bt	Backtest results as produced by the function portfolioBacktest .
portfolios	String with portfolio names to be charted. Default charts all portfolios in the backtest.
dataset_num	Dataset index to be charted. Default is dataset_num = 1.
type	Type of plot. Valid options: "ggplot2", "simple". Default is "ggplot2".
...	Additional parameters.

Author(s)

Daniel P. Palomar and Rui Zhou

See Also

[summaryBarPlot](#), [backtestBoxPlot](#), [backtestChartCumReturns](#), [backtestChartStackedBar](#)

Examples

```
library(portfolioBacktest)
data(dataset10) # load dataset

# define your own portfolio function
quintile_portfolio <- function(data) {
  X <- diff(log(data$adjusted))[-1]
  N <- ncol(X)
  ranking <- sort(colMeans(X), decreasing = TRUE, index.return = TRUE)$ix
  w <- rep(0, N)
  w[ranking[1:round(N/5)]] <- 1/round(N/5)
  return(w)
}

# do backtest
bt <- portfolioBacktest(list("Quintile" = quintile_portfolio), dataset10,
  benchmark = c("uniform", "index"))

# now we can chart
backtestChartDrawdown(bt)
```

backtestChartStackedBar

Chart of the weight allocation over time for a portfolio over a single backtest

Description

Create chart of the weight allocation over time for a portfolio over a single backtest obtained with the function [portfolioBacktest](#). By default the chart is based on the package `ggplot2`, but the user can also specify a plot based on `PerformanceAnalytics`.

Usage

```
backtestChartStackedBar(bt, portfolio = names(bt[1]), dataset_num = 1,
  type = c("ggplot2", "simple"), legend = FALSE)
```

Arguments

<code>bt</code>	Backtest results as produced by the function portfolioBacktest .
<code>portfolio</code>	String with portfolio name to be charted. Default charts the first portfolio in the backtest.
<code>dataset_num</code>	Dataset index to be charted. Default is <code>dataset_num = 1</code> .
<code>type</code>	Type of plot. Valid options: "ggplot2", "simple". Default is "ggplot2".
<code>legend</code>	Boolean to choose whether legend is plotted or not. Default is <code>legend = FALSE</code> .

Author(s)

Daniel P. Palomar and Rui Zhou

See Also

[summaryBarPlot](#), [backtestBoxPlot](#), [backtestChartCumReturns](#), [backtestChartDrawdown](#)

Examples

```
library(portfolioBacktest)
data(dataset10) # load dataset

# for better illustration, let's use only the first 5 stocks
dataset10_5stocks <- lapply(dataset10, function(x) {x$adjusted <- x$adjusted[, 1:5]; return(x)})

# define GMVP (with heuristic not to allow shorting)
GMVP_portfolio_fun <- function(dataset) {
  X <- diff(log(dataset$adjusted))[-1] # compute log returns
  Sigma <- cov(X) # compute SCM
  # design GMVP
```

```

w <- solve(Sigma, rep(1, nrow(Sigma)))
w <- abs(w)/sum(abs(w))
return(w)
}

# backtest
bt <- portfolioBacktest(list("GMVP" = GMVP_portfolio_fun), dataset10_5stocks, rebalance_every = 20)

# now we can chart
backtestChartStackedBar(bt, "GMVP", type = "simple")
backtestChartStackedBar(bt, "GMVP", type = "simple", legend = TRUE)
backtestChartStackedBar(bt, "GMVP")
backtestChartStackedBar(bt, "GMVP", legend = TRUE)

```

backtestLeaderboard *Leaderboard of portfolios from the backtest results*

Description

Leaderboard of portfolios according to the backtesting results and a ranking based on the combination of several performance criteria. Since the different performance measures have different ranges and distributions, each is first transformed according to its empirical distribution function (along the empirical distribution of the portfolios being ranked) to obtain percentile scores. After that transformation, each of the measures has an empirical uniform distribution in the interval $[0, 100]$ and can be weighted to obtain the final ranking.

Usage

```
backtestLeaderboard(bt = NA, weights = list(), summary_fun = median,
  show_benchmark = TRUE)
```

Arguments

bt	Backtest results as produced by the function portfolioBacktest .
weights	List of weights for the different performance measures as obtained in backtestSummary() \$performance (i.e., "Sharpe ratio", "max drawdown", "annual return", "annual volatility", "Sterling ratio", "Omega ratio", "ROT bps", "cpu_time", and "failure ratio"), as well as "cpu time" and "failure rate". For example: <code>weights = list("Sharpe ratio" = 8, "max drawdown" = 4)</code> .
summary_fun	Summary function to be employed (e.g., median or mean).
show_benchmark	Logical value indicating whether to include benchmarks in the summary (default is TRUE).

Value

List with the following elements:

leaderboard_scores	Matrix with the individual scores for the portfolios (as chosen in weights) and the final score.
leaderboard_performance	Matrix with all the performance measures for the portfolios.
error_summary	Error messages generated by each portfolio on each dataset. Useful for debugging and give feedback to the portfolio managers of the different portfolios.

Author(s)

Daniel P. Palomar and Rui Zhou

Examples

```

library(portfolioBacktest)
data(dataset10) # load dataset

# define your own portfolio function
quintile_portfolio <- function(data) {
  X <- diff(log(data$adjusted))[-1]
  N <- ncol(X)
  ranking <- sort(colMeans(X), decreasing = TRUE, index.return = TRUE)$ix
  w <- rep(0, N)
  w[ranking[1:round(N/5)]] <- 1/round(N/5)
  return(w)
}

# do backtest
bt <- portfolioBacktest(quintile_portfolio, dataset10,
  benchmark = c("uniform", "index"))

# see all performance measures available for the ranking
backtestSummary(bt)$performance

# show leaderboard
leaderboard <- backtestLeaderboard(bt, weights = list("Sharpe ratio" = 6,
  "max drawdown" = 1,
  "ROT (bps)" = 1,
  "cpu time" = 1,
  "failure rate" = 1))

leaderboard$leaderboard_scores

```

backtestSelector *Selector of portfolio backtest results*

Description

Select the results from a portfolio backtest.

Usage

```
backtestSelector(bt, portfolio_index = NULL, portfolio_name = NULL,
  measures = NULL)
```

Arguments

bt	Backtest results as produced by the function portfolioBacktest .
portfolio_index	Index number of a portfolio, e.g., 1 means to select the performance of the first portfolio recorded in bt.
portfolio_name	String name of a portfolio, e.g., "GMVP" means to select the performance of portfolio with name "GMVP" in bt. Only considered when portfolio_index is not passed.
measures	String vector to select performane measures (default is all) from "Sharpe ratio", "max drawdown", "annual return", "annual volatility", "Sterling ratio", "Omega ratio", and "ROT bps".

Value

List with the following elements:

performance	Performance measures selected by argument measures.
error	Error status (TRUE or FALSE) of portfolio over each dataset (TRUE is when the portfolio function generates an error or the maximum CPU time is exceeded).
error_message	Error messages generated by portfolio function over each dataset. Useful for debugging purposes.
cpu_time	CPU usage by portfolio function over each dataset.
portfolio	Portfolio weights generated by portfolio function over each dataset.
return	Portfolio returns over each dataset.
wealth	Portfolio wealth (aka cumulative returns or cumulative P&L) over each dataset.

Author(s)

Rui Zhou and Daniel P. Palomar

Examples

```

library(portfolioBacktest)
data("dataset10") # load dataset

# define your own portfolio function
uniform_portfolio <- function(dataset) {
  N <- ncol(dataset$adjusted)
  return(rep(1/N, N))
}

# do backtest
bt <- portfolioBacktest(list("Uniform" = uniform_portfolio), dataset10)

# extract your interested portfolio result
bt_sel <- backtestSelector(bt, portfolio_name = "Uniform")
names(bt_sel)

```

backtestSummary *Summary of portfolio backtest*

Description

Summarize the results from a portfolio backtest.

Usage

```
backtestSummary(bt, portfolio_indexes = NA, portfolio_names = NA,
  summary_fun = median, show_benchmark = TRUE)
```

Arguments

bt	Backtest results as produced by the function portfolioBacktest .
portfolio_indexes	Numerical vector of portfolio indexes whose performance will be summarized, e.g., c(1,2) means to summarize the performance of the first and second portfolios recorded in bt.
portfolio_names	String vector of portfolio names whose performance will be summarized, e.g., c("Uniform", "GMVP") means to summarize the performance of portfolios with names "Uniform" and "GMVP" in bt (default is names(bt) except the benchmark names). Only considered when portfolio_indexes is not passed.
summary_fun	Summary function to be employed (e.g., median or mean).
show_benchmark	Logical value indicating whether to include benchmarks in the summary (default is TRUE).

Value

List with the following elements:

performance_summary	Performance criteria: "Sharpe ratio", "max drawdown", "annual return", "annual volatility", "Sterling ratio", "Omega ratio", and "ROT bps". Default is "Sharpe ratio".
failure_rate	Failure rate of each portfolio (failure is when the portfolio function generates an error or the maximum CPU time is exceeded).
cpu_time_summary	Summary of the CPU usage by each portfolio function.
error_message	Error messages generated by each portfolio function over each dataset. Useful for debugging purposes.

Author(s)

Rui Zhou and Daniel P. Palomar

Examples

```
library(portfolioBacktest)
data(dataset10) # load dataset

# define your own portfolio function
uniform_portfolio <- function(dataset) {
  N <- ncol(dataset$adjusted)
  return(rep(1/N, N))
}

# do backtest
bt <- portfolioBacktest(list("Uniform" = uniform_portfolio), dataset10)

# show the summary
bt_sum <- backtestSummary(bt)
names(bt_sum)
bt_sum$performance_summary
```

backtestTable

Table with portfolio backtest results

Description

Create table with the results from a portfolio backtest.

Usage

```
backtestTable(bt, portfolio_indexes = NA, portfolio_names = NA,
  show_benchmark = TRUE, measures = NULL)
```

Arguments

bt Backtest results as produced by the function `portfolioBacktest`.

portfolio_indexes Numerical vector of portfolio indexes whose performance will be summarized, e.g., `c(1, 2)` means to summarize the performance of the first and second portfolios recorded in `bt`.

portfolio_names String vector of portfolio names whose performance will be summarized, e.g., `c("Uniform", "GMVP")` means to summarize the performance of portfolios with names "Uniform" and "GMVP" in `bt` (default is `names(bt)` except the benchmark names). Only considered when `portfolio_indexes` is not passed.

show_benchmark Logical value indicating whether to include benchmarks in the summary (default is TRUE).

measures String vector to select performane measures (default is all) from "Sharpe ratio", "max drawdown", "annual return", "annual volatility", "Sterling ratio", "Omega ratio", "ROT bps", "error", "cpu_time", and "error_message".

Value

List with the following elements:

`<performance criterion>` One item per performance measures as selected by argument `measures`.

error Error status (TRUE or FALSE) for each portfolio over each dataset (TRUE is when the portfolio function generates an error or the maximum CPU time is exceeded).

cpu_time CPU usage by each portfolio function over each dataset.

error_message Error messages generated by each portfolio function over each dataset. Useful for debugging purposes.

Author(s)

Rui Zhou and Daniel P. Palomar

Examples

```
library(portfolioBacktest)
data(dataset10) # load dataset

# define your own portfolio function
uniform_portfolio <- function(dataset) {
  N <- ncol(dataset$adjusted)
  return(rep(1/N, N))
}
```

```

}

# do backtest
bt <- portfolioBacktest(list("Uniform" = uniform_portfolio), dataset10)

# show the backtest results in table
bt_tab <- backtestTable(bt)
bt_tab[c("Sharpe ratio", "max drawdown")]

```

dataset10	<i>Ten datasets obtained by resampling the S&P 500</i>
-----------	--

Description

Ten datasets of stock market data resampled from the S&P 500. Each resample contains a random selection of 50 stocks from the S&P 500 universe and a period of two years with a random initial point.

Usage

```
data(dataset10)
```

Format

List of 10 datasets, each contains two xts objects:

adjusted 505 x 50 xts with the adjusted prices of the 50 stocks

index 505 x 1 xts with the market index prices

Source

[Yahoo! Finance](#)

genRandomFuns	<i>Generate multiple versions of a function with randomly chosen parameters</i>
---------------	---

Description

Portfolio functions usually contain some parameters that can be tuned. This function creates multiple versions of a function with randomly chosen parameters. After backtesting those portfolios, the plotting function [plotPerformanceVsParams](#) can be used to show the performance vs parameters.

Usage

```
genRandomFuns(portfolio_fun, params_grid, name = "portfolio",
              N_funs = NULL)
```

Arguments

`portfolio_fun` Portfolio function with parameters unspecified.

`params_grid` Named list containing for each parameter the possible values it can take.

`name` String with the name of the portfolio function.

`N_funs` Number of functions to be generated.

Author(s)

Daniel P. Palomar and Rui Zhou

See Also

[plotPerformanceVsParams](#)

Examples

```
library(portfolioBacktest)

# define GMVP with parameters "delay", "lookback", and "regularize"
GMVP_portfolio_fun <- function(dataset) {
  prices <- tail(lag(dataset$adjusted, delay), lookback)
  X <- diff(log(prices))[-1]
  Sigma <- cov(X)
  if (regularize)
    Sigma <- Sigma + 0.1 * mean(diag(Sigma)) * diag(ncol(Sigma))
  # design GMVP
  w <- solve(Sigma, rep(1, ncol(Sigma)))
  return(w/sum(w))
}

# generate the functions with random parameters
portfolio_list <- genRandomFuns(portfolio_fun = GMVP_portfolio_fun,
                              params_grid = list(lookback = c(100, 120, 140, 160),
                                                  delay = c(0, 5, 10, 15, 20),
                                                  regularize = c(FALSE, TRUE)),
                              name = "GMVP",
                              N_funs = 40)

names(portfolio_list)
portfolio_list[[1]]
rlang::env_print(portfolio_list[[1]])
rlang::fn_env(portfolio_list[[1]])$lookback
rlang::fn_env(portfolio_list[[1]])$delay
rlang::fn_env(portfolio_list[[1]])$regularize
```

plotPerformanceVsParams

Plot performance of portfolio function vs choice of parameters

Description

Portfolio functions usually contain some parameters that can be tuned. After generating multiple versions of a portfolio function with randomly chosen parameters with the function [genRandomFuns](#) and doing the backtesting, this function can be used to plot the performance vs choice of parameters.

Usage

```
plotPerformanceVsParams(bt_all_portfolios, params_subset = NULL,  
  name_performance = "Sharpe ratio", summary_fun = median)
```

Arguments

`bt_all_portfolios` Backtest results as produced by the function [portfolioBacktest](#).

`params_subset` List of named parameters with a subset of the values to be considered. By default all the possible values will be considered.

`name_performance` String with the name of the performance measure to be used.

`summary_fun` Summary function to be employed (e.g., median or mean). Default is median.

Author(s)

Daniel P. Palomar and Rui Zhou

See Also

[genRandomFuns](#)

Examples

```
library(portfolioBacktest)  
  
# define GMVP with parameters "delay", "lookback", and "regularize"  
GMVP_portfolio_fun <- function(dataset) {  
  prices <- tail(lag(dataset$adjusted, delay), lookback)  
  X <- diff(log(prices))[-1]  
  Sigma <- cov(X)  
  if (regularize)  
    Sigma <- Sigma + 0.01*diag(ncol(Sigma))  
  # design GMVP  
  w <- solve(Sigma, rep(1, ncol(Sigma)))  
  return(w/sum(w))  
}
```



```

}

# generate the functions with random parameters
portfolio_list <- genRandomFuns(portfolio_fun = GMVP_portfolio_fun,
                               params_grid = list(lookback = c(100, 120, 140, 160),
                                                  delay = c(0, 5, 10, 15, 20),
                                                  regularize = c(FALSE, TRUE)),
                               name = "GMVP",
                               N_funs = 40)

# backtest portfolios
bt <- portfolioBacktest(portfolio_list, dataset10)

# plot
plotPerformanceVsParams(bt)
plotPerformanceVsParams(bt, params_subset = list(regularize = TRUE))
plotPerformanceVsParams(bt, params_subset = list(delay = 5))
plotPerformanceVsParams(bt, params_subset = list(delay = 5, regularize = TRUE))

```

portfolioBacktest	<i>Backtest multiple portfolios over multiple datasets of stock prices in a rolling-window basis</i>
-------------------	--

Description

Automated backtesting of multiple portfolios over multiple datasets of stock prices in a rolling-window fashion. Each portfolio design is easily defined as a function that takes as input a window of the stock prices and outputs the portfolio weights. Multiple portfolios can be easily specified as a list of functions or as files in a folder. Multiple datasets can be conveniently obtained with the function [stockDataResample](#) that resamples the data downloaded with the function [stockDataDownload](#). The results can be later assessed and arranged with tables and plots. The backtesting can be highly time-consuming depending on the number of portfolios and datasets can be performed with parallel computation over multiple cores. Errors in functions are properly caught and handled so that the execution of the overall backtesting is not stopped (error messages are stored for debugging purposes). See [vignette](#) for a detailed explanation.

Usage

```

portfolioBacktest(portfolio_funs = NULL, dataset_list,
                  folder_path = NULL, price_name = "adjusted", paral_portfolios = 1,
                  paral_datasets = 1, show_progress_bar = FALSE, benchmark = NULL,
                  shortselling = TRUE, leverage = Inf, T_rolling_window = 252,
                  optimize_every = 20, rebalance_every = 1, execution = c("same day",
                  "next day"), cost = list(buy = 0, sell = 0, short = 0, long_leverage =
                  0), cpu_time_limit = Inf, return_portfolio = TRUE,
                  return_returns = TRUE)

```

Arguments

portfolio_funs	List of functions (can also be a single function), each of them taking as input a dataset containing a list of xts objects (following the format of each element of the argument dataset_list) properly windowed (following the rolling-window approach) and returning the portfolio as a vector of normalized weights. See vignette for details.
dataset_list	List of datasets, each containing a list of xts objects, as generated by the function stockDataResample .
folder_path	If portfolio_funs is not defined, this should contain the path to a folder containing the portfolio functions saved in files. See vignette for details.
price_name	Name of the xts column in each dataset that contains the prices to be used in the portfolio return computation (default is "adjusted").
paral_portfolios	Interger indicating number of portfolios to be evaluated in parallel (default is 1).
paral_datasets	Interger indicating number of datasets to be evaluated in parallel (default is 1).
show_progress_bar	Logical value indicating whether to show progress bar (default is FALSE).
benchmark	String vector indicating the benchmark portfolios to be incorporated, currently supports: <ul style="list-style-type: none"> • uniform - the uniform portfolio, $w = [1/N, \dots, 1/N]$ with N be number of stocks • index - the market index, requires an xts named 'index' in the datasets.
shortselling	Logical value indicating whether shortselling is allowed or not (default is TRUE, so no control for shorselling in the backtesting).
leverage	Amount of leverage as in $\ w\ _1 \leq leverage$ (default is Inf, so no control for leverage in the backtesting).
T_rolling_window	Length of the lookback rolling window (default is 252).
optimize_every	How often the portfolio is to be optimized (default is 20).
rebalance_every	How often the portfolio is to be rebalanced (default is 1).
execution	String that can be either "same day" (default) or "next day". At the rebalancing period t , the portfolio has used information up to (and including) period t . Same day execution means one can get into the position at that period t , whereas the next day execution means that one can only get into the position the following day.
cost	List containing four different types of transaction costs (common for all assets) for buying, selling, shorting, and long leveraging. The default is <code>cost = list(buy = 0e-4, sell = 0e-4, short = 0e-4, long_leverage = 0e-4)</code> . If some elements are not specified then they will be automatically set to zero.
cpu_time_limit	Time limit for executing each portfolio function over a single data set (default is Inf, so no time limit).

return_portfolio

Logical value indicating whether to return the portfolios (default is TRUE). Two portfolios are returned: `w_designed` is the designed portfolio at each given rebalancing period (using all the information up to and including that period, which can be executed either on the same day or the following day) and `w_bop` is the "beginning-of-period" portfolio (i.e., at each period it contains the weights held in the market in the previous period so that the portfolio return at that period is just the product of the asset returns and `w_bop` at that period.)

return_returns Logical value indicating whether to return the portfolio returns (default is TRUE). Two series are returned: `return` with the portfolio returns and `wealth` with the portfolio wealth (aka cumulative P&L).

Value

List with the portfolio backtest results, see [vignette-result-format](#) for details. It can be accessed directly, but we highly recommend the use of the package specific functions to extract any required information, namely, [backtestSelector](#), [backtestTable](#), [backtestBoxPlot](#), [backtestLeaderboard](#), [backtestSummary](#), [summaryTable](#), [summaryBarPlot](#).

Author(s)

Daniel P. Palomar and Rui Zhou

See Also

[stockDataDownload](#), [stockDataResample](#), [backtestSelector](#), [backtestTable](#), [backtestBoxPlot](#), [backtestLeaderboard](#), [backtestSummary](#), [summaryTable](#), [summaryBarPlot](#).

Examples

```
library(portfolioBacktest)
data(dataset10) # load dataset

# define your own portfolio function
uniform_portfolio <- function(dataset) {
  N <- ncol(dataset$adjusted)
  return(rep(1/N, N))
}

# do backtest
bt <- portfolioBacktest(list("Uniform" = uniform_portfolio), dataset10)

# check your result
names(bt)
backtestSelector(bt, portfolio_name = "Uniform", measures = c("Sharpe ratio", "max drawdown"))
backtestTable(bt, measures = c("Sharpe ratio", "max drawdown"))
bt_summary <- backtestSummary(bt)
summaryTable(bt_summary)
```

SP500_symbols	<i>Stock symbols of the S&P 500 constituents</i>
---------------	--

Description

Stock symbols of the S&P 500 constituents

Usage

```
data(SP500_symbols)
```

Format

String vector of stock symbols of the S&P 500 constituents. The market index symbol is concluded as the attribute "index_symbol".

Source

[Yahoo! Finance](#)

stockDataDownload	<i>Download stock data from the Internet</i>
-------------------	--

Description

This function is basically a robust wrapper for [quantmod:getSymbols](#) to download stock data from the internet. It will return 6 xts objects of the same dimensions named 'open', 'high', 'low', 'close', 'volume', 'adjusted' and 'index'. Additionally, it can return an xts object with an index. If the download for some stock fails after a few attempts they will be ignored and reported. Also, stocks with missing values can be optionally removed.

Usage

```
stockDataDownload(stock_symbols, index_symbol = NULL, from, to,
  rm_stocks_with_na = TRUE, local_file_path = getwd(), ...)
```

Arguments

stock_symbols	String vector containing the symbols of the stocks to be downloaded. User can pass the market index symbol as its attribute 'index_symbol' (only considered when argument 'index_symbol' is not passed).
index_symbol	String of the market index symbol.
from	String as the starting date, e.g., "2017-08-17".
to	String as the ending date (not included), e.g., "2017-09-17".

rm_stocks_with_na Logical value indicating whether to remove stocks with missing values (ignoring leading missing values). Default is TRUE.

local_file_path Path where the stock data will be saved after the first time is downloaded, so that in future retrievals it will be locally loaded (if the same arguments are used). Default is getwd(). If local caching is not desired, it can be deactivated by setting local_file_path = NULL.

... Additional arguments to be passed to [quantmod:getSymbols](#).

Value

List of 7 xts objects named 'open', 'high', 'low', 'close', 'volume', 'adjusted' and 'index'. Note that 'index' will only be returned when correct index symbols is passed.

Author(s)

Rui Zhou and Daniel P. Palomar

See Also

[stockDataResample](#)

Examples

```
library(portfolioBacktest)
data(SP500_symbols)

# download data from internet
SP500_data <- stockDataDownload(stock_symbols = SP500_symbols,
                                from = "2008-12-01", to = "2009-12-01")
```

stockDataResample *Generate random resamples from stock data*

Description

This function resamples the stock data downloaded by [stockDataDownload](#) to obtain many datasets for a subsequent backtesting with [portfolioBacktest](#). Given the original data, each resample is obtained by randomly choosing a subset of the stock names and randomly choosing a time period over the available long period.

Usage

```
stockDataResample(X, N_sample = 50, T_sample = 2 * 252,
                  num_datasets = 10, rm_stocks_with_na = TRUE)
```

Arguments

<code>X</code>	List of xts objects matching the structure returned by the function stockDataDownload .
<code>N_sample</code>	Number of stocks in each resample.
<code>T_sample</code>	Length of each resample (consecutive samples with a random initial time).
<code>num_datasets</code>	Number of resampled datasets (chosen randomly among the stock universe).
<code>rm_stocks_with_na</code>	Logical value indicating whether to remove stocks with missing values (ignoring leading missing values). Default is TRUE.

Value

List of datasets resampled from `X`.

Author(s)

Rui Zhou and Daniel P. Palomar

See Also

[stockDataDownload](#), [portfolioBacktest](#)

Examples

```
library(portfolioBacktest)
data(SP500_symbols)

# download data from internet
SP500_data <- stockDataDownload(stock_symbols = SP500_symbols,
                                from = "2008-12-01", to = "2011-12-01")
# resample from downloaded, each with 50 stocks and 2-year continuous data
my_dataset_list <- stockDataResample(SP500_data, N = 50, T = 2*252, num_datasets = 10)
```

summaryBarPlot

Create barplot from backtest summary

Description

After performing a backtest with [portfolioBacktest](#) and obtaining a summary of the performance measures with [backtestSummary](#), this function creates a barplot from the summary. By default the plot is based on the package `ggplot2`, but the user can also specify a simple base plot.

Usage

```
summaryBarPlot(bt_summary, measures = NULL, type = c("ggplot2",
"simple"), ...)
```

Arguments

bt_summary	Backtest summary as obtained from the function backtestSummary.
measures	String vector to select performane measures (default is all) from ‘Sharpe ratio’, ‘max drawdown’, ‘annual return’, ‘annual volatility’, ‘Sterling ratio’, ‘Omega ratio’, and ‘ROT bps’.
type	Type of plot. Valid options: "ggplot2", "simple". Default is "ggplot2".
...	Additional parameters (only used for plot type = "simple"); for example: mar for margins as in par(), inset for the legend inset as in legend(), legend_loc for the legend location as in legend().

Author(s)

Daniel P. Palomar and Rui Zhou

See Also

[summaryTable](#), [backtestBoxPlot](#), [backtestChartCumReturns](#), [backtestChartDrawdown](#), [backtestChartStackedBar](#)

Examples

```
library(portfolioBacktest)
data(dataset10) # load dataset

# define your own portfolio function
quintile_portfolio <- function(data) {
  X <- diff(log(data$adjusted))[-1]
  N <- ncol(X)
  ranking <- sort(colMeans(X), decreasing = TRUE, index.return = TRUE)$ix
  w <- rep(0, N)
  w[ranking[1:round(N/5)]] <- 1/round(N/5)
  return(w)
}

# do backtest
bt <- portfolioBacktest(list("Quintile" = quintile_portfolio), dataset10,
  benchmark = c("uniform", "index"))

# now we can obtain the table
bt_summary_median <- backtestSummary(bt)
summaryBarPlot(bt_summary_median, measures = c("max drawdown", "annual volatility"))
summaryBarPlot(bt_summary_median, measures = c("max drawdown", "annual volatility"),
  type = "simple")
```

summaryTable	<i>Create table from backtest summary</i>
--------------	---

Description

After performing a backtest with [portfolioBacktest](#) and obtaining a summary of the performance measures with [backtestSummary](#), this function creates a table from the summary. By default the table is a simple matrix, but if the user has installed the package DT or grid.table nicer tables can be generated.

Usage

```
summaryTable(bt_summary, measures = NULL, type = c("simple", "DT",
  "grid.table"), order_col = NULL, order_dir = c("asc", "desc"),
  page_length = 10)
```

Arguments

bt_summary	Backtest summary as obtained from the function backtestSummary.
measures	String vector to select performane measures (default is all) from ‘Sharpe ratio’, ‘max drawdown’, ‘annual return’, ‘annual volatility’, ‘Sterling ratio’, ‘Omega ratio’, and ‘ROT bps’.
type	Type of table. Valid options: "simple", "DT", "grid.table". Default is "simple" and generates a simple matrix (with the other choices the corresponding package must be installed).
order_col	Column number or column name of the performance measure to be used to sort the rows (only used for table type = "DT"). By default the last column will be used.
order_dir	Direction to be used to sort the rows (only used for table type = "DT"). Valid options: "asc", "desc". Default is "asc".
page_length	Page length for the table (only used for table type = "DT"). Default is 10.

Author(s)

Daniel P. Palomar and Rui Zhou

See Also

[summaryBarPlot](#)

Examples

```
library(portfolioBacktest)
data(dataset10) # load dataset
```



```
# define your own portfolio function
quintile_portfolio <- function(data) {
  X <- diff(log(data$adjusted))[-1]
  N <- ncol(X)
  ranking <- sort(colMeans(X), decreasing = TRUE, index.return = TRUE)$ix
  w <- rep(0, N)
  w[ranking[1:round(N/5)]] <- 1/round(N/5)
  return(w)
}

# do backtest
bt <- portfolioBacktest(list("Quintile" = quintile_portfolio),
                        dataset10,
                        benchmark = c("uniform", "index"))

# now we can obtain the table
bt_summary_median <- backtestSummary(bt)
summaryTable(bt_summary_median, measures = c("max drawdown", "annual volatility"))
summaryTable(bt_summary_median, measures = c("max drawdown", "annual volatility"), type = "DT")
```

Index

*Topic **SP500_symbols**

SP500_symbols, [20](#)

*Topic **dataset**

dataset10, [14](#)

backtestBoxPlot, [3](#), [3](#), [5–7](#), [19](#), [23](#)

backtestChartCumReturns, [3](#), [4](#), [4](#), [6](#), [7](#), [23](#)

backtestChartDrawdown, [3–5](#), [5](#), [7](#), [23](#)

backtestChartStackedBar, [3–6](#), [7](#), [23](#)

backtestLeaderboard, [3](#), [8](#), [19](#)

backtestSelector, [3](#), [10](#), [19](#)

backtestSummary, [3](#), [8](#), [11](#), [19](#), [22](#), [24](#)

backtestTable, [3](#), [12](#), [19](#)

dataset10, [3](#), [14](#)

genRandomFuns, [14](#), [16](#)

plotPerformanceVsParams, [14](#), [15](#), [16](#)

portfolioBacktest, [3–8](#), [10](#), [11](#), [13](#), [16](#), [17](#),
[21](#), [22](#), [24](#)

portfolioBacktest-package, [2](#)

quantmod:getSymbols, [20](#), [21](#)

SP500_symbols, [3](#), [20](#)

stockDataDownload, [3](#), [17](#), [19](#), [20](#), [21](#), [22](#)

stockDataResample, [3](#), [17–19](#), [21](#), [21](#)

summaryBarPlot, [3–7](#), [19](#), [22](#), [24](#)

summaryTable, [3](#), [19](#), [23](#), [24](#)