

# Package ‘deductive’

April 10, 2019

**Maintainer** Mark van der Loo <mark.vanderloo@gmail.com>

**License** GPL-3

**Title** Data Correction and Imputation Using Deductive Methods

**LazyData** no

**Type** Package

**LazyLoad** yes

**Description** Attempt to repair inconsistencies and missing values in data records by using information from valid values and validation rules restricting the data.

**Version** 0.1.3

**Depends** R (>= 3.2.0)

**URL** <https://github.com/data-cleaning/deductive>

**BugReports** <https://github.com/data-cleaning/deductive/issues>

**Imports** methods, lintools (>= 0.1.2), validate, stringdist

**Suggests** testthat, knitr

**RoxygenNote** 6.1.1

**NeedsCompilation** yes

**Author** Mark van der Loo [cre, aut],  
Edwin de Jonge [aut]

**Repository** CRAN

**Date/Publication** 2019-04-10 13:55:46 UTC

## R topics documented:

correct_typos	2
deductive	3
impute_lr	3

<b>Index</b>	<b>5</b>
--------------	----------

---

correct_typos	<i>Correct typos in restricted numeric data</i>
---------------	---

---

### Description

Attempt to fix violations of linear (in)equality restrictions imposed on a record by replacing values with values that differ from the original values by typographical errors.

### Usage

```
correct_typos(dat, x, ...)

## S4 method for signature 'data.frame,validator'
correct_typos(dat, x, fixate = NULL,
              eps = 1e-08, maxdist = 1, ...)
```

### Arguments

dat	An R object holding numeric (integer) data.
x	An R object holding linear data validation rules
...	Options to be passed to <code>stringdist</code> which is used to determine the typographic distance between the original value and candidate solutions. By default, the optimal string alignment distance is used, with all weights equal to one.
fixate	[character] vector of variable names that may not be changed
eps	[numeric] maximum roundoff error
maxdist	[numeric] maximum allowed typographical distance

### Value

dat, with values corrected.

### Details

The algorithm works by proposing candidate replacement values and checking whether they are likely to be the result of a typographical error. A value is accepted as a solution when it resolves at least one equality violation. An equality restriction  $a \cdot x = b$  is considered satisfied when  $\text{abs}(a \cdot x - b) < \text{eps}$ . Setting eps to one or two units of measurement allows for robust typographical error detection in the presence of roundoff-errors.

The algorithm is meant to be used on numeric data representing integers.

### References

- The first version of the algorithm was described by S. Scholtus (2009). Automatic correction of simple typing errors in numerical data with balance edits. Statistics Netherlands, Discussion Paper [09046](#)

- The generalized version of this algorithm that is implemented for this package is described in M. van der Loo, E. de Jonge and S. Scholtus (2011). Correction of rounding, typing and sign errors with the deducorrect package. Statistics Netherlands, Discussion Paper [2011019](#)

## Examples

```
library(validate)

# example from section 4 in Scholtus (2009)

v <-validate::validator(
  x1 + x2 == x3
, x2 == x4
, x5 + x6 + x7 == x8
, x3 + x8 == x9
, x9 - x10 == x11
)

dat <- read.csv(textConnection(
"x1, x2 , x3 , x4 , x5 , x6, x7, x8 , x9 , x10 , x11
1452, 116, 1568, 116, 323, 76, 12, 411, 1979, 1842, 137
1452, 116, 1568, 161, 323, 76, 12, 411, 1979, 1842, 137
1452, 116, 1568, 161, 323, 76, 12, 411, 19979, 1842, 137
1452, 116, 1568, 161, 0, 0, 0, 411, 19979, 1842, 137
1452, 116, 1568, 161, 323, 76, 12, 0, 19979, 1842, 137"
))
cor <- correct_typos(dat,v)
dat - cor
```

---

deductive

*Deductive Data Correction and Imputation*

---

## Description

Deductive Data Correction and Imputation

---

impute\_lr

*Impute values derived from linear (in)equality restrictions.*

---

**Description**

Partially filled records  $x$  under linear (in)equality restrictions may reveal unique imputation solutions when the system of linear inequalities is reduced by substituting observed values. This function applies a number of fast heuristic methods before deriving all variable ranges and unique values.

**Usage**

```
impute_lr(dat, x, ...)  
  
## S4 method for signature 'data.frame,validator'  
impute_lr(dat, x, ...)
```

**Arguments**

dat	an R object carrying data
x	an R object carrying validation rules
...	arguments to be passed to other methods.

**Examples**

```
v <- validate::validator(y ==2,y + z ==3, x +y <= 0)  
dat <- data.frame(x=NA_real_,y=NA_real_,z=NA_real_)  
impute_lr(dat,v)
```

# Index

`correct_typos`, [2](#)  
`correct_typos`, `data.frame`, `validator-method`  
    (`correct_typos`), [2](#)

`deductive`, [3](#)  
`deductive-package` (`deductive`), [3](#)

`impute_lr`, [3](#)  
`impute_lr`, `data.frame`, `validator-method`  
    (`impute_lr`), [3](#)

`stringdist`, [2](#)