

Package ‘flexpolyline’

October 2, 2021

Type Package

Title Flexible Polyline Encoding

Version 0.2.4

Description Binding to the C++ implementation of the flexible polyline encoding by HERE <<https://github.com/heremaps/flexible-polyline>>. The flexible polyline encoding is a lossy compressed representation of a list of coordinate pairs or coordinate triples. The encoding is achieved by:

- (1) Reducing the decimal digits of each value;
- (2) encoding only the offset from the previous point;
- (3) using variable length for each coordinate delta; and
- (4) using 64 URL-safe characters to display the result.

License GPL-3

URL <https://munterfi.github.io/flexpolyline/>,
<https://github.com/munterfi/flexpolyline/>

BugReports <https://github.com/munterfi/flexpolyline/issues/>

LinkingTo Rcpp

Imports Rcpp, sf (>= 0.9-3)

Suggests testthat (>= 2.3.2), stringr (>= 1.4.0), knitr (>= 1.28),
rmarkdown (>= 2.1), covr (>= 3.5.0)

Encoding UTF-8

RoxygenNote 7.1.2

VignetteBuilder knitr

NeedsCompilation yes

Author Merlin Unterfinger [aut, cre] (<<https://orcid.org/0000-0003-2020-2366>>),
HERE Europe B.V. [aut, cph] (Flexible polyline encoding C++
implementation)

Maintainer Merlin Unterfinger <info@munterfinger.ch>

Repository CRAN

Date/Publication 2021-10-02 15:10:02 UTC

R topics documented:

decode	2
decode_sf	3
encode	3
encode_sf	4
get_third_dimension	6
set_third_dimension	6
Index	8

decode	<i>Decode a flexible polyline encoded string</i>
--------	--

Description

This function calls `hf::polyline_decode` and `hf::get_third_dimension` of the C++ implementation of the flexible polyline encoding by [HERE](#). Depending on the dimensions of the encoded line, a two or three dimensional line is decoded.

Usage

```
decode(encoded)
```

Arguments

encoded character, encoded flexible polyline string.

Value

A matrix containing the coordinates of the decoded line.

Examples

```
# 2d line
decode("BFoz5xJ67i1B1B7PzIhaxL7Y")

# 3d line
decode("B1Boz5xJ67i1BU1B7PUzIhaUxL7YU")
```

decode_sf	<i>Wrapper function for decoding to simple features</i>
-----------	---

Description

A wrapper function for [decode](#) that converts the input polylines, encoded in the flexible polyline encoding, to simple feature geometries of the sf package.

Usage

```
decode_sf(encoded, crs = sf::NA_crs_)
```

Arguments

encoded	character, encoded flexible polyline string.
crs	integer or character, coordinate reference system to assign to the sf object (default = sf::NA_crs_).

Value

An sf object, containing the geometries of the decoded lines (Geometry type: "LINESTRING").

Note

The function returns an sf object, therefore the input set of encoded polylines must be of consistent dimension (e.g "XY", "XYM" or "XYZ") to meet the requirements of the constructor of sf objects. For mixed dimensions use the [decode](#) function directly.

Examples

```
decode_sf("B1Voz5xJ67i1Bgkh9B")
decode_sf("BFoz5xJ67i1B1B7P1U9yB")
decode_sf("B1Xoz5xJ67i1Bgkh9B1B7Pgkh9BzIhagkh9BqK-pB_ni6D")
```

encode	<i>Encode a line in the flexible polyline encoding format</i>
--------	---

Description

This function calls `hf::polyline_encode` of the C++ implementation of the flexible polyline encoding by [HERE](#). Depending on the dimensions of the input coordinates, a two or three dimensional line is encoded.

Usage

```
encode(line, precision = 5L, third_dim = 3L, third_dim_precision = 5L)
```

Arguments

line	matrix, coordinates of the line in 2d or 3d (column order: LNG, LAT, DIM3).
precision	integer, precision to use in encoding (between 0 and 15, default=5).
third_dim	integer, type of the third dimension (0: ABSENT, 1: LEVEL, 2: ALTITUDE, 3: ELEVATION, 4, 6: CUSTOM1, 7: CUSTOM2, default=3).
third_dim_precision	integer, precision to use in encoding for the third dimension (between 1 and 15, default=5).

Value

The line as string in the flexible polyline encoding format.

Examples

```
# 2D
line2d <- matrix(
  c(8.69821, 50.10228,
    8.69567, 50.10201,
    8.69150, 50.10063,
    8.68752, 50.09878),
  ncol = 2, byrow = TRUE
)
encode(line2d)

# 3D
line3d <- matrix(
  c(8.69821, 50.10228, 10,
    8.69567, 50.10201, 20,
    8.69150, 50.10063, 30,
    8.68752, 50.09878, 40),
  ncol = 3, byrow = TRUE
)
encode(line3d)
```

encode_sf

Wrapper function for encoding simple features

Description

A wrapper function for [encode](#) that converts simple feature geometries of the sf package to flexible polyline encoded strings.

Usage

```
encode_sf(
  geom,
  precision = 5,
  third_dim = NULL,
  third_dim_precision = precision
)
```

Arguments

geom	simple feature, sf, sfc or sfg object with geometry type "POINT", "LINESTRING" or "POLYGON".
precision	integer, precision to use in encoding (between 0 and 15, default=5).
third_dim	integer, type of the third dimension (0: ABSENT, 1: LEVEL, 2: ALTITUDE, 3: ELEVATION, 4, 6: CUSTOM1, 7: CUSTOM2, default=NULL).
third_dim_precision	integer, precision to use in encoding for the third dimension (between 1 and 15, default=precision).

Value

The line as string in the flexible polyline encoding format.

Examples

```
# 3D point
point3d <- sf::st_point(
  matrix(c(8.69821, 50.10228, 10), ncol = 3, byrow = TRUE),
  dim = "XYZ"
)
encode_sf(point3d)

# 2D linestring
line2d <- sf::st_linestring(
  matrix(c(
    8.69821, 50.10228,
    8.69567, 50.10201,
    8.68752, 50.09878
  ), ncol = 2, byrow = TRUE)
)
encode_sf(line2d)

# 3D polygon
poly3d <- sf::st_polygon(list(
  matrix(c(
    8.69821, 50.10228, 10,
    8.69567, 50.10201, 20,
    8.69150, 50.10063, 30,
    8.69821, 50.10228, 10
  ), ncol = 3, byrow = TRUE)
)
```

```
), dim = "XYM")
encode_sf(poly3d)
```

```
get_third_dimension    Get third dimension of a flexible polyline encoded string
```

Description

This function calls `hf::get_third_dimension` of the C++ implementation of the flexible polyline encoding by HERE and return the type of the third dimension.

Usage

```
get_third_dimension(encoded)
```

Arguments

`encoded` character, encoded flexible polyline string.

Value

A string describing the third dimension.

Examples

```
# 2d line
get_third_dimension("BFoz5xJ67i1B1B7PzIhaxL7Y")

# 3d line
get_third_dimension("B1Boz5xJ67i1BU1B7PUzIhaUxL7YU")
```

```
set_third_dimension    Set third dimension of a flexible polyline encoded string
```

Description

This function decodes the flexible polyline encoded line, changes the third dimension and encodes the line again.

Usage

```
set_third_dimension(
  encoded,
  third_dim_name,
  precision = 5L,
  third_dim_precision = 5L
)
```

Arguments

`encoded` character, encoded flexible polyline string.
`third_dim_name` character, name of the third dimension to set (ABSENT, LEVEL, ALTITUDE, ELEVATION, CUSTOM1, CUSTOM2).
`precision` integer, precision to use in encoding (between 0 and 15, default=5).
`third_dim_precision` integer, precision to use in encoding for the third dimension (between 1 and 15, default=5).

Value

The line with the new third dimension as string in the flexible polyline encoding format.

Note

The precision is not read from the header of the encoded line. Therefore it must be provided as a parameter for re-encoding.

Examples

```
# 2d line (nothing happens...)  
set_third_dimension("BFoz5xJ67i1B1B7PzIhaxL7Y", "ELEVATION")  
  
# 3d line  
set_third_dimension("B1Boz5xJ67i1BU1B7PUzIhaUxL7YU", "ELEVATION")
```

Index

decode, [2](#), [3](#)
decode_sf, [3](#)

encode, [3](#), [4](#)
encode_sf, [4](#)

get_third_dimension, [6](#)

set_third_dimension, [6](#)