

Package ‘cmsafvis’

March 15, 2022

Title Tools to Visualize CM SAF NetCDF Data

Version 1.1.11

Description The Satellite Application Facility on Climate Monitoring (CM SAF) is a ground segment of the European Organization for the Exploitation of Meteorological Satellites (EUMETSAT) and one of EUMETSAT's Satellite Application Facilities. The CM SAF contributes to the sustainable monitoring of the climate system by providing essential climate variables related to the energy and water cycle of the atmosphere (<<https://www.cmsaf.eu>>). It is a joint cooperation of eight National Meteorological and Hydrological Services. The 'cmsafvis' R-package provides a collection of R-operators for the analysis and visualization of CM SAF NetCDF data. CM SAF climate data records are provided for free via (<<https://wui.cmsaf.eu/safira>>). Detailed information and test data are provided on the CM SAF webpage (<http://www.cmsaf.eu/R_toolbox>).

License GPL (>= 3)

Depends R (>= 3.6)

Imports animation (>= 2.6), assertthat (>= 0.2.1), cmsafops (>= 1.2.1), colorspace (>= 1.4), countrycode (>= 1.1), fields (>= 10.3), mapproj (>= 1.2.7), maps (>= 3.3.0), maptools (>= 0.9), methods (>= 3.6), ncdf4 (>= 1.17), png (>= 0.1), progress (>= 1.2.2), raster (>= 3.0), rworldxtra (>= 1.01), sp (>= 1.4), yaml (>= 2.2), RColorBrewer, rasterVis, gridExtra, SearchTrees, rgdal, utils

NeedsCompilation no

Repository CRAN

RoxygenNote 7.1.2

Encoding UTF-8

Language en-US

Suggests plotKML (>= 0.8), rnaturalearth (>= 0.1), spelling (>= 2.1), testthat (>= 2.3)

Maintainer Steffen Kothe <Steffen.Kothe@dwd.de>

Author Steffen Kothe [aut, cre],
Danny Parsons [ctb]

Date/Publication 2022-03-15 14:20:02 UTC

R topics documented:

absolute_map	2
anomaly_map	5
climatology_map	8
cmsaf.diff	10
cmsaf.hist	12
cmsaf.hovmoller	13
cmsaf.scatter	14
cmsaf.side.by.side	16
cmsaf.time.series	17
cmsafvis	18
fieldmean_and_anomaly_map	19
fieldmean_plot	22
get_basename_vis	25
helper_time_series_compare	26
monitor_climate	26
quicklook	29
recalculateImageDimensions	31
render_hist_plot	31
render_instat_plot	32
render_plot	33
render_plot_1d	35
render_plot_1d_advanced	36
render_plot_hist_compare	38
render_plot_hovmoller	39
render_plot_scatter	40
render_plot_side_by_side	41
render_plot_time_series_compare	43
render_preview_plot	45
render_region_plot	45
time_series_plot	47
trend_plot	50
warming_stripes_plot	52
Index	55

absolute_map	<i>A 'cmsaf' extension for creating absolute valued plots.</i>
--------------	--

Description

This plotting routine generates graphical output for the given variable within the given time range and area. Dependent on the output format a PNG or MP4 is created.

Usage

```

absolute_map(
  config = NULL,
  variable = NULL,
  accumulate = FALSE,
  mean_value = FALSE,
  infile = NULL,
  temp_dir = tempdir(),
  out_dir = getwd(),
  start_date = NULL,
  end_date = NULL,
  country_code = "S_A",
  lon_min = NULL,
  lon_max = NULL,
  lat_min = NULL,
  lat_max = NULL,
  outfile_name = NULL,
  output_format = "animation",
  animation_pace = 0.07,
  freeze_animation = FALSE,
  min_value = NULL,
  max_value = NULL,
  nbreaks = NULL,
  language = "eng",
  keep_files = TRUE,
  states = FALSE,
  attach = FALSE,
  infile_attach = "auto",
  dwd_logo = FALSE,
  verbose = TRUE,
  nc = NULL
)

```

Arguments

config	Path to YAML config file (character). The config file does not have to specify all arguments. Each addressed argument has to be formatted according to the example config file: (#TODO: LINK EXAMPLE CONFIG FILE!).
variable	Name of variable in infile (NULL or character). If NULL then the first variable from the infile is taken.
accumulate	Whether the input file should be accumulated (logical).
mean_value	Whether the input file should be averaged (logical).
infile	Path to NetCDF file (NULL or character). If NULL then it needs to be specified in the config file.
temp_dir	Path to temporary working directory (character).
out_dir	Path to output directory (character).

start_date	Start date in format of 'YYYY-MM-DD' (NULL or character). If NULL then the first date of the infile is used.
end_date	End date in format of 'YYYY-MM-DD' (NULL or character). If NULL then the last date of the infile is used.
country_code	Either a country code in iso3c format or from the following: 'AFR' for Africa, 'EUR' for Europe, 'TOT' for the total disc, or 'S_A' for an arbitrary region selection (character). If a country is passed the data from within this country is extracted, else a rectangular box is visualized. Directly provided latitude and longitude ranges will be ignored in case of 'AFR', 'EUR' or 'TOT'.
lon_min	Longitude of lower left corner (NULL or numeric). If NULL then the smallest longitude of the infile is used.
lon_max	Longitude of upper right left corner (NULL or numeric). If NULL then the largest longitude of the infile is used.
lat_min	Latitude of lower left corner (NULL or numeric). If NULL then the smallest latitude of the infile is used.
lat_max	Latitude of upper right corner (NULL or numeric). If NULL then the largest latitude of the infile is used.
outfile_name	Filename of the PNG or MP4 outfile (NULL or character). If NULL then a name is computed from the current configuration. Please match the file ending according to the output_format.
output_format	Specification of output format (either 'graphic' for PNG or 'animation' for MP4).
animation_pace	Pace of the animation in seconds (positive numeric). This only has an effect if output_format == 'animation'.
freeze_animation	If TRUE then the animation will freeze at the last frame (logical).
min_value	Lower values than this are ignored (NULL or numeric). If NULL, no values are ignored.
max_value	Larger values than this are ignored (NULL or numeric). If NULL, no values are ignored.
nbreaks	Number of color breaks (NULL or positive integer). A value will be computed if NULL is passed.
language	Language used for title, legend, etc. in plots (either 'eng' for English or 'deu' for German).
keep_files	A flag indicating whether all files created in the process of obtaining the output file should be kept (logical). If false, all intermediate results are deleted, otherwise all are kept. Keeping these files could improve performance in further function calls.
states	Whether to crop/plot administration level of states (logical).
attach	Whether to temporarily merge the infile to an already existing one. (logical).
infile_attach	File to attach the infile to. When 'auto', a suitable file will be searched in out_dir. If attach is false, this will be ignored(character).
dwd_logo	Whether to add the DWD logo (logical).
verbose	Whether to display progress messages (logical).
nc	Alternatively to infile you can specify the input as an object of class ncdf4 (as returned from ncdf4::nc_open).

Details

You can pass a YAML config file and/or specify the arguments directly. Argument prioritization is done in the following way: Direct argument > config argument > default argument. Thus, if you pass a existing config file but also want to modify a specific argument you can do that easily.

anomaly_map

A 'cmsaf' extension for creating an anomaly map.

Description

This plotting routine generates a graph showing the anomaly of a given variable within the given time range and area. The intended application is for daily accumulated data, such as sunshine duration. Dependent on the output format a PNG or MP4 is created.

Usage

```
anomaly_map(  
  config = NULL,  
  variable = NULL,  
  accumulate = FALSE,  
  mean_value = FALSE,  
  infile = NULL,  
  temp_dir = tempdir(),  
  out_dir = getwd(),  
  climate_dir = NULL,  
  climate_year_start = 1983,  
  climate_year_end = 2018,  
  start_date = NULL,  
  end_date = NULL,  
  country_code = "S_A",  
  lon_min = NULL,  
  lon_max = NULL,  
  lat_min = NULL,  
  lat_max = NULL,  
  outfile_name = NULL,  
  output_format = "animation",  
  animation_pace = 0.07,  
  freeze_animation = FALSE,  
  min_value = NULL,  
  max_value = NULL,  
  color_pal = 1,  
  relative = FALSE,  
  nbreaks = NULL,  
  language = "eng",  
  keep_files = TRUE,  
  states = FALSE,
```

```

attach = FALSE,
infile_attach = "auto",
dwd_logo = FALSE,
verbose = TRUE,
nc = NULL
)

```

Arguments

config	Path to YAML config file (character). The config file does not have to specify all arguments. Each addressed argument has to be formatted according to the example config file: (#TODO: LINK EXAMPLE CONFIG FILE!).
variable	Name of variable in infile (NULL or character). If NULL then the first variable from the infile is taken.
accumulate	Whether the input file should be accumulated (logical).
mean_value	Whether the input file should be averaged (logical).
infile	Path to NetCDF file (NULL or character). If NULL then it needs to be specified in the config file.
temp_dir	Path to temporary working directory (character).
out_dir	Path to output directory (character).
climate_dir	Path to directory in which climatology is computed or contained (NULL or character). If NULL then the temp_dir directory is taken.
climate_year_start	Start year of climatology (integer).
climate_year_end	End year of climatology (integer).
start_date	Start date in format of 'YYYY-MM-DD' (NULL or character). If NULL then the first date of the infile is used.
end_date	End date in format of 'YYYY-MM-DD' (NULL or character). If NULL then the last date of the infile is used.
country_code	Either a country code in iso3c format or from the following: 'AFR' for Africa, 'EUR' for Europe, 'TOT' for the total disc, or 'S_A' for an arbitrary region selection (character). If a country is passed the data from within this country is extracted, else a rectangular box is visualized. Directly provided latitude and longitude ranges will be ignored in case of 'AFR', 'EUR' or 'TOT'.
lon_min	Longitude of lower left corner (NULL or numeric). If NULL then the smallest longitude of the infile is used.
lon_max	Longitude of upper right left corner (NULL or numeric). If NULL then the largest longitude of the infile is used.
lat_min	Latitude of lower left corner (NULL or numeric). If NULL then the smallest latitude of the infile is used.
lat_max	Latitude of upper right corner (NULL or numeric). If NULL then the largest latitude of the infile is used.

outfile_name	Filename of the PNG or MP4 outfile (NULL or character). If NULL then a name is computed from the current configuration. Please match the file ending according to the output_format.
output_format	Specification of output format (either 'graphic' for PNG or 'animation' for MP4).
animation_pace	Pace of the animation in seconds (positive numeric). This only has an effect if output_format == 'animation'.
freeze_animation	If TRUE then the animation will freeze at the last frame (logical).
min_value	Lower values than this are ignored (NULL or numeric). If NULL, no values are ignored.
max_value	Larger values than this are ignored (NULL or numeric). If NULL, no values are ignored.
color_pal	Color option for stripe and anomaly plots
relative	Use relative values for anomaly plots
nbreaks	Number of color breaks (NULL or positive integer). A value will be computed if NULL is passed.
language	Language used for title, legend, etc. in plots (either 'eng' for English or 'deu' for German).
keep_files	A flag indicating whether all files created in the process of obtaining the output file should be kept (logical). If false, all intermediate results are deleted, otherwise all are kept. Keeping these files could improve performance in further function calls.
states	Whether to crop/plot administration level of states (logical).
attach	Whether to temporarily merge the infile to an already existing one. (logical).
infile_attach	File to attach the infile to. When 'auto', a suitable file will be searched in out_dir. If attach is false, this will be ignored(character).
dwd_logo	Whether to add the DWD logo (logical).
verbose	Whether to display progress messages (logical).
nc	Alternatively to infile you can specify the input as an object of class ncd4 (as returned from ncd4::nc_open).

Details

You can pass a YAML config file and / or specify the arguments directly. Argument prioritization is done in the following way: Direct argument > config argument > default argument. Thus, if you pass a existing config file but also want to modify a specific argument you can do that easily.

climatology_map *A 'cmsaf' extension for creating a climatology map.*

Description

This plotting routine generates the climatological mean for the given variable within the given time range and area. The intended application is for daily accumulated data, such as sunshine duration. Dependent on the output format a PNG or MP4 is created.

Usage

```
climatology_map(  
  config = NULL,  
  variable = NULL,  
  accumulate = FALSE,  
  mean_value = FALSE,  
  infile = NULL,  
  temp_dir = tempdir(),  
  out_dir = getwd(),  
  climate_dir = NULL,  
  climate_year_start = 1983,  
  climate_year_end = 2018,  
  start_date = NULL,  
  end_date = NULL,  
  country_code = "S_A",  
  lon_min = NULL,  
  lon_max = NULL,  
  lat_min = NULL,  
  lat_max = NULL,  
  outfile_name = NULL,  
  output_format = "animation",  
  animation_pace = 0.07,  
  freeze_animation = FALSE,  
  min_value = NULL,  
  max_value = NULL,  
  nbreaks = NULL,  
  language = "eng",  
  keep_files = TRUE,  
  states = FALSE,  
  attach = FALSE,  
  infile_attach = "auto",  
  dwd_logo = FALSE,  
  verbose = TRUE,  
  nc = NULL  
)
```


Arguments

config	Path to YAML config file (character). The config file does not have to specify all arguments. Each addressed argument has to be formatted according to the example config file: (#TODO: LINK EXAMPLE CONFIG FILE!).
variable	Name of variable in infile (NULL or character). If NULL then the first variable from the infile is taken.
accumulate	Whether the input file should be accumulated (logical).
mean_value	Whether the input file should be averaged (logical).
infile	Path to NetCDF file (NULL or character). If NULL then it needs to be specified in the config file.
temp_dir	Path to temporary working directory (character).
out_dir	Path to output directory (character).
climate_dir	Path to directory in which climatology is computed or contained (NULL or character). If NULL then the temp_dir directory is taken.
climate_year_start	Start year of climatology (integer).
climate_year_end	End year of climatology (integer).
start_date	Start date in format of 'YYYY-MM-DD' (NULL or character). If NULL then the first date of the infile is used.
end_date	End date in format of 'YYYY-MM-DD' (NULL or character). If NULL then the last date of the infile is used.
country_code	Either a country code in iso3c format or from the following: 'AFR' for Africa, 'EUR' for Europe, 'TOT' for the total disc, or 'S_A' for an arbitrary region selection (character). If a country is passed the data from within this country is extracted, else a rectangular box is visualized. Directly provided latitude and longitude ranges will be ignored in case of 'AFR', 'EUR' or 'TOT'.
lon_min	Longitude of lower left corner (NULL or numeric). If NULL then the smallest longitude of the infile is used.
lon_max	Longitude of upper right left corner (NULL or numeric). If NULL then the largest longitude of the infile is used.
lat_min	Latitude of lower left corner (NULL or numeric). If NULL then the smallest latitude of the infile is used.
lat_max	Latitude of upper right corner (NULL or numeric). If NULL then the largest latitude of the infile is used.
outfile_name	Filename of the PNG or MP4 outfile (NULL or character). If NULL then a name is computed from the current configuration. Please match the file ending according to the output_format.
output_format	Specification of output format (either 'graphic' for PNG or 'animation' for MP4).
animation_pace	Pace of the animation in seconds (positive numeric). This only has an effect if output_format == 'animation'.
freeze_animation	If TRUE then the animation will freeze at the last frame (logical).

min_value	Lower values than this are ignored (NULL or numeric). If NULL, no values are ignored.
max_value	Larger values than this are ignored (NULL or numeric). If NULL, no values are ignored.
nbreaks	Number of color breaks (NULL or positive integer). A value will be computed if NULL is passed.
language	Language used for title, legend, etc. in plots (either 'eng' for English or 'deu' for German).
keep_files	A flag indicating whether all files created in the process of obtaining the output file should be kept (logical). If false, all intermediate results are deleted, otherwise all are kept. Keeping these files could improve performance in further function calls.
states	Whether to crop/plot administration level of states (logical).
attach	Whether to temporarily merge the infile to an already existing one. (logical).
infile_attach	File to attach the infile to. When 'auto', a suitable file will be searched in out_dir. If attach is false, this will be ignored(character).
dwd_logo	Whether to add the DWD logo (logical).
verbose	Whether to display progress messages (logical).
nc	Alternatively to infile you can specify the input as an object of class ncdf4 (as returned from ncdf4::nc_open).

Details

You can pass a YAML config file and/or specify the arguments directly. Argument prioritization is done in the following way: Direct argument > config argument > default argument. Thus, if you pass a existing config file but also want to modify a specific argument you can do that easily.

cmsaf.diff

Plotting routine designed for the CM SAF R Toolbox.

Description

This function renders a difference plot (absolute or relative) of two variables.

Usage

```
cmsaf.diff(
  var1,
  infile1,
  var2,
  infile2,
  outfile,
  plot.out = FALSE,
  relative = FALSE,
```

```
nc34 = 4,  
overwrite = FALSE,  
verbose = FALSE,  
toolbox = FALSE,  
nc1 = NULL,  
nc2 = NULL  
)
```

Arguments

var1	Name of the first NetCDF variable (character).
infile1	Filename of the first input NetCDF file. This may include the directory (character).
var2	Name of the second NetCDF variable (character).
infile2	Filename of the second input NetCDF file. This may include the directory (character).
outfile	Filename of output NetCDF file. This may include the directory (character).
plot.out	logical; if TRUE, the plot will be stored in the same folder as outfile. If FALSE, the plot will not be saved.
relative	logical; if TRUE, plot a relative difference plot
nc34	NetCDF version of output file. If nc34 = 3 the output file will be in NetCDFv3 format (numeric). Default output is NetCDFv4.
overwrite	logical; should existing output file be overwritten?
verbose	logical; if TRUE, progress messages are shown
toolbox	logical; if TRUE, toolbox mode enabled. The two files are adjusted in space and time so that they can be plotted.
nc1	Alternatively to <code>infile1</code> you can specify the input as an object of class <code>ncdf4</code> (as returned from <code>ncdf4::nc_open</code>).
nc2	Alternatively to <code>infile2</code> you can specify the input as an object of class <code>ncdf4</code> (as returned from <code>ncdf4::nc_open</code>).

Value

A NetCDF file is written.

See Also

Other 2d visualization: [cmsaf.side.by.side\(\)](#)

`cmsaf.hist`*Plotting routine designed for the CM SAF R Toolbox.*

Description

This function renders a histogram plot of two variables.

Usage

```
cmsaf.hist(  
  var1,  
  infile1,  
  var2,  
  infile2,  
  outfile1,  
  outfile2,  
  plot.out = FALSE,  
  nc34 = 4,  
  overwrite = FALSE,  
  verbose = FALSE,  
  toolbox = FALSE,  
  nc1 = NULL,  
  nc2 = NULL  
)
```

Arguments

<code>var1</code>	Name of the first NetCDF variable (character).
<code>infile1</code>	Filename of the first input NetCDF file. This may include the directory (character).
<code>var2</code>	Name of the second NetCDF variable (character).
<code>infile2</code>	Filename of the second input NetCDF file. This may include the directory (character).
<code>outfile1</code>	Filename of the first output NetCDF file. This may include the directory (character).
<code>outfile2</code>	Filename of the second output NetCDF file. This may include the directory (character).
<code>plot.out</code>	logical; if TRUE, the plot will be stored in the same folder as <code>outfile1</code> . If FALSE, the plot will not be saved.
<code>nc34</code>	NetCDF version of output file. If <code>nc34 = 3</code> the output file will be in NetCDFv3 format (numeric). Default output is NetCDFv4.
<code>overwrite</code>	logical; should existing output file be overwritten?
<code>verbose</code>	logical; if TRUE, progress messages are shown

toolbox	logical; if TRUE, toolbox mode enabled. The two files are adjusted in space and time so that they can be plotted.
nc1	Alternatively to infile1 you can specify the input as an object of class ncdf4 (as returned from ncdf4::nc_open).
nc2	Alternatively to infile2 you can specify the input as an object of class ncdf4 (as returned from ncdf4::nc_open).

Value

Two NetCDF files are written.

See Also

Other 1d visualization: [cmsaf.hovmoller\(\)](#), [cmsaf.scatter\(\)](#), [cmsaf.time.series\(\)](#)

`cmsaf.hovmoller` *Plotting routine designed for the CM SAF R Toolbox.*

Description

This function renders a hovmoller plot of two variables.

Usage

```
cmsaf.hovmoller(
  var1,
  infile1,
  var2,
  infile2,
  outfile1,
  outfile2,
  plot.out = FALSE,
  nc34 = 4,
  overwrite = FALSE,
  verbose = FALSE,
  toolbox = FALSE,
  nc1 = NULL,
  nc2 = NULL
)
```

Arguments

var1	Name of the first NetCDF variable (character).
infile1	Filename of the first input NetCDF file. This may include the directory (character).
var2	Name of the second NetCDF variable (character).

infile2	Filename of the second input NetCDF file. This may include the directory (character).
outfile1	Filename of the first output NetCDF file. This may include the directory (character).
outfile2	Filename of the second output NetCDF file. This may include the directory (character).
plot.out	logical; if TRUE, the plot will be stored in the same folder as outfile1. If FALSE, the plot will not be saved.
nc34	NetCDF version of output file. If nc34 = 3 the output file will be in NetCDFv3 format (numeric). Default output is NetCDFv4.
overwrite	logical; should existing output file be overwritten?
verbose	logical; if TRUE, progress messages are shown
toolbox	logical; if TRUE, toolbox mode enabled. The two files are adjusted in space and time so that they can be plotted.
nc1	Alternatively to infile1 you can specify the input as an object of class ncdf4 (as returned from ncdf4::nc_open).
nc2	Alternatively to infile2 you can specify the input as an object of class ncdf4 (as returned from ncdf4::nc_open).

Value

Two NetCDF files are written.

See Also

Other 1d visualization: [cmsaf.hist\(\)](#), [cmsaf.scatter\(\)](#), [cmsaf.time.series\(\)](#)

cmsaf.scatter

Plotting routine designed for the CM SAF R Toolbox.

Description

This function renders a scatter plot of two variables.

Usage

```
cmsaf.scatter(
  var1,
  infile1,
  var2,
  infile2,
  outfile1,
  outfile2,
  plot.out = FALSE,
  nc34 = 4,
```

```

    overwrite = FALSE,
    verbose = FALSE,
    toolbox = FALSE,
    nc1 = NULL,
    nc2 = NULL
)

```

Arguments

var1	Name of the first NetCDF variable (character).
infile1	Filename of the first input NetCDF file. This may include the directory (character).
var2	Name of the second NetCDF variable (character).
infile2	Filename of the second input NetCDF file. This may include the directory (character).
outfile1	Filename of the first output NetCDF file. This may include the directory (character).
outfile2	Filename of the second output NetCDF file. This may include the directory (character).
plot.out	logical; if TRUE, the plot will be stored in the same folder as outfile1. If FALSE, the plot will not be saved.
nc34	NetCDF version of output file. If nc34 = 3 the output file will be in NetCDFv3 format (numeric). Default output is NetCDFv4.
overwrite	logical; should existing output file be overwritten?
verbose	logical; if TRUE, progress messages are shown
toolbox	logical; if TRUE, toolbox mode enabled. The two files are adjusted in space and time so that they can be plotted.
nc1	Alternatively to infile1 you can specify the input as an object of class ncdf4 (as returned from ncdf4::nc_open).
nc2	Alternatively to infile2 you can specify the input as an object of class ncdf4 (as returned from ncdf4::nc_open).

Value

Two NetCDF files are written.

See Also

Other 1d visualization: [cmsaf.hist\(\)](#), [cmsaf.hovmoller\(\)](#), [cmsaf.time.series\(\)](#)

cmsaf.side.by.side *Plotting routine designed for the CM SAF R Toolbox.*

Description

This function renders a side by side plot of two variables.

Usage

```
cmsaf.side.by.side(
  var1,
  infile1,
  var2,
  infile2,
  outfile1,
  outfile2,
  plot.out = FALSE,
  nc34 = 4,
  overwrite = FALSE,
  verbose = FALSE,
  toolbox = FALSE,
  nc1 = NULL,
  nc2 = NULL
)
```

Arguments

var1	Name of the first NetCDF variable (character).
infile1	Filename of the first input NetCDF file. This may include the directory (character).
var2	Name of the second NetCDF variable (character).
infile2	Filename of the second input NetCDF file. This may include the directory (character).
outfile1	Filename of the first output NetCDF file. This may include the directory (character).
outfile2	Filename of the second output NetCDF file. This may include the directory (character).
plot.out	logical; if TRUE, the plot will be stored in the same folder as outfile1. If FALSE, the plot will not be saved.
nc34	NetCDF version of output file. If nc34 = 3 the output file will be in NetCDFv3 format (numeric). Default output is NetCDFv4.
overwrite	logical; should existing output file be overwritten?
verbose	logical; if TRUE, progress messages are shown

toolbox	logical; if TRUE, toolbox mode enabled. The two files are adjusted in space and time so that they can be plotted.
nc1	Alternatively to infile1 you can specify the input as an object of class ncdf4 (as returned from ncdf4::nc_open).
nc2	Alternatively to infile2 you can specify the input as an object of class ncdf4 (as returned from ncdf4::nc_open).

Value

Two NetCDF files are written.

See Also

Other 2d visualization: [cmsaf.diff\(\)](#)

cmsaf.time.series *Plotting routine designed for the CM SAF R Toolbox.*

Description

This function renders a time series plot of two variables.

Usage

```
cmsaf.time.series(  
  var1,  
  infile1,  
  var2,  
  infile2,  
  outfile1,  
  outfile2,  
  plot.out = FALSE,  
  nc34 = 4,  
  overwrite = FALSE,  
  verbose = FALSE,  
  toolbox = FALSE,  
  nc1 = NULL,  
  nc2 = NULL  
)
```

Arguments

var1	Name of the first NetCDF variable (character).
infile1	Filename of the first input NetCDF file. This may include the directory (character).
var2	Name of the second NetCDF variable (character).

infile2	Filename of the second input NetCDF file. This may include the directory (character).
outfile1	Filename of the first output NetCDF file. This may include the directory (character).
outfile2	Filename of the second output NetCDF file. This may include the directory (character).
plot.out	logical; if TRUE, the plot will be stored in the same folder as outfile1. If FALSE, the plot will not be saved.
nc34	NetCDF version of output file. If nc34 = 3 the output file will be in NetCDFv3 format (numeric). Default output is NetCDFv4.
overwrite	logical; should existing output file be overwritten?
verbose	logical; if TRUE, progress messages are shown
toolbox	logical; if TRUE, toolbox mode enabled. The two files are adjusted in space and time so that they can be plotted.
nc1	Alternatively to infile1 you can specify the input as an object of class ncd4 (as returned from ncd4::nc_open).
nc2	Alternatively to infile2 you can specify the input as an object of class ncd4 (as returned from ncd4::nc_open).

Value

Two NetCDF files are written.

See Also

Other 1d visualization: [cmsaf.hist\(\)](#), [cmsaf.hovmoller\(\)](#), [cmsaf.scatter\(\)](#)

cmsafvis	<i>cmsafvis: A 'cmsaf' package extension for visualization of CM SAF NetCDF data.</i>
----------	---

Description

The 'cmsafvis' plotting routines are designed to analyze climate files by generating graphics or videos. The functions (Fieldmean, Fieldmean and anomaly plots) were designed and tested for daily valued CM SAF NetCDF data. The functions (Absolute Map, Anomaly Map, Climatology, Warming Stripes Plot, Time Series Plot, Trend Plot) were designed and tested for daily or monthly valued CM SAF NetCDF data. As interface to NetCDF data the [ncdf4 package](#) is used.

Absolute

[absolute_map](#)

Anomaly

[anomaly_map](#)

Climatology

[climatology_map](#)

Fieldmean

[fieldmean_plot](#)

Fieldmean and anomaly plots

[fieldmean_and_anomaly_map](#)

Warming Stripes Plot

[warming_stripes_plot](#)

Time Series Plot

[time_series_plot](#)

Trend Plot

[trend_plot](#)

Author(s)

Maintainer: Steffen Kothe <Steffen.Kothe@dwd.de>

Contact: CM SAF Team <contact.cmsaf@dwd.de>

References

http://www.cmsaf.eu/R_toolbox

Kothe, S.; Hollmann, R.; Pfeifroth, U.; Träger-Chatterjee, C.; Trentmann, J. The CM SAF R Toolbox—A Tool for the Easy Usage of Satellite-Based Climate Data in NetCDF Format. ISPRS Int. J. Geo-Inf. 2019, 8, 109. doi: [10.3390/ijgi8030109](https://doi.org/10.3390/ijgi8030109)

fieldmean_and_anomaly_map

A 'cmsaf' extension for creating both, a spatial mean and an anomaly map.

Description

This plotting routine generates a graph showing the evolution of the spatial mean of a given variable and the corresponding anomaly map within the given time range and area. The intended application is for daily accumulated data, such as sunshine duration. Dependent on the output format a PNG or MP4 is created.

Usage

```

fieldmean_and_anomaly_map(
  config = NULL,
  variable = NULL,
  accumulate = FALSE,
  infile = NULL,
  temp_dir = tempdir(),
  out_dir = getwd(),
  climate_dir = NULL,
  climate_year_start,
  climate_year_end,
  show_extreme_climate_years = NULL,
  climatology_until_eoy = FALSE,
  start_date = NULL,
  end_date = NULL,
  country_code = "S_A",
  lon_min = NULL,
  lon_max = NULL,
  lat_min = NULL,
  lat_max = NULL,
  outfile_name = NULL,
  output_format = "animation",
  animation_pace = 0.07,
  freeze_animation = FALSE,
  min_value = NULL,
  max_value = NULL,
  nbreaks = NULL,
  language = "eng",
  keep_files = TRUE,
  states = FALSE,
  attach = FALSE,
  infile_attach = "auto",
  dwd_logo = FALSE,
  verbose = TRUE,
  nc = NULL
)

```

Arguments

<code>config</code>	Path to YAML config file (character). The config file does not have to specify all arguments. Each addressed argument has to be formatted according to the example config file: (#TODO: LINK EXAMPLE CONFIG FILE!).
<code>variable</code>	Name of variable in infile (NULL or character). If NULL then the first variable from the infile is taken.
<code>accumulate</code>	Whether the input file should be accumulated (logical).
<code>infile</code>	Path to NetCDF file (NULL or character). If NULL then it needs to be specified in the config file.

temp_dir	Path to temporary working directory (character).
out_dir	Path to output directory (character).
climate_dir	Path to directory in which climatology is computed or contained (NULL or character). If NULL then the temp_dir directory is taken.
climate_year_start	Start year of climatology (integer).
climate_year_end	End year of climatology (integer).
show_extreme_climate_years	Whether the minimum and maximum of the climate years should be titled in the fieldmean plot (NULL or logical). This is usually only of interest when plotting accumulated data. If the default NULL is chosen, then it will be set to the value of accumulate.
climatology_until_eoy	Plot the climatology and fieldmeans until the end of year (logical). Only affects fieldmean plots analyzed from January 1st.
start_date	Start date in format of 'YYYY-MM-DD' (NULL or character). If NULL then the first date of the infile is used.
end_date	End date in format of 'YYYY-MM-DD' (NULL or character). If NULL then the last date of the infile is used.
country_code	Either a country code in iso3c format or from the following: 'AFR' for Africa, 'EUR' for Europe, 'TOT' for the total disc, or 'S_A' for an arbitrary region selection (character). If a country is passed the data from within this country is extracted, else a rectangular box is visualized. Directly provided latitude and longitude ranges will be ignored in case of 'AFR', 'EUR' or 'TOT'.
lon_min	Longitude of lower left corner (NULL or numeric). If NULL then the smallest longitude of the infile is used.
lon_max	Longitude of upper right left corner (NULL or numeric). If NULL then the largest longitude of the infile is used.
lat_min	Latitude of lower left corner (NULL or numeric). If NULL then the smallest latitude of the infile is used.
lat_max	Latitude of upper right corner (NULL or numeric). If NULL then the largest latitude of the infile is used.
outfile_name	Filename of the PNG or MP4 outfile (NULL or character). If NULL then a name is computed from the current configuration. Please match the file ending according to the output_format.
output_format	Specification of output format (either 'graphic' for PNG or 'animation' for MP4).
animation_pace	Pace of the animation in seconds (positive numeric). This only has an effect if output_format == 'animation'.
freeze_animation	If TRUE then the animation will freeze at the last frame (logical).
min_value	Lower values than this are ignored (NULL or numeric). If NULL, no values are ignored.

max_value	Larger values than this are ignored (NULL or numeric). If NULL, no values are ignored.
nbreaks	Number of color breaks (NULL or positive integer). A value will be computed if NULL is passed.
language	Language used for title, legend, etc. in plots (either 'eng' for English or 'deu' for German).
keep_files	A flag indicating whether all files created in the process of obtaining the output file should be kept (logical). If false, all intermediate results are deleted, otherwise all are kept. Keeping these files could improve performance in further function calls.
states	Whether to crop/plot administration level of states (logical).
attach	Whether to temporaly merge the infile to an already existing one. (logical).
infile_attach	File to attach the infile to. When 'auto', a suitable file will be searched in out_dir. If attach is false, this will be ignored(character).
dwd_logo	Whether to add the DWD logo (logical).
verbose	Whether to display progress messages (logical).
nc	Alternatively to infile you can specify the input as an object of class ncdf4 (as returned from ncdf4::nc_open).

Details

You can pass a YAML config file and/or specify the arguments directly. Argument prioritization is done in the following way: Direct argument > config argument > default argument. Thus, if you pass a existing config file but also want to modify a specific argument you can do that easily.

fieldmean_plot	<i>A 'cmsaf' extension for creating spatial mean plots.</i>
----------------	---

Description

This plotting routine generates a graph showing the evolution of the spatial mean of a given variable within the given time range and area. The intended application is for daily accumulated data, such as sunshine duration. Dependent on the output format a PNG or MP4 is created.

Usage

```
fieldmean_plot(
  config = NULL,
  variable = NULL,
  accumulate = FALSE,
  infile = NULL,
  temp_dir = tempdir(),
  out_dir = getwd(),
  climate_dir = NULL,
```

```

climate_year_start = 1983,
climate_year_end = 2018,
show_extreme_climate_years = NULL,
climatology_until_eoy = FALSE,
start_date = NULL,
end_date = NULL,
country_code = "S_A",
lon_min = NULL,
lon_max = NULL,
lat_min = NULL,
lat_max = NULL,
outfile_name = NULL,
output_format = "animation",
animation_pace = 0.07,
freeze_animation = FALSE,
language = "eng",
keep_files = TRUE,
states = FALSE,
attach = FALSE,
infile_attach = "auto",
dwd_logo = FALSE,
verbose = TRUE,
nc = NULL
)

```

Arguments

config	Path to YAML config file (character). The config file does not have to specify all arguments. Each addressed argument has to be formatted according to the example config file: (#TODO: LINK EXAMPLE CONFIG FILE!).
variable	Name of variable in infile (NULL or character). If NULL then the first variable from the infile is taken.
accumulate	Whether the input file should be accumulated (logical).
infile	Path to NetCDF file (NULL or character). If NULL then it needs to be specified in the config file.
temp_dir	Path to temporary working directory (character).
out_dir	Path to output directory (character).
climate_dir	Path to directory in which climatology is computed or contained (NULL or character). If NULL then the temp_dir directory is taken.
climate_year_start	Start year of climatology (integer).
climate_year_end	End year of climatology (integer).
show_extreme_climate_years	Whether the minimum and maximum of the climate years should be titled in the fieldmean plot (NULL or logical). This is usually only of interest when plotting

	accumulated data. If the default NULL is chosen, then it will be set to the value of accumulate.
climatology_until_eoy	Plot the climatology and fieldmeans until the end of year (logical). Only affects fieldmean plots analyzed from January 1st.
start_date	Start date in format of 'YYYY-MM-DD' (NULL or character). If NULL then the first date of the infile is used.
end_date	End date in format of 'YYYY-MM-DD' (NULL or character). If NULL then the last date of the infile is used.
country_code	Either a country code in iso3c format or from the following: 'AFR' for Africa, 'EUR' for Europe, 'TOT' for the total disc, or 'S_A' for an arbitrary region selection (character). If a country is passed the data from within this country is extracted, else a rectangular box is visualized. Directly provided latitude and longitude ranges will be ignored in case of 'AFR', 'EUR' or 'TOT'.
lon_min	Longitude of lower left corner (NULL or numeric). If NULL then the smallest longitude of the infile is used.
lon_max	Longitude of upper right left corner (NULL or numeric). If NULL then the largest longitude of the infile is used.
lat_min	Latitude of lower left corner (NULL or numeric). If NULL then the smallest latitude of the infile is used.
lat_max	Latitude of upper right corner (NULL or numeric). If NULL then the largest latitude of the infile is used.
outfile_name	Filename of the PNG or MP4 outfile (NULL or character). If NULL then a name is computed from the current configuration. Please match the file ending according to the output_format.
output_format	Specification of output format (either 'graphic' for PNG or 'animation' for MP4).
animation_pace	Pace of the animation in seconds (positive numeric). This only has an effect if output_format == 'animation'.
freeze_animation	If TRUE then the animation will freeze at the last frame (logical).
language	Language used for title, legend, etc. in plots (either 'eng' for English or 'deu' for German).
keep_files	A flag indicating whether all files created in the process of obtaining the output file should be kept (logical). If false, all intermediate results are deleted, otherwise all are kept. Keeping these files could improve performance in further function calls.
states	Whether to crop/plot administration level of states (logical).
attach	Whether to temporaly merge the infile to an already existing one. (logical).
infile_attach	File to attach the infile to. When 'auto', a suitable file will be searched in out_dir. If attach is false, this will be ignored(character).
dwd_logo	Whether to add the DWD logo (logical).
verbose	Whether to display progress messages (logical).
nc	Alternatively to infile you can specify the input as an object of class ncd4 (as returned from ncd4::nc_open).

Details

You can pass a YAML config file and/or specify the arguments directly. Argument prioritization is done in the following way: Direct argument > config argument > default argument. Thus, if you pass a existing config file but also want to modify a specific argument you can do that easily.

get_basename_vis	<i>Determine the basename of a NetCDF file</i>
------------------	--

Description

This function determines the basename of either a file/URL path or an 'nc' object (using nc\$filename).

Usage

```
get_basename_vis(infile, nc = NULL)
```

Arguments

infile	Filename of input NetCDF file. This may include the directory (character).
nc	Alternatively to infile you can specify the input as an object of class ncd4 (as returned from ncd4::nc_open).

Details

When the origin of the file path is a local .nc file then get_basename_vis() is equivalent to base::basename().

get_basename_vis() also handles the case of infile/nc originating from a URL.

The value of get_basename_vis() always ends in ".nc".

If both infile and nc are specified, infile is ignored.

Value

A character string giving the basename.

helper_time_series_compare

Designed for the CM SAF R Toolbox.

Description

This function is a helper function for render_plot_time_series_compare.

Usage

```
helper_time_series_compare(visualizeVariables)
```

Arguments

visualizeVariables

A data frame containing all meta data for the plotting process (data.frame).

monitor_climate

A 'cmsaf' extension for creating various climate plots.

Description

This plotting routine generates graphical output of the evolution of the given variable within the given time range and area. The intended application is for daily accumulated data, such as sunshine duration. Dependent on the output format a PNG or MP4 is created.

Usage

```
monitor_climate(
  plot_type = "absolute_map",
  config = NULL,
  variable = NULL,
  accumulate = FALSE,
  mean_value = FALSE,
  infile = NULL,
  temp_dir = tempdir(),
  out_dir = getwd(),
  climate_dir = NULL,
  climate_year_start = 1983,
  climate_year_end = 2018,
  show_extreme_climate_years = NULL,
  climatology_until_eoy = FALSE,
  start_date = NULL,
  end_date = NULL,
  country_code = "S_A",
```

```

lon_min = NULL,
lon_max = NULL,
lat_min = NULL,
lat_max = NULL,
outfile_name = NULL,
output_format = "animation",
animation_pace = 0.07,
freeze_animation = FALSE,
min_value = NULL,
max_value = NULL,
nbreaks = NULL,
language = "eng",
keep_files = TRUE,
states = FALSE,
attach = FALSE,
infile_attach = "auto",
analyze_method = TRUE,
selected_number = 1,
color_pal = 1,
relative = FALSE,
circ_plot = FALSE,
dwd_logo = FALSE,
verbose = TRUE,
nc = NULL
)

```

Arguments

plot_type	Specifies the type of the plot ('absolute_map', 'anomaly_map', 'climatology_map', 'fieldmean_plot', 'fieldmean_and_anomaly_map').
config	Path to YAML config file (character). The config file does not have to specify all arguments. Each addressed argument has to be formatted according to the example config file: (#TODO: LINK EXAMPLE CONFIG FILE!).
variable	Name of variable in infile (NULL or character). If NULL then the first variable from the infile is taken.
accumulate	Whether the input file should be accumulated (logical).
mean_value	Whether the input file should be averaged (logical).
infile	Path to NetCDF file (NULL or character). If NULL then it needs to be specified in the config file.
temp_dir	Path to temporary working directory (character).
out_dir	Path to output directory (character).
climate_dir	Path to directory in which climatology is computed or contained (NULL or character). If NULL then the temp_dir directory is taken.
climate_year_start	Start year of climatology (integer).

climate_year_end	End year of climatology (integer).
show_extreme_climate_years	Whether the minimum and maximum of the climate years should be titled in the fieldmean plot (NULL or logical). This is usually only of interest when plotting accumulated data. If the default NULL is chosen, then it will be set to the value of accumulate.
climatology_until_eoy	Plot the climatology and fieldmeans until the end of year (logical). Only affects fieldmean plots analyzed from January 1st.
start_date	Start date in format of 'YYYY-MM-DD' (NULL or character). If NULL then the first date of the infile is used.
end_date	End date in format of 'YYYY-MM-DD' (NULL or character). If NULL then the last date of the infile is used.
country_code	Either a country code in iso3c format or from the following: 'AFR' for Africa, 'EUR' for Europe, 'TOT' for the total disc, or 'S_A' for an arbitrary region selection (character). If a country is passed the data from within this country is extracted, else a rectangular box is visualized. Directly provided latitude and longitude ranges will be ignored in case of 'AFR', 'EUR' or 'TOT'.
lon_min	Longitude of lower left corner (NULL or numeric). If NULL then the smallest longitude of the infile is used.
lon_max	Longitude of upper right left corner (NULL or numeric). If NULL then the largest longitude of the infile is used.
lat_min	Latitude of lower left corner (NULL or numeric). If NULL then the smallest latitude of the infile is used.
lat_max	Latitude of upper right corner (NULL or numeric). If NULL then the largest latitude of the infile is used.
outfile_name	Filename of the PNG or MP4 outfile (NULL or character). If NULL then a name is computed from the current configuration. Please match the file ending according to the output_format.
output_format	Specification of output format (either 'graphic' for PNG or 'animation' for MP4).
animation_pace	Pace of the animation in seconds (positive numeric). This only has an effect if output_format == 'animation'.
freeze_animation	If TRUE then the animation will freeze at the last frame (logical).
min_value	Lower values than this are ignored (NULL or numeric). If NULL, no values are ignored.
max_value	Larger values than this are ignored (NULL or numeric). If NULL, no values are ignored.
nbreaks	Number of color breaks (NULL or positive integer). A value will be computed if NULL is passed.
language	Language used for title, legend, etc. in plots (either 'eng' for English or 'deu' for German).

keep_files	A flag indicating whether all files created in the process of obtaining the output file should be kept (logical). If false, all intermediate results are deleted, otherwise all are kept. Keeping these files could improve performance in further function calls.
states	Whether to crop/plot administration level of states (logical).
attach	Whether to temporaly merge the infile to an already existing one. (logical).
infile_attach	File to attach the infile to. When 'auto', a suitable file will be searched in out_dir. If attach is false, this will be ignored(character).
analyze_method	Two analyze methods: mean == FALSE; accumulate == TRUE (logical) (Warming Stripes Plots, Time Series Plots, Trend Plots)
selected_number	Timesteps of the same selected time range (Warming Stripes Plots, Time Series Plots, Trend Plots)
color_pal	Color option for stripe and anomaly plots
relative	Use relative values for anomaly plots
circ_plot	Circular stripe plots (logical)
dwd_logo	Whether to add the DWD logo (logical).
verbose	Whether to display progress messages (logical).
nc	Alternatively to infile you can specify the input as an object of class ncdf4 (as returned from ncdf4::nc_open).

Details

Circular stripe plots are inspired by Emanuele Bevacqua (see emanuele.bevacqua.eu)

You can pass a YAML config file and/or specify the arguments directly. Argument prioritization is done in the following way: Direct argument > config argument > default argument. Thus, if you pass a existing config file but also want to modify a specific argument you can do that easily.

quicklook

Create a quicklook of NetCDF data

Description

The function creates a plot of the variables in NetCDF file(s) specified in the config file. Only NetCDF files that conform to the **CM SAF naming convention** are supported.

Usage

```
quicklook(
  config,
  filelist,
  outpath = getwd(),
  jpeg_quality = 100,
  dpi = 150,
```

```

iwidth = 1242,
logo = TRUE,
copyright = TRUE,
blumarble = FALSE,
verbose = TRUE
)

```

Arguments

config	filename of configuration file. This may include the directory (character).
filelist	list of NetCDF file to create plots from (character).
outpath	directory in which to save the output files. (character).
jpeg_quality	jpeg quality for the image in percent, see grDevices::jpeg()
dpi	resolution of the image in dots per inch, see grDevices::jpeg()
iwidth	width of the resulting image in pixels, see grDevices::jpeg()
logo	logical; should the cmsaf logo be added to the plot?
copyright	logical; should the copyright text be added to the plot?
blumarble	logical; should the data be plotted onto a NASA blumarble (only available for MSG/Seviri based data)? Due to data size this option is not available for the cmsafvis package on CRAN. Please have a look at our website https://www.cmsaf.eu/R_toolbox
verbose	logical; if TRUE, progress messages are shown

Details

This operator can be applied using a configuration file (quicklook_config.yml). An example config file can be found in the extdata folder of this package. The following parameters can be defined:

- logo: color / black
- slot: numeric (e.g., 13)
- invert_col: TRUE / FALSE
- Dataset: character (e.g., ICDR Seviri Radiation)
- limits: min: numeric; max: numeric
- legend: TRUE / FALSE
- colorscale: character (e.g., Viridis)
- unit: character (e.g., Percent / '%')

Value

A jpeg file with the same name as the original NetCDF file.

`recalculateImageDimensions`*Get rectangular image dimensions*

Description

Given regional bounds image width and height are computed in order to display a region without distortion.

Usage

```
recalculateImageDimensions(  
  visualizeVariables,  
  lon_bounds,  
  lat_bounds,  
  image_def,  
  ihsf  
)
```

Arguments

<code>visualizeVariables</code>	A dataframe containing \$lon and \$lat values which will be bounded by lon/lat_bounds (data.frame).
<code>lon_bounds</code>	Array containing two values for longitude min and max (numeric).
<code>lat_bounds</code>	Array containing two values for latitude min and max (numeric).
<code>image_def</code>	Minimal image default size for width and height (numeric).
<code>ihsf</code>	Image height rescaling factor (numeric).

`render_hist_plot`*Creating a simple histogram.*

Description

This routine was implemented for creating histograms in the CM SAF R Toolbox.

Usage

```
render_hist_plot(  
  dastat,  
  shortDescription,  
  grid_col,  
  bordercolor,  
  linesize,  
  xlab  
)
```

Arguments

dastat	Statistics given to hist plot (numeric).
shortDescription	A title will be generated using "Histogram of" + description (character).
grid_col	Color used for the grid.
bordercolor	Color used for borders.
linesize	Line width to be used (positive numeric).
xlab	Label for x axis (character).

render_instat_plot *Creating a simple instat plot.*

Description

This function creates a simple r-instat plot.

Usage

```
render_instat_plot(  
  co.data,  
  shortDescription,  
  grid_col,  
  bordercolor,  
  linesize,  
  ylab  
)
```

Arguments

co.data	Statistics given to hist plot (data.frame).
shortDescription	A title will be generated using "Comparison of" + description (character).
grid_col	Color used for the grid.
bordercolor	Color used for borders.
linesize	Line width to be used (positive numeric).
ylab	Label for y axis (character).

`render_plot`*Plotting routine designed for the CM SAF R Toolbox.*

Description

This function renders a 2D image usually called by the CM SAF R Toolbox.

Usage

```
render_plot(  
  plot_rinstat,  
  outfile = NULL,  
  fileExtension = ".png",  
  visualizeVariables,  
  visualizeDataTimestep,  
  nc_path_visualize,  
  visualizeDataMax,  
  lon_bounds,  
  lat_bounds,  
  lon_loc_vec,  
  lat_loc_vec,  
  name_loc_vec,  
  timestep,  
  num_tick,  
  num_rmin,  
  num_rmax,  
  num_brk,  
  co.data,  
  co.data.compare.diff,  
  proj,  
  xort,  
  yort,  
  rort,  
  slider1,  
  slider2,  
  imagewidth,  
  imageheight,  
  location,  
  int,  
  text1,  
  text2,  
  text3,  
  textsize,  
  bordercolor,  
  linesize,  
  na.color,  
  PAL,
```

```

    palettes,
    reverse,
    plot_grid,
    grid_col
  )

```

Arguments

<code>plot_rinstat</code>	Whether to create an R-Instat plot (logical).
<code>outfile</code>	Name of the outfile (NULL or character). Should match the <code>fileExtension</code> . If NULL is passed a file is created in the R session temporary directory.
<code>fileExtension</code>	The file extension of the image (character). Has to be one of the following: 'png', 'jpg', 'tif', 'kml', 'pdf'.
<code>visualizeVariables</code>	A data frame containing all meta data for the plotting process (data.frame).
<code>visualizeDataTimestep</code>	The data to be plotted.
<code>nc_path_visualize</code>	The nc file path of which the plot is generated for.
<code>visualizeDataMax</code>	Maximal data for computing breaks.
<code>lon_bounds</code>	Array containing two values for longitude min and max (numeric).
<code>lat_bounds</code>	Array containing two values for latitude min and max (numeric).
<code>lon_loc_vec</code>	All longitude entries for points at (<code>lat_loc_vec</code> , <code>lon_loc_vec</code>) to be specified on the map (numeric).
<code>lat_loc_vec</code>	All latitude entries for points at (<code>lat_loc_vec</code> , <code>lon_loc_vec</code>) to be specified on the map (numeric).
<code>name_loc_vec</code>	Names for the points at (<code>lat_loc_vec</code> , <code>lon_loc_vec</code>) to be specified on the map (numeric).
<code>timestep</code>	The current timestep chosen.
<code>num_tick</code>	Number of ticks (numeric).
<code>num_rmin</code>	Color scale range minimum (numeric).
<code>num_rmax</code>	Color scale range maximum (numeric).
<code>num_brk</code>	Number of breaks (numeric).
<code>co.data</code>	Data to be plotted in R-Instat mode (data.frame).
<code>co.data.compare.diff</code>	Data to be plotted in compare data mode (data.frame).
<code>proj</code>	The chosen projection (either 'rect' for rectangular or 'ortho' for orthographic).
<code>xort</code>	Centering the globe at longitude <code>xort</code> (numeric). Only in orthographic mode.
<code>yort</code>	Centering the globe at latitude <code>yort</code> (numeric). Only in orthographic mode.
<code>rort</code>	Rotation of the globe (numeric). Only in orthographic mode.
<code>slider1</code>	Controlling the horizontal plot position as vector of two values min and max (numeric).

slider2	Controlling the vertical plot position as vector of two values min and max (numeric).
imagewidth	Width of the image (numeric).
imageheight	Height of the image (numeric).
location	Whether points specified by (lat_loc_vec, lon_loc_vec, name_loc_vec) should be added to the map (logical).
int	Whether interior country borders should be added (logical).
text1	Title text (character).
text2	Text to be passed to graphics::mtext (character).
text3	Text to be added to the legend (character).
textsize	Textsize to be used (cex).
bordercolor	Color used for borders.
linesize	Line width to be used (positive numeric).
na.color	The color to be used for NA values.
PAL	Color palette.
palettes	Color palettes to be used.
reverse	Whether to revert the color palette (logical).
plot_grid	Whether to plot a grid using color grid_col (logical).
grid_col	Color used for the grid.

render_plot_1d

Plotting routine designed for the CM SAF R Toolbox.

Description

This function renders a 1D plot of data at one single lon / lat point.

Usage

```
render_plot_1d(
  outfile = NULL,
  fileExtension = ".png",
  visualizeVariables,
  ticknumber,
  dateformat,
  analyze_timeseries,
  addTrend,
  sliderx,
  slidery,
  checkGroup_type,
  imagewidth,
  imageheight,
```

```

    text1_1d,
    text2_1d,
    textsize,
    linesize,
    col
  )

```

Arguments

outfile	Name of the outfile (NULL or character). Should match the fileExtension. If NULL is passed a file is created in the R session temporary directory.
fileExtension	The file extension of the image (character). Has to be one of the following: 'png', 'jpg', 'tif', 'kml', 'pdf'.
visualizeVariables	A data frame containing all meta data for the plotting process (data.frame).
ticknumber	Number of ticks (numeric).
dateformat	Date format for constructing a date label.
analyze_timeseries	Whether or not to analyze the timeseries of the given point (logical).
addTrend	Whether to add a trend line (logical).
sliderx	Limiting the time series with a two valued vector for min and max (numeric).
slidery	Limiting the y axis with a two valued vector for min and max (numeric).
checkGroup_type	An integer between 1 and 5 indicating group type (numeric). 1 for Line, 2 for Points, 3 for Line and Points, 4 for steps, 5 for histogram.
imagewidth	Width of the image (numeric).
imageheight	Height of the image (numeric).
text1_1d	Title text (character).
text2_1d	Text to be passed to graphics::mtext (character).
textsize	Textsize to be used (cex).
linesize	Line width to be used (positive numeric).
col	A color chosen via colourpicker::colourInput.

render_plot_1d_advanced

Plotting routine designed for the CM SAF R Toolbox.

Description

This function renders a 1D plot of data at one single lon or one single lat point.

Usage

```
render_plot_1d_advanced(
  outfile = NULL,
  fileExtension = ".png",
  visualizeVariables,
  ticknumber,
  addTrend,
  sliderx,
  slidery,
  checkGroup_type,
  imagewidth,
  imageheight,
  text1_1d,
  text2_1d,
  textsize,
  linesize,
  col,
  timestep_1d_visualize
)
```

Arguments

outfile	Name of the outfile (NULL or character). Should match the fileExtension. If NULL is passed a file is created in the R session temporary directory.
fileExtension	The file extension of the image (character). Has to be one of the following: 'png', 'jpg', 'tif', 'kml', 'pdf'.
visualizeVariables	A data frame containing all meta data for the plotting process (data.frame).
ticknumber	Number of ticks (numeric).
addTrend	Whether to add a trend line (logical).
sliderx	Limiting the time series with a two valued vector for min and max (numeric).
slidery	Limiting the y axis with a two valued vector for min and max (numeric).
checkGroup_type	An integer between 1 and 5 indicating group type (numeric). 1 for Line, 2 for Points, 3 for Line and Points, 4 for steps, 5 for histogram.
imagewidth	Width of the image (numeric).
imageheight	Height of the image (numeric).
text1_1d	Title text (character).
text2_1d	Text to be passed to graphics::mtext (character).
textsize	Textsize to be used (cex).
linesize	Line width to be used (positive numeric).
col	A color chosen via colourpicker::colourInput.
timestep_1d_visualize	The time step to be visualized.

 render_plot_hist_compare

Plotting routine designed for the CM SAF R Toolbox.

Description

This function renders a histogram of two variables.

Usage

```
render_plot_hist_compare(
  outfile = NULL,
  fileExtension = ".png",
  visualizeVariables,
  imagewidth,
  imageheight,
  text1_1d,
  text2_1d,
  textsize,
  legend_label1,
  legend_label2,
  timestep_1d_visualize
)
```

Arguments

outfile	Name of the outfile (NULL or character). Should match the fileExtension. If NULL is passed a file is created in the R session temporary directory.
fileExtension	The file extension of the image (character). Has to be one of the following: 'png', 'jpg', 'tif', 'kml', 'pdf'.
visualizeVariables	A data frame containing all meta data for the plotting process (data.frame).
imagewidth	Width of the image (numeric).
imageheight	Height of the image (numeric).
text1_1d	Title text (character).
text2_1d	Text to be passed to graphics::mtext (character).
textsize	Textsize to be used (cex).
legend_label1	Legend label of the first data set
legend_label2	Legend label of the second data set
timestep_1d_visualize	Selected timestep

render_plot_hovmoller *Plotting routine designed for the CM SAF R Toolbox.*

Description

This function renders a hovmoller plot of two variables.

Usage

```
render_plot_hovmoller(
  outfile = NULL,
  fileExtension = ".png",
  visualizeVariables,
  imagewidth,
  imageheight,
  textsize,
  linesize,
  title_data1,
  title_data2,
  nc = NULL,
  nc2 = NULL
)
```

Arguments

outfile	Name of the outfile (NULL or character). Should match the fileExtension. If NULL is passed a file is created in the R session temporary directory.
fileExtension	The file extension of the image (character). Has to be one of the following: 'png', 'jpg', 'tif', 'kml', 'pdf'.
visualizeVariables	A data frame containing all meta data for the plotting process (data.frame).
imagewidth	Width of the image (numeric).
imageheight	Height of the image (numeric).
textsize	Textsize to be used (cex).
linesize	Line width to be used (positive numeric).
title_data1	Title of the first data set
title_data2	Title of the second data set
nc	Alternatively to infile1 you can specify the input as an object of class ncdf4 (as returned from ncdf4::nc_open).
nc2	Alternatively to infile2 you can specify the input as an object of class ncdf4 (as returned from ncdf4::nc_open).

render_plot_scatter *Plotting routine designed for the CM SAF R Toolbox.*

Description

This function renders a scatter plot of two variables.

Usage

```
render_plot_scatter(
  outfile = NULL,
  fileExtension = ".png",
  visualizeVariables,
  dateformat,
  ticknumber,
  imagewidth,
  imageheight,
  text1_1d,
  text2_1d,
  textsize,
  linesize,
  x_axis_label_1d,
  y_axis_label_1d,
  timestep_1d_visualize
)
```

Arguments

outfile	Name of the outfile (NULL or character). Should match the fileExtension. If NULL is passed a file is created in the R session temporary directory.
fileExtension	The file extension of the image (character). Has to be one of the following: 'png', 'jpg', 'tif', 'kml', 'pdf'.
visualizeVariables	A data frame containing all meta data for the plotting process (data.frame).
dateformat	Date format for constructing a date label.
ticknumber	Number of ticks (numeric).
imagewidth	Width of the image (numeric).
imageheight	Height of the image (numeric).
text1_1d	Title text (character).
text2_1d	Text to be passed to graphics::mtext (character).
textsize	Textsize to be used (cex).
linesize	Line width to be used (positive numeric).
x_axis_label_1d	x-label (first data set)


```
y_axis_label_1d  
                y-label (second data set)  
timestep_1d_visualize  
                Selected timestep
```

```
render_plot_side_by_side
```

Plotting routine designed for the CM SAF R Toolbox.

Description

This function renders a 2D image of two files usually called by the CM SAF R Toolbox.

Usage

```
render_plot_side_by_side(  
  plot_rinstat,  
  outfile = NULL,  
  fileExtension = ".png",  
  visualizeVariables,  
  visualizeDataTimestep,  
  nc_path_visualize,  
  visualizeDataMax,  
  timestep_2d,  
  lon_bounds,  
  lat_bounds,  
  lon_loc_vec,  
  lat_loc_vec,  
  name_loc_vec,  
  timestep,  
  num_tick,  
  num_rmin,  
  num_rmax,  
  num_brk,  
  co.data,  
  proj,  
  xort,  
  yort,  
  rort,  
  slider1,  
  slider2,  
  imagewidth,  
  imageheight,  
  location,  
  int,  
  text1,  
  text2,
```

```

text3,
textsize,
bordercolor,
linesize,
na.color,
PAL,
palettes,
reverse,
plot_grid,
grid_col,
text1_2,
text2_2
)

```

Arguments

<code>plot_rinstat</code>	Whether to create an R-Instat plot (logical).
<code>outfile</code>	Name of the outfile (NULL or character). Should match the fileExtension. If NULL is passed a file is created in the R session temporary directory.
<code>fileExtension</code>	The file extension of the image (character). Has to be one of the following: 'png', 'jpg', 'tif', 'kml', 'pdf'.
<code>visualizeVariables</code>	A data frame containing all meta data for the plotting process (data.frame).
<code>visualizeDataTimestep</code>	The data to be plotted.
<code>nc_path_visualize</code>	The nc file path of which the plot is generated for.
<code>visualizeDataMax</code>	Maximal data for computing breaks.
<code>timestep_2d</code>	The time step to be visualized.
<code>lon_bounds</code>	Array containing two values for longitude min and max (numeric).
<code>lat_bounds</code>	Array containing two values for latitude min and max (numeric).
<code>lon_loc_vec</code>	All longitude entries for points at (lat_loc_vec, lon_loc_vec) to be specified on the map (numeric).
<code>lat_loc_vec</code>	All latitude entries for points at (lat_loc_vec, lon_loc_vec) to be specified on the map (numeric).
<code>name_loc_vec</code>	Names for the points at (lat_loc_vec, lon_loc_vec) to be specified on the map (numeric).
<code>timestep</code>	The current timestep chosen.
<code>num_tick</code>	Number of ticks (numeric).
<code>num_rmin</code>	Color scale range minimum (numeric).
<code>num_rmax</code>	Color scale range maximum (numeric).
<code>num_brk</code>	Number of breaks (numeric).
<code>co.data</code>	Data to be plotted in R-Instat mode (data.frame).

proj	The chosen projection (either 'rect' for rectangular or 'ortho' for orthographic).
xort	Centering the globe at longitude xort (numeric). Only in orthographic mode.
yort	Centering the globe at latitude yort (numeric). Only in orthographic mode.
rort	Rotation of the globe (numeric). Only in orthographic mode.
slider1	Controlling the horizontal plot position as vector of two values min and max (numeric).
slider2	Controlling the vertical plot position as vector of two values min and max (numeric).
imagewidth	Width of the image (numeric).
imageheight	Height of the image (numeric).
location	Whether points specified by (lat_loc_vec, lon_loc_vec, name_loc_vec) should be added to the map (logical).
int	Whether interior country borders should be added (logical).
text1	Title text data set 1 (character).
text2	Text to be passed to graphics::mtext for data set 1 (character).
text3	Text to be added to the legend (character).
textsize	Textsize to be used (cex).
bordercolor	Color used for borders.
linesize	Line width to be used (positive numeric).
na.color	The color to be used for NA values.
PAL	Color palette.
palettes	Color palettes to be used.
reverse	Whether to revert the color palette (logical).
plot_grid	Whether to plot a grid using color_grid_col (logical).
grid_col	Color used for the grid.
text1_2	Title text data set 2 (character).
text2_2	Text to be passed to graphics::mtext for data set 2 (character).

render_plot_time_series_compare

Plotting routine designed for the CM SAF R Toolbox.

Description

This function provides a time series comparison of two data sets.

Usage

```
render_plot_time_series_compare(
  outfile = NULL,
  fileExtension = ".png",
  visualizeVariables,
  ticknumber,
  dateformat,
  sliderx,
  slidery,
  checkGroup_type,
  imagewidth,
  imageheight,
  text1_1d,
  text2_1d,
  textsize,
  linesize,
  col,
  legend_label1,
  legend_label2,
  station_number
)
```

Arguments

<code>outfile</code>	Name of the outfile (NULL or character). Should match the <code>fileExtension</code> . If NULL is passed a file is created in the R session temporary directory.
<code>fileExtension</code>	The file extension of the image (character). Has to be one of the following: 'png', 'jpg', 'tif', 'kml', 'pdf'.
<code>visualizeVariables</code>	A data frame containing all meta data for the plotting process (data.frame).
<code>ticknumber</code>	Number of ticks (numeric).
<code>dateformat</code>	Date format for constructing a date label.
<code>sliderx</code>	Limiting the time series with a two valued vector for min and max (numeric).
<code>slidery</code>	Limiting the y axis with a two valued vector for min and max (numeric).
<code>checkGroup_type</code>	An integer between 1 and 5 indicating group type (numeric). 1 for Line, 2 for Points, 3 for Line and Points, 4 for steps, 5 for histogram.
<code>imagewidth</code>	Width of the image (numeric).
<code>imageheight</code>	Height of the image (numeric).
<code>text1_1d</code>	Title text (character).
<code>text2_1d</code>	Text to be passed to <code>graphics::mtext</code> (character).
<code>textsize</code>	Textsize to be used (cex).
<code>linesize</code>	Line width to be used (positive numeric).
<code>col</code>	A color chosen via <code>colourpicker::colourInput</code> .

legend_label1 Legend label of the first data set
 legend_label2 Legend label of the second data set
 station_number For station data compare; which station is selected

render_preview_plot *Creates a preview plot of a selected area*

Description

This function creates a simple preview plot via maps::map of a given region.

Usage

```
render_preview_plot(spatial_lon_range, spatial_lat_range, lonRange, latRange)
```

Arguments

spatial_lon_range Array containing two values for longitude min and max (numeric).
 spatial_lat_range Array containing two values for latitude min and max (numeric).
 lonRange Array containing two values for longitude min and max (numeric).
 latRange Array containing two values for latitude min and max (numeric).

render_region_plot *Function to create a plot of a selected country.*

Description

This function generates a plot of within a certain region (e.g. a country).

Usage

```

render_region_plot(
  infile,
  outfile = NULL,
  fileExtension = ".png",
  visualizeVariables,
  visualizeDataMax,
  lon_bounds,
  lat_bounds,
  lon_loc_vec,
  lat_loc_vec,
  name_loc_vec,

```

```

division,
selectedRegion,
region_data,
timestep,
num_tick,
num_rmin,
num_rmax,
location,
text1,
text2,
text3,
PAL,
palettes,
num_brk,
reverse,
textsize,
bordercolor,
plot_grid,
grid_col,
image_def,
ihsf,
nc = NULL
)

```

Arguments

<code>infile</code>	The nc file to be visualized.
<code>outfile</code>	Name of the outfile (NULL or character). Should match the <code>fileExtension</code> . If NULL is passed a file is created in the R session temporary directory.
<code>fileExtension</code>	The file extension of the image (character). Has to be one of the following: 'png', 'jpg', 'tif', 'kml', 'pdf'.
<code>visualizeVariables</code>	A data frame containing all meta data for the plotting process (data.frame).
<code>visualizeDataMax</code>	Maximal data for computing breaks.
<code>lon_bounds</code>	Array containing two values for longitude min and max (numeric).
<code>lat_bounds</code>	Array containing two values for latitude min and max (numeric).
<code>lon_loc_vec</code>	All longitude entries for points at (<code>lat_loc_vec</code> , <code>lon_loc_vec</code>) to be specified on the map (numeric).
<code>lat_loc_vec</code>	All latitude entries for points at (<code>lat_loc_vec</code> , <code>lon_loc_vec</code>) to be specified on the map (numeric).
<code>name_loc_vec</code>	Names for the points at (<code>lat_loc_vec</code> , <code>lon_loc_vec</code>) to be specified on the map (numeric).
<code>division</code>	Division to contain region (either 'COUNTRY' or something coherent to <code>region_data</code>).

selectedRegion	The region to be cropped according to division. If division == "COUNTRY", the country's 3-character ISO code should be used. Otherwise it has to fit to the passed region data.
region_data	If Division is not 'COUNTRY' then region_data has to contain spatial data of the given division.
timestep	Timestep to visualize at (character).
num_tick	Number of ticks (numeric).
num_rmin	Color scale range minimum (numeric).
num_rmax	Color scale range maximum (numeric).
location	Whether points specified by (lat_loc_vec, lon_loc_vec, name_loc_vec) should be added to the map (logical).
text1	Title text (character).
text2	Text to be passed to graphics::mtext (character).
text3	Text to be added to the legend (character).
PAL	Color palette.
palettes	Color palettes to be used.
num_brk	Number of breaks (numeric).
reverse	Whether to revert the color palette (logical).
textsize	Textsize to be used (cex).
bordercolor	Color used for borders.
plot_grid	Whether to plot a grid using color grid_col (logical).
grid_col	Color used for the grid.
image_def	Default size (positive numeric).
ihsf	Image height scaling factor (positive numeric).
nc	Alternatively to infile you can specify the input as an object of class ncdf4 (as returned from ncdf4::nc_open).

time_series_plot *A 'cmsaf' extension for creating time series plots.*

Description

This plotting routine generates graphical output for the given variable within the given time range and area. Dependent on the output format a PNG is created.

Usage

```

time_series_plot(
  variable = NULL,
  infile = NULL,
  selected_number = 1,
  analyze_method = TRUE,
  temp_dir = tempdir(),
  out_dir = getwd(),
  climate_dir = NULL,
  climate_year_start = 1983,
  climate_year_end = 2018,
  start_date = NULL,
  end_date = NULL,
  country_code = "S_A",
  lon_min = NULL,
  lon_max = NULL,
  lat_min = NULL,
  lat_max = NULL,
  outfile_name = NULL,
  output_format = "graphic",
  language = "eng",
  keep_files = TRUE,
  states = FALSE,
  attach = FALSE,
  infile_attach = "auto",
  title = "",
  verbose = TRUE,
  nc = NULL
)

```

Arguments

variable	Name of variable in infile (NULL or character). If NULL then the first variable from the infile is taken.
infile	Path to NetCDF file (NULL or character). If NULL then it needs to be specified in the config file.
selected_number	Timesteps of the same selected time range (Warming Stripes Plots, Time Series Plots, Trend Plots)
analyze_method	Two analyze methods: mean == FALSE; accumulate == TRUE (logical) (Warming Stripes Plots, Time Series Plots, Trend Plots)
temp_dir	Path to temporary working directory (character).
out_dir	Path to output directory (character).
climate_dir	Path to directory in which climatology is computed or contained (NULL or character). If NULL then the temp_dir directory is taken.
climate_year_start	Start year of climatology (integer).

climate_year_end	End year of climatology (integer).
start_date	Start date in format of 'YYYY-MM-DD' (NULL or character). If NULL then the first date of the infile is used.
end_date	End date in format of 'YYYY-MM-DD' (NULL or character). If NULL then the last date of the infile is used.
country_code	Either a country code in iso3c format or from the following: 'AFR' for Africa, 'EUR' for Europe, 'TOT' for the total disc, or 'S_A' for an arbitrary region selection (character). If a country is passed the data from within this country is extracted, else a rectangular box is visualized. Directly provided latitude and longitude ranges will be ignored in case of 'AFR', 'EUR' or 'TOT'.
lon_min	Longitude of lower left corner (NULL or numeric). If NULL then the smallest longitude of the infile is used.
lon_max	Longitude of upper right left corner (NULL or numeric). If NULL then the largest longitude of the infile is used.
lat_min	Latitude of lower left corner (NULL or numeric). If NULL then the smallest latitude of the infile is used.
lat_max	Latitude of upper right corner (NULL or numeric). If NULL then the largest latitude of the infile is used.
outfile_name	Filename of the PNG or MP4 outfile (NULL or character). If NULL then a name is computed from the current configuration. Please match the file ending according to the output_format.
output_format	Specification of output format (either 'graphic' for PNG or 'animation' for MP4).
language	Language used for title, legend, etc. in plots (either 'eng' for English or 'deu' for German).
keep_files	A flag indicating whether all files created in the process of obtaining the output file should be kept (logical). If false, all intermediate results are deleted, otherwise all are kept. Keeping these files could improve performance in further function calls.
states	Whether to crop/plot administration level of states (logical).
attach	Whether to temporary merge the infile to an already existing one. (logical).
infile_attach	File to attach the infile to. When 'auto', a suitable file will be searched in out_dir. If attach is false, this will be ignored(character).
title	Set title (character).
verbose	Whether to display progress messages (logical).
nc	Alternatively to infile you can specify the input as an object of class ncd4 (as returned from ncd4::nc_open).

trend_plot	<i>A 'cmsaf' extension for creating trend plots.</i>
------------	--

Description

This plotting routine generates graphical output for the given variable within the given time range and area. Dependent on the output format a PNG is created.

Usage

```
trend_plot(
  variable = NULL,
  infile = NULL,
  selected_number = 1,
  analyze_method = TRUE,
  temp_dir = tempdir(),
  out_dir = getwd(),
  climate_dir = NULL,
  climate_year_start = 1983,
  climate_year_end = 2018,
  start_date = NULL,
  end_date = NULL,
  country_code = "S_A",
  lon_min = NULL,
  lon_max = NULL,
  lat_min = NULL,
  lat_max = NULL,
  outfile_name = NULL,
  output_format = "graphic",
  language = "eng",
  keep_files = TRUE,
  states = FALSE,
  attach = FALSE,
  infile_attach = "auto",
  verbose = TRUE,
  nc = NULL
)
```

Arguments

variable	Name of variable in infile (NULL or character). If NULL then the first variable from the infile is taken.
infile	Path to NetCDF file (NULL or character). If NULL then it needs to be specified in the config file.
selected_number	Timesteps of the same selected time range (Warming Stripes Plots, Time Series Plots, Trend Plots)

analyze_method	Two analyze methods: mean == FALSE; accumulate == TRUE (logical) (Warming Stripes Plots, Time Series Plots, Trend Plots)
temp_dir	Path to temporary working directory (character).
out_dir	Path to output directory (character).
climate_dir	Path to directory in which climatology is computed or contained (NULL or character). If NULL then the temp_dir directory is taken.
climate_year_start	Start year of climatology (integer).
climate_year_end	End year of climatology (integer).
start_date	Start date in format of 'YYYY-MM-DD' (NULL or character). If NULL then the first date of the infile is used.
end_date	End date in format of 'YYYY-MM-DD' (NULL or character). If NULL then the last date of the infile is used.
country_code	Either a country code in iso3c format or from the following: 'AFR' for Africa, 'EUR' for Europe, 'TOT' for the total disc, or 'S_A' for an arbitrary region selection (character). If a country is passed the data from within this country is extracted, else a rectangular box is visualized. Directly provided latitude and longitude ranges will be ignored in case of 'AFR', 'EUR' or 'TOT'.
lon_min	Longitude of lower left corner (NULL or numeric). If NULL then the smallest longitude of the infile is used.
lon_max	Longitude of upper right left corner (NULL or numeric). If NULL then the largest longitude of the infile is used.
lat_min	Latitude of lower left corner (NULL or numeric). If NULL then the smallest latitude of the infile is used.
lat_max	Latitude of upper right corner (NULL or numeric). If NULL then the largest latitude of the infile is used.
outfile_name	Filename of the PNG or MP4 outfile (NULL or character). If NULL then a name is computed from the current configuration. Please match the file ending according to the output_format.
output_format	Specification of output format (either 'graphic' for PNG or 'animation' for MP4).
language	Language used for title, legend, etc. in plots (either 'eng' for English or 'deu' for German).
keep_files	A flag indicating whether all files created in the process of obtaining the output file should be kept (logical). If false, all intermediate results are deleted, otherwise all are kept. Keeping these files could improve performance in further function calls.
states	Whether to crop/plot administration level of states (logical).
attach	Whether to temporaly merge the infile to an already existing one. (logical).
infile_attach	File to attach the infile to. When 'auto', a suitable file will be searched in out_dir. If attach is false, this will be ignored(character).
verbose	Whether to display progress messages (logical).
nc	Alternatively to infile you can specify the input as an object of class ncdf4 (as returned from ncdf4::nc_open).

warming_stripes_plot A 'cmsaf' extension for creating warming stripes plots.

Description

This plotting routine generates graphical output for the given variable within the given time range and area. Dependent on the output format a PNG is created.

Usage

```
warming_stripes_plot(  
  variable = NULL,  
  infile = NULL,  
  selected_number = 1,  
  color_pal = 1,  
  analyze_method = TRUE,  
  temp_dir = tempdir(),  
  out_dir = getwd(),  
  climate_dir = NULL,  
  climate_year_start = 1983,  
  climate_year_end = 2018,  
  start_date = NULL,  
  end_date = NULL,  
  country_code = "S_A",  
  lon_min = NULL,  
  lon_max = NULL,  
  lat_min = NULL,  
  lat_max = NULL,  
  outfile_name = NULL,  
  output_format = "graphic",  
  language = "eng",  
  keep_files = TRUE,  
  states = FALSE,  
  attach = FALSE,  
  infile_attach = "auto",  
  pointsTF = FALSE,  
  lineTF = FALSE,  
  circ_plot = FALSE,  
  title = "",  
  verbose = TRUE,  
  nc = NULL  
)
```

Arguments

variable	Name of variable in infile (NULL or character). If NULL then the first variable from the infile is taken.
----------	---

infile	Path to NetCDF file (NULL or character). If NULL then it needs to be specified in the config file.
selected_number	Timesteps of the same selected time range (Warming Stripes Plots, Time Series Plots, Trend Plots)
color_pal	Color option for stripe and anomaly plots
analyze_method	Two analyze methods: mean == FALSE; accumulate == TRUE (logical) (Warming Stripes Plots, Time Series Plots, Trend Plots)
temp_dir	Path to temporary working directory (character).
out_dir	Path to output directory (character).
climate_dir	Path to directory in which climatology is computed or contained (NULL or character). If NULL then the temp_dir directory is taken.
climate_year_start	Start year of climatology (integer).
climate_year_end	End year of climatology (integer).
start_date	Start date in format of 'YYYY-MM-DD' (NULL or character). If NULL then the first date of the infile is used.
end_date	End date in format of 'YYYY-MM-DD' (NULL or character). If NULL then the last date of the infile is used.
country_code	Either a country code in iso3c format or from the following: 'AFR' for Africa, 'EUR' for Europe, 'TOT' for the total disc, or 'S_A' for an arbitrary region selection (character). If a country is passed the data from within this country is extracted, else a rectangular box is visualized. Directly provided latitude and longitude ranges will be ignored in case of 'AFR', 'EUR' or 'TOT'.
lon_min	Longitude of lower left corner (NULL or numeric). If NULL then the smallest longitude of the infile is used.
lon_max	Longitude of upper right left corner (NULL or numeric). If NULL then the largest longitude of the infile is used.
lat_min	Latitude of lower left corner (NULL or numeric). If NULL then the smallest latitude of the infile is used.
lat_max	Latitude of upper right corner (NULL or numeric). If NULL then the largest latitude of the infile is used.
outfile_name	Filename of the PNG or MP4 outfile (NULL or character). If NULL then a name is computed from the current configuration. Please match the file ending according to the output_format.
output_format	Specification of output format (either 'graphic' for PNG or 'animation' for MP4).
language	Language used for title, legend, etc. in plots (either 'eng' for English or 'deu' for German).
keep_files	A flag indicating whether all files created in the process of obtaining the output file should be kept (logical). If false, all intermediate results are deleted, otherwise all are kept. Keeping these files could improve performance in further function calls.

<code>states</code>	Whether to crop/plot administration level of states (logical).
<code>attach</code>	Whether to temporaly merge the infile to an already existing one. (logical).
<code>infile_attach</code>	File to attach the infile to. When 'auto', a suitable file will be searched in <code>out_dir</code> . If <code>attach</code> is false, this will be ignored(character).
<code>pointsTF</code>	Show data points (logical).
<code>lineTF</code>	Show trend line (logical).
<code>circ_plot</code>	Circular stripe plots (logical)
<code>title</code>	Set title (character).
<code>verbose</code>	Whether to display progress messages (logical).
<code>nc</code>	Alternatively to <code>infile</code> you can specify the input as an object of class <code>ncdf4</code> (as returned from <code>ncdf4::nc_open</code>).

Details

Circular stripe plots are inspired by Emanuele Bevacqua (see emanuele.bevacqua.eu)

Index

- * **1d visualization**
 - [cmsaf.hist](#), [12](#)
 - [cmsaf.hovmoller](#), [13](#)
 - [cmsaf.scatter](#), [14](#)
 - [cmsaf.time.series](#), [17](#)
 - * **2d visualization**
 - [cmsaf.diff](#), [10](#)
 - [cmsaf.side.by.side](#), [16](#)
 - * **datagen**
 - [cmsafvis](#), [18](#)
 - * **manip**
 - [cmsafvis](#), [18](#)
 - * **package**
 - [cmsafvis](#), [18](#)
 - * **spatial**
 - [cmsafvis](#), [18](#)
 - * **ts**
 - [cmsafvis](#), [18](#)
 - * **univar**
 - [cmsafvis](#), [18](#)
- [absolute_map](#), [2](#), [18](#)
- [anomaly_map](#), [5](#), [18](#)
- [climatology_map](#), [8](#), [19](#)
- [cmsaf.diff](#), [10](#), [17](#)
- [cmsaf.hist](#), [12](#), [14](#), [15](#), [18](#)
- [cmsaf.hovmoller](#), [13](#), [13](#), [15](#), [18](#)
- [cmsaf.scatter](#), [13](#), [14](#), [14](#), [18](#)
- [cmsaf.side.by.side](#), [11](#), [16](#)
- [cmsaf.time.series](#), [13–15](#), [17](#)
- [cmsafvis](#), [18](#)
- [fieldmean_and_anomaly_map](#), [19](#), [19](#)
- [fieldmean_plot](#), [19](#), [22](#)
- [get_basename_vis](#), [25](#)
- [grDevices::jpeg\(\)](#), [30](#)
- [helper_time_series_compare](#), [26](#)
- [monitor_climate](#), [26](#)
- [ncdf4 package](#), [18](#)
- [quicklook](#), [29](#)
- [recalculateImageDimensions](#), [31](#)
- [render_hist_plot](#), [31](#)
- [render_instat_plot](#), [32](#)
- [render_plot](#), [33](#)
- [render_plot_1d](#), [35](#)
- [render_plot_1d_advanced](#), [36](#)
- [render_plot_hist_compare](#), [38](#)
- [render_plot_hovmoller](#), [39](#)
- [render_plot_scatter](#), [40](#)
- [render_plot_side_by_side](#), [41](#)
- [render_plot_time_series_compare](#), [43](#)
- [render_preview_plot](#), [45](#)
- [render_region_plot](#), [45](#)
- [time_series_plot](#), [19](#), [47](#)
- [trend_plot](#), [19](#), [50](#)
- [warming_stripes_plot](#), [19](#), [52](#)