

Package ‘huito’

April 1, 2022

Type Package

Version 0.1.3

Title Flexible and Reproducible Label Designs

Description An open-source R package to deploys flexible and reproducible labels using layers. The 'huito' package is part of the 'inkaverse' project for developing different procedures and tools used in plant science and experimental designs. Learn more about the 'inkaverse' project at <<https://inkaverse.com/>>.

Date 2022-04-01

URL <https://huito.inkaverse.com/>, <https://github.com/flavjack/huito>

BugReports <https://github.com/flavjack/huito/issues/>

Depends magick, cowplot, ggplot2, dplyr, R (>= 2.10)

Imports tidyr, tibble, purrr, sysfonts, showtext, qrcode, pdftools

Suggests knitr, rmarkdown, bookdown, gsheets, inti

VignetteBuilder knitr

License GPL-3 | file LICENSE

Encoding UTF-8

RoxygenNote 7.1.2

LazyData true

NeedsCompilation no

Author Flavio Lozano-Isla [aut, cre] (<<https://orcid.org/0000-0002-0714-669X>>),
Inkaverse [cph]

Maintainer Flavio Lozano-Isla <flavjack@gmail.com>

Repository CRAN

Date/Publication 2022-04-01 11:20:02 UTC

R topics documented:

barcode_qr	2
fieldbook	3
huito_fonts	3
image_import	4
include_barcode	4
include_image	5
include_shape	6
include_text	7
label_layout	8
label_print	9
shape_hexagon	10

Index	12
--------------	-----------

barcode_qr	<i>Barcode generator</i>
------------	--------------------------

Description

Generate bar codes using QR codes

Usage

```
barcode_qr(text, color = "black", alpha = 1, ecl = "H")
```

Arguments

text	text to convert to QR bar code
color	Bar code color
alpha	Intensity of the bar code color
ecl	Error correction level (percentage). "L" (7), "M" (15), "Q" (25) and "H" (30). Defaults to "H"

Value

plot

Examples

```
library(huito)

barcode_qr("LIMA-2021-11-03_15_3_4")
```

`fieldbook`*Fieldbook experimental design*

Description

The dataset were obtained using inti package. The data set is a randomize complete block design (RCBD) with three replications.

Usage

```
fieldbook
```

Format

A data frame with 24 rows and 5 variables:

barcode barcode for each experimental unit

plots Plot number

block Blocks (3): number of replication in the design

condition Factor with two levels: irrigated and drought

genotypes Factor with four levels: choclito, salcedo, pandela, puno

`huito_fonts`*Fonts import*

Description

Import fonts from Google fonts

Usage

```
huito_fonts(fonts = NA)
```

Arguments

`fonts` fonts names

Details

For more fonts visit: <https://fonts.google.com/>

Value

fonts

image_import	<i>Image import</i>
--------------	---------------------

Description

Import images and include R magick options

Usage

```
image_import(image, opts = NA)
```

Arguments

image	path or url
opts	R magick functions by layers

Value

image

include_barcode	<i>Barcode layer</i>
-----------------	----------------------

Description

Insert barcode in label

Usage

```
include_barcode(  
  label,  
  value,  
  size,  
  position = NA,  
  type = "static",  
  color = "auto",  
  units = "cm"  
)
```

Arguments

label	label output
value	column or path
size	image size
position	position coordinate
type	type of entry: dynamic or static
color	image color
units	units for the label options

Value

data frame

include_image	<i>Image layer</i>
---------------	--------------------

Description

Insert image in label

Usage

```
include_image(
  label,
  value,
  size,
  position = NA,
  type = "static",
  units = "cm",
  opts = NA
)
```

Arguments

label	label output
value	column or path
size	image size
position	position coordinate
type	type of entry: dynamic or static
units	units for the label options
opts	R magick funtions

Value

data frame

include_shape	<i>Shape layer</i>
---------------	--------------------

Description

Insert shape in label

Usage

```
include_shape(  
  label,  
  value = "hexagon",  
  size = 4.325,  
  position = NA,  
  border_color = "black",  
  border_width = 2,  
  background = NA,  
  margin = 0,  
  units = "cm",  
  panel_color = NA,  
  panel_size = 5.08  
)
```

Arguments

label	label output
value	column or path
size	image size
position	position coordinate
border_color	image color
border_width	shape line width
background	background color
margin	= shape margin
units	units for shape
panel_color	panel color
panel_size	panel size

Value

data frame

Examples

```
label <- label_layout(data = NA
  , size = c(10, 2.5)
  ) %>%
  include_shape(
    value = "hexagon"
    , position = c(1.2, 1.25)
    , size = 3
    )

label %>% label_print("sample")

ts <- label$opts
```

include_text	<i>Text layer</i>
--------------	-------------------

Description

Insert text in label

Usage

```
include_text(
  label,
  value,
  position = NA,
  size = 11,
  font = NA,
  type = "static",
  color = NA,
  angle = 0,
  opts = NA
)
```

Arguments

label	label output
value	column or string
position	position coordinate
size	text size
font	font type

type	type of entry: dynamic or static
color	image color
angle	angle of the text
opts	list arguments from draw_label()

Value

data frame

label_layout	<i>Label layout</i>
--------------	---------------------

Description

Generate labels options

Usage

```
label_layout(
  data = NA,
  size,
  background = "white",
  border_color = "black",
  border_width = 0.5,
  units = "cm"
)
```

Arguments

data	data frame to build the labels
size	label size
background	background color
border_color	border color
border_width	border width
units	units for the label options

Value

data frame

Examples

```
label <- label_layout(size = c(10, 2.5)
  , border_color = "red"
  , border_width = 1
  ) %>%
  label_print()
```

label_print

*Label print***Description**

Generate labels based in a data frame

Usage

```
label_print(
  label,
  mode = "sample",
  filename = "labels",
  margin = 0.04,
  paper = c(21, 29.7),
  units = "cm",
  viewer = FALSE,
  smpres = 200,
  nlabels = NA
)
```

Arguments

label	Data frame to build the labels or n repeated labels
mode	Label in "sample/preview" or "complete" mode
filename	Labels file name
margin	Labels margins. margin(t = 0, r = 0, b = 0, l = 0)
paper	Paper size. Default A4 (21.0 x 29.7)
units	Units for the label options
viewer	Show the sample in the "Plots" or "Viewer" panel
smpres	Sample resolution
nlabels	Number of labels to generate

Value

pdf

Examples

```

library(huito)

fb <- fieldbook

label <- fb %>%
label_layout(size = c(10, 2.5)
             , border_color = "blue"
             ) %>%
include_image(
  value = "https://flavjack.github.io/inti/img/inkaverse.png"
  , size = c(2.4, 2.4)
  , position = c(1.2, 1.25)
  ) %>%
include_barcode(
  value = "barcode"
  , size = c(2.5, 2.5)
  , position = c(8.2, 1.25)
  ) %>%
include_text(value = "plots"
            , position = c(9.7, 1.25)
            , angle = 90
            , size = 15
            , color = "red"
            ) %>%
include_text(value = "Inkaverse"
            , position = c(4.6, 2)
            , size = 30
            , color = "brown"
            ) %>%
include_text(value = "condition"
            , position = c(4.6, 1.2)
            , size = 13
            , color = "orange"
            ) %>%
include_text(value = "genotypes"
            , position = c(4.6, 0.5)
            , size = 13
            , color = "#009966"
            ) %>%
label_print(mode = "sample")

```

shape_hexagon

Shape hexagon

Description

Hexagon geom shape for ggplot2

Usage

```
shape_hexagon(  
  size = 4.39,  
  border_width = 2,  
  background = "transparent",  
  border_color = "black",  
  margin = 0,  
  units = "cm",  
  panel_color = "green",  
  panel_size = 5.08  
)
```

Arguments

size	hexagon size
border_width	line width
background	background color
border_color	border color
margin	margin
units	units for shape
panel_color	panel color
panel_size	panel size

Value

geom

Examples

```
shape_hexagon(border_width = 3, background = "red")
```

Index

* datasets

- fieldbook, [3](#)

barcode_qr, [2](#)

fieldbook, [3](#)

huito_fonts, [3](#)

image_import, [4](#)

include_barcode, [4](#)

include_image, [5](#)

include_shape, [6](#)

include_text, [7](#)

label_layout, [8](#)

label_print, [9](#)

shape_hexagon, [10](#)